

How to host popper.js locally

Asked 1 year, 10 months ago Active 1 year, 1 month ago Viewed 3k times



1

I just upgraded to Bootstrap four, and realized [Popper.js](#) was a dependency. I like to host libraries locally, as I sometimes need to work offline, but when I try to use it offline, I get an error `unexpected token export`. It works, however, when I use the cloudflare cdn version, but how can I host popper.js locally?



(I don't want to use any package management for this.)



Thank You

javascript

twitter-bootstrap

popper.js

asked Sep 20 '17 at 3:57



[jeffkmeng](#)

428 4 20

Can you post the code segment where you are calling popper initialization in your code? – [Sahan Serasinghe](#) Sep 20 '17 at 4:04

How did you download it? Package manager? – [Amy](#) Sep 20 '17 at 4:04

4 Answers



3

Because you haven't read the README of the project.



Dist targets

Popper.js is currently shipped with 3 targets in mind: UMD, ESM and ESNext.



- UMD - Universal Module Definition: AMD, RequireJS and globals;

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

Make sure to use the right one for your needs. If you want to import it with a `<script>` tag, use UMD.

Via | <https://github.com/FezVrasta/popper.js#dist-targets>

Now that you have **read** the README of the project, you know that if you want to use Popper.js with a `<script />` tag you want to use the `umd` version of it. Located in [dist/umd](#).

answered Sep 25 '17 at 13:12



[Fez Vrasta](#)

7,013 14 57 112

Have you tried just downloading the source code and refer to it?

0

Get the source code from [the github page](#), then refer to it in your html

```
<script type="text/javascript" src="/path/to/downloaded/popper.js-1.12.5/dist/popper.js" />
```

Will that work?

answered Sep 20 '17 at 4:05



[vleong](#)

573 6 27

I also tried downloading popper and I tried to recreate your problem, and you are correct.

0

If you check the Quick Start section of [getbootstrap.com](#) page, you can find the following line in their example:

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/popper.js/1.11.0/umd/popper.min.js" integrity="sha384-b/U6ypiBEHpOf/4+1nzFpr53nxSS+GLCKfwBdFNTxtclqgenISfwAzpKaMNFNmj4" crossorigin="anonymous"></script>
```

Note the **umd** part in their link. You can download that file and add it locally and it will work.

answered Sep 20 '17 at 4:16



Sahan Serasinghe

1,103 14 21



If you download Popper.js though

0

npm install popper.js



I found there are difference between npm package and its original source which is here <https://popper.js.org/>.

I just download popper.js from its original source and put it new js file. It worked for me.

answered Jul 5 '18 at 7:30



Dilshod

1 1