30-103. Signal THRSTD is generated if bit position 4 of output channel 14 contains a ONE, and signal EMSD if position 5 contains a ONE. The + and - signals (008 through 030 above) are generated according to the content of the same two bit positions.

30-104. Once a desired quantity (for instance plus 246) has been entered into counter THRUST or EMS (counter THRUST for example, table 30-4) and output channel 14 has been set properly (a ONE has been entered into bit position 4), the drive control generates a corresponding D signal (THRSTD). The D signal sets cell 36 in the Counter Priority Control which then supplies the address of the proper counter (0055) and triggers the SQG to execute a DINC instruction (DINC THRUST). As the instruction is executed, the cell is reset, an OUT/ signal is generated by the SQG (POUT/ in the example), and the counter content is diminished by one (to plus 245). A POUT/ or MOUT/ signal causes the drive control to start transmitting + or - drive pulses (THRUST+) at a rate of 3.2 kpps. Since the priority cell is set again by another D signal, the execution of another DINC instruction is requested. This is repeated until the counter content has diminished. Once the counter contains zero and a DINC instruction is executed, signal ZOUT/ is generated which clears the proper bit position of channel 14, thus stopping the transmission of drive pulses.

30-105. Radar Control

30-106. The Radar Control (figure 30-8D) is controlled by bit positions 1 through 4 of output channel 13 (table 30-5B) and accepts the following signals from the radars:

RRIN0	(031)	Serial data from rendezvous radar (RR)
RRIN1	(032)	
LRIN0	(071)	Serial data from landing radar (LR), LEM only
LRIN1	(072)	

30-107. Depending on the inputs, the Radar Control generates the following signals:

RRRANG	(041)	supply RR range data	3.2 kpps pulse trains controlling the radars
RRRARA	(042)	supply RR range rate data	
LRRANG	(046)	supply LR range data	
LRXVEL	(043)	supply LR X velocity data	
LRYVEL	(044)	supply LR Y velocity data	
LRZVEL	(045)	supply LR Z velocity data	
RRSYNC	(047)	3.2 kpps sync pulses for read out of RR data	
LRSYNC	(051)	3.2 kpps sync pulses for read out of LR data	