

UNIVERSITY...

DISSERTATION...

DISSERTATION...

---

**Title...**

---

*Author:*

Aleksander WILUSZ

*Supervisor:*

Eddie WILSON

September 1, 2016

# Contents

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>Introduction</b>  | <b>3</b>  |
| <b>2</b> | <b>Literature review</b>                                     | <b>6</b>  |
| 2.1      | Current and future development of autonomous cars . . . . .  | 6         |
| 2.2      | Implications of autonomous cars revolution . . . . .         | 7         |
| 2.3      | Maximum Capacity Theorem . . . . .                           | 8         |
| 2.4      | Conflicts, collisions and interactions on the road . . . . . | 9         |
| 2.5      | How people will cooperate with autonomous cars . . . . .     | 9         |
| 2.6      | Measuring traffic parameters . . . . .                       | 10        |
| 2.7      | Modelling car behavior . . . . .                             | 10        |
| 2.8      | SUMO . . . . .   | 10        |
| 2.9      | Communication between machines - maybe . . . . .             | 11        |
| 2.10     | Experiment design - real world research . . . . .            | 11        |
| <b>3</b> | <b>Research Methodology</b>                                  | <b>12</b> |
| 3.1      | Experiment design and implementation? . . . . .              | 13        |
| 3.2      | Inspiration by SUMO package . . . . .                        | 13        |
| 3.2.1    | some other subsections . . . . .                             | 13        |
| 3.2.2    | Data collection . . . . .                                    | 13        |
| 3.3      | Software development . . . . .                               | 14        |
| 3.3.1    | Simulation master design . . . . .                           | 14        |
| 3.3.2    | Client's interface design . . . . .                          | 14        |
| 3.3.3    | Car control . . . . .  | 14        |
| 3.4      | Communication between machines . . . . .                     | 14        |
| 3.5      | Autonomous car model . . . . .                               | 14        |
| 3.6      | Experiment design and execution . . . . .                    | 15        |

|          |                              |           |
|----------|------------------------------|-----------|
| <b>4</b> | <b>Findings and results</b>  | <b>15</b> |
| <b>5</b> | <b>Discussion of results</b> | <b>15</b> |
| <b>6</b> | <b>Conclusions</b>           | <b>15</b> |

# 1 Introduction

Autonomous cars are currently a topic of great interest. Around the world the biggest private companies or governments initiatives are developing self-driving vehicles (uber, google, britol car citations), competing for new emerging market. Each company focuses efforts in different direction. The companies are either trying to develop an all-round car that could perform in both city and on highways or restrict the usage to particular types of roads (tesla). Or anything in between. The most significant commercial initiatives include Google driverless car, Tesla, Uber (). Government founded initiatives include Venturer and ...

Background of the problem, context of the research, reasons why the study was carried out, significance of the study

Many experts around the world are trying to predict how autonomous cars will influence our lives. One of the questions is how the traffic itself will change. Most of the experts agree that in the next decades we will observe gradual process of increasing the share of autonomous cars on our roads. In that time human-driven cars and self driving cars will have to successfully interact with each other. According to predictions the fully automated traffic will become reality only around year 2060 or year 2040 in more optimistic predictions and first commercial autonomous cars are already appearing on the roads (singapore, uber). Although there are numerous studies on many aspect of autonomous driving as well as on interactions between regular cars in all-human-traffic there is little research on interactions between these two types of vehicles and all its consequences.

A statement of the problem to be addressed

reflect on original Eddie's idea

The focus of this research is to investigate how autonomous cars will influence traffic itself and how human and autonomous cars will interact with each other.

clear and succinct statement of research questions, aims and objectives.

The main aim of the research was trying to predict what will happen when autonomous cars are introduced to the traffic. Results obtained were analysed from the point of view to traffic parameters such as velocities, densities, congestion and from the point of view how individual drivers reacted differently when autonomous vehicle was encountered.

The main objective of the project was to create a an on-line traffic simulation that would allow to connect multiple people together at the same time. People were asked to drive a car

**How scope was reduced** The original scope of the project included also in-silico implementation that would be using remotely controlled "slot-cars". It was believed that that physical model would have features that could not be accounted for or predicted in computer simulation. It was estimated for around 50% of implementation effort. However, the final version of the project the physical model was not implemented. After the project went into development the advantages of creating a physical model appeared less and less attractive. Especially compared to the cost of implementation. Original idea assumed using digital slot-car set with cars and track, as well as computer vision to track vehicles on the track and live video streaming to multiple computers. After more careful consideration the benefits of implementing above described would be very minor or none. In addition

to this, implementing the computer simulation consumed more time than estimated.

It has to be admitted that scope was drastically limited in terms of implementation effort. It did not, however, have much impact on the quality of the research and conclusions. One would even venture to say that project should only consist of computer simulation even if more time and resources were allowed for project execution.

**A road map of what is going to be discussed** The project consisted of three main parts. First one was software development. This accounted for around 50% of all efforts. The chapter on Research Methodology is mostly dedicated to this. Software section is divided into most significant components that include the design of simulation master, design of client's interface and vehicle's control. The chapter on research methodology also describes how communication between machines was established and the algorithm behind autonomous vehicles. Although these two aspects were integral parts of the software it was decided to write about them separately. It is due to the significance and universality of communication solution and autonomous car algorithm. Most of decisions made throughout the development stage were aimed for successful experiment execution. The design of the experiment and how it was eventually conducted are described at the of Research Methodology chapter.

The Research Methodology chapter is preceded with in-depth chapter describing literature relevant to the project.

The data obtained during the experiment was described in Findings and Results chapter. This chapter also talks about different ways in which data was analysed.

The last two closing chapters discuss the results of the experiment, attempt to draw conclusions and generalize findings in wider context.

## 2 Literature review

There is plenty of literature dedicated to autonomous cars.

### 2.1 Current and future development of autonomous cars

The prime examples of the most recent achievements in the field of autonomous cars are visible through cutting-edge commercial projects such as google self driving car, uber's and jshanghai something. Google is probably the most experienced player as it's self driving car project started already in the year 2009 (google self driving car website). Google's car is classified as level 3 in automated vehicle classification system proposed by NHTSA in 2013 (<http://www.nhtsa.gov/About+NHTSA/Press+Releases/U.S.+Department+of+Transportation>) which is described as "Limited Self-Driving Automation". The car takes full control over all safety-critical functions but at certain times driver can be asked to retake control.

List of trials on autonomous vehicles is here: (?) googel, volvo, audi, singapore, and add uber

More and more commercially available vehicles feature level 2 of autonomy and are capable of emergency braking, lane control or adaptive cruise control. Even more advanced cars, like Tesla S are able to actively change lanes on a motorway when instructed by driver(link to tesla's manual).

Vehicle classified at level 4 would have to

Uber is a relatively new player in the business of autonomous cars.

Write about audi autonomous racing car

In the near future we should be able to see more and more autonomous vehicles on the roads. The report released by UK Department of Transport titled "The Pathway to Driverless Cars Summary report and action plan" (?) states that government recognises the benefits of autonomous vehicles and is undertaking actions to aid the development of technologies and law that would allow to bring driverless cars on public roads.

## **2.2 Implications of autonomous cars revolution**

Experts around the world argue about the consequences of introducing self-driving cars. The report by UK Department of Transport "The Pathway to Driverless Cars" summarizes some main benefits of having autonomous cars. Most important points include significant reduction of time spent in vehicles and largely improved safety. It is stated that an average driver could save up to 6 working weeks of driving time in a single year. A claim on potential safety improvements is backed by existing evidence from automated vehicles that are already commercially available and feature level 2 autonomy. Another important benefits include reduced emission and reduced congestion. Vehicles that are connected into one system would be able to drive in the interest of all traffic participants and therefore greatly optimize traffic. A consequence of traffic optimization and overall reduction of Total Kilometers Traveled would be major cost reduction and the result could be increased access to vehicles for everyone(?).

On the other hand, it is argued that autonomous vehicles will not be as robust as expected and traffic parameters will, in fact, worsen(?).

There are also many other indirect implications. As stated in (?) an example will be a family that decides to settle further from the city because



they can spend time in the car productively rather than controlling the vehicle. In consequence the benefits of faster and more optimized travel will be counteracted by overall increase in road demand. Consecutively the traffic parameters may not improve as expected.

Rely heavily on: (?)

adittionally:

### **2.3 Maximum Capacity Theorem**

Traffic has an ability to self organize close to its capacity. This rule called Fundamental Law of Traffic Congestion or Maximum Capacity Theorem states that when stock of available roads rises, the overall driving increases too (?). The theory behind it explains why building new roads or adding new lanes does not necessary yield proportional decrease in congestion.

Duranton and Turner identified four major sources of additional traffic such as increased commercial traffic, alteration to individual driving behaviour, population growth and diversion from other roads. Raised availability of roads cause an increase in Vehicle Kilometres Travelled(VKT) by commercial vehicles as well as private commuters. Choosing a car as a mean of transport will appear as a more attractive option.

This theorem could be put in the context of autonomous vehicles. As mentioned before, introducing autonomous cars to the traffic should result in reduced congestion as travelling would be more optimized. However, according to the Fundamental Law of Traffic Congestion, less traffic on the roads can encourage people to travel more. Consequently this will rise overall road demand and the traffic will reach it's new capacity.

## 2.4 Conflicts, collisions and interactions on the road

(?)

According to (Contributory factors of reported accidents, Great Britain excel) most accidents are caused by human failure. The main contributory factors are failure to look properly, failure to judge other's person speed or path and driver, carelessness, recklessness or being in a hurry.

(writing about it in the context that autonomous cars can potentially improve these things)

Although the study on conflicts on the road is very complex and hard to quantify according to (?) there are numerous factors that contribute to creating conflicts. These factors include excessive speed or poorly adopted speed, too small distance to proceeding car, violations of the right-of-way and many other types of behaviour.

More about interactions in general...

## 2.5 How people will cooperate with autonomous cars

In the next decades driverless cars will be required to successfully cooperate with human drivers. Even when all cars become autonomous, pedestrians, cyclists and other traffic participants must still be able to move around. Human driver have certain expectations from other drivers. Things like eye-contact are often important for successful communication. That kind of interaction will be absent in encounters with autonomous vehicles. Moreover, drivers often possess skills and experience that may not be easy to quantify and program into machine. Therefore driverless cars can, in fact, perform worse in certain situations(?). During transition period the amount of accident can in fact increase.

As mentioned in introducing autonomous cars should result in smaller number of accidents. A machine would be free from factors mentioned in previous chapter.

## 2.6 Measuring traffic parameters

In order to evaluate traffic performance four key parameters will be measured as suggested in a paper by Beymer and McLauchlan (?).

- Flow - Amount of vehicles in one hour (will be separately evaluated for different parts of the track)
- Velocity - Average velocity of individual car or multiple cars
- Density - Amount of vehicles in for specified distance
- Headway - Spacing between vehicles

Additionally to the parameters above the traffic will be analysed in terms of amount of accidents.

## 2.7 Modelling car behavior

write about the model in sumo

write how it applied to both human and autonomous

write about possible models of car's behaviours

Intelligent driver model etc

gipps

## 2.8 SUMO

SUMO stands for Simulation of Urban MObility. It's an open source framework used for traffic simulation(?). SUMO was first introduced in 2002 and

since then it became a popular tool for scientist as well as people involved in practical traffic planning tasks.

SUMO is a purely microscopic simulation which means every traffic participant is modelled separately. The framework is designed to simulate large cities that contain thousands of roads and more than one million of vehicles.

The core of the SUMO package is a logical representation of road layout. Segments of roads separated by junctions are described as nodes and edges. Edges consist of directed lanes. Vehicle's position is described in terms of edge and lane number and distance from origin node. At every step of the simulation interaction between individual simulation entities are computed and all parameters updated. (?)

SUMO is supported by additional pieces of software such as a tool for importing map structure and a plug-in for providing on-line inputs.

The applications of SUMO include designing traffic light sequence, predicting demands on planned roads or creating traffic control systems.

It is a microscopic

It allows to account for multiple factors to create  
quick summary of sumo

## **2.9 Communication between machines - maybe**

### **2.10 Experiment design - real world research**

?

### 3 Research Methodology

The main aim of the project was to look into interactions between autonomous and human-driven vehicles. The main method that was used to achieve this was to create a simulation of traffic with both types of traffic participants. By reviewing the literature it was found that there are numerous car-following models that could be used for the purpose of this simulation. However, no matter how good were these models, they could only work as approximation of how humans would actually control the cars. It was decided that differences between any of the reviewed car-following algorithms and actual human control are so significant that the study should rely on the experiment involving multiple human participants controlling cars in real-time simulation.

The decision to create such a simulation was a key factor influenced the shape to the whole project.

The consequence of heaving an experiment that involves multiple participants was that the major effort was put into developing software that would allow to conduct the experiment.

Creating such a simulation was the most significant factor accounting for the complexity of the project.

This decision accounted for the most complexity

Although there are numerous models of (some citation) cars

Justify the structure of the project. Why the experiment was a key part. Why this was the best option rather than for example use data from some database?...hmmm

### 3.1 Experiment design and implementation?

The experiment was arguably the most important part of the project. All work done before was aimed at successful conductance of the experiment and all work done after was based on the data collected during the experiment.

The experiment was planned to involve ten to twenty people. Each of them would sit in front of a computer where they could use the keyboard and observe the screen. They would be asked to control one of the vehicles in the simulation. On the screen they would see a top down view of their own vehicle and it's surrounding. By using the keyboard they would control the acceleration of their vehicle. The instructions given would encourage them to explore the map and avoid collisions with other traffic participants.

### 3.2 Inspiration by SUMO package

The design of the map structure that vehicles are moving on was inspired by Simulation of Urban MObility (SUMO) package. The details of the SUMO framework are described in literature review section.

SUMO was simply not design for

, however, found that

why matlab?

The freedom of movement

map design

Justify all major design decisions. Plenty of them! All the actions undertaken to ensure most meaningful results

### **3.2.1 some other subsections**

### **3.2.2 Data collection**

How the experiment was eventually conducted

## **3.3 Software development**

Justify all major design decisions

### **3.3.1 Environment choice**

Choosing the right environment to develop software was a key decision that determined many parts of the project. The initial Project Proposal written by Eddie Wilson suggested using SUMO package as a core of the simulation. It was assumed that a small part of SUMO capabilities would be utilized in combinations with additional software written for the purpose of this project. SUMO features Traffic Control Interface (TraCI) that gives access to running simulation. The parameters of the simulation like car's location could be retrieved and manipulated in real-time. The additional software would be responsible for data exchange over the network, visualizing car's surrounding and capturing inputs from experiment participants. All these features

The initial idea was to use SUMO package as a fundamental

At the beginning SUMO was considered a primary tool for implementing the whole simulation. It was hoped that ability to serve on-line inputs would allow to control vehicles in the simulation in real-time, proving inputs coming from many machines. However, it was found that none of the features available in SUMO would allow for such operation.

### **3.3.2 Simulation master design**

### **3.3.3 Client's interface design**

General description Simplifications and yet still accounting for most important parts of the car model

### **3.3.4 Car control**

## **3.4 Communication between machines**

From one point of view this a tightly coupled with software development but the way communication was established doesnt matter from the point of view of software structure. Simply speaking the comms should only meet some requirements derived from the main piece of software and the details of implementation doesnt matter. This was a significant part of the job and its an achievement on its own.

## **3.5 Autonomous car model**

Say why this is important from the point of view of results obtained. Again justify all design decisions



**3.6 Experiment design and execution**

**4 Findings and results**

**5 Discussion of results**

**6 Conclusions**

**References**