



- FOUNDATION PLAN** SCALE: 1/8" = 1'-0"
1. SLAB ON GRADE TO BE 6" MIN THICK, 4000 P.S.I., CONCRETE REINF 6 x 6 x 11 24 x 11 24 MIN AND 15 POUNDS PER C.YD. OF FIBER MESH OVER 6 MIL VAPOR BARRIER AND 4" MIN DEEP STONE BASE.
 2. MODULUS OF SUBGRADE SHALL BE VERIFIED TO BE A MINIMUM OF 180 P.C.I.
 3. ELEVATION TOP OF SLAB = 184.00'
 4. ELEVATION TOP OF FOOTINGS NOTED (XXXX) IN PLAN.

FOOTING SCHEDULE

MARK	SIZE	REINFORCING
F50	5'-0" x 5'-0" x 1'-0"	6-#6 EACH WAY BOTT.
F66	6'-6" x 6'-6" x 2'-0"	7-#7 EACH WAY BOTT.
F75	7'-6" x 7'-6" x 1'-4"	8-#7 EACH WAY BOTT.



Dunlap Engineering, Inc.
Structural Consultants
14119 Blenheim Road
Pikesville, MD 21113
Phone: (410) 817-9900
Fax: (410) 817-9901

FRP DEVELOPMENT CORP.
34 LOVETON CIRCLE, SUITE 100
SPARKS, MARYLAND 21152
410-771-4100

**NEW BUILDING AT
HILLSIDE BUSINESS PARK
7020 DORSEY ROAD
ANNE ARUNDEL COUNTY, MARYLAND**

No. Description Date
Revisions

Proj. No.

Date 09-12-05

Scale AS NOTED

Last Rev.

Title:

**FOUNDATION
PLAN**

REVIEWED

OCT 10 2005

Sheet COMMERCIAL REVIEW
AA CO. - PAC

S-1