



FOUNDATION PLAN SCALE: 1" = 20'-0"

SLAB ON GRADE TO BE 6" MIN THICK 4000 P.S.I. CONCRETE REINFT
6 X 6 X 2.4 X 2.4 IN. AND 15 POUNDS PER C.Y.D. OF FIBER WEIGH OVER
6 MIL VAPOR BARRIER AND 4" MIN DEEP STONE BASE.

2. MODULUS OF SUBGRADE SHALL BE VERIFIED TO BE A MINIMUM OF 180 P.C.I.

3. ELEVATION TOP OF SLAB = 45.50'

4. ELEVATION TOP OF FOOTINGS NOTED (XXXV) IN PLAN.

FOOTING SCHEDULE		
MARK	SIZE	REINFORCING
F46	4'-6" X 4'-6" X 2'-0"	7-#1 EACH WAY BOT.
F66	6'-6" X 6'-6" X 2'-0"	7-#6 EACH WAY BOT.
F16	7'-6" X 7'-6" X 1'-4"	7-#1 EACH WAY BOT.

NEW BUILDING AT 2201 LAKESIDE BLVD.
LAKESIDE BUSINESS PARK
ABERDEEN, MARYLAND

FRP DEVELOPMENT CORP.
34 LOVETON CIRCLE, SUITE 100
SPARKS, MARYLAND 21152
410-771-4100

unlap Engineering, Inc.
Structural Consultants
14119 Blenheim Road
Phoenix, Maryland 21131
Phone: (410) 817-9900
Fax: (410) 817-9901

Title:	
Last Rev.	
Scale	AS NOTED
Date	
Proj. No.	
Revisions	
Mod/Description	Date
3 OWNER REV.	05/13/05
2 COUNTY REV.	02/14/05
1 CODE REVISION	11/28/07