

```
#include <stdlib.h>
#include <string.h>
#include <ctype.h>
```

```
#define MAXPAROLA 30
#define MAXRIGA 80
```

```
int main(int argc, char *argv[])
```

```
{
```

```
    int freq[MAXPAROLA]; /* vettore di contatori
delle frequenze delle lunghezze delle parole */
    char riga[MAXRIGA];
    int i, inizio, lunghezza;
    FILE *f;
```

```
    for(i=0; i<MAXPAROLA; i++)
        freq[i]=0;
```

```
    if(argc != 2)
```

```
    {
        fprintf(stderr, "ERRORE, serve un parametro con il nome del file\n");
        exit(1);
    }
```

```
    f = fopen(argv[1], "r");
    if(f==NULL)
```

```
    {
        fprintf(stderr, "ERRORE, impossibile aprire il file %s\n", argv[1]);
        exit(1);
    }
```

```
    while( fgets( riga, MAXRIGA, f ) != NULL )
```



Linked Lists

Atomic Operations

Stefano Quer

Dipartimento di Automatica e Informatica

Politecnico di Torino

Linked list: Definition

Definition of a C structure

```
typedef struct list_s {  
    int key;  
    ...  
    list_t *next;  
} list_t;
```

Key and data fields

Auto-referencing
pointer

```
typedef struct list_s list_t;  
struct list_s {  
    int key;  
    ...  
    list_t *next;  
};
```

Allocation of a new node

Memory allocation


```
list_t *new_element ( ) {
    list_t *e_ptr;
    e_ptr = (list_t *) malloc (sizeof (list_t));
    if (e_ptr==NULL) {
        fprintf (stderr, "Memory allocation error.\n");
        exit (FAILURE);
    }
    return (e_ptr);
}
```

Function call

```
list_t *head, *new;
...
head = NULL;
...
new = new_element();
```

Initially the list is empty, thus,
head must be initially set to NULL

Visit



```
list_t *p;
```

```
...
```

```
p = head;
```

```
while (p != NULL) {
```

```
...
```

```
p = p->next;
```


```
}
```

We check up-front, thus the algorithm works even for empty lists

Visit the element p, i.e., p->key and all data fields

Move to the next element

Search 1



Looking for a specific **value**

```


list_t *p;
...
p = head;
while (p!=NULL) {
    if (value==p->key) {
        ...
    } else {
        p = p->next;
    }
}

```

Element found

Need to break out of the while loop once done

Search 2





Looking for a specific **value**

```
list_t *p;
...
p = head;
while ((p!=NULL) && (p->key!=value)) {
    p = p->next;
}
if (p!=NULL) {
    ...
}
```

Element found

The order **matter**
 ((p!=NULL) && (p->key!=value))
is buggy

Head extraction




```

if (head!=NULL) {
Step 1    p = head;
Step 2    head = head->next;
    ...
}
    
```

Deal with the element p, i.e.,
p->key and all data fields.
Finally, free it

In-order extraction

- ❖ The extraction of a given element is possible only if we have access to the element placed **before** it
 - To extract an element we need its pointer
 - This pointer is stored in the element placed in the list before the element
 - For now, we suppose we need to extract the successor of an element
 - We will analyze how to reach it in the next section




With pointer p, we can extract node C not node B


If we visit the list looking for the node to erase, we may be too late to perform the operation

In-order extraction 1

Step 1



Ergo ... We need to traverse the list using two pointers or the pointer of the pointed node




Step 2

```
Step 1  p = q->next;
Step 2  q->next = p->next;
...
```


Deal with the element p, i.e.,
p->key and all data fields.
Finally, free it

In-order extraction 2

Step 1



Ergo ... We need to traverse the list using two pointers or the pointer of the pointed node




$q \rightarrow \text{next} = q \rightarrow \text{next} \rightarrow \text{next}$

Step 2

```
Step 1  p = q->next;
Step 2  q->next = q->next->next;
...
```

p is required only to deal with the extracted element

Head insertion



```


Step 1  new = new_element();
        ...
Step 2  new->next = head;
Step 3  head = new;
    
```

Set key and data fields
(possibly using strcpy, strcat, etc.)

Does it work if the list is empty?
Yes, it does ...
If the list is empty `head=NULL`,
then `p->next` will be `NULL`

In-order insertion


- ❖ Similarly to the extraction case, to insert a new element before a given element p , it is necessary to access the pointer field within the element coming before p
- ❖ Thus, we focus on the insertion of a new element after (not before) an existing element p
 - We will analyze how to reach it in the next section



With pointer p , we can insert a node after B not before it

If we visit the list looking for the position to insert, we may be too late to perform the operation

In-order insertion




```

Step 1  new = new_element();
        ...
Step 2  new->next = p->next;
Step 3  p->next = new;
    
```

Tail insertion

- ❖ If it is necessary insert an element into the list tail, i.e., as a last element
 - Just use the previous code after making **p** referring to the last element of the list



```
Step 1 new = new_element();
```


```
...
```

```
Step 2 new->next = p->next;
```

```
Step 3 p->next = new;
```


The only difference is that
p->next is NULL

Dispose a list



- ❖ Lists must be freed when they are no longer necessary
 - To free a list, we must visit it and free its elements one by one

Dispose a list




```
p = head;
while (p != NULL) {
    ...
    free (p);
    p = p->next;
}
head = NULL;
```

First, free inner fields
Then free the element itself

Buggy code
With **p = p->next**, we make an access
to the **next** field of a freed element

Dispose a list



We can use **head** directly to visit the list and **p** can be dedicated to extracted elements

```
while (head != NULL) {
    p = head;
    head = head->next;
    ...
    free (p);
}
```

First, free inner fields
Then free the element itself

Lists with special elements

- ❖ Several operations on lists can be simplified using the so called **sentinels**
 - A sentinel (also called signal value, or dummy value, or flag value) is often used to indicate the **end** or the **beginning** of the list
 - There are at least three type of extensions using sentinels, as sentinels can be used on
 - The head of the list
 - The tail
 - On both the head and tail

Example

List search


```
p = head;
while ((p!=NULL) && (p->key!=value)) {
    p = p->next;
}
if (p!=NULL) {
    ...
}
```

The **value** has been found

- ❖ Searching for an element implies checking 2 conditions
 - p does not have to be NULL **and** it does not have to refer to the node storing value
 - Checking the logical AND of two conditions is more expensive than checking only one condition

Lists with special elements

- ❖ We insert a sentinel element at the end of the list
 - We always have at least one element in the list, i.e., the sentinel
 - We waste a small chunk of memory
 - We can use the extra element to store the value we are looking for
 - Thus, we can simplify the search condition



- ❖ We need to maintain sentinel in all cases from the list initialization on

Lists with special elements

```
sentinel->key = value;  
p = head;  
while (value!=p->key) {  
    p = p->next;  
}  
if (p!=sentinel) {  
    ...  
} else {  
    ...  
}
```

At the very beginning, we insert the value in the sentinel

Thus, **value** is always in the list and we can simplify the condition

value found

value **not** found

- ❖ We need to maintain the sentinel in all cases from the list initialization on