Assignment 4

By Paula Pino, CPS393-2

1. UPDATE States SET State = TRIM(State), Abbreviation = TRIM(Abbreviation);

Check that it worked:

```
MariaDB [pino]> SELECT * FROM States WHERE Abbreviation = 'GU';
+-------+--------------+
| State | Abbreviation |
+-------+--------------+
| Guam  | GU           |
+-------+--------------+
1 row in set (0.001 sec)
```

2. SELECT state, COUNT(*) as statecnt FROM vets GROUP BY state ORDER BY cnt DESC;

```
+-------+----------+
| state | statecnt |
+-------+----------+
| CA    |     5575 |
| NY    |     4120 |
| TX    |     3414 |
| PA    |     3141 |
| OH    |     3092 |
| IL    |     2930 |
| MI    |     2654 |
| FL    |     1950 |
| NC    |     1609 |
| GA    |     1583 |
| IN    |     1531 |
```

...

```
| SO    |        4 |
| XJ    |        4 |
| XB    |        3 |
| XN    |        3 |
| ZZ    |        3 |
| XE    |        3 |
| XF    |        2 |
| XI    |        2 |
| CZ    |        2 |
| XS    |        1 |
| XA    |        1 |
+-------+----------+
69 rows in set (0.066 sec)
```

3. SELECT DISTINCT state FROM vets WHERE state NOT IN (SELECT Abbreviation FROM States);

```
MariaDB [pino]> SELECT DISTINCT state FROM vets WHERE
state NOT IN (SELECT Abbreviation FROM States);
+-------+
| state |
+-------+
| XP    |
| XJ    |
| VQ    |
| XS    |
| XC    |
| XB    |
| ZZ    |
| XI    |
| XN    |
| XE    |
| XG    |
| XM    |
| XF    |
| SO    |
| XA    |
| CZ    |
+-------+
16 rows in set (0.099 sec)
```

4. I created new databases for to source the SQL files into

   Mynewpaltz:

```
MariaDB [employees]> USE mynewpaltz;
Database changed
MariaDB [mynewpaltz]> DESCRIBE studenttable;
+-----------+-------------+------+-----+---------+-------+
| Field     | Type        | Null | Key | Default | Extra |
+-----------+-------------+------+-----+---------+-------+
| ssn       | int(11)     | NO   | PRI | NULL    |       |
| firstName | varchar(20) | YES  |     | NULL    |       |
| mi        | varchar(1)  | YES  |     | NULL    |       |
| lastName  | varchar(20) | YES  |     | NULL    |       |
| phone     | varchar(10) | YES  |     | NULL    |       |
| birthDate | date        | YES  |     | NULL    |       |
| street    | varchar(30) | YES  |     | NULL    |       |
| zipCode   | int(11)     | YES  |     | NULL    |       |
| deptId    | varchar(4)  | YES  |     | NULL    |       |
+-----------+-------------+------+-----+---------+-------+
9 rows in set (0.063 sec)
```

   Employees:

```
MariaDB [employees]> DESCRIBE employees;
+--------------+--------------+------+-----+---------+-------+
| Field        | Type         | Null | Key | Default | Extra |
+--------------+--------------+------+-----+---------+-------+
| id           | int(11)      | NO   | PRI | NULL    |       |
| name         | varchar(100) | YES  |     | NULL    |       |
| salary       | decimal(10,2) | YES  |     | NULL    |       |
| department_id | int(11)      | YES  | MUL | NULL    |       |
| manager_id   | int(11)      | YES  | MUL | NULL    |       |
+--------------+--------------+------+-----+---------+-------+
5 rows in set (0.034 sec)
```