

Interdependent Evolution of Non-Spectral Opinions and Social Networks

Fabian Russmann and Stefan Rustler
"Social State Physicists"

Zurich, December 18 2012

OVERVIEW

INTRODUCTION

- Background and Motivation

THE MODEL

- Initial Setup

- Time Evolution Algorithm

RESULTS

- Cluster Size Distribution

- Phase Transition and Critical Point

- Convergence Time

- Comparisons to Empirical Data

CONCLUSION

- Summary

- References

BACKGROUND AND MOTIVATION

- ▶ Opinion Formation (e.g. voter models) is a common and very fundamental problem in the social sciences
- ▶ Goal: Modelling the *coevolution* of both opinions and the underlying social network
- ▶ **Does our social network shape the opinion we hold or does our opinion determine who is part of our network?**
- ▶ Preview: Analogies to statistical physics, e.g. *phase transitions* can be identified
- ▶ "Opinion" must be mutually exclusive and "non-spectral", e.g. brand preference, religious views...

INITIAL SETUP

- ▶ Random graph with N nodes (opinion holder) and M edges (social connection)
- ▶ Random opinion $g_i \in G$ assigned to node i
- ▶ Nodes exchange information (opinion) via undirected edges
- ▶ Externally set parameters:
 - ▶ N - number of nodes
 - ▶ $\gamma = \frac{N}{G}$ - average number of nodes per opinion
 - ▶ $k_{avg} = \frac{2M}{N}$ - average degree
 - ▶ Φ - reconnection probability

TIME EVOLUTION ALGORITHM

1. Pick a random node i with opinion g_i .
2. (a) With probability Φ select at random one of the nodes j that i is connected to.
 - ▶ If $g_i = g_j$, start over at step 1.
 - ▶ Otherwise, reconnect to a randomly chosen j' of same opinion, i.e. $g_{j'} = g_i$.
3. (b) Otherwise, with probability $1 - \Phi$ randomly select one of the neighboring vertices j and change g_i to g_j .
4. Repeat until *consensus state* is achieved.





Figure: Holme and Newman, 2006 [5]

CLUSTER SIZE DISTRIBUTION

CONTINUOUS PHASE TRANSITION?




CLUSTER SIZE DISTRIBUTION

- ▶ Ordered phase
 - ▶ Low Φ , i.e. tendency to change opinion
 - ▶ Small clusters follow power law distribution
 - ▶ Existence of giant cluster
- ▶ Unordered phase
 - ▶ High Φ , i.e. tendency to keep opinion
 - ▶ Clusters follow Poisson-like distribution
 - ▶ No giant cluster!
- ▶ Phase transition
 - ▶ First guess: $\Phi_c = 0.39 \pm 0.05$
 - ▶ Power law behavior over the whole s -range
 - ▶ Order parameter $S = \frac{s_{max}}{N}$

- ▶ Really continuous phase transition
- ▶ Bigger $N \rightarrow$ more dramatic transition
- ▶ $\Phi_c = 0.32 \pm 0.02$ independent of system size N
- ▶ Weak agreement with $\Phi_c = 0.39 \pm 0.05$


CONVERGENCE TIME

- ▶ Iterations per node to reach consensus as function of Φ :
- ▶ "Divergence" at some Φ_c for different N
- ▶ Similar to divergent response functions in physics
- ▶ Supporting phase transition interpretation, but difficult to find direct analogy to τ_{avg}



COMPARISONS TO EMPIRICAL DATA

- ▶ Idea: Compare distributions of some "opinion" in real world to the model → identify and interpret corresponding Φ
- ▶ **Religion:**
- ▶ Worldwide distribution of religions follows power law: Neither adaptation nor reconnection dominate in the formation?



- Interpret Φ as an "intolerance indicator"?

SUMMARY

- ▶ Interdependent evolution of opinions and networks, combining two mechanisms of adaption and reconnection determined by Φ
- ▶ Holme's and Newman's [5] work could be reproduced with more realistic assumptions
- ▶ Continuous phase transition
 - ▶ N -independent critical value $\Phi_c = 0.32 \pm 0.02$
 - ▶ Divergent consensus time at Φ_c

Outlook

- ▶ Variation of γ (diversity) and k_{avg} (density)
- ▶ Include analogue of "magnetic field" in model: "*informed agents*"?
- ▶ Make opinions *spectral*
- ▶ More detailed comparisons to empirical data

REFERENCES



R. Albert, A.-L. Barabasi. *Statistical mechanics of complex networks*. Rev. Mod. Phys, 74:4798, 2002.



S. Brügger, C. Schwirzer. *Opinion formation by "employed agents" in social networks*. Project Report: Modelling and Simulating Social Systems with MATLAB, ETH Zurich, 2011.



C. Castellano, D. Vilone, and A. Vespignani. *Incomplete ordering of the voter model on small-world networks*. Europhys. Lett., 63:153158, 2003.



P. Erdős, A. Rényi. *On the evolution of random graphs*. Publications of the Mathematical Institute of the Hungarian Academy of Sciences 5: 1761, 1960.



P. Holme, M. E. J. Newman. *Nonequilibrium phase transition in the coevolution of networks and opinions*. Physical Review E, vol. 74, Issue 5, id. 056108, 11/2006.



W. Nolting. *Grundkurs Theoretische Physik 6: Statistische Physik*. Springer Berlin Heidelberg. 5. Aufl, 2004.



Quantcast, *Quantcast Review of 2009 Mobile Web Trends*.

"<https://www.quantcast.com/inside-quantcast/2010/01/quantcast-review-of-2009-mobile-web-trends-mobile-web-share-up-110-in-north-america-and-148-globally>" Accessed December 13, 2012.



V. Sood, S. Redner. *Voter model on heterogeneous graphs*. Phys. Rev. Lett., 94:178701, 2005.



D. H. Zanette, S. C. Manrubia. *Vertical transmission of culture and the distribution of family names*. Physica A, 295:18, 2001.



A. Zheludev. *Advanced solid state physics*. Lecture, ETH Zurich, Fall 2012.