Table of Contents

```
INITIALIZE variables 2
% Harbor queueing simulation
clear all; close all
%%DEFINE ALL VARIABLES
%between(i) = time between arrival of ship i and i-1.
%arrive(i) = time at which ship i arrives to harbor
%unload(i) = time to unload ship i
%start(i) = time at which ship i begins getting unloaded
%idle(i) = time harbor is idle for ship i
%wait(i) = time ship i waits in line
%finish(i) time ship i leaves harbor
%harbor(i) = total time at harbor for ship i
%CUMULATIVE VARIABLES
%hartime = average time per ship in the harbor
%maxtime = max time in the harbor
%waittime = avg wait time per ship
%maxwait = max waiting time
%idletime = percent of total sim time harbor is idle
```

ENTER input variables

```
% #2 Parameters
aunload = 10;
bunload = 20;
aarrive = 20;
barrive = 30;

% #3 Parameters
%aunload = 50;
%bunload = 70;
%aarrive = 49;
%barrive = 70;

maxQ = 25;

% Interarrival times are uniformly distributed.
```

N = 1000; % number of ships to simulate

INITIALIZE variables

```
%ship 1 is special case
between(1) = 0;
arrive(1) = 0 + between(1);
unload(1) = rand * (bunload - aunload) + aunload;
start(1) = arrive(1);
wait(1) = 0;
finish(1) = unload(1);
harbor(1) = unload(1);
idle(1) = 0;
qlength(1) = 0;
% cumulative variables
left = 0;
```

RUN the simulation for N ships

```
for i = 2:N
    %determine interarrival and unload times
   between(i) = rand * (barrive - aarrive) + aarrive;
   unload(i) = rand * (bunload - aunload) + aunload;
   arrive(i) = arrive(i-1) + between(i);
    %determine if dock is idle or not
   timediff = arrive(i) - finish(i-1);
   if qlength(i-1) > maxQ
        left = left + 1;
       wait(i) = 0;
        idle(i) = 0;
       qlength(i) = qlength(i - 1);
   else
        if timediff > 0 %dock is idle %arrive(i)>finish(i-1)
            wait(i) = 0;
            idle(i) = timediff;
            qlength(i) = 0;
        else
            wait(i) = -timediff;
            idle(i) = 0;
            if arrive(i) > start(i-1)
                qlength(i) = 1;
            else
                glength(i) = glength(i-1) + 1;
            end
        end
   end
   %calculate start and finish times, and duration in harbor
   start(i) = arrive(i) + wait(i);
   finish(i) = start(i) + unload(i);
   harbor(i) = finish(i) - arrive(i);
```

%Update Cumulative Variables

Create a nice table

0

maxq =


```
fprintf('Begin One Bay Simulation for %i ships\n', N)
fprintf('Avg time at harbor Max time at harbor
wait time Max wait time Percent Time harbor idle
\n')
fprintf (' %5.1f
                              %5.1f
      %5.1f
                                      %5.1f
                      %5.1f
\n', avghartime, maxhar, avgwaittime, maxwait, avgidletime)
figure(1);hist(between); title('Interarrival Times')
figure(2); hist(unload); title('Service Times');
figure(3); hist(harbor); title('Harbor Times');
figure(4); hist(wait); title('Wait Times');
figure(5); hist(idle); title('Idle Times');
figure(6); plot(qlength); title('Queue Lengths');
```


Begin One Bay Simulation for 1000 ships


Avg time at harbor Max time at harbor Avg wait time Max wait time Percent Time harbor idle


15.0 20.0 0.0 0.0


10.0














Published with MATLAB® R2018b