```
/**
* Kotlin syntax grammar in ANTLR4 notation
*/
// SECTION: general
kotlinFile
    : packageHeader importList topLevelObject*
packageHeader
    : (PACKAGE identifier)?
importList
    : importHeader*
importHeader
    : IMPORT identifier MULT?
topLevelObject
    : declaration
declaration
    : classDeclaration
    | functionDeclaration
    | propertyDeclaration
// SECTION: classes
classDeclaration
    : modifiers? (CLASS | FUN? INTERFACE) simpleIdentifier
    typeParameters? primaryConstructor?
    delegationSpecifiers?
    (classBody | enumClassBody)?
primaryConstructor
    : (modifiers? CONSTRUCTOR)? classParameters
classBody
```

```
: classMemberDeclarations
classParameters
    : classParameter*
classParameter
    : modifiers? VAL? simpleIdentifier type expression?
delegationSpecifiers
    : annotatedDelegationSpecifier*
delegationSpecifier
    : constructorInvocation
    | userType
    | functionType
constructorInvocation
    : userType valueArguments
annotatedDelegationSpecifier
    : annotation* delegationSpecifier
typeParameters
    : LANGLE typeParameter+ RANGLE
typeParameter
    : simpleIdentifier type?
// SECTION: classMembers
classMemberDeclarations
    : classMemberDeclaration*
classMemberDeclaration
    : declaration
```

```
functionValueParameters
    : functionValueParameter*
functionValueParameter
    : parameter expression?
functionDeclaration
    : modifiers?
    FUN (typeParameters)? simpleIdentifier
    functionValueParameters
    type? functionBody?
functionBody
    : block
    | expression
variableDeclaration
    : annotation* simpleIdentifier type?
propertyDeclaration
    : modifiers? VAL typeParameters? variableDeclaration expression?
parameter
    : simpleIdentifier type
// SECTION: enumClasses
enumClassBody
    : enumEntries? classMemberDeclarations?
enumEntries
    : enumEntry*
enumEntry
    : modifiers? simpleIdentifier valueArguments? classBody?
```

```
// SECTION: types
type
    : parenthesizedType
    | typeReference
    | functionType
typeReference
    : userType
    DYNAMIC
userType
    : simpleUserType+
simpleUserType
    : simpleIdentifier (typeArguments)?
typeProjection
    : type | MULT
functionType
    : functionTypeParameters type
function Type Parameters\\
    : (parameter | type)*
parenthesizedType
    : type
// SECTION: statements
statements
    : statement*
statement
    : annotation*
```

```
( declaration
    | loopStatement
    | expression)
controlStructureBody
    : block
    | statement
block
    : statements
loopStatement
    : forStatement
    | whileStatement
    | doWhileStatement
forStatement
    : annotation* variableDeclaration expression
controlStructureBody?
whileStatement
    : expression controlStructureBody?
doWhileStatement
    : controlStructureBody? expression
// SECTION: expressions
expression
    : disjunction
disjunction
    : conjunction+
conjunction
    : equality+
```

```
equality
    : comparison (equalityOperator comparison)*
comparison
    : infixOperation (comparisonOperator infixOperation)?
infixOperation
    : elvisExpression (inOperator elvisExpression)*
elvisExpression
    : infixFunctionCall
infixFunctionCall
    : rangeExpression (simpleIdentifier rangeExpression)*
rangeExpression
    : additiveExpression+
additiveExpression
    : multiplicativeExpression (additiveOperator
multiplicativeExpression)*
multiplicativeExpression
    : asExpression (multiplicativeOperator asExpression)*
asExpression
    : comparisonWithLiteralRightSide
comparisonWithLiteralRightSide
    : prefixUnaryExpression (LANGLE literalConstant RANGLE
expression)*
    ;
prefixUnaryExpression
    : unaryPrefix* postfixUnaryExpression
```

```
unaryPrefix
    : annotation
    | prefixUnaryOperator
postfixUnaryExpression
    : primaryExpression postfixUnarySuffix*
postfixUnarySuffix
    | typeArguments
     callSuffix
    | indexingSuffix
     navigationSuffix
indexingSuffix
    : expression+
navigationSuffix
    : memberAccessOperator (simpleIdentifier |
parenthesizedExpression | CLASS)
callSuffix
    : typeArguments? valueArguments? annotatedLambda
    | typeArguments? valueArguments
annotatedLambda
    : annotation* lambdaLiteral
typeArguments
    : LANGLE typeProjection+ RANGLE
valueArguments
    : valueArgument*
valueArgument
    : annotation? simpleIdentifier? MULT? expression
```

```
primaryExpression
    : parenthesizedExpression
     simpleIdentifier
     literalConstant
      stringLiteral
      functionLiteral
     thisExpression
      superExpression
     ifExpression
     whenExpression
     jumpExpression
parenthesizedExpression
    : expression
literalConstant
    : BooleanLiteral
    | IntegerLiteral
    | HexLiteral
     BinLiteral
    | NullLiteral
stringLiteral
    : lineStringLiteral
lineStringLiteral
    : (lineStringContent | lineStringExpression)*
lineStringContent
    : LineStrText
    | LineStrEscapedChar
    LineStrRef
lineStringExpression
    : expression
lambdaLiteral
    : lambdaParameters? statements
```

```
lambdaParameters
    : lambdaParameter+
lambdaParameter
    : variableDeclaration
functionLiteral
    : lambdaLiteral
thisExpression
    : THIS
    | THIS AT
superExpression
    : SUPER (LANGLE type RANGLE)? (AT_NO_WS simpleIdentifier)?
ifExpression
    : expression controlStructureBody?
    | expression controlStructureBody? ELSE controlStructureBody?
whenSubject
    : (annotation* VAL variableDeclaration)? expression
whenExpression
    : whenSubject? whenEntry*
whenEntry
    : whenCondition+ controlStructureBody
    | ELSE controlStructureBody
whenCondition
    : expression
jumpExpression
```

```
: RETURN expression?
    | CONTINUE
    | BREAK
equalityOperator
    : EXCL_EQ
    | EQEQ
comparisonOperator
    : LANGLE
    | RANGLE
    l LE
    | GE
inOperator
    : IN
additiveOperator
    : ADD | SUB
multiplicativeOperator
    : MULT
prefixUnaryOperator
    : SUB
    | ADD
    excl
excl
    : EXCL_NO_WS
    | EXCL_WS
memberAccessOperator
// SECTION: modifiers
modifiers
    : (annotation | modifier)+
```

```
modifier
    : classModifier
    | memberModifier
      propertyModifier
    | inheritanceModifier
classModifier
    : ENUM
      SEALED
      ANNOTATION
     DATA
      INNER
memberModifier
    : OVERRIDE
    | LATEINIT
propertyModifier
    : CONST
inheritanceModifier
    : ABSTRACT
     FINAL
    | OPEN
// SECTION: annotations
annotation
    : singleAnnotation
singleAnnotation
    : (AT_NO_WS | AT_PRE_WS) unescapedAnnotation
unescapedAnnotation
    : constructorInvocation
    | userType
```

## // SECTION: identifiers

```
simpleIdentifier: Identifier
      ABSTRACT
      ANNOTATION
      BY
      CATCH
      COMPANION
      CONSTRUCTOR
      CROSSINLINE
      DATA
      DYNAMIC
      ENUM
      EXTERNAL
      FINAL
      FINALLY
      GET
      IMPORT
      INFIX
      INIT
      INLINE
      INNER
      INTERNAL
      LATEINIT
      NOINLINE
      OPEN
      OPERATOR
      0UT
      OVERRIDE
      PRIVATE
      PROTECTED
      PUBLIC
      REIFIED
      SEALED
      TAILREC
      SET
      VARARG
      WHERE
      FIELD
      PROPERTY
      RECEIVER
      PARAM
      SETPARAM
      DELEGATE
```

**FILE** 

```
| EXPECT
    | ACTUAL
     I CONST
    | SUSPEND
identifier
    : simpleIdentifier+
/**
 * Kotlin lexical grammar in ANTLR4 notation
 */
// SECTION: separatorsAndOperations
MULT: '*';
ADD: '+';
SUB: '-';
EXCL_WS: '!' Hidden;
EXCL_NO_WS: '!';
AT_NO_WS: '@';
AT PRE WS: (Hidden | NL) '@';
LANGLE: '<';
RANGLE: '>';
LE: '<=';
GE: '>=';
EXCL_EQ: '!=';
EQEQ: '==';
// SECTION: keywords
THIS_AT: 'this@' Identifier;
FILE: 'file';
FIELD: 'field';
PROPERTY: 'property';
GET: 'get';
SET: 'set';
RECEIVER: 'receiver';
PARAM: 'param';
SETPARAM: 'setparam';
DELEGATE: 'delegate';
PACKAGE: 'package';
IMPORT: 'import';
```

```
CLASS: 'class';
INTERFACE: 'interface';
FUN: 'fun':
VAL: 'val';
CONSTRUCTOR: 'constructor';
BY: 'by';
COMPANION: 'companion';
INIT: 'init';
THIS: 'this';
SUPER: 'super';
WHERE: 'where';
ELSE: 'else';
CATCH: 'catch';
FINALLY: 'finally';
RETURN: 'return';
CONTINUE: 'continue';
BREAK: 'break';
OUT: 'out';
DYNAMIC: 'dynamic';
// SECTION: lexicalModifiers
PUBLIC: 'public';
PRIVATE: 'private';
PROTECTED: 'protected';
INTERNAL: 'internal';
ENUM: 'enum';
SEALED: 'sealed';
ANNOTATION: 'annotation';
DATA: 'data';
INNER: 'inner';
TAILREC: 'tailrec';
OPERATOR: 'operator';
INLINE: 'inline';
INFIX: 'infix';
EXTERNAL: 'external';
SUSPEND: 'suspend';
OVERRIDE: 'override';
ABSTRACT: 'abstract';
FINAL: 'final';
OPEN: 'open';
CONST: 'const';
LATEINIT: 'lateinit';
VARARG: 'vararg';
NOINLINE: 'noinline';
CROSSINLINE: 'crossinline';
```

```
REIFIED: 'reified';
EXPECT: 'expect';
ACTUAL: 'actual';
// SECTION: literals
IntegerLiteral
    : DecDigitNoZero DecDigitOrSeparator* DecDigit
    | DecDigit
HexLiteral
    : '0' [xX] HexDigit HexDigitOrSeparator* HexDigit
    | '0' [xX] HexDigit
BinLiteral
    : '0' [bB] BinDigit BinDigitOrSeparator* BinDigit
    | '0' [bB] BinDigit
BooleanLiteral: 'true'| 'false';
NullLiteral: 'null';
// SECTION: lexicalIdentifiers
Identifier
    : (Letter | '_') (Letter | '_' | UnicodeDigit)*
| '`' ~([\r\n] | '`')+ '`'
// SECTION: strings
LineStrRef
    : FieldIdentifier
LineStrText
    : ~('\\' | '"' | '$')+ | '$'
LineStrEscapedChar
    : EscapedIdentifier
    | UniCharacterLiteral
```