```
/**
 * Kotlin syntax grammar in ANTLR4 notation
 */
// SECTION: general
kotlinFile
    : packageHeader importList topLevelObject*
packageHeader
    : (PACKAGE identifier)?
importList
    : importHeader*
importHeader
    : IMPORT identifier MULT?
topLevelObject
    : declaration
declaration
    : classDeclaration
    | functionDeclaration
    | propertyDeclaration
// SECTION: classes
classDeclaration
    : modifiers? CLASS simpleIdentifier
    typeParameters? primaryConstructor?
    delegationSpecifiers?
    (classBody | enumClassBody)?
primaryConstructor
    : (modifiers? CONSTRUCTOR)? classParameters
classBody
```

```
: classMemberDeclarations
classParameters
    : classParameter*
classParameter
    : modifiers? VAL? simpleIdentifier type expression?
delegationSpecifiers
    : annotatedDelegationSpecifier*
delegationSpecifier
    : constructorInvocation
    | userType
    | functionType
constructorInvocation
    : userType valueArguments
annotatedDelegationSpecifier
    : annotation* delegationSpecifier
typeParameters
    : LANGLE typeParameter+ RANGLE
typeParameter
    : simpleIdentifier type?
// SECTION: classMembers
classMemberDeclarations
    : classMemberDeclaration*
classMemberDeclaration
    : declaration
```

```
functionValueParameters
    : functionValueParameter*
functionValueParameter
    : parameter expression?
functionDeclaration
    : modifiers?
    FUN typeParameters? simpleIdentifier
    functionValueParameters
    type? functionBody?
functionBody
    : block
    | expression
variableDeclaration
    : annotation∗ simpleIdentifier type?
propertyDeclaration
    : modifiers? VAL typeParameters? variableDeclaration expression?
parameter
    : simpleIdentifier type
// SECTION: enumClasses
enumClassBody
    : enumEntries? classMemberDeclarations?
enumEntries
    : enumEntry*
enumEntry
    : modifiers? simpleIdentifier valueArguments? classBody?
```

```
// SECTION: types
type
    : parenthesizedType
    | typeReference
    | functionType
typeReference
    : userType
    DYNAMIC
userType
    : simpleUserType+
simpleUserType
    : simpleIdentifier (typeArguments)?
typeProjection
    : type | MULT
functionType
    : functionTypeParameters type
functionTypeParameters
    : (parameter | type)*
parenthesizedType
    : type
// SECTION: statements
statements
    : statement*
statement
    : annotation*
```

```
( declaration
    | loopStatement
    | expression)
controlStructureBody
    : block
    | statement
block
    : statements
loopStatement
    : forStatement
    | whileStatement
    | doWhileStatement
forStatement
    : annotation* variableDeclaration expression
controlStructureBody?
whileStatement
    : expression controlStructureBody?
doWhileStatement
    : controlStructureBody? expression
// SECTION: expressions
expression
    : disjunction
disjunction
    : conjunction+
conjunction
    : equality+
```

```
equality
    : comparison (equalityOperator comparison)*
comparison
    : infixOperation (comparisonOperator infixOperation)?
infixOperation
    : elvisExpression (inOperator elvisExpression)*
elvisExpression
    : infixFunctionCall
infixFunctionCall
    : rangeExpression (simpleIdentifier rangeExpression)*
rangeExpression
    : additiveExpression+
additiveExpression
    : multiplicativeExpression (additiveOperator
multiplicativeExpression)*
multiplicativeExpression
    : asExpression (multiplicativeOperator asExpression)*
asExpression
    : comparisonWithLiteralRightSide
comparisonWithLiteralRightSide
    : prefixUnaryExpression (LANGLE literalConstant RANGLE
expression)*
    ;
prefixUnaryExpression
    : unaryPrefix* postfixUnaryExpression
```

```
unaryPrefix
    : annotation
    | prefixUnaryOperator
postfixUnaryExpression
    : primaryExpression postfixUnarySuffix*
postfixUnarySuffix
      typeArguments
    | callSuffix
    | indexingSuffix
     navigationSuffix
indexingSuffix
    : expression+
navigationSuffix
    : memberAccessOperator (simpleIdentifier |
parenthesizedExpression | CLASS)
callSuffix
    : typeArguments? valueArguments? annotatedLambda
    | typeArguments? valueArguments
annotatedLambda
    : annotation* lambdaLiteral
typeArguments
    : LANGLE typeProjection+ RANGLE
valueArguments
    : valueArgument*
valueArgument
    : annotation? simpleIdentifier? MULT? expression
```

```
primaryExpression
    : parenthesizedExpression
     simpleIdentifier
     literalConstant
      stringLiteral
     functionLiteral
     thisExpression
     superExpression
     ifExpression
    whenExpression
     jumpExpression
parenthesizedExpression
    : expression
literalConstant
    : BooleanLiteral
    | IntegerLiteral
    | HexLiteral
    BinLiteral
    | NullLiteral
stringLiteral
    : lineStringLiteral
lineStringLiteral
    : (lineStringContent | lineStringExpression)*
lineStringContent
    : LineStrText
    | LineStrEscapedChar
    | LineStrRef
lineStringExpression
    : expression
lambdaLiteral
    : lambdaParameters? statements
```

```
lambdaParameters
    : lambdaParameter+
lambdaParameter
    : variableDeclaration
functionLiteral
    : lambdaLiteral
thisExpression
    : THIS
superExpression
    : SUPER (LANGLE type RANGLE)? (AT_NO_WS simpleIdentifier)?
ifExpression
    : expression controlStructureBody?
    | expression controlStructureBody? ELSE controlStructureBody?
whenSubject
    : (annotation* VAL variableDeclaration)? expression
whenExpression
    : whenSubject? whenEntry*
whenEntry
    : whenCondition+ controlStructureBody
    | ELSE controlStructureBody
whenCondition
    : expression
    : rangeTest
rangeTest
```

```
: inOperator expression
jumpExpression
    : RETURN expression?
    | CONTINUE
    | BREAK
equalityOperator
    : EXCL_EQ
    | EQEQ
comparisonOperator
    : LANGLE
    | RANGLE
    | LE
    | GE
inOperator
    : IN | NOT_IN
additiveOperator
    : ADD | SUB
multiplicativeOperator
    : MULT
    | DIV
    j MOD
prefixUnaryOperator
    : SUB
    | ADD
    | excl
excl
    : EXCL_NO_WS
    | EXCL_WS
memberAccessOperator
```

```
// SECTION: modifiers
modifiers
    : (annotation | modifier)+
modifier
    : classModifier
    | memberModifier
    | visibilityModifier
    | inheritanceModifier
classModifier
    : ENUM
      SEALED
      ANNOTATION
     DATA
      INNER
memberModifier
    : OVERRIDE
    | LATEINIT
visibilityModifier
    : PUBLIC
    | PRIVATE
    .
I INTERNAL
    | PROTECTED
inheritanceModifier
    : ABSTRACT
    | FINAL
    | OPEN
// SECTION: annotations
annotation
    : singleAnnotation
```

```
singleAnnotation
    : (AT_NO_WS | AT_PRE_WS) unescapedAnnotation
unescaped Annotation\\
    : constructorInvocation
    | userType
// SECTION: identifiers
simpleIdentifier: Identifier
    | ABSTRACT
      ANNOTATION
      BY
      CATCH
      COMPANION
      CONSTRUCTOR
      CROSSINLINE
      DATA
      DYNAMIC
      ENUM
      EXTERNAL
      FINAL
      FINALLY
      GET
      IMPORT
      INFIX
      INIT
      INLINE
      INNER
      INTERNAL
      LATEINIT
      NOINLINE
      OPEN
      OPERATOR
      0UT
      OVERRIDE
      PRIVATE
      PROTECTED
      PUBLIC
      REIFIED
      SEALED
      TAILREC
      SET
```

```
VARARG
      WHERE
     | FIELD
     | PROPERTY
     | RECEIVER
     | PARAM
     | SETPARAM
     | DELEGATE
     | FILE
     | EXPECT
     | ACTUAL
     I CONST
     | SUSPEND
identifier
    : simpleIdentifier+
/**
 * Kotlin lexical grammar in ANTLR4 notation
 */
// SECTION: separatorsAndOperations
MULT: '*';
MOD: '%';
DIV: '/';
ADD: '+';
SUB: '-';
EXCL_WS: '!' Hidden;
EXCL NO WS: '!';
AT_NO_WS: '@';
AT PRE WS: (Hidden | NL) '@';
LANGLE: '<';
RANGLE: '>';
LE: '<=';
GE: '>=';
EXCL_EQ: '!=';
EQEQ: '==';
// SECTION: keywords
FILE: 'file';
FIELD: 'field';
PROPERTY: 'property';
```

```
GET: 'get';
SET: 'set';
RECEIVER: 'receiver';
PARAM: 'param';
SETPARAM: 'setparam';
DELEGATE: 'delegate';
PACKAGE: 'package';
IMPORT: 'import';
CLASS: 'class';
FUN: 'fun';
VAL: 'val';
CONSTRUCTOR: 'constructor';
BY: 'by';
COMPANION: 'companion';
INIT: 'init';
THIS: 'this';
SUPER: 'super';
WHERE: 'where';
ELSE: 'else';
CATCH: 'catch';
FINALLY: 'finally';
RETURN: 'return';
CONTINUE: 'continue';
BREAK: 'break';
IN: 'in';
NOT_IN '!in';
OUT: 'out';
DYNAMIC: 'dynamic';
// SECTION: lexicalModifiers
PUBLIC: 'public';
PRIVATE: 'private';
PROTECTED: 'protected';
INTERNAL: 'internal';
ENUM: 'enum';
SEALED: 'sealed';
ANNOTATION: 'annotation';
DATA: 'data';
INNER: 'inner';
TAILREC: 'tailrec';
OPERATOR: 'operator';
INLINE: 'inline';
INFIX: 'infix';
EXTERNAL: 'external';
```

```
SUSPEND: 'suspend';
OVERRIDE: 'override';
ABSTRACT: 'abstract';
FINAL: 'final';
OPEN: 'open';
CONST: 'const';
LATEINIT: 'lateinit';
VARARG: 'vararg';
NOINLINE: 'noinline';
CROSSINLINE: 'crossinline';
REIFIED: 'reified';
EXPECT: 'expect';
ACTUAL: 'actual';
// SECTION: literals
IntegerLiteral
    : DecDigitNoZero DecDigitOrSeparator* DecDigit
    | DecDigit
HexLiteral
    : '0' [xX] HexDigit HexDigitOrSeparator* HexDigit
    | '0' [xX] HexDigit
BinLiteral
    : '0' [bB] BinDigit BinDigitOrSeparator* BinDigit
    | '0' [bB] BinDigit
BooleanLiteral: 'true'| 'false';
NullLiteral: 'null';
// SECTION: lexicalIdentifiers
Identifier
    : (Letter | '_') (Letter | '_' | UnicodeDigit)*
| '`' ~([\r\n] | '`')+ '`'
// SECTION: strings
LineStrRef
    : FieldIdentifier
```

```
;
LineStrText
: ~('\\' | '"' | '$')+ | '$';
LineStrEscapedChar
: EscapedIdentifier
| UniCharacterLiteral
```