

>>> Introduction to SQL  
>>> Featuring MySQL and T-SQL

Daniel Fryer <sup>†</sup>

Nov, 2021

---

<sup>†</sup>[daniel@vfryer.com](mailto:daniel@vfryer.com)

```
>>> Daily schedule
```

---

| Timetable |   |         |                  |          |
|-----------|---|---------|------------------|----------|
| 9:00am    | - | 10:30am | lecture 1        | (1.5 hr) |
| 10:30am   | - | 11:00am | morning tea      | (30 min) |
| 11:00am   | - | 12:30pm | lecture 2        | (1.5 hr) |
| 12:30pm   | - | 1:30pm  | lunch            | (1 hr)   |
| 1:30pm    | - | 3:00pm  | guided exercises | (1.5 hr) |
| 3:00pm    | - | 5:00pm  | one-on-one help  | (2 hr)   |

---

>>> Where are we now?

Day 2

1. Recap of day 1
2. Reading the docs
3. Aggregating
4. Subqueries
5. Windowing

Send me questions and give feedback

Page is hyperlinked: click a topic above to jump to it.



>>> Where are we now?

## Day 2

1. Recap of day 1
2. Reading the docs
3. Aggregating
4. Subqueries
5. Windowing

Send me questions and give feedback

Page is hyperlinked: click a topic above to jump to it.

>>> Reading the docs

- \* Quickly look something up when you forget syntax
- \* Learn new things while you browse and decipher
- \* Gain a deeper understanding
- \* It actually gets easy pretty quickly

```
>>> Reading the docs
```

- \* Quickly look something up when you forget syntax
- \* Learn new things while you browse and decipher
- \* Gain a deeper understanding
- \* It actually gets easy pretty quickly

Be brave, the documentation can sense fear

## >>> Data Manipulation Language (DML)

Later, we will learn some Data Definition Language (DDL).

- \* [Click here for MySQL DML docs](#)

- \* [Click here for T-SQL DML docs](#)



>>> Data Manipulation Language (DML)

Later, we will learn some Data Definition Language (DDL).

- \* [Click here for MySQL DML docs](#)

- \* [Click here for T-SQL DML docs](#)

Wait, what have we been learning?

- \* [Click here for MySQL SELECT docs](#)

- \* [Click here for T-SQL SELECT docs](#)

The word 'query' actually refers to `SELECT`!

>>> The syntax conventions

Why is it so hard to read? Syntax, used to make the documentation clearer and more succinct.

- \* [Click here for MySQL Syntax Conventions](#)
- \* [Click here for T-SQL Syntax Conventions](#)

## >>> The important syntax conventions

| MySQL       | T-SQL     | Description                      |
|-------------|-----------|----------------------------------|
| [a]         | [a]       | a is optional                    |
| {a}         | {a}       | a is not optional                |
| [a b]       | [a b]     | optionally, choose a or b        |
| {a b}       | {a b}     | not optional, choose a or b      |
| a [, a] ... | a [,...n] | optionally repeat a (with comma) |
| label       | <label>   | a label/placeholder              |

>>> The SELECT clause

---

```
SELECT [ALL | DISTINCT] select_expr [, select_expr] ...  
[ INTO <new_table> ]  
  
[ FROM <table_source> [,...n] ]  
  
[ WHERE <search_condition> ]  
  
[ GROUP BY {col_name | expr }, ... ]  
  
[ HAVING <search_condition> ]  
  
[ ORDER BY {order_by_expression [ ASC | DESC ]} [,...n] ]
```

---

>>> The SELECT clause

Square brackets mean content is optional.

---

```
SELECT [ALL | DISTINCT] select_expr [, select_expr] ...
```

```
[ INTO <new_table> ]
```

```
[ FROM <table_source> [,...n] ]
```

```
[ WHERE <search_condition> ]
```

```
[ GROUP BY {col_name | expr }, ... ]
```

```
[ HAVING <search_condition> ]
```

```
[ ORDER BY {order_by_expression [ ASC | DESC ]} [,...n] ]
```

---

>>> The SELECT clause

Curly brackets mean content is mandatory.

---

```
SELECT [ALL | DISTINCT] select_expr [, select_expr] ...  
[ INTO <new_table> ]  
  
[ FROM <table_source> [,...n] ]  
  
[ WHERE <search_condition> ]  
  
[ GROUP BY {col_name | expr }, ... ]  
  
[ HAVING <search_condition> ]  
  
[ ORDER BY {order_by_expression [ ASC | DESC ]} [,...n] ]
```

---

>>> The SELECT clause

Vertical line means choose one.

---

```
SELECT [ALL | DISTINCT] select_expr [, select_expr] ...
```

```
[ INTO <new_table> ]
```

```
[ FROM <table_source> [,...n] ]
```

```
[ WHERE <search_condition> ]
```

```
[ GROUP BY {col_name | expr }, ... ]
```

```
[ HAVING <search_condition> ]
```

```
[ ORDER BY {order_by_expression [ ASC | DESC ]} [,...n] ]
```

---

>>> The SELECT clause

must choose one.

---

```
SELECT [ALL | DISTINCT] select_expr [, select_expr] ...
```

```
[ INTO <new_table> ]
```

```
[ FROM <table_source> [,...n] ]
```

```
[ WHERE <search_condition> ]
```

```
[ GROUP BY {col_name | expr }, ... ]
```

```
[ HAVING <search_condition> ]
```

```
[ ORDER BY {order_by_expression [ ASC | DESC ]} [,...n] ]
```

---



>>> The SELECT clause

optionally choose one.

---

```
SELECT [ALL | DISTINCT] select_expr [, select_expr] ...
```

```
[ INTO <new_table> ]
```

```
[ FROM <table_source> [,...n] ]
```

```
[ WHERE <search_condition> ]
```

```
[ GROUP BY {col_name | expr }, ... ]
```

```
[ HAVING <search_condition> ]
```

```
[ ORDER BY {order_by_expression [ ASC | DESC ]} [,...n] ]
```

---

>>> The SELECT clause

Repeat with commas (T-SQL)

---

```
SELECT [ALL | DISTINCT] select_expr [, select_expr] ...
```

```
[ INTO <new_table> ]
```

```
[ FROM <table_source> [,...n] ]
```

```
[ WHERE <search_condition> ]
```

```
[ GROUP BY {col_name | expr }, ... ]
```

```
[ HAVING <search_condition> ]
```

```
[ ORDER BY {order_by_expression [ ASC | DESC ]} [,...n] ]
```

---

>>> The SELECT clause

Repeat with commas (MySQL)

---

```
SELECT [ALL | DISTINCT] select_expr [, select_expr] ...  
[ INTO <new_table> ]  
  
[ FROM <table_source> [,...n] ]  
  
[ WHERE <search_condition> ]  
  
[ GROUP BY {col_name | expr }, ... ]  
  
[ HAVING <search_condition> ]  
  
[ ORDER BY {order_by_expression [ ASC | DESC ]} [,...n] ]
```

---

>>> The SELECT clause

Also repeat with commas (MySQL)

---

```
SELECT [ALL | DISTINCT] select_expr [, select_expr] ...  
[ INTO <new_table> ]  
  
[ FROM <table_source> [,...n] ]  
  
[ WHERE <search_condition> ]  
  
[ GROUP BY {col_name | expr }, ... ]  
  
[ HAVING <search_condition> ]  
  
[ ORDER BY {order_by_expression [ ASC | DESC ]} [,...n] ]
```

---

>>> The SELECT clause

## Labels or placeholders

---

```
SELECT [ALL | DISTINCT] select_expr [, select_expr] ...
```

```
[ INTO <new_table> ]
```

```
[ FROM <table_source> [,...n] ]
```

```
[ WHERE <search_condition> ]
```

```
[ GROUP BY {col_name | expr }, ... ]
```

```
[ HAVING <search_condition> ]
```

```
[ ORDER BY {order_by_expression [ ASC | DESC ]} [,...n] ]
```

---

```
>>> A discovery...
```

---

```
SELECT [ALL|DISTINCT] FirstName, LastName, FavColour
```

---

From the MySQL SELECT docs ([click here](#)):

The ALL and DISTINCT modifiers specify whether duplicate rows should be returned. ALL (the default), specifies that all matching rows should be returned, including duplicates. DISTINCT specifies removal of duplicate rows from the result set. It is an error to specify both modifiers. DISTINCTROW is a synonym for DISTINCT.

```
>>> Read the docs: FROM
```

T-SQL will often use `::=` to define placeholders.

```
FROM {<table_source>} [...n]
```

where

```
{<table_source>} ::= table_or_view_name [[AS] table_alias]
```

```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [...n]
```



```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [,...n]
```

```
* { } curly braces group required items
```

```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [...n]
```

- \* { } curly braces group required items
- \* <label> placeholder for a block of syntax

```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [,...n]
```

- \* { } curly braces group required items
- \* <label> placeholder for a block of syntax
- \* [,...n] means you can repeat with commas between

```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [,...n]
```

- \* { } curly braces group required items
- \* <label> placeholder for a block of syntax
- \* [,...n] means you can repeat with commas between

```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [,...n]
```

- \* { } curly braces group required items
- \* <label> placeholder for a block of syntax
- \* [,...n] means you can repeat with commas between

```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [,...n]
```

where

```
<table_source> ::= table_or_view_name [[AS] table_alias]
```

- \* { } curly braces group required items
- \* <label> placeholder for a block of syntax
- \* [,...n] means you can repeat with commas between
- \* <label> ::= defining the placeholder

```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [,...n]
```

where

```
<table_source> ::= table_or_view_name [[AS] table_alias]
```

- \* { } curly braces group required items
- \* <label> placeholder for a block of syntax
- \* [,...n] means you can repeat with commas between
- \* <label> ::= defining the placeholder

```
FROM MyTable, MyOtherTable
```

```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [,...n]
```

where

```
<table_source> ::= table_or_view_name [[AS] table_alias]
```

- \* { } curly braces group required items
- \* <label> placeholder for a block of syntax
- \* [,...n] means you can repeat with commas between
- \* <label> ::= defining the placeholder
- \* [ ] square brackets indicate optional items



```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [,...n]
```

where

```
<table_source> ::= table_or_view_name [[AS] table_alias]
```

- \* { } curly braces group required items
- \* <label> placeholder for a block of syntax
- \* [,...n] means you can repeat with commas between
- \* <label> ::= defining the placeholder
- \* [ ] square brackets indicate optional items

```
FROM MyTable M
```

```
>>> Reading the docs: FROM
```

```
FROM {<table_source>} [,...n]
```

where

```
<table_source> ::= table_or_view_name [[AS] table_alias]
```

- \* { } curly braces group required items
- \* <label> placeholder for a block of syntax
- \* [,...n] means you can repeat with commas between
- \* <label> ::= defining the placeholder
- \* [ ] square brackets indicate optional items

```
FROM MyTable AS M
```

```
>>> Feeling confident?
```

```
Have a look at the T-SQL FROM documentation
```

```
>>> Feeling confident?
```

Have a look at the **T-SQL FROM** documentation

- \* It really is more of the same
- \* It gets easier very quickly with practice
- \* Google, StackExchange, etc
- \* Beginner tutorial
- \* Syntax guides and **cheat sheets**

```
>>> Practice
```

```
<greeting> ::= {{Hello | Hi} [...n] .}  
              [Do you {love | hate} reading the docs?]
```

```
* Hello.
```

>>> Practice

```
<greeting> ::= {{Hello | Hi} [,...n] .}  
              [Do you {love | hate} reading the docs?]
```

\* Hello.

\* Hi.

>>> Practice

```
<greeting> ::= {{Hello | Hi} [...n] .}  
              [Do you {love | hate} reading the docs?]
```

\* Hello.

\* Hi.

\* Hello. Do you love reading the docs?

>>> Practice

```
<greeting> ::= {{Hello | Hi} [...n] .}  
              [Do you {love | hate} reading the docs?]
```

- \* Hello.
- \* Hi.
- \* Hello. Do you love reading the docs?
- \* Hi. Do you love reading the docs?



>>> Practice

```
<greeting> ::= {{Hello | Hi} [,...n] .}  
              [Do you {love | hate} reading the docs?]
```

- \* Hello.
- \* Hi.
- \* Hello. Do you love reading the docs?
- \* Hi. Do you love reading the docs?
- \* Hello, Hello, Hi, Hello, Hi, Hi.

>>> Practice

```
<greeting> ::= {{Hello | Hi} [,...n] .}  
              [Do you {love | hate} reading the docs?]
```

- \* Hello.
- \* Hi.
- \* Hello. Do you love reading the docs?
- \* Hi. Do you love reading the docs?
- \* Hello, Hello, Hi, Hello, Hi, Hi.
- \* Hello, Hi, Hello, Hello. Do you love reading the docs?

>>> Practice

```
<greeting> ::= {{Hello | Hi} [,...n] .}  
              [Do you {love | hate} reading the docs?]
```

- \* Hello.
- \* Hi.
- \* Hello. Do you love reading the docs?
- \* Hi. Do you love reading the docs?
- \* Hello, Hello, Hi, Hello, Hi, Hi.
- \* Hello, Hi, Hello, Hello. Do you love reading the docs?
- \* etc.

```
>>> Example from the docs (logical operator IN)
```

```
test_expression [ NOT ] IN ( subquery | expression [ ,...n ] )
```

Don't miss the round brackets!

```
>>> Example from the docs (logical operator IN)
```

```
test_expression [ NOT ] IN ( subquery | expression [ ,...n ] )
```

```
* test_expression IN (expression)
```

```
Example: FavColour IN ('red')
```

>>> Example from the docs (logical operator IN)

```
test_expression [ NOT ] IN ( subquery | expression [ ,...n ] )
```

- \* test\_expression IN (expression)

- \* test\_expression IN (subquery)

Example: FriendID IN (SELECT FriendID FROM Notes.Pets)

```
>>> Example from the docs (logical operator IN)
```

```
test_expression [ NOT ] IN ( subquery | expression [ ,...n ] )
```

- \* test\_expression IN (expression)
- \* test\_expression IN (subquery)
- \* test\_expression NOT IN (expression)

Example: FavColour NOT IN ('red')

>>> Example from the docs (logical operator IN)

```
test_expression [ NOT ] IN ( subquery | expression [ ,...n ] )
```

- \* test\_expression IN (expression)
- \* test\_expression IN (subquery)
- \* test\_expression NOT IN (expression)
- \* test\_expression NOT IN (subquery)

Example: FriendID NOT IN (SELECT FriendID FROM Notes.Pets)



>>> Example from the docs (logical operator IN)

```
test_expression [ NOT ] IN ( subquery | expression [ ,...n ] )
```

- \* test\_expression IN (expression)
- \* test\_expression IN (subquery)
- \* test\_expression NOT IN (expression)
- \* test\_expression NOT IN (subquery)
- \* test\_expression NOT IN (expression, expression, expression)

Example: FavColour IN ('red', 'blue', 'green')



>>> Where are we now?

Day 2

1. Recap of day 1
2. Reading the docs
3. Aggregating
4. Subqueries
5. Windowing

Send me questions and give feedback

Page is hyperlinked: click a topic above to jump to it.

## >>> Aggregating queries

Aggregating queries collect the rows of a table into groups, and return a single value for each group. They can also discard groups.

We will cover:

1. GROUP BY clause
2. Aggregation function
3. HAVING clause

## >>> Aggregating queries

Aggregating queries collect the rows of a table into groups, and return a single value for each group. They can also discard groups.

We will cover:

1. GROUP BY clause - creates the groups
2. Aggregation function
3. HAVING clause

## >>> Aggregating queries

Aggregating queries collect the rows of a table into groups, and return a single value for each group. They can also discard groups.

We will cover:

1. GROUP BY clause - creates the groups
2. Aggregation function - computes one value for each group
3. HAVING clause

## >>> Aggregating queries

Aggregating queries collect the rows of a table into groups, and return a single value for each group. They can also discard groups.

We will cover:

1. GROUP BY clause - creates the groups
2. Aggregation function - computes one value for each group
3. HAVING clause - discards groups

The HAVING clause discards groups just like the WHERE clause discards rows.

```
>>> SQL clause: GROUP BY
```

The `GROUP BY` clause groups the rows of a table according to the values of one or more columns. The easiest way to understand it is with examples.

We will look at the execution of this query:

---

```
SELECT P.friendID  
FROM Notes.Pets P  
GROUP BY P.friendID;
```

---



```
>>> SQL clause: GROUP BY
```

```
FROM Notes.Pets P
```

| Pets  |         |            |          |
|-------|---------|------------|----------|
| PetID | PetName | PetDOB     | FriendID |
| 1     | Chikin  | 24/09/2016 | 2        |
| 2     | Cauchy  | 01/03/2012 | 3        |
| 3     | Gauss   | 01/03/2012 | 3        |

```
>>> SQL clause: GROUP BY
```

GROUP BY P.FriendID

| Pets  |         |            |          |
|-------|---------|------------|----------|
| PetID | PetName | PetDOB     | FriendID |
| 1     | Chikin  | 24/09/2016 | 2        |
| 2     | Cauchy  | 01/03/2012 | 3        |
| 3     | Gauss   | 01/03/2012 | 3        |

```
>>> SQL clause: GROUP BY
```

GROUP BY P.FriendID

| Unnamed |                    |                             |          |
|---------|--------------------|-----------------------------|----------|
| PetID   | PetName            | PetDOB                      | FriendID |
| {2}     | {Chikin}           | {24/09/2016}                | 2        |
| {2,3}   | {Cauchy,<br>Gauss} | {01/03/2012,<br>01/03/2012} | 3        |

```
>>> SQL clause: GROUP BY
```

```
SELECT P.FriendID
```

| Unnamed |                    |                             |          |
|---------|--------------------|-----------------------------|----------|
| PetID   | PetName            | PetDOB                      | FriendID |
| {2}     | {Chikin}           | {24/09/2016}                | 2        |
| {2,3}   | {Cauchy,<br>Gauss} | {01/03/2012,<br>01/03/2012} | 3        |

```
>>> SQL clause: GROUP BY
```

result

| Unnamed  |
|----------|
| FriendID |
| 2        |
| 3        |

```
>>> Can we select any of the other columns?
```

```
SELECT ???
```

| Unnamed |                    |                             |          |
|---------|--------------------|-----------------------------|----------|
| PetID   | PetName            | PetDOB                      | FriendID |
| {2}     | {Chikin}           | {24/09/2016}                | 2        |
| {2,3}   | {Cauchy,<br>Gauss} | {01/03/2012,<br>01/03/2012} | 3        |

Error: SQL can't be sure the entries are atomic.

>>> What will happen if we run this?

---

```
SELECT P.friendID, P.petDOB  
FROM Notes.Pets P  
GROUP BY P.friendID;
```

---





```
>>> Error
```

```
Msg 8120, Level 16, State 1, Line 1  
Column 'Notes.Pets.PetDOB' is invalid in the select list  
because it is not contained in either an aggregate function  
or the GROUP BY clause.
```

```
>>> This will fix the error
```

---

```
SELECT P.friendID, P.petDOB  
FROM Notes.Pets P  
GROUP BY P.friendID, P.petDOB;
```

---

```
>>> SQL clause: GROUP BY
```

```
GROUP BY P.FriendID, P.PetDOB
```

| Pets  |         |            |          |
|-------|---------|------------|----------|
| PetID | PetName | PetDOB     | FriendID |
| 1     | Chikin  | 24/09/2016 | 2        |
| 2     | Cauchy  | 01/03/2012 | 3        |
| 3     | Gauss   | 01/03/2012 | 3        |

```
>>> SQL clause: GROUP BY
```

```
GROUP BY P.FriendID, P.PetDOB
```

| Unnamed |                    |            |          |
|---------|--------------------|------------|----------|
| PetID   | PetName            | PetDOB     | FriendID |
| {2}     | {Chikin}           | 24/09/2016 | 2        |
| {2,3}   | {Cauchy,<br>Gauss} | 01/03/2012 | 3        |

```
>>> More examples
```

Watch the curly braces

| Letters  |          |     |
|----------|----------|-----|
| <i>A</i> | <i>B</i> | Num |
| a        | b        | 1   |
| a        | c        | 2   |
| a        | b        | 3   |
| a        | c        | 4   |

- \* GROUP BY B
- \* GROUP BY A
- \* GROUP BY A, B

```
>>> Solutions
```

```
* GROUP BY B
```

| Unnamed |     |        |
|---------|-----|--------|
| $A$     | $B$ | Num    |
| {a, a}  | b   | {1, 3} |
| {a, a}  | c   | {2, 4} |

```
>>> Solutions
```

```
* GROUP BY B
```

| Unnamed  |          |        |
|----------|----------|--------|
| <i>A</i> | <i>B</i> | Num    |
| {a, a}   | b        | {1, 3} |
| {a, a}   | c        | {2, 4} |

```
* GROUP BY A
```

| Unnamed  |              |              |
|----------|--------------|--------------|
| <i>A</i> | <i>B</i>     | Num          |
| a        | {b, c, b, c} | {1, 2, 3, 4} |

## >>> Solutions

\* GROUP BY B

| Unnamed  |          |        |
|----------|----------|--------|
| <i>A</i> | <i>B</i> | Num    |
| {a, a}   | b        | {1, 3} |
| {a, a}   | c        | {2, 4} |

\* GROUP BY A

| Unnamed  |              |              |
|----------|--------------|--------------|
| <i>A</i> | <i>B</i>     | Num          |
| a        | {b, c, b, c} | {1, 2, 3, 4} |

\* GROUP BY A, B

| Unnamed  |          |        |
|----------|----------|--------|
| <i>A</i> | <i>B</i> | Num    |
| a        | b        | {1, 3} |
| a        | c        | {2, 4} |



```
>>> Aggregation functions
```

Aggregation functions compute one value for each group.  
Aggregating frees us to select more columns.

We will look at the execution of this query:

---

```
SELECT RP.gender, AVG(RP.age) AS AverageAge  
FROM Notes.RandomPeople RP  
GROUP BY RP.gender;
```

---

```
>>> Aggregation functions
```

Aggregation functions compute one value for each group.  
Aggregating frees us to select more columns.

We will look at the execution of this query:

---

```
SELECT RP.gender, AVG(RP.age) AS AverageAge  
FROM Notes.RandomPeople RP  
GROUP BY RP.gender;
```

---

Aggregation function

```
>>> Aggregation functions
```

Aggregation functions compute one value for each group.  
Aggregating frees us to select more columns.

We will look at the execution of this query:

---

```
SELECT RP.gender, AVG(RP.age) AS AverageAge  
FROM Notes.RandomPeople RP  
GROUP BY RP.gender;
```

---

Column name alias

```
>>> Aggregation function: AVG
```

```
FROM Notes.RandomPeople RP
```

| RandomPeople  |        |     |
|---------------|--------|-----|
| PersonName    | Gender | Age |
| Beyoncé       | F      | 37  |
| Laura Marling | F      | 28  |
| Darren Hayes  | M      | 46  |
| Bret McKenzie | M      | 42  |
| Jack Monroe   | NB     | 30  |

```
>>> Aggregation function: AVG
```

GROUP BY RP.Gender

| RandomPeople  |        |     |
|---------------|--------|-----|
| Name          | Gender | Age |
| Beyoncé       | F      | 37  |
| Laura Marling | F      | 28  |
| Darren Hayes  | M      | 46  |
| Bret McKenzie | M      | 42  |
| Jack Monroe   | NB     | 30  |

```
>>> Aggregation function: AVG
```

GROUP BY RP.Gender

| Unnamed                          |        |             |
|----------------------------------|--------|-------------|
| PersonName                       | Gender | Age         |
| {Beyoncé,<br>Laura Marling}      | F      | {37,<br>28} |
| {Darren Hayes,<br>Bret McKenzie} | M      | {46,<br>42} |
| {Jack Monroe}                    | NB     | {30}        |

```
>>> Aggregation function: AVG
```

AVG(RP.Age)

| Unnamed                          |        |              |
|----------------------------------|--------|--------------|
| PersonName                       | Gender | (unnamed)    |
| {Beyoncé,<br>Laura Marling}      | F      | AVG({37,28}) |
| {Darren Hayes,<br>Bret McKenzie} | M      | AVG({46,42}) |
| {Jack Monroe}                    | NB     | AVG({30})    |

```
>>> Aggregation function: AVG
```

AVG(RP.Age)

| Unnamed                          |        |           |
|----------------------------------|--------|-----------|
| PersonName                       | Gender | (unnamed) |
| {Beyoncé,<br>Laura Marling}      | F      | 32.5      |
| {Darren Hayes,<br>Bret McKenzie} | M      | 44        |
| {Jack Monroe}                    | NB     | 30        |



```
>>> Aggregation function: AVG
```

```
SELECT RP.Gender, AVG(RP.Age) AS AverageAge
```

| Unnamed                          |        |           |
|----------------------------------|--------|-----------|
| PersonName                       | Gender | (unnamed) |
| {Beyoncé,<br>Laura Marling}      | F      | 32.5      |
| {Darren Hayes,<br>Bret McKenzie} | M      | 44        |
| {Jack Monroe}                    | NB     | 30        |

```
>>> Aggregation function: AVG
```

result

| Unnamed |            |
|---------|------------|
| Gender  | AverageAge |
| F       | 32.5       |
| M       | 44         |
| NB      | 30         |

We retrieved the average age for each gender in the table!

>>> What happens if we throw in a WHERE clause?

We will look at the execution of this query:

---

```
SELECT RP.gender, AVG(RP.age) AS AverageAge
FROM Notes.RandomPeople RP
WHERE RP.gender = 'F'
GROUP BY RP.gender;
```

---

>>> What happens if we throw in a WHERE clause?

FROM Notes.RandomPeople RP

| RandomPeople  |        |     |
|---------------|--------|-----|
| PersonName    | Gender | Age |
| Beyoncé       | F      | 37  |
| Laura Marling | F      | 28  |
| Darren Hayes  | M      | 46  |
| Bret McKenzie | M      | 42  |
| Jack Monroe   | NB     | 30  |

>>> What happens if we throw in a WHERE clause?

WHERE RP.Gender = 'F'

| RandomPeople  |        |     |
|---------------|--------|-----|
| PersonName    | Gender | Age |
| Beyoncé       | F      | 37  |
| Laura Marling | F      | 28  |
| Darren Hayes  | M      | 46  |
| Bret McKenzie | M      | 42  |
| Jack Monroe   | NB     | 30  |

>>> What happens if we throw in a WHERE clause?

GROUP BY RP.Gender

| Unnamed                     |        |             |
|-----------------------------|--------|-------------|
| PersonName                  | Gender | Age         |
| {Beyoncé,<br>Laura Marling} | F      | {37,<br>28} |

>>> What happens if we throw in a WHERE clause?

AVG(RP.Age)

| Unnamed                     |        |           |
|-----------------------------|--------|-----------|
| PersonName                  | Gender | (unnamed) |
| {Beyoncé,<br>Laura Marling} | F      | 32.5      |

>>> What happens if we throw in a WHERE clause?

```
SELECT RP.Gender, AVG(RP.Age) AS AverageAge
```

| Unnamed                     |        |           |
|-----------------------------|--------|-----------|
| PersonName                  | Gender | (unnamed) |
| {Beyoncé,<br>Laura Marling} | F      | 32.5      |



```
>>> What happens if we throw in a WHERE clause?
```

```
result
```

| Unnamed |            |
|---------|------------|
| Gender  | AverageAge |
| F       | 32.5       |

We retrieved the average age for females in the table!



```
>>> Order of execution
```

1. FROM
2. WHERE
- 3.
- 4.
- 5.

```
>>> Order of execution
```

1. FROM
2. WHERE
3. GROUP BY
- 4.
- 5.

```
>>> Order of execution
```

1. FROM
2. WHERE
3. GROUP BY
4. Aggregation
- 5.

```
>>> Order of execution
```

1. FROM
2. WHERE
3. GROUP BY
4. Aggregation
5. SELECT

## >>> More aggregation functions

| T-SQL  | MySQL       | Purpose                       |
|--------|-------------|-------------------------------|
| AVG    | AVG         | Average                       |
| STDEV  | STDDEV_SAMP | Sample standard deviation     |
| STDEVP | STDDEV_POP  | Population standard deviation |
| VAR    | VAR_SAMP    | Sample variance               |
| VARP   | VAR_POP     | Population variance           |
| COUNT  | COUNT       | Count number of rows          |
| MIN    | MIN         | Minimum                       |
| MAX    | MAX         | Maximum                       |
| SUM    | SUM         | Sum                           |

See the full list in the [T-SQL](#) or [MySQL](#) docs (click).

## >>> More aggregation functions

| T-SQL  | MySQL       | Purpose                       |
|--------|-------------|-------------------------------|
| AVG    | AVG         | Average                       |
| STDEV  | STDDEV_SAMP | Sample standard deviation     |
| STDEVP | STDDEV_POP  | Population standard deviation |
| VAR    | VAR_SAMP    | Sample variance               |
| VARP   | VAR_POP     | Population variance           |
| COUNT  | COUNT       | Count number of rows          |
| MIN    | MIN         | Minimum                       |
| MAX    | MAX         | Maximum                       |
| SUM    | SUM         | Sum                           |

See the full list in the [T-SQL](#) or [MySQL](#) docs (click).



```
>>> Casting - aggregation warning!
```

We cannot ignore data types! Arithmetic with integers always returns an integer (by rounding down).

$$\text{AVG}(\{1,2\}) = 1$$

So we need to use CAST.

```
>>> Casting - aggregation warning!
```

We cannot ignore data types! Arithmetic with integers always returns an integer (by rounding down).

$$\text{AVG}(\{1,2\}) = 1$$

So we need to use `CAST`. For example, in `Notes.RandomPeople`, the data type for Age is integer.

---

```
SELECT gender, AVG(age) AS AverageAge
FROM Notes.RandomPeople
GROUP BY gender;
```

---

Must be changed to:

---

```
SELECT gender, AVG(CAST(age AS decimal(5,2))) AS AverageAge
FROM Notes.RandomPeople
GROUP BY gender;
```

---

```
>>> SQL clause: HAVING
```

The HAVING clause was created because WHERE is executed before GROUP BY.

We will look at the execution of this query:

---

```
SELECT RP.gender, AVG(RP.age) AS AverageAge  
FROM Notes.RandomPeople RP  
GROUP BY RP.gender  
HAVING AVG(RP.age) > 40;
```

---

The HAVING clause is like WHERE, but it acts on groups.

```
>>> SQL clause: HAVING
```

The HAVING clause was created because WHERE is executed before GROUP BY.

We will look at the execution of this query:

---

```
SELECT RP.gender, AVG(RP.age) AS AverageAge  
FROM Notes.RandomPeople RP  
GROUP BY RP.gender  
HAVING AVG(RP.age) > 40;
```

---

Search condition with aggregation function

The HAVING clause is like WHERE, but it acts on groups.

```
>>> SQL clause: HAVING
```

```
FROM Notes.RandomPeople RP
```

| RandomPeople  |        |     |
|---------------|--------|-----|
| PersonName    | Gender | Age |
| Beyoncé       | F      | 37  |
| Laura Marling | F      | 28  |
| Darren Hayes  | M      | 46  |
| Bret McKenzie | M      | 42  |
| Jack Monroe   | NB     | 30  |

```
>>> SQL clause: HAVING
```

GROUP BY RP.Gender

| Unnamed                          |        |             |
|----------------------------------|--------|-------------|
| PersonName                       | Gender | Age         |
| {Beyoncé,<br>Laura Marling}      | F      | {37,<br>28} |
| {Darren Hayes,<br>Bret McKenzie} | M      | {46,<br>42} |
| {Jack Monroe}                    | NB     | {30}        |

```
>>> SQL clause: HAVING
```

AVG(RP.Age)

| Unnamed                          |        |           |
|----------------------------------|--------|-----------|
| PersonName                       | Gender | (unnamed) |
| {Beyoncé,<br>Laura Marling}      | F      | 32.5      |
| {Darren Hayes,<br>Bret McKenzie} | M      | 44        |
| {Jack Monroe}                    | NB     | 30        |

```
>>> SQL clause: HAVING
```

```
HAVING AVG(RP.Age) > 40
```

| Unnamed                          |        |           |
|----------------------------------|--------|-----------|
| PersonName                       | Gender | (unnamed) |
| {Beyoncé,<br>Laura Marling}      | F      | 32.5      |
| {Darren Hayes,<br>Bret McKenzie} | M      | 44        |
| {Jack Monroe}                    | NB     | 30        |



```
>>> SQL clause: HAVING
```

```
SELECT RP.Gender, AVG(RP.Age) AS AverageAge
```

| Unnamed                          |        |           |
|----------------------------------|--------|-----------|
| PersonName                       | Gender | (unnamed) |
| {Darren Hayes,<br>Bret McKenzie} | M      | 44        |

```
>>> SQL clause: HAVING
```

result

| Unnamed |            |
|---------|------------|
| Gender  | AverageAge |
| M       | 44         |



```
>>> Order of execution
```

1. FROM
2. WHERE
- 3.
- 4.
- 5.
- 6.

```
>>> Order of execution
```

1. FROM
2. WHERE
3. GROUP BY
- 4.
- 5.
- 6.

```
>>> Order of execution
```

1. FROM
2. WHERE
3. GROUP BY
4. Aggregation
- 5.
- 6.

```
>>> Order of execution
```

1. FROM
2. WHERE
3. GROUP BY
4. Aggregation
5. HAVING
- 6.

>>> Order of execution

1. FROM
2. WHERE
3. GROUP BY
4. Aggregation
5. HAVING
6. SELECT



## >>> Group practice

The aggregation function in the `HAVING` clause does not have to match the one in the `SELECT` clause.

---

```
SELECT RP.gender, STDEV(RP.age) AS AverageAge
FROM Notes.RandomPeople RP
GROUP BY RP.gender
HAVING AVG(RP.age) > 40;
```

---

Explain in words what the above query achieves.

```
>>> Solution
```

The query finds the sample standard deviation of the ages for each gender that has an average age greater than 40.



```
>>> Where are we now?
```

Day 2

1. Recap of day 1
2. Reading the docs
3. Aggregating
4. Subqueries
5. Windowing

Send me questions and give feedback

Page is hyperlinked: click a topic above to jump to it.

```
>>> Basic subquery
```

**Subqueries** (next slide) are powerful with search conditions.  
In fact, some logical operators only work with subqueries:

- \* EXISTS
- \* ALL
- \* ANY

Subqueries are also known as **nested queries**.

>>> Class practice

Can anyone figure out what this does?

Note: the subquery is executed first.

---

```
SELECT *  
FROM Notes.Friends F  
WHERE F.friendID IN (SELECT P.friendID  
                     FROM Notes.Pets P);
```

---

```
>>> Solution
```

```
1. SELECT P.friendID FROM Notes.Pets P
```

>>> Solution

1. `SELECT P.friendID FROM Notes.Pets P`

Retrieves a table of all the FriendIDs in `Notes.Pets`.



>>> Solution

1. `SELECT P.friendID FROM Notes.Pets P`

Retrieves a table of all the FriendIDs in Notes.Pets.

2. Let's refer to the output of Step 1 as `RESULT`.

>>> Solution

1. `SELECT P.friendID FROM Notes.Pets P`

Retrieves a table of all the FriendIDs in Notes.Pets.

2. Let's refer to the output of Step 1 as `RESULT`.

3. `SELECT * FROM Notes.Friends F WHERE F.FriendID IN RESULT`

>>> Solution

1. `SELECT P.friendID FROM Notes.Pets P`

Retrieves a table of all the FriendIDs in `Notes.Pets`.

2. Let's refer to the output of Step 1 as `RESULT`.

3. `SELECT * FROM Notes.Friends F WHERE F.FriendID IN RESULT`

Retrieves only the rows of `Notes.Friends`  
whose `FriendID` is in `RESULT`.

>>> Solution

1. `SELECT P.friendID FROM Notes.Pets P`

Retrieves a table of all the FriendIDs in `Notes.Pets`.

2. Let's refer to the output of Step 1 as `RESULT`.

3. `SELECT * FROM Notes.Friends F WHERE F.FriendID IN RESULT`

Retrieves only the rows of `Notes.Friends`  
whose `FriendID` is in `RESULT`.

It retrieved the details of all friends who have pets.  
Let's execute it to experiment.

>>> Challenge

Can we rewrite it as a join?

---

```
SELECT *  
FROM Notes.Friends F  
WHERE F.friendID IN (SELECT P.friendID  
                     FROM Notes.Pets P);
```

---

```
>>> Subquery anywhere!
```

Quick note: a subquery does not have to be used only in the `WHERE` clause. It can be used almost anywhere, but we will look at this later.

```
>>> How about this one?
```

Find all the people whose Gender has `AVG(Age)` less than 40.

Easy, right?

>>> How about this one?

Find all the people whose Gender has AVG(Age) less than 40.

Easy, right?

---

```
SELECT PersonName
FROM RandomPeople
GROUP BY Gender
HAVING AVG(Age) < 40;
```

---



>>> How about this one?

Find all the people whose Gender has AVG(Age) less than 40.

Easy, right?

---

```
SELECT PersonName
FROM RandomPeople
GROUP BY Gender
HAVING AVG(Age) < 40;
```

---

Wrong!

Let's try and execute it.

>>> Can you explain why?

FROM RandomPeople GROUP BY Gender

| Unnamed                          |        |             |
|----------------------------------|--------|-------------|
| PersonName                       | Gender | Age         |
| (Beyoncé,<br>Laura Marling)      | F      | (37,<br>28) |
| (Darren Hayes,<br>Bret McKenzie) | M      | (46,<br>42) |
| (Jack Monroe)                    | NB     | (30)        |

---

```
SELECT PersonName
FROM RandomPeople
GROUP BY Gender
HAVING AVG(Age) < 40;
```

---

>>> Use a subquery instead

---

```
SELECT PersonName
FROM RandomPeople
WHERE Gender IN (SELECT Gender
                  FROM RandomPeople
                  GROUP BY Gender
                  HAVING AVG(Age) < 40);
```

---

Let's execute it and explore.

>>> Correlated subquery

The hardest thing in introductory SQL...

---

```
SELECT PersonName
FROM RandomPeople RP
WHERE age > (SELECT AVG(age)
             FROM RandomPeople
             WHERE gender = RP.gender);
```

---

>>> Correlated subquery

The hardest thing in introductory SQL...

---

```
SELECT PersonName
FROM RandomPeople RP
WHERE age > (SELECT AVG(age)
             FROM RandomPeople
             WHERE gender = RP.gender);
```

---

The notes have a good diagram for this...

```
>>> A subquery in FROM
```

What does it do?

---

```
SELECT Gender, AvgAge  
FROM (SELECT Gender, AVG(Age) AS AvgAge  
      FROM RandomPeople  
      GROUP BY Gender)  
WHERE AvgAge < 40;
```

---

```
>>> A subquery in FROM
```

What does it do?

---

```
SELECT Gender, AvgAge  
FROM (SELECT Gender, AVG(Age) AS AvgAge  
      FROM RandomPeople  
      GROUP BY Gender)  
WHERE AvgAge < 40;
```

---

Can we rewrite it with HAVING?

>>> Where are we now?

Day 2

1. Recap of day 1
2. Reading the docs
3. Aggregating
4. Subqueries
5. Windowing

Send me questions and give feedback

Page is hyperlinked: click a topic above to jump to it.



```
>>> What is windowing?
```

- \* Aggregation functions return one value per group.
- \* Window functions return one value per row.
- \* Window functions are not scalar functions.

On the next slide: what are windows?

```
>>> Windows are... groups
```

The only reason we don't call them groups is because we use (and create) them differently.

```
>>> Windows are... groups
```

The only reason we don't call them groups is because we use (and create) them differently.

Sometimes they're called **partitions** instead of windows.

- \* 'Groups' when we return one value per group.
- \* 'Partitions'/'windows' when we return one value per row.

```
>>> First few window functions
```

You ready...?

```
>>> First few window functions
```

You ready...?

| T-SQL  | MySQL       | Purpose                       |
|--------|-------------|-------------------------------|
| AVG    | AVG         | Average                       |
| STDEV  | STDDEV_SAMP | Sample standard deviation     |
| STDEVP | STDDEV_POP  | Population standard deviation |
| VAR    | VAR_SAMP    | Sample variance               |
| VARP   | VAR_POP     | Population variance           |
| COUNT  | COUNT       | Count number of rows          |
| MIN    | MIN         | Minimum                       |
| MAX    | MAX         | Maximum                       |
| SUM    | SUM         | Sum                           |

Danny... what are you talking about??

Those are aggregation functions.

```
>>> Aggregation functions work on windows
```

What will this do?

---

```
SELECT PersonName, MIN(Age) AS MinimumAge  
FROM RandomPeople;
```

---

>>> Aggregation functions work on windows

What will this do?

---

```
SELECT PersonName, MIN(Age) AS MinimumAge
FROM RandomPeople;
```

---

Error: MIN made the whole table one group

>>> Aggregation functions work on windows

What will this do?

---

```
SELECT PersonName, MIN(Age) AS MinimumAge
FROM RandomPeople;
```

---

Error: MIN made the whole table one group

Here we go

---

```
SELECT PersonName, MIN(Age) OVER() AS MinimumAge
FROM RandomPeople;
```

---

Success: OVER() made the whole table one partition.



>>> Aggregation functions work on windows

What will this do?

---

```
SELECT PersonName, MIN(Age) AS MinimumAge
FROM RandomPeople;
```

---

Error: MIN made the whole table one group

Here we go

---

```
SELECT PersonName, MIN(Age) OVER() AS MinimumAge
FROM RandomPeople;
```

---

Success: OVER() made the whole table one partition.

The aggregation still returns one result per partition, but now that single result gets duplicated for each row.

>>> So how do we form the windows?

The minimum age for each person's gender?

---

```
SELECT PersonName, MIN(Age) OVER() AS MinimumAge
FROM RandomPeople;
```

---

>>> So how do we form the windows?

The minimum age for each person's gender?

---

```
SELECT PersonName, MIN(Age) OVER(PARTITION BY Gender) AS MinimumAge
FROM RandomPeople;
```

---

So what will this do?

---

```
SELECT PersonName,
       Age - MIN(Age) OVER(PARTITION BY Gender) AS AgeDiff
FROM RandomPeople;
```

---

>>> Remember this?

Find all the people whose Gender has `AVG(Age)` less than 40.

---

```
SELECT PersonName
FROM RandomPeople
WHERE Gender IN (SELECT Gender
                  FROM RandomPeople
                  GROUP BY Gender
                  HAVING AVG(Age) < 40);
```

---

Can we rewrite it? Let's do it live.

>>> Thinking about order of operations

We know `SELECT` executes last, so what will this do?

---

```
SELECT Gender, MAX(Age) OVER()  
FROM Notes.RandomPeople  
GROUP BY Gender;
```

---

>>> Thinking about order of operations

We know `SELECT` executes last, so what will this do?

---

```
SELECT Gender, MAX(Age) OVER()  
FROM Notes.RandomPeople  
GROUP BY Gender;
```

---

Error: `MAX` is a windowed aggregation function now.

\* `MAX((37,28)) = 37`

\* `MAX((37,28)) OVER() = (37,37)`

>>> Thinking about order of operations

We know `SELECT` executes last, so what will this do?

---

```
SELECT Gender, MAX(MAX(Age)) OVER()  
FROM Notes.RandomPeople  
GROUP BY Gender;
```

---

**Fixed:** we can add a regular aggregation function inside it.

>>> Thinking about order of operations

We know `SELECT` executes last, so what will this do?

---

```
SELECT Gender, MAX(Age) OVER()  
FROM Notes.RandomPeople  
GROUP BY Gender;
```

---

**Fixed:** we can add a regular aggregation function inside it.

Shall I go through it on the blackboard?





>>> Exercises

Do exercises at the end of Chapter 3.

[Click here to find the textbook.](#)