

Team notebook

TonNgoKhong

October 29, 2024

Contents		
1	DP	2
1.1	DivideAndConquerDP	2
1.2	LineContainer	2
1.3	LIS	2
2	DS	2
2.1	DSURollback	2
2.2	LazySegtree	3
2.3	MeldableHeap	3
2.4	OrderStatisticTree	3
2.5	PalindromeTree	4
2.6	RMQ	4
2.7	SegmentTree	4
3	FastInput	4
4	Geometry	4
4.1	AngleBisector	4
4.2	Centroid	4
4.3	Circle	5
4.4	ClosestPair	6
4.5	ConvexPolygon	6
4.6	ExtremeVertex	7
4.7	GeometricMedian	7
4.8	GeometryTemplate	7
4.9	HalfPlane	8
4.10	IsPoint	8
4.11	Line	8
4.12	LineLineIntersection	9
4.13	MaximumCircleCover	9
4.14	MaximumInscribedCircle	9
4.15	MinimumEnclosingCircle	9
4.16	MinimumEnclosingRectangle	9
4.17	MinkowskiSum	9
4.18	MonotoneChain	10
4.19	Point2D	10
4.20	PointInsideHull	10
4.21	PointPolygonTangents	10
4.22	PolarSort	11
4.23	PolygonCircleIntersection	11
4.24	PolygonCut	11
4.25	PolygonDiameter	11
4.26	PolygonDistances	11
4.27	PolygonLineIntersection	12
4.28	PolygonUnion	12
4.29	PolygonWidth	12
4.30	Ray	12
4.31	Segment	13
4.32	SmallestEnclosingCircle	13
4.33	TriangleCircleIntersection	13
4.34	Utilities	14
5	Graph	14
5.1	BiconnectedComponents	14
5.2	CentroidDecomposition	14
5.3	Dinic	14
5.4	EulerPath	15
5.5	EulerPathDirected	15
5.6	GeneralMatching	16
5.7	GlobalMinCut	16
5.8	KhopCau	17
5.9	MCMF	17
5.10	StronglyConnected	17
5.11	TopoSort	18
6	Math	18
6.1	Euclid	18
6.2	Factorization	18
6.3	FFT	18
6.4	Interpolate	19
6.5	LinearDeterminant	19
6.6	Lucas	20
6.7	Matrix	20
6.8	MillerRabin	20
6.9	Mobius	20
6.10	ModInverse	21
6.11	ModMulLL	21
6.12	ModularArithmetic	21
6.13	Notes	21
6.13.1	Cycles	21
6.13.2	Derangements	21
6.13.3	Burnside's lemma	21
6.13.4	Partition function	21
6.13.5	Lucas' Theorem	21
6.13.6	Bernoulli numbers	21
6.13.7	Stirling numbers of the first kind	21
6.13.8	Eulerian numbers	21
6.13.9	Stirling numbers of the second kind	21
6.13.10	Bell numbers	22
6.13.11	Labeled unrooted trees	22
6.13.12	Catalan numbers	22
6.14	NTT	22
6.15	PhiFunction	22
6.16	PollardFactorize	22
6.17	PrimitiveRoot	23
6.18	TwoSat	24
6.19	XorBasis	24
7	String	24
7.1	AhoCorasick	24
7.2	KMP	24
7.3	Manacher	25
7.4	StringHashing	25
7.5	SuffixArray	25
7.6	Z	26
8	template	26

1 DP

1.1 DivideAndConquerDP

```
const ll INF = 1e18;

void calc(int i, int l, int r, int optL, int optR) {
    if (l > r) return;
    int mid = (l + r) / 2;
    f[i][mid] = INF; // change to -INF to find max
    int opt = -1;
    for (int k = optL; k <= min(mid, optR); ++k) {
        ll c = f[i - 1][k] + cost(k + 1, mid);
        if (c < f[i][mid]) {
            f[i][mid] = c;
            opt = k;
        }
    }
    calc(i, l, mid - 1, optL, opt);
    calc(i, mid + 1, r, opt, optR);
}
```

1.2 LineContainer

```
bool Q;
struct Line {
    mutable ll k, m, p;
    bool operator<(const Line& o) const { return Q ? p < o.p : k < o.k; }
};
struct LineContainer : multiset<Line> {
    // ( for doubles , use inf = 1/.0 , div (a, b) = a/b)
    const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        return a / b - ((a / b) < 0 && a % b);
    }
    bool isect(iterator x, iterator y) {
        if (y == end()) {
            x->p = inf;
            return false;
        }
        if (x->k == y->k)
            x->p = x->m > y->m ? inf : -inf;
        else
            x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(ll k, ll m) {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p) isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());
```

```
Q = 1;
auto l = *lower_bound({0, 0, x});
Q = 0;
return l.k * x + l.m;
}
};
```

1.3 LIS

```
int lis_non_strict(const vector<int>& a) {
    multiset<int> s;
    for (int x : a) {
        s.insert(x);
        auto it = s.upper_bound(x);

        if (it != s.end()) s.erase(it);
    }
    return s.size();
}

// Strict.
int lis_strict(const vector<int>& a) {
    multiset<int> s;
    for (int x : a) {
        s.insert(x);
        auto it = s.lower_bound(x);
        it++;

        if (it != s.end()) s.erase(it);
    }
    return s.size();
}

// Return indices of LIS (strict)
vector<int> lis_strict_trace(const vector<int>& a) {
    int n = (int)a.size();
    vector<int> b(n + 1, 0), f(n, 0);
    int answer = 0;
    for (int i = 0; i < n; i++) {
        f[i] = lower_bound(b.begin() + 1, b.begin() + answer + 1, a[i]) - b.begin();
        answer = max(answer, f[i]);
        b[f[i]] = a[i];
    }

    int require = answer;
    vector<int> T;
    for (int i = n - 1; i >= 0; i--) {
        if (f[i] == require) {
            T.push_back(i);
            require--;
        }
    }
    reverse(T.begin(), T.end());
    return T;
}
```

```
// Count number of LIS
using mint = long long; // Cnt is exponential. Check if
// statement says ModInt here?
// Returns: (length of LIS, number of LIS)
pair<int, mint> count_lis(const vector<int>& a) {
    if (a.empty()) {
        return {0, 1};
    }

    // dp[i] = [ (last value, accumulate count) ] for increasing
    // seq of length i+1
    // last value are decreasing
    vector<vector<pair<int, mint>>> dp(a.size() + 1);
    int max_len = 0;

    // returns true if we can append 'val' to LIS stored at 'cur'.
    auto pred_len = [] (const vector<pair<int, mint>>& cur, int val) { return cur.empty() && cur.back().first < val; };
    // returns true if we can append 'val' after the LIS
    // represented with 'p'.
    auto pred_val = [] (int val, const pair<int, mint>& p) { return val > p.first; };

    for (int x : a) {
        int len = lower_bound(dp.begin(), dp.end(), x, pred_len) - dp.begin();

        mint cnt = 1;
        if (len >= 1) {
            int pos = upper_bound(dp[len - 1].begin(), dp[len - 1].end(), x, pred_val) - dp[len - 1].begin();
            cnt = dp[len - 1].back().second;
            cnt -= (pos == 0) ? 0 : dp[len - 1][pos - 1].second;
        }
        dp[len].emplace_back(x, cnt + (dp[len].empty() ? 0 : dp[len].back().second));
        max_len = max(max_len, len + 1);
    }
    assert(max_len > 0);
    return {
        max_len,
        dp[max_len - 1].back().second,
    };
}
```

2 DS

2.1 DSURollback

```
struct Data {
    int time, u, par; // before 'time', 'par' = par[u]
};

struct DSU {
    vector<int> par;
```

```

vector<Data> change;

DSU(int n) : par(n + 5, -1) {}

// find root of x.
// if par[x] < 0 then x is a root, and its tree has -par[x]
// nodes
int getRoot(int x) {
    while (par[x] >= 0) x = par[x];
    return x;
}

bool same_component(int u, int v) { return getRoot(u) ==
    getRoot(v); }

// join components containing x and y.
// t should be current time. We use it to update 'change'.
bool join(int x, int y, int t) {
    x = getRoot(x);
    y = getRoot(y);
    if (x == y) return false;

    // union by rank
    if (par[x] < par[y]) swap(x, y);
    // now x's tree has less nodes than y's tree
    change.push_back({t, y, par[y]});
    par[y] += par[x];
    change.push_back({t, x, par[x]});
    par[x] = y;
    return true;
}

// rollback all changes at time > t.
void rollback(int t) {
    while (!change.empty() && change.back().time > t) {
        par[change.back().u] = change.back().par;
        change.pop_back();
    }
}
};

```

2.2 LazySegtree

```

template <class S, S (*op)(S, S), S (*e)(), class F, S
    (*mapping)(F, S),
    F (*composition)(F, F), F (*id)()>
class LazySeg {
    int N, log;
    vector<S> d;
    vector<F> lz;

    void pull(int k) { d[k] = op(d[2 * k], d[2 * k + 1]); }
    void put(int k, F f) {
        d[k] = mapping(f, d[k]);
        if (k < N) lz[k] = composition(f, lz[k]);
    }
    void push(int k) {

```

```

        put(2 * k, lz[k]);
        put(2 * k + 1, lz[k]);
        lz[k] = id();
    }
};

public:
LazySeg() : LazySeg(0) {}
explicit LazySeg(int n) : LazySeg(vector<S>(n, e())) {}
explicit LazySeg(const vector<S> &v) {
    log = 31 - __builtin_clz(v.size() | 1);
    N = 1 << log;
    d = vector<S>(2 * N, e());
    lz = vector<F>(N, id());
    for (int i = 0; i < (int)v.size(); i++) d[N + i] = v[i];
    for (int i = N - 1; i >= 1; i--) pull(i);
}

void set(int p, S x) {
    p += N;
    for (int i = log; i >= 1; i--) push(p >> i);
    d[p] = x;
    for (int i = 1; i <= log; i++) pull(p >> i);
}

S prod(int l, int r) {
    if (l == r) return e();
    l += N, r += N;
    for (int i = log; i >= 1; i--) {
        if (((l >> i) << i) != 1) push(l >> i);
        if (((r >> i) << i) != r) push((r - 1) >> i);
    }
    S sml = e(), smr = e();
    while (l < r) {
        if (l & 1) sml = op(sml, d[l++]);
        if (r & 1) smr = op(d[--r], smr);
        l >>= 1, r >>= 1;
    }
    return op(sml, smr);
}

S all_prod() { return d[1]; }
void apply(int l, int r, F f) {
    if (l == r) return;
    l += N, r += N;
    for (int i = log; i >= 1; i--) {
        if (((l >> i) << i) != 1) push(l >> i);
        if (((r >> i) << i) != r) push((r - 1) >> i);
    }
    l = l2, r = r2;
    while (l < r) {
        if (l & 1) put(l++, f);
        if (r & 1) put(--r, f);
        l >>= 1, r >>= 1;
    }
    l = l2, r = r2;
    for (int i = 1; i <= log; i++) {
        if (((l >> i) << i) != 1) pull(l >> i);
        if (((r >> i) << i) != r) pull((r - 1) >> i);
    }
}
};

```

2.3 MeldableHeap

```

mt19937 gen(0x94949);
template<typename T>
struct Node {
    Node *l, *r;
    T v;
    Node(T x): l(0), r(0), v(x){}
};

template<typename T>
Node<T>* Meld(Node<T>* A, Node<T>* B) {
    if(!A) return B; if(!B) return A;
    if(B->v < A->v) swap(A, B);
    if(gen() & 1) A->l = Meld(A->l, B);
    else A->r = Meld(A->r, B);
    return A;
}

template<typename T>
struct Heap {
    Node<T> *r; int s;
    Heap(): r(0), s(0){}
    void push(T x) {
        r = Meld(new Node<T>(x), r);
        ++s;
    }
    int size(){ return s; }
    bool empty(){ return s == 0; }
    T top(){ return r->v; }
    void pop() {
        Node<T>* p = r;
        r = Meld(r->l, r->r);
        delete p;
        --s;
    }
    void Meld(Heap x) {
        s += x->s;
        r = Meld(r, x->r);
    }
};

```

2.4 OrderStatisticTree

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
template <class T>
using Tree =
    tree<T, null_type, less<T>, rb_tree_tag,
        tree_order_statistics_node_update>;

void example() {
    Tree<int> t, t2;
    t.insert(8);
    auto it = t.insert(10).first;
    assert(it == t.lower_bound(9));
    assert(t.order_of_key(10) == 1);
    assert(t.order_of_key(11) == 2);
}

```

```
assert(*t.find_by_order(0) == 8);
t.join(t2); // assuming T < T2 or T > T2, merge t2 into t
}
```

2.5 PalindromeTree

```
template <int MAXC = 26>
struct PalindromicTree {
    PalindromicTree(const string& str) : _sz(str.size() + 5),
        next(_sz, vector<int>(MAXC, 0)), link(_sz, 0),
        qlink(_sz, 0), cnt(_sz, 0), right_id(_sz, 0), len(_sz,
        0), s(_sz, 0) {
        init();
        for (int i = 0; i < (int)str.size(); ++i) {
            add(str[i], i);
        }
        count();
    }
    int _sz;

    // returns vector of (left, right, frequency)
    vector<tuple<int, int, int>> get_palindromes() {
        vector<tuple<int, int, int>> res;
        dfs(0, res);
        dfs(1, res);
        return res;
    }

    void dfs(int u, vector<tuple<int, int, int>>& res) {
        if (u > 1) { // u = 0 and u = 1 are two empty nodes
            res.emplace_back(right_id[u] - len[u] + 1, right_id[u],
                cnt[u]);
        }
        for (int i = 0; i < MAXC; ++i) {
            if (next[u][i]) dfs(next[u][i], res);
        }
    }

    int last, n, p;
    vector<vector<int>> next, dlink;
    vector<int> link, qlink, cnt, right_id, len, s;

    int newnode(int l, int right) {
        len[p] = l;
        right_id[p] = right;
        return p++;
    }

    void init() {
        p = 0;
        newnode(0, -1), newnode(-1, -1);
        n = last = 0;
        s[n] = -1, link[0] = 1;
    }

    int getlink(int x) {
        while (s[n - len[x] - 1] != s[n]) {
            if (s[n - len[link[x]] - 1] == s[n])
                x = link[x];
        }
    }
}
```

```
    else
        x = qlink[x];
    }
    return x;
}

void add(char c, int right) {
    c -= 'a';
    s[++n] = c;
    int cur = getlink(last);
    if (!next[cur][(int)c]) {
        int now = newnode(len[cur] + 2, right);
        link[now] = next[getlink(link[cur])][(int)c];
        next[cur][(int)c] = now;
        if (s[n - len[link[now]]] == s[n - len[link[link[now]]]])
            {
                qlink[now] = qlink[link[now]];
            }
        else {
            qlink[now] = link[link[now]];
        }
    }
    last = next[cur][(int)c];
    cnt[last]++;
}

void count() {
    for (int i = p - 1; i >= 0; i--) {
        cnt[link[i]] += cnt[i];
    }
}
};
```

2.6 RMQ

```
ll a[N], st[LG + 1][N];

void pre() {
    for (int i = 1; i <= n; ++i) st[0][i] = a[i];
    for (int j = 1; j <= LG; ++j)
        for (int i = 1; i + (1 << j) - 1 <= n; ++i)
            st[j][i] = __gcd(st[j - 1][i], st[j - 1][i + (1 << (j - 1))]);
}

ll query(int l, int r) {
    int k = __lg(r - l + 1);
    return __gcd(st[k][l], st[k][r - (1 << k) + 1]);
}
```

2.7 SegmentTree

```
struct Tree {
    typedef int T;
    static constexpr T unit = INT_MIN;
    T f(T a, T b) { return max(a, b); } // (any associative fn)
    vector<T> s;
```

```
int n;
Tree(int n = 0, T def = unit) : s(2 * n, def), n(n) {}
void update(int pos, T val) {
    for (s[pos += n] = val; pos /= 2; s[pos] = f(s[pos * 2],
        s[pos * 2 + 1]));
}
T query(int b, int e) { // query [b, e)
    T ra = unit, rb = unit;
    for (b += n, e += n; b < e; b /= 2, e /= 2) {
        if (b % 2) ra = f(ra, s[b++]);
        if (e % 2) rb = f(s[--e], rb);
    }
    return f(ra, rb);
}
};
```

3 FastInput

```
inline char gc() { // l ike getchar ()
    static char buf[1 << 16];
    static size_t bc, be;
    if (bc >= be) {
        buf[0] = 0, bc = 0;
        be = fread(buf, 1, sizeof(buf), stdin);
    }
    return buf[bc++]; // returns 0 on EOF
}

int readInt() {
    int a, c;
    while ((a = gc()) < 40)
        ;
    if (a == '-') return -readInt();
    while ((c = gc()) >= 48) a = a * 10 + c - 48;
    return a - 48;
}
```

4 Geometry

4.1 AngleBisector

```
// bisector vector of <abc
PT angle_bisector(PT &a, PT &b, PT &c){
    PT p = a - b, q = c - b;
    return p + q * sqrt(dot(p, p) / dot(q, q));
}
```

4.2 Centroid

```
// centroid of a (possibly non-convex) polygon,
```

```
// assuming that the coordinates are listed in a clockwise or
// counterclockwise fashion. Note that the centroid is often
// known as
// the "center of gravity" or "center of mass".
PT centroid(vector<PT> &p) {
    int n = p.size(); PT c(0, 0);
    double sum = 0;
    for (int i = 0; i < n; i++) sum += cross(p[i], p[(i + 1) %
        n]);
    double scale = 3.0 * sum;
    for (int i = 0; i < n; i++) {
        int j = (i + 1) % n;
        c = c + (p[i] + p[j]) * cross(p[i], p[j]);
    }
    return c / scale;
}
```

4.3 Circle

```
struct circle {
    PT p; double r;
    circle() {}
    circle(PT _p, double _r): p(_p), r(_r) {};
    // center (x, y) and radius r
    circle(double x, double y, double _r): p(PT(x, y)), r(_r)
        {};
    // circumcircle of a triangle
    // the three points must be unique
    circle(PT a, PT b, PT c) {
        b = (a + b) * 0.5;
        c = (a + c) * 0.5;
        line_line_intersection(b, b + rotatecw90(a - b), c, c +
            rotatecw90(a - c), p);
        r = dist(a, p);
    }
    // inscribed circle of a triangle
    circle(PT a, PT b, PT c, bool t) {
        line u, v;
        double m = atan2(b.y - a.y, b.x - a.x), n = atan2(c.y -
            a.y, c.x - a.x);
        u.a = a;
        u.b = u.a + (PT(cos((n + m)/2.0), sin((n + m)/2.0)));
        v.a = b;
        m = atan2(a.y - b.y, a.x - b.x), n = atan2(c.y - b.y,
            c.x - b.x);
        v.b = v.a + (PT(cos((n + m)/2.0), sin((n + m)/2.0)));
        line_line_intersection(u.a, u.b, v.a, v.b, p);
        r = dist_from_point_to_seg(a, b, p);
    }
    bool operator == (circle v) { return p == v.p && sign(r -
        v.r) == 0; }
    double area() { return PI * r * r; }
    double circumference() { return 2.0 * PI * r; }
};
//0 if outside, 1 if on circumference, 2 if inside circle
int circle_point_relation(PT p, double r, PT b) {
    double d = dist(p, b);
```

```
    if (sign(d - r) < 0) return 2;
    if (sign(d - r) == 0) return 1;
    return 0;
}
// 0 if outside, 1 if on circumference, 2 if inside circle
int circle_line_relation(PT p, double r, PT a, PT b) {
    double d = dist_from_point_to_line(a, b, p);
    if (sign(d - r) < 0) return 2;
    if (sign(d - r) == 0) return 1;
    return 0;
}
//compute intersection of line through points a and b with
//circle centered at c with radius r > 0
vector<PT> circle_line_intersection(PT c, double r, PT a, PT b)
{
    vector<PT> ret;
    b = b - a; a = a - c;
    double A = dot(b, b), B = dot(a, b);
    double C = dot(a, a) - r * r, D = B * B - A * C;
    if (D < -eps) return ret;
    ret.push_back(c + a + b * (-B + sqrt(D + eps)) / A);
    if (D > eps) ret.push_back(c + a + b * (-B - sqrt(D)) / A);
    return ret;
}
//5 - outside and do not intersect
//4 - intersect outside in one point
//3 - intersect in 2 points
//2 - intersect inside in one point
//1 - inside and do not intersect
int circle_circle_relation(PT a, double r, PT b, double R) {
    double d = dist(a, b);
    if (sign(d - r - R) > 0) return 5;
    if (sign(d - r - R) == 0) return 4;
    double l = fabs(r - R);
    if (sign(d - r - R) < 0 && sign(d - l) > 0) return 3;
    if (sign(d - l) == 0) return 2;
    if (sign(d - l) < 0) return 1;
    assert(0); return -1;
}
vector<PT> circle_circle_intersection(PT a, double r, PT b,
    double R) {
    if (a == b && sign(r - R) == 0) return {PT(1e18, 1e18)};
    vector<PT> ret;
    double d = sqrt(dist2(a, b));
    if (d > r + R || d + min(r, R) < max(r, R)) return ret;
    double x = (d * d - R * R + r * r) / (2 * d);
    double y = sqrt(r * r - x * x);
    PT v = (b - a) / d;
    ret.push_back(a + v * x + rotateccw90(v) * y);
    if (y > 0) ret.push_back(a + v * x - rotateccw90(v) * y);
    return ret;
}
// returns two circle c1, c2 through points a, b and of radius r
// 0 if there is no such circle, 1 if one circle, 2 if two
// circle
int get_circle(PT a, PT b, double r, circle &c1, circle &c2) {
    vector<PT> v = circle_circle_intersection(a, r, b, r);
    int t = v.size();
    if (!t) return 0;
    c1.p = v[0], c1.r = r;
```

```
    if (t == 2) c2.p = v[1], c2.r = r;
    return t;
}
// returns two circle c1, c2 which is tangent to line u, goes
// through
// point q and has radius r1; 0 for no circle, 1 if c1 = c2, 2
// if c1 != c2
int get_circle(line u, PT q, double r1, circle &c1, circle &c2)
{
    double d = dist_from_point_to_line(u.a, u.b, q);
    if (sign(d - r1 * 2.0) > 0) return 0;
    if (sign(d) == 0) {
        cout << u.v.x << ' ' << u.v.y << '\n';
        c1.p = q + rotateccw90(u.v).truncate(r1);
        c2.p = q + rotatecw90(u.v).truncate(r1);
        c1.r = c2.r = r1;
        return 2;
    }
    line u1 = line(u.a + rotateccw90(u.v).truncate(r1), u.b +
        rotateccw90(u.v).truncate(r1));
    line u2 = line(u.a + rotatecw90(u.v).truncate(r1), u.b +
        rotatecw90(u.v).truncate(r1));
    circle cc = circle(q, r1);
    PT p1, p2; vector<PT> v;
    v = circle_line_intersection(q, r1, u1.a, u1.b);
    if (!v.size()) v = circle_line_intersection(q, r1, u2.a,
        u2.b);
    v.push_back(v[0]);
    p1 = v[0], p2 = v[1];
    c1 = circle(p1, r1);
    if (p1 == p2) {
        c2 = c1;
        return 1;
    }
    c2 = circle(p2, r1);
    return 2;
}
// returns area of intersection between two circles
double circle_circle_area(PT a, double r1, PT b, double r2) {
    double d = (a - b).norm();
    if (r1 + r2 < d + eps) return 0;
    if (r1 + d < r2 + eps) return PI * r1 * r1;
    if (r2 + d < r1 + eps) return PI * r2 * r2;
    double theta_1 = acos((r1 * r1 + d * d - r2 * r2) / (2 * r1
        * d));
    theta_2 = acos((r2 * r2 + d * d - r1 * r1) / (2 * r2 *
        d));
    return r1 * r1 * (theta_1 - sin(2 * theta_1)/2.) + r2 * r2
        * (theta_2 - sin(2 * theta_2)/2.);
}
// tangent lines from point q to the circle
int tangent_lines_from_point(PT p, double r, PT q, line &u,
    line &v) {
    int x = sign(dist2(p, q) - r * r);
    if (x < 0) return 0; // point in cricle
    if (x == 0) { // point on circle
        u = line(q, q + rotateccw90(q - p));
        v = u;
        return 1;
    }
}
```

```

double d = dist(p, q);
double l = r * r / d;
double h = sqrt(r * r - l * l);
u = line(q, p + ((q - p).truncate(l) + (rotateccw90(q -
p).truncate(h))));
v = line(q, p + ((q - p).truncate(l) + (rotatcw90(q -
p).truncate(h))));
return 2;
}
// returns outer tangents line of two circles
// if inner == 1 it returns inner tangent lines
int tangents_lines_from_circle(PT c1, double r1, PT c2, double
r2, bool inner, line &u, line &v) {
if (inner) r2 = -r2;
PT d = c2 - c1;
double dr = r1 - r2, d2 = d.norm2(), h2 = d2 - dr * dr;
if (d2 == 0 || h2 < 0) {
assert(h2 != 0);
return 0;
}
vector<pair<PT, PT>>out;
for (int tmp: {-1, 1}) {
PT v = (d * dr + rotateccw90(d) * sqrt(h2) * tmp) / d2;
out.push_back({c1 + v * r1, c2 + v * r2});
}
u = line(out[0].first, out[0].second);
if (out.size() == 2) v = line(out[1].first, out[1].second);
return 1 + (h2 > 0);
}
//O(n^2 log n)
struct CircleUnion {
int n;
double x[2020], y[2020], r[2020];
int covered[2020];
vector<pair<double, double>> seg, cover;
double arc, pol;
inline int sign(double x) {return x < -eps ? -1 : x > eps;}
inline int sign(double x, double y) {return sign(x - y);}
inline double SQ(const double x) {return x * x;}
inline double dist(double x1, double y1, double x2, double
y2) {return sqrt(SQ(x1 - x2) + SQ(y1 - y2));}
inline double angle(double A, double B, double C) {
double val = (SQ(A) + SQ(B) - SQ(C)) / (2 * A * B);
if (val < -1) val = -1;
if (val > +1) val = +1;
return acos(val);
}
CircleUnion() {
n = 0;
seg.clear(), cover.clear();
arc = pol = 0;
}
void init() {
n = 0;
seg.clear(), cover.clear();
arc = pol = 0;
}
void add(double xx, double yy, double rr) {
x[n] = xx, y[n] = yy, r[n] = rr, covered[n] = 0, n++;
}
}

```

```

void getarea(int i, double lef, double rig) {
arc += 0.5 * r[i] * r[i] * (rig - lef - sin(rig - lef));
double x1 = x[i] + r[i] * cos(lef), y1 = y[i] + r[i] *
sin(lef);
double x2 = x[i] + r[i] * cos(rig), y2 = y[i] + r[i] *
sin(rig);
pol += x1 * y2 - x2 * y1;
}
double solve() {
for (int i = 0; i < n; i++) {
for (int j = 0; j < i; j++) {
if (!sign(x[i] - x[j]) && !sign(y[i] - y[j]) &&
!sign(r[i] - r[j])) {
r[i] = 0.0;
break;
}
}
}
for (int i = 0; i < n; i++) {
for (int j = 0; j < n; j++) {
if (i != j && sign(r[j] - r[i]) >= 0 &&
sign(dist(x[i], y[i], x[j], y[j]) - (r[j] -
r[i])) <= 0) {
covered[i] = 1;
break;
}
}
}
for (int i = 0; i < n; i++) {
if (sign(r[i]) && !covered[i]) {
seg.clear();
for (int j = 0; j < n; j++) {
if (i != j) {
double d = dist(x[i], y[i], x[j], y[j]);
if (sign(d - (r[j] + r[i])) >= 0 ||
sign(d - abs(r[j] - r[i])) <= 0) {
continue;
}
double alpha = atan2(y[j] - y[i], x[j] -
x[i]);
double beta = angle(r[i], d, r[j]);
pair<double, double> tmp(alpha - beta,
alpha + beta);
if (sign(tmp.first) <= 0 &&
sign(tmp.second) <= 0) {
seg.push_back(pair<double, double>(2
* PI + tmp.first, 2 * PI +
tmp.second));
}
else if (sign(tmp.first) < 0) {
seg.push_back(pair<double, double>(2
* PI + tmp.first, 2 * PI));
seg.push_back(pair<double, double>(0,
tmp.second));
}
else {
seg.push_back(tmp);
}
}
}
}
}
}

```

```

sort(seg.begin(), seg.end());
double rig = 0;
for (vector<pair<double, double>>::iterator
iter = seg.begin(); iter != seg.end();
iter++) {
if (sign(rig - iter->first) >= 0) {
rig = max(rig, iter->second);
}
else {
getarea(i, rig, iter->first);
rig = iter->second;
}
}
if (!sign(rig)) {
arc += r[i] * r[i] * PI;
}
else {
getarea(i, rig, 2 * PI);
}
}
return pol / 2.0 + arc;
}
} CU;

```

4.4 ClosestPair

```

typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
assert(sz(v) > 1);
set<P> S;
sort(all(v), [](P a, P b) { return a.y < b.y; });
pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
int j = 0;
for (P p : v) {
P d{1 + (ll)sqrt(ret.first), 0};
while (v[j].y <= p.y - d.x) S.erase(v[j++]);
auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
for (; lo != hi; ++lo) ret = min(ret, {(*lo - p).dist2(),
{*lo, p}});
S.insert(p);
}
return ret.second;
}

```

4.5 ConvexPolygon

```

vector<PT> convex_hull(vector<PT> &p) {
if (p.size() <= 1) return p;
vector<PT> v = p;
sort(v.begin(), v.end());
vector<PT> up, dn;
for (auto& p : v) {
while (up.size() > 1 && orientation(up[up.size() - 2],
up.back(), p) >= 0) {

```

```

        up.pop_back();
    }
    while (dn.size() > 1 && orientation(dn[dn.size() - 2],
        dn.back(), p) <= 0) {
        dn.pop_back();
    }
    up.push_back(p);
    dn.push_back(p);
}
v = dn;
if (v.size() > 1) v.pop_back();
reverse(up.begin(), up.end());
up.pop_back();
for (auto& p : up) {
    v.push_back(p);
}
if (v.size() == 2 && v[0] == v[1]) v.pop_back();
return v;
}
//checks if convex or not
bool is_convex(vector<PT> &p) {
    bool s[3]; s[0] = s[1] = s[2] = 0;
    int n = p.size();
    for (int i = 0; i < n; i++) {
        int j = (i + 1) % n;
        int k = (j + 1) % n;
        s[sign(cross(p[j] - p[i], p[k] - p[i])) + 1] = 1;
        if (s[0] && s[2]) return 0;
    }
    return 1;
}
// -1 if strictly inside, 0 if on the polygon, 1 if strictly
// outside
// it must be strictly convex, otherwise make it strictly
// convex first
int is_point_in_convex(vector<PT> &p, const PT& x) { // 0(log n)
    int n = p.size(); assert(n >= 3);
    int a = orientation(p[0], p[1], x), b = orientation(p[0],
        p[n - 1], x);
    if (a < 0 || b > 0) return 1;
    int l = 1, r = n - 1;
    while (l + 1 < r) {
        int mid = l + r >> 1;
        if (orientation(p[0], p[mid], x) >= 0) l = mid;
        else r = mid;
    }
    int k = orientation(p[l], p[r], x);
    if (k <= 0) return -k;
    if (l == 1 && a == 0) return 0;
    if (r == n - 1 && b == 0) return 0;
    return -1;
}
}

```

4.6 ExtremeVertex

```

// id of the vertex having maximum dot product with z
// polygon must need to be convex

```

```

// top - upper right vertex
// for minimum dot prouct negate z and return -dot(z, p[id])
int extreme_vertex(vector<PT> &p, const PT &z, const int top) {
    // 0(log n)
    int n = p.size();
    if (n == 1) return 0;
    double ans = dot(p[0], z); int id = 0;
    if (dot(p[top], z) > ans) ans = dot(p[top], z), id = top;
    int l = 1, r = top - 1;
    while (l < r) {
        int mid = l + r >> 1;
        if (dot(p[mid + 1], z) >= dot(p[mid], z)) l = mid + 1;
        else r = mid;
    }
    if (dot(p[l], z) > ans) ans = dot(p[l], z), id = l;
    l = top + 1, r = n - 1;
    while (l < r) {
        int mid = l + r >> 1;
        if (dot(p[(mid + 1) % n], z) >= dot(p[mid], z)) l = mid
            + 1;
        else r = mid;
    }
    l %= n;
    if (dot(p[l], z) > ans) ans = dot(p[l], z), id = l;
    return id;
}

```

4.7 GeometricMedian

```

// it returns a point such that the sum of distances
// from that point to all points in p is minimum
// 0(n log^2 MX)
PT geometric_median(vector<PT> p) {
    auto tot_dist = [&](PT x) {
        double res = 0;
        for (int i = 0; i < p.size(); i++) res += dist(p[i], x);
        return res;
    };
    auto findY = [&](double x) {
        double y1 = -1e5, yr = 1e5;
        for (int i = 0; i < 60; i++) {
            double ym1 = y1 + (yr - y1) / 3;
            double ym2 = yr - (yr - y1) / 3;
            double d1 = tot_dist(PT(x, ym1));
            double d2 = tot_dist(PT(x, ym2));
            if (d1 < d2) yr = ym2;
            else y1 = ym1;
        }
        return pair<double, double> (y1, tot_dist(PT(x, y1)));
    };
    double x1 = -1e5, xr = 1e5;
    for (int i = 0; i < 60; i++) {
        double xm1 = x1 + (xr - x1) / 3;
        double xm2 = xr - (xr - x1) / 3;
        double y1, d1, y2, d2;
        auto z = findY(xm1); y1 = z.first; d1 = z.second;
        z = findY(xm2); y2 = z.first; d2 = z.second;
    }
}

```

```

        if (d1 < d2) xr = xm2;
        else x1 = xm1;
    }
    return {x1, findY(x1).first };
}

```

4.8 GeometryTemplate

```

const long double PI = acos(-1);
struct Vector {
    using type = long long;
    type x, y;
    Vector operator-(const Vector &other) const {
        return {x - other.x, y - other.y};
    }
    type operator*(const Vector &other) const {
        return x * other.y - other.x * y;
    }
    type operator%(const Vector &other) const {
        return x * other.x + y * other.y;
    }
    bool operator==(const Vector &other) const {
        return x == other.x and y == other.y;
    }
    bool operator!=(const Vector &other) const { return !(*this
        == other); }
    friend type cross(const Vector &A, const Vector &B, const
        Vector &C) {
        return (B - A) * (C - A);
    }
    friend type dist(Vector A) { return A.x * A.x + A.y * A.y; }
    friend type dot(const Vector &A, const Vector &B, const
        Vector &C) {
        Vector u = (B - A), v = (C - A);
        return u % v;
    }
    friend istream &operator>>(istream &is, Vector &V) {
        is >> V.x >> V.y;
        return is;
    }
    friend ostream &operator<<(ostream &os, Vector &V) {
        os << V.x << ' ' << V.y;
        return os;
    }
    friend double angle(const Vector &A, const Vector &B, const
        Vector &C) {
        double x = dot(B, A, C) / sqrt(dist(A - B) * dist(C - B));
        return acos(min(1.0, max(-1.0, x))) * 180.0 / PI;
    }
};
using Point = Vector;
const Point origin = {0, 0};

long double area(Point A, Point B, Point C) {
    long double res =
        cross(origin, A, B) + cross(origin, B, C) + cross(origin,
            C, A);
}

```



```

    return abs(res) / 2.0;
}

```

4.9 HalfPlane

```

// contains all points p such that: cross(b - a, p - a) >= 0
struct HP {
    PT a, b;
    HP() {}
    HP(PT a, PT b) : a(a), b(b) {}
    HP(const HP& rhs) : a(rhs.a), b(rhs.b) {}
    int operator < (const HP& rhs) const {
        PT p = b - a;
        PT q = rhs.b - rhs.a;
        int fp = (p.y < 0 || (p.y == 0 && p.x < 0));
        int fq = (q.y < 0 || (q.y == 0 && q.x < 0));
        if (fp != fq) return fp == 0;
        if (cross(p, q)) return cross(p, q) > 0;
        return cross(p, rhs.b - a) < 0;
    }
    PT line_line_intersection(PT a, PT b, PT c, PT d) {
        b = b - a; d = d - c; c = c - a;
        return a + b * cross(c, d) / cross(b, d);
    }
    PT intersection(const HP &v) {
        return line_line_intersection(a, b, v.a, v.b);
    }
};
int check(HP a, HP b, HP c) {
    return cross(a.b - a.a, b.intersection(c) - a.a) > -eps;
    // -eps to include polygons of zero area (straight
    // lines, points)
}
// consider half-plane of counter-clockwise side of each line
// if lines are not bounded add infinity rectangle
// returns a convex polygon, a point can occur multiple times
// though
// complexity: O(n log(n))
vector<PT> half_plane_intersection(vector<HP> h) {
    sort(h.begin(), h.end());
    vector<HP> tmp;
    for (int i = 0; i < h.size(); i++) {
        if (!i || cross(h[i].b - h[i].a, h[i - 1].b - h[i - 1].a) {
            tmp.push_back(h[i]);
        }
    }
    h = tmp;
    vector<HP> q(h.size() + 10);
    int qh = 0, qe = 0;
    for (int i = 0; i < h.size(); i++) {
        while (qh - qh > 1 && !check(h[i], q[qh - 2], q[qh - 1])) qe--;
        while (qh - qh > 1 && !check(h[i], q[qh], q[qh + 1])) qh++;
        q[qe++] = h[i];
    }
}

```

```

while (qh - qh > 2 && !check(q[qh], q[qh - 2], q[qh - 1]))
    qe--;
while (qh - qh > 2 && !check(q[qh - 1], q[qh], q[qh + 1]))
    qh++;
vector<HP> res;
for (int i = qh; i < qe; i++) res.push_back(q[i]);
vector<PT> hull;
if (res.size() > 2) {
    for (int i = 0; i < res.size(); i++) {
        hull.push_back(res[i].intersection(res[(i + 1) %
            ((int)res.size())]));
    }
}
return hull;
}

```

4.10 IsPoint

```

// -1 if strictly inside, 0 if on the polygon, 1 if strictly
// outside
int is_point_in_triangle(PT a, PT b, PT c, PT p) {
    if (sign(cross(b - a, c - a)) < 0) swap(b, c);
    int c1 = sign(cross(b - a, p - a));
    int c2 = sign(cross(c - b, p - b));
    int c3 = sign(cross(a - c, p - c));
    if (c1 < 0 || c2 < 0 || c3 < 0) return 1;
    if (c1 + c2 + c3 != 3) return 0;
    return -1;
}

bool is_point_on_polygon(vector<PT> &p, const PT& z) {
    int n = p.size();
    for (int i = 0; i < n; i++) {
        if (is_point_on_seg(p[i], p[(i + 1) % n], z)) return 1;
    }
    return 0;
}

// returns 1e9 if the point is on the polygon
int winding_number(vector<PT> &p, const PT& z) { // O(n)
    if (is_point_on_polygon(p, z)) return 1e9;
    int n = p.size(), ans = 0;
    for (int i = 0; i < n; ++i) {
        int j = (i + 1) % n;
        bool below = p[i].y < z.y;
        if (below != (p[j].y < z.y)) {
            auto orient = orientation(z, p[j], p[i]);
            if (orient == 0) return 0;
            if (below == (orient > 0)) ans += below ? 1 : -1;
        }
    }
    return ans;
}

// -1 if strictly inside, 0 if on the polygon, 1 if strictly
// outside
int is_point_in_polygon(vector<PT> &p, const PT& z) { // O(n)
    int k = winding_number(p, z);
}

```

```

    return k == 1e9 ? 0 : k == 0 ? 1 : -1;
}

```

4.11 Line

```

struct line {
    PT a, b; // goes through points a and b
    PT v; double c; // line form: direction vec [cross] (x, y) =
    c
    line() {}
    // direction vector v and offset c
    line(PT v, double c) : v(v), c(c) {
        auto p = get_points();
        a = p.first; b = p.second;
    }
    // equation ax + by + c = 0
    line(double _a, double _b, double _c) : v({_b, -_a}),
        c(-_c) {
        auto p = get_points();
        a = p.first; b = p.second;
    }
    // goes through points p and q
    line(PT p, PT q) : v(q - p), c(cross(v, p)), a(p), b(q) {}
    pair<PT, PT> get_points() { // extract any two points
        from this line
        PT p, q; double a = -v.y, b = v.x; // ax + by = c
        if (sign(a) == 0) {
            p = PT(0, c / b);
            q = PT(1, c / b);
        }
        else if (sign(b) == 0) {
            p = PT(c / a, 0);
            q = PT(c / a, 1);
        }
        else {
            p = PT(0, c / b);
            q = PT(1, (c - a) / b);
        }
        return {p, q};
    }
    // ax + by + c = 0
    array<double, 3> get_abc() {
        double a = -v.y, b = v.x;
        return {a, b, c};
    }
    // 1 if on the left, -1 if on the right, 0 if on the line
    int side(PT p) { return sign(cross(v, p) - c); }
    // line that is perpendicular to this and goes through
    // point p
    line perpendicular_through(PT p) { return {p, p + perp(v)}; }
}
// translate the line by vector t i.e. shifting it by
// vector t
line translate(PT t) { return {v, c + cross(v, t)}; }
// compare two points by their orthogonal projection on
// this line

```



```

// a projection point comes before another if it comes
// first according to vector v
bool cmp_by_projection(PT p, PT q) { return dot(v, p) <
dot(v, q); }
line shift_left(double d) {
PT z = v.perp().truncate(d);
return line(a + z, b + z);
}
};

```

4.12 LineLineIntersection

```

// intersection point between ab and cd assuming unique
// intersection exists
bool line_line_intersection(PT a, PT b, PT c, PT d, PT &ans) {
double a1 = a.y - b.y, b1 = b.x - a.x, c1 = cross(a, b);
double a2 = c.y - d.y, b2 = d.x - c.x, c2 = cross(c, d);
double det = a1 * b2 - a2 * b1;
if (det == 0) return 0;
ans = PT((b1 * c2 - b2 * c1) / det, (c1 * a2 - a1 * c2) /
det);
return 1;
}

```

4.13 MaximumCircleCover

```

// find a circle of radius r that contains as many points as
// possible
// O(n^2 log n);
double maximum_circle_cover(vector<PT> p, double r, circle &c) {
int n = p.size();
int ans = 0;
int id = 0; double th = 0;
for (int i = 0; i < n; ++i) {
// maximum circle cover when the circle goes through
// this point
vector<pair<double, int>> events = {{-PI, +1}, {PI,
-1}};
for (int j = 0; j < n; ++j) {
if (j == i) continue;
double d = dist(p[i], p[j]);
if (d > r * 2) continue;
double dir = (p[j] - p[i]).arg();
double ang = acos(d / 2 / r);
double st = dir - ang, ed = dir + ang;
if (st > PI) st -= PI * 2;
if (st <= -PI) st += PI * 2;
if (ed > PI) ed -= PI * 2;
if (ed <= -PI) ed += PI * 2;
events.push_back({st - eps, +1}); // take care of
precisions!
events.push_back({ed, -1});
if (st > ed) {
events.push_back({-PI, +1});
}
}
}
}

```

```

events.push_back({+PI, -1});
}
}
sort(events.begin(), events.end());
int cnt = 0;
for (auto &&e: events) {
cnt += e.second;
if (cnt > ans) {
ans = cnt;
id = i; th = e.first;
}
}
}
PT w = PT(p[id].x + r * cos(th), p[id].y + r * sin(th));
c = circle(w, r); //best_circle
return ans;
}

```

4.14 MaximumInscribedCircle

```

// radius of the maximum inscribed circle in a convex polygon
double maximum_inscribed_circle(vector<PT> p) {
int n = p.size();
if (n <= 2) return 0;
double l = 0, r = 20000;
while (r - l > eps) {
double mid = (l + r) * 0.5;
vector<HP> h;
const int L = 1e9;
h.push_back(HP(PT(-L, -L), PT(L, -L)));
h.push_back(HP(PT(L, -L), PT(L, L)));
h.push_back(HP(PT(L, L), PT(-L, L)));
h.push_back(HP(PT(-L, L), PT(-L, -L)));
for (int i = 0; i < n; i++) {
PT z = (p[(i + 1) % n] - p[i]).perp();
z = z.truncate(mid);
PT y = p[i] + z, q = p[(i + 1) % n] + z;
h.push_back(HP(p[i] + z, p[(i + 1) % n] + z));
}
vector<PT> nw = half_plane_intersection(h);
if (!nw.empty()) l = mid;
else r = mid;
}
return l;
}

```

4.15 MinimumEnclosingCircle

```

// given n points, find the minimum enclosing circle of the
// points
// call convex_hull() before this for faster solution
// expected O(n)
circle minimum_enclosing_circle(vector<PT> &p) {
random_shuffle(p.begin(), p.end());
}

```

```

int n = p.size();
circle c(p[0], 0);
for (int i = 1; i < n; i++) {
if (sign(dist(c.p, p[i]) - c.r) > 0) {
c = circle(p[i], 0);
for (int j = 0; j < i; j++) {
if (sign(dist(c.p, p[j]) - c.r) > 0) {
c = circle((p[i] + p[j]) / 2, dist(p[i],
p[j]) / 2);
for (int k = 0; k < j; k++) {
if (sign(dist(c.p, p[k]) - c.r) > 0) {
c = circle(p[i], p[j], p[k]);
}
}
}
}
}
}
}
return c;
}

```

4.16 MinimumEnclosingRectangle

```

// minimum perimeter
double minimum_enclosing_rectangle(vector<PT> &p) {
int n = p.size();
if (n <= 2) return perimeter(p);
int mndot = 0; double tmp = dot(p[1] - p[0], p[0]);
for (int i = 1; i < n; i++) {
if (dot(p[1] - p[0], p[i]) <= tmp) {
tmp = dot(p[i] - p[0], p[i]);
mndot = i;
}
}
double ans = inf;
int i = 0, j = 1, mxdot = 1;
while (i < n) {
PT cur = p[(i + 1) % n] - p[i];
while (cross(cur, p[(j + 1) % n] - p[j]) >= 0) j = (j +
1) % n;
while (dot(p[(mxdot + 1) % n], cur) >= dot(p[mxdot],
cur)) mxdot = (mxdot + 1) % n;
while (dot(p[(mndot + 1) % n], cur) <= dot(p[mndot],
cur)) mndot = (mndot + 1) % n;
ans = min(ans, 2.0 * ((dot(p[mxdot], cur) / cur.norm()
- dot(p[mndot], cur) / cur.norm()) +
dist_from_point_to_line(p[i], p[(i + 1) % n],
p[j])));
i++;
}
return ans;
}

```

4.17 MinkowskiSum

```
// a and b are strictly convex polygons of DISTINCT points
// returns a convex hull of their minkowski sum with distinct points
vector<PT> minkowski_sum(vector<PT> &a, vector<PT> &b) {
    int n = (int)a.size(), m = (int)b.size();
    int i = 0, j = 0; //assuming a[i] and b[j] both are (left,
        bottom)-most points
    vector<PT> c;
    c.push_back(a[i] + b[j]);
    while (1) {
        PT p1 = a[i] + b[(j + 1) % m];
        PT p2 = a[(i + 1) % n] + b[j];
        int t = orientation(c.back(), p1, p2);
        if (t >= 0) j = (j + 1) % m;
        if (t <= 0) i = (i + 1) % n, p1 = p2;
        if (t == 0) p1 = a[i] + b[j];
        if (p1 == c[0]) break;
        c.push_back(p1);
    }
    return c;
}
```

4.18 MonotoneChain

```
// warning: different template
vector<Point> convex_hull(vector<Point> p, int n){
    sort(p.begin(), p.end(), [](const Point &A, const Point &B){
        return A.x != B.x ? A.x < B.x : A.y < B.y;
    });
    Point st = p[0], en = p[n - 1];
    vector<Point> up = {p[0]};
    vector<Point> down = {p[0]};
    for(int i = 1; i < n; ++i){
        // upper hull
        if(i == n - 1 or cross(st, p[i], en) < 0){
            while((int)up.size() >= 2 and cross(up[up.size() - 2], up.back(), p[i]) >= 0)
                up.pop_back();
            up.push_back(p[i]);
        }
        // lower hull
        if(i == n - 1 or cross(st, p[i], en) > 0){
            while((int)down.size() >= 2 and
                cross(down[down.size() - 2], down.back(), p[i]) <= 0)
                down.pop_back();
            down.push_back(p[i]);
        }
    }
    p.clear();
    for(int i = 0; i < (int)up.size(); ++i)
        p.push_back(up[i]);
    for(int i = down.size() - 2; i >= 1; --i)
        p.push_back(down[i]);
    // return hull in clockwise order
    return p;
}
```

}

4.19 Point2D

```
const double inf = 1e100;
const double eps = 1e-9;
const double PI = acos((double)-1.0);
int sign(double x) { return (x > eps) - (x < -eps); }
struct PT {
    double x, y;
    PT() { x = 0, y = 0; }
    PT(double x, double y) : x(x), y(y) {}
    PT(const PT &p) : x(p.x), y(p.y) {}
    PT operator + (const PT &a) const { return PT(x + a.x, y + a.y); }
    PT operator - (const PT &a) const { return PT(x - a.x, y - a.y); }
    PT operator * (const double a) const { return PT(x * a, y * a); }
    friend PT operator * (const double &a, const PT &b) {
        return PT(a * b.x, a * b.y); }
    PT operator / (const double a) const { return PT(x / a, y / a); }
    bool operator == (PT a) const { return sign(a.x - x) == 0
        && sign(a.y - y) == 0; }
    bool operator != (PT a) const { return !(*this == a); }
    bool operator < (PT a) const { return sign(a.x - x) == 0 ?
        y < a.y : x < a.x; }
    bool operator > (PT a) const { return sign(a.x - x) == 0 ?
        y > a.y : x > a.x; }
    double norm() { return sqrt(x * x + y * y); }
    double norm2() { return x * x + y * y; }
    PT perp() { return PT(-y, x); }
    double arg() { return atan2(y, x); }
    PT truncate(double r) { // returns a vector with norm r and
        having same direction
        double k = norm();
        if (!sign(k)) return *this;
        r /= k;
        return PT(x * r, y * r);
    }
};
inline double dot(PT a, PT b) { return a.x * b.x + a.y * b.y; }
inline double dist2(PT a, PT b) { return dot(a - b, a - b); }
inline double dist(PT a, PT b) { return sqrt(dot(a - b, a - b)); }
inline double cross(PT a, PT b) { return a.x * b.y - a.y * b.x; }
inline double cross2(PT a, PT b, PT c) { return cross(b - a, c - a); }
inline int orientation(PT a, PT b, PT c) { return sign(cross(b - a, c - a)); }
PT perp(PT a) { return PT(-a.y, a.x); }
PT rotateccw90(PT a) { return PT(-a.y, a.x); }
PT rotatecw90(PT a) { return PT(a.y, -a.x); }
PT rotateccw(PT a, double t) { return PT(a.x * cos(t) - a.y * sin(t), a.x * sin(t) + a.y * cos(t)); }
```

```
PT rotatecw(PT a, double t) { return PT(a.x * cos(t) + a.y * sin(t), -a.x * sin(t) + a.y * cos(t)); }
double SQ(double x) { return x * x; }
double rad_to_deg(double r) { return (r * 180.0 / PI); }
double deg_to_rad(double d) { return (d * PI / 180.0); }
double get_angle(PT a, PT b) {
    double costheta = dot(a, b) / a.norm() / b.norm();
    return acos(max((double)-1.0, min((double)1.0, costheta)));
}
bool is_point_in_angle(PT b, PT a, PT c, PT p) { // does point
    p lie in angle <bac
    assert(orientation(a, b, c) != 0);
    if (orientation(a, c, b) < 0) swap(b, c);
    return orientation(a, c, p) >= 0 && orientation(a, b, p) <= 0;
}
```

4.20 PointInsideHull

```
bool on_segment(const Point &A, const Point &B, const Point &C)
{ return cross(A, B, C) == 0 and dot(C, A, B) <= 0; }

bool check(vector<Point> &hull, Point &a) {
    int n = sz(hull);
    if (n == 1) return hull[0] == a;
    if (n == 2) return on_segment(hull[0], hull[1], a);
    if (cross(hull[0], hull[1], a) > 0) return 0;
    if (cross(hull[n - 1], hull[0], a) >= 0) return
        on_segment(hull[n - 1], hull[0], a);
    int l = 2, r = n - 1, ans = -1;
    while (l <= r) {
        int mid = (l + r) / 2;
        if (cross(hull[0], hull[mid], a) >= 0) {
            ans = mid;
            r = mid - 1;
        } else
            l = mid + 1;
    }
    debug(hull[0], hull[ans - 1], hull[ans], a, ans);
    return cross(hull[ans - 1], hull[ans], a) < 0 or
        on_segment(hull[ans - 1], hull[ans], a);
}
```

4.21 PointPolygonTangents

```
pair<PT, PT> convex_line_intersection(vector<PT> &p, PT a, PT b) {
    return {{0, 0}, {0, 0}};
}

pair<PT, int> point_poly_tangent(vector<PT> &p, PT Q, int dir,
    int l, int r) {
    while (r - l > 1) {
        int mid = (l + r) >> 1;
```

```

bool pvs = orientation(Q, p[mid], p[mid - 1]) != -dir;
bool nxt = orientation(Q, p[mid], p[mid + 1]) != -dir;
if (pvs && nxt) return {p[mid], mid};
if (!(pvs || nxt)) {
    auto p1 = point_poly_tangent(p, Q, dir, mid + 1, r);
    auto p2 = point_poly_tangent(p, Q, dir, 1, mid - 1);
    return orientation(Q, p1.first, p2.first) == dir ?
        p1 : p2;
}
if (!pvs) {
    if (orientation(Q, p[mid], p[l]) == dir) r = mid - 1;
    else if (orientation(Q, p[l], p[r]) == dir) r = mid
        - 1;
    else l = mid + 1;
}
if (!nxt) {
    if (orientation(Q, p[mid], p[l]) == dir) l = mid + 1;
    else if (orientation(Q, p[l], p[r]) == dir) r = mid
        - 1;
    else l = mid + 1;
}
}
pair<PT, int> ret = {p[l], l};
for (int i = l + 1; i <= r; i++) ret = orientation(Q,
    ret.first, p[i]) != dir ? make_pair(p[i], i) : ret;
return ret;
}
// (cw, ccw) tangents from a point that is outside this convex
// polygon
// returns indexes of the points
pair<int, int> tangents_from_point_to_polygon(vector<PT> &p, PT
Q) {
    int cw = point_poly_tangent(p, Q, 1, 0, (int)p.size() -
        1).second;
    int ccw = point_poly_tangent(p, Q, -1, 0, (int)p.size() -
        1).second;
    return make_pair(cw, ccw);
}

```

4.22 PolarSort

```

bool half(PT p) {
    return p.y > 0.0 || (p.y == 0.0 && p.x < 0.0);
}
void polar_sort(vector<PT> &v) { // sort points in
    counterclockwise
    sort(v.begin(), v.end(), [](PT a, PT b) {
        return make_tuple(half(a), 0.0, a.norm2()) <
            make_tuple(half(b), cross(a, b), b.norm2());
    });
}
void polar_sort(vector<PT> &v, PT o) { // sort points in
    counterclockwise with respect to point o
    sort(v.begin(), v.end(), [](PT a, PT b) {
        return make_tuple(half(a - o), 0.0, (a - o).norm2()) <
            make_tuple(half(b - o), cross(a - o, b - o), (b -
                o).norm2());
    });
}

```

```

});
}

```

4.23 PolygonCircleIntersection

```

// intersection between a simple polygon and a circle
double polygon_circle_intersection(vector<PT> &v, PT p, double
r) {
    int n = v.size();
    double ans = 0.00;
    PT org = {0, 0};
    for (int i = 0; i < n; i++) {
        int x = orientation(p, v[i], v[(i + 1) % n]);
        if (x == 0) continue;
        double area = triangle_circle_intersection(org, r, v[i]
            - p, v[(i + 1) % n] - p);
        if (x < 0) ans -= area;
        else ans += area;
    }
    return abs(ans);
}

```

4.24 PolygonCut

```

// returns a vector with the vertices of a polygon with
// everything
// to the left of the line going from a to b cut away.
vector<PT> cut(vector<PT> &p, PT a, PT b) {
    vector<PT> ans;
    int n = (int)p.size();
    for (int i = 0; i < n; i++) {
        double c1 = cross(b - a, p[i] - a);
        double c2 = cross(b - a, p[(i + 1) % n] - a);
        if (sign(c1) >= 0) ans.push_back(p[i]);
        if (sign(c1 * c2) < 0) {
            if (!is_parallel(p[i], p[(i + 1) % n], a, b)) {
                PT tmp; line_line_intersection(p[i], p[(i + 1) %
                    n], a, b, tmp);
                ans.push_back(tmp);
            }
        }
    }
    return ans;
}

```

4.25 PolygonDiameter

```

// Maximum distance of 2 points
double diameter(vector<PT> &p) {
    int n = (int)p.size();
    if (n == 1) return 0;
}

```

```

if (n == 2) return dist(p[0], p[1]);
double ans = 0;
int i = 0, j = 1;
while (i < n) {
    while (cross(p[(i + 1) % n] - p[i], p[(j + 1) % n] -
        p[j]) >= 0) {
        ans = max(ans, dist2(p[i], p[j]));
        j = (j + 1) % n;
    }
    ans = max(ans, dist2(p[i], p[j]));
    i++;
}
return sqrt(ans);
}

```

4.26 PolygonDistances

```

// minimum distance from a point to a convex polygon
// it assumes point lie strictly outside the polygon
double dist_from_point_to_polygon(vector<PT> &p, PT z) {
    double ans = inf;
    int n = p.size();
    if (n <= 3) {
        for (int i = 0; i < n; i++) ans = min(ans,
            dist_from_point_to_seg(p[i], p[(i + 1) % n], z));
        return ans;
    }
    auto [r, l] = tangents_from_point_to_polygon(p, z);
    if (l > r) r += n;
    while (l < r) {
        int mid = (l + r) >> 1;
        double left = dist2(p[mid % n], z), right = dist2(p[(mid
            + 1) % n], z);
        ans = min({ans, left, right});
        if (left < right) r = mid;
        else l = mid + 1;
    }
    ans = sqrt(ans);
    ans = min(ans, dist_from_point_to_seg(p[l % n], p[(l + 1) %
        n], z));
    ans = min(ans, dist_from_point_to_seg(p[l % n], p[(l - 1 +
        n) % n], z));
    return ans;
}
// minimum distance from convex polygon p to line ab
// returns 0 is it intersects with the polygon
// top - upper right vertex
double dist_from_polygon_to_line(vector<PT> &p, PT a, PT b, int
top) { // O(log n)
    PT orth = (b - a).perp();
    if (orientation(a, b, p[0]) > 0) orth = (a - b).perp();
    int id = extreme_vertex(p, orth, top);
    if (dot(p[id] - a, orth) > 0) return 0.0; //if orth and a
    are in the same half of the line, then poly and line
    intersects
    return dist_from_point_to_line(a, b, p[id]); //does not
    intersect
}

```

```

}
// minimum distance from a convex polygon to another convex
// polygon
// the polygon doesnot overlap or touch
// tested in https://toph.co/p/the-wall
double dist_from_polygon_to_polygon(vector<PT> &p1, vector<PT>
&p2) { // O(n log n)
    double ans = inf;
    for (int i = 0; i < p1.size(); i++) {
        ans = min(ans, dist_from_point_to_polygon(p2, p1[i]));
    }
    for (int i = 0; i < p2.size(); i++) {
        ans = min(ans, dist_from_point_to_polygon(p1, p2[i]));
    }
    return ans;
}
// maximum distance from a convex polygon to another convex
// polygon
double maximum_dist_from_polygon_to_polygon(vector<PT> &u,
vector<PT> &v){ //O(n)
    int n = (int)u.size(), m = (int)v.size();
    double ans = 0;
    if (n < 3 || m < 3) {
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < m; j++) ans = max(ans,
                dist2(u[i], v[j]));
        }
        return sqrt(ans);
    }
    if (u[0].x > v[0].x) swap(n, m), swap(u, v);
    int i = 0, j = 0, step = n + m + 10;
    while (j + 1 < m && v[j].x < v[j + 1].x) j++;
    while (step-- > 0) {
        if (cross(u[(i + 1) % n] - u[i], v[(j + 1) % m] - v[j]) >=
            0) j = (j + 1) % m;
        else i = (i + 1) % n;
        ans = max(ans, dist2(u[i], v[j]));
    }
    return sqrt(ans);
}

```

4.27 PolygonLineIntersection

```

// not necessarily convex, boundary is included in the
// intersection
// returns total intersected length
double polygon_line_intersection(vector<PT> p, PT a, PT b) {
    int n = p.size();
    p.push_back(p[0]);
    line l = line(a, b);
    double ans = 0.0;
    vector<pair<double, int>> vec;
    for (int i = 0; i < n; i++) {
        int s1 = sign(cross(b - a, p[i] - a));
        int s2 = sign(cross(b - a, p[i+1] - a));
        if (s1 == s2) continue;
        line t = line(p[i], p[i + 1]);
    }

```

```

    PT inter = (t.v * l.c - l.v * t.c) / cross(l.v, t.v);
    double tmp = dot(inter, l.v);
    int f;
    if (s1 > s2) f = s1 && s2 ? 2 : 1;
    else f = s1 && s2 ? -2 : -1;
    vec.push_back(make_pair(tmp, f));
}
sort(vec.begin(), vec.end());
for (int i = 0, j = 0; i + 1 < (int)vec.size(); i++){
    j += vec[i].second;
    if (j) ans += vec[i + 1].first - vec[i].first;
}
ans = ans / sqrt(dot(l.v, l.v));
p.pop_back();
return ans;
}

```

4.28 PolygonUnion

```

// calculates the area of the union of n polygons (not
// necessarily convex).
// the points within each polygon must be given in CCW order.
// complexity: O(N^2), where N is the total number of points
double rat(PT a, PT b, PT p) {
    return !sign(a.x - b.x) ? (p.y - a.y) / (b.y - a.y) :
        (p.x - a.x) / (b.x - a.x);
};
double polygon_union(vector<vector<PT>> &p) {
    int n = p.size();
    double ans=0;
    for(int i = 0; i < n; ++i) {
        for (int v = 0; v < (int)p[i].size(); ++v) {
            PT a = p[i][v], b = p[i][(v + 1) % p[i].size()];
            vector<pair<double, int>> segs;
            segs.emplace_back(0, 0), segs.emplace_back(1, 0);
            for(int j = 0; j < n; ++j) {
                if(i != j) {
                    for(size_t u = 0; u < p[j].size(); ++u) {
                        PT c = p[j][u], d = p[j][(u + 1) %
                            p[j].size()];
                        int sc = sign(cross(b - a, c - a)), sd =
                            sign(cross(b - a, d - a));
                        if(!sc && !sd) {
                            if(sign(dot(b - a, d - c)) > 0 && i >
                                j) {
                                segs.emplace_back(rat(a, b, c),
                                    1), segs.emplace_back(rat(a,
                                    b, d), -1);
                            }
                        }
                    }
                }
            }
            sort(segs.begin(), segs.end());
            double sa = cross(d - c, a - c), sb =
                cross(d - c, b - c);
            if(sc >= 0 && sd < 0)
                segs.emplace_back(sa / (sa -
                    sb), 1);
        }
    }
}

```

```

        else if(sc < 0 && sd >= 0)
            segs.emplace_back(sa / (sa -
                sb), -1);
        }
    }
    sort(segs.begin(), segs.end());
    double pre = min(max(segs[0].first, 0.0), 1.0), now,
        sum = 0;
    int cnt = segs[0].second;
    for(int j = 1; j < segs.size(); ++j) {
        now = min(max(segs[j].first, 0.0), 1.0);
        if (!cnt) sum += now - pre;
        cnt += segs[j].second;
        pre = now;
    }
    ans += cross(a, b) * sum;
}
return ans * 0.5;
}

```

4.29 PolygonWidth

```

// Maximum distance between 2 points IN the polygon
double width(vector<PT> &p) {
    int n = (int)p.size();
    if (n <= 2) return 0;
    double ans = inf;
    int i = 0, j = 1;
    while (i < n) {
        while (cross(p[(i + 1) % n] - p[i], p[(j + 1) % n] -
            p[j]) >= 0) j = (j + 1) % n;
        ans = min(ans, dist_from_point_to_line(p[i], p[(i + 1)
            % n], p[j]));
        i++;
    }
    return ans;
}

```

4.30 Ray

```

// minimum distance from point c to ray (starting point a and
// direction vector b)
double dist_from_point_to_ray(PT a, PT b, PT c) {
    b = a + b;
    double r = dot(c - a, b - a);
    if (r < 0.0) return dist(c, a);
    return dist_from_point_to_line(a, b, c);
}
// starting point as and direction vector ad
bool ray_ray_intersection(PT as, PT ad, PT bs, PT bd) {
    double dx = bs.x - as.x, dy = bs.y - as.y;
}

```

```

double det = bd.x * ad.y - bd.y * ad.x;
if (fabs(det) < eps) return 0;
double u = (dy * bd.x - dx * bd.y) / det;
double v = (dy * ad.x - dx * ad.y) / det;
if (sign(u) >= 0 && sign(v) >= 0) return 1;
else return 0;
}
double ray_ray_distance(PT as, PT ad, PT bs, PT bd) {
    if (ray_ray_intersection(as, ad, bs, bd)) return 0.0;
    double ans = dist_from_point_to_ray(as, ad, bs);
    ans = min(ans, dist_from_point_to_ray(bs, bd, as));
    return ans;
}

```

4.31 Segment

```

// returns true if point p is on line segment ab
bool is_point_on_seg(PT a, PT b, PT p) {
    if (fabs(cross(p - b, a - b)) < eps) {
        if (p.x < min(a.x, b.x) || p.x > max(a.x, b.x)) return
            false;
        if (p.y < min(a.y, b.y) || p.y > max(a.y, b.y)) return
            false;
        return true;
    }
    return false;
}
// minimum distance point from point c to segment ab that lies
// on segment ab
PT project_from_point_to_seg(PT a, PT b, PT c) {
    double r = dist2(a, b);
    if (sign(r) == 0) return a;
    r = dot(c - a, b - a) / r;
    if (r < 0) return a;
    if (r > 1) return b;
    return a + (b - a) * r;
}
// minimum distance from point c to segment ab
double dist_from_point_to_seg(PT a, PT b, PT c) {
    return dist(c, project_from_point_to_seg(a, b, c));
}
// intersection point between segment ab and segment cd
// assuming unique intersection exists
bool seg_seg_intersection(PT a, PT b, PT c, PT d, PT &ans) {
    double oa = cross2(c, d, a), ob = cross2(c, d, b);
    double oc = cross2(a, b, c), od = cross2(a, b, d);
    if (oa * ob < 0 && oc * od < 0) {
        ans = (a * ob - b * oa) / (ob - oa);
        return 1;
    }
    else return 0;
}
// intersection point between segment ab and segment cd
// assuming unique intersection may not exists
// se.size()==0 means no intersection
// se.size()==1 means one intersection
// se.size()==2 means range intersection

```

```

set<PT> seg_seg_intersection_inside(PT a, PT b, PT c, PT d) {
    PT ans;
    if (seg_seg_intersection(a, b, c, d, ans)) return {ans};
    set<PT> se;
    if (is_point_on_seg(c, d, a)) se.insert(a);
    if (is_point_on_seg(c, d, b)) se.insert(b);
    if (is_point_on_seg(a, b, c)) se.insert(c);
    if (is_point_on_seg(a, b, d)) se.insert(d);
    return se;
}
// intersection between segment ab and line cd
// 0 if do not intersect, 1 if proper intersect, 2 if segment
// intersect
int seg_line_relation(PT a, PT b, PT c, PT d) {
    double p = cross2(c, d, a);
    double q = cross2(c, d, b);
    if (sign(p) == 0 && sign(q) == 0) return 2;
    else if (p * q < 0) return 1;
    else return 0;
}
// intersection between segment ab and line cd assuming unique
// intersection exists
bool seg_line_intersection(PT a, PT b, PT c, PT d, PT &ans) {
    bool k = seg_line_relation(a, b, c, d);
    assert(k != 2);
    if (k) line_line_intersection(a, b, c, d, ans);
    return k;
}
// minimum distance from segment ab to segment cd
double dist_from_seg_to_seg(PT a, PT b, PT c, PT d) {
    PT dummy;
    if (seg_seg_intersection(a, b, c, d, dummy)) return 0.0;
    else return min({dist_from_point_to_seg(a, b, c),
        dist_from_point_to_seg(a, b, d),
        dist_from_point_to_seg(c, d, a),
        dist_from_point_to_seg(c, d, b)});
}

```

4.32 SmallestEnclosingCircle

```

double eps = 1e-9;
using Point = complex<double>;
struct Circle { Point p; double r; };
double dist(Point p, Point q) { return abs(p-q); }
double area2(Point p, Point q) { return (conj(p)*q).imag(); }
bool in(const Circle& c, Point p) { return dist(c.p, p) < c.r +
    eps; }
Circle INVALID = Circle{Point(0, 0), -1};
Circle mCC(Point a, Point b, Point c) {
    b -= a; c -= a;
    double d = 2*(conj(b)*c).imag(); if (abs(d)<eps) return
        INVALID;
    Point ans = (c*norm(b) - b*norm(c)) * Point(0, -1) / d;
    return Circle{a + ans, abs(ans)};
}
Circle solve(vector<Point> p) {
    mt19937 gen(0x9494949); shuffle(p.begin(), p.end(), gen);
}

```

```

Circle c = INVALID;
for(int i=0; i<p.size(); ++i) if(c.r<0 || !in(c, p[i])){
    c = Circle{p[i], 0};
    for(int j=0; j<=i; ++j) if(!in(c, p[j])){
        Circle ans{(p[i]+p[j])*0.5, dist(p[i],
            p[j])*0.5};
        if(c.r == 0) {c = ans; continue;}
        Circle l, r; l = r = INVALID;
        Point pq = p[j]-p[i];
        for(int k=0; k<=j; ++k) if(!in(ans,
            p[k])) {
            double a2 = area2(pq, p[k]-p[i]);
            Circle c = mCC(p[i], p[j], p[k]);
            if(c.r<0) continue;
            else if(a2 > 0 &&
                (1.r<0 || area2(pq, c.p-p[i])
                    > area2(pq, l.p-p[i]))) l =
                c;
            else if(a2 < 0 &&
                (r.r<0 || area2(pq, c.p-p[i])
                    < area2(pq, r.p-p[i]))) r =
                c;
        }
        if(1.r<0 && r.r<0) c = ans;
        else if(1.r<0) c = r;
        else if(r.r<0) c = l;
        else c = 1.r<=r.r ? l : r;
    }
}
return c;
}

```

4.33 TriangleCircleIntersection

```

// system should be translated from circle center
double triangle_circle_intersection(PT c, double r, PT a, PT b)
{
    double sd1 = dist2(c, a), sd2 = dist2(c, b);
    if(sd1 > sd2) swap(a, b), swap(sd1, sd2);
    double sd = dist2(a, b);
    double d1 = sqrt1(sd1), d2 = sqrt1(sd2), d = sqrt(sd);
    double x = abs(sd2 - sd - sd1) / (2 * d);
    double h = sqrt1(sd1 - x * x);
    if(r >= d2) return h * d / 2;
    double area = 0;
    if(sd + sd1 < sd2) {
        if(r < d1) area = r * r * (acos(h / d2) - acos(h / d1))
            / 2;
        else {
            area = r * r * (acos(h / d2) - acos(h / r)) / 2;
            double y = sqrt1(r * r - h * h);
            area += h * (y - x) / 2;
        }
    }
    else {
        if(r < h) area = r * r * (acos(h / d2) + acos(h / d1))
            / 2;
    }
}

```

```

    else {
        area += r * r * (acos(h / d2) - acos(h / r)) / 2;
        double y = sqrt1(r * r - h * h);
        area += h * y / 2;
        if (r < d1) {
            area += r * r * (acos(h / d1) - acos(h / r)) / 2;
            area += h * y / 2;
        }
        else area += h * x / 2;
    }
}
return area;
}

```

4.34 Utilities

```

double perimeter(vector<PT> &p) {
    double ans=0; int n = p.size();
    for (int i = 0; i < n; i++) ans += dist(p[i], p[(i + 1) % n]);
    return ans;
}

double area(vector<PT> &p) {
    double ans = 0; int n = p.size();
    for (int i = 0; i < n; i++) ans += cross(p[i], p[(i + 1) % n]);
    return fabs(ans) * 0.5;
}

double area_of_triangle(PT a, PT b, PT c) {
    return fabs(cross(b - a, c - a) * 0.5);
}

// 0 if cw, 1 if ccw
bool get_direction(vector<PT> &p) {
    double ans = 0; int n = p.size();
    for (int i = 0; i < n; i++) ans += cross(p[i], p[(i + 1) % n]);
    if (sign(ans) > 0) return 1;
    return 0;
}

// find a point from a through b with distance d
PT point_along_line(PT a, PT b, double d) {
    assert(a != b);
    return a + ((b - a) / (b - a).norm()) * d;
}

// projection point c onto line through a and b assuming a != b
PT project_from_point_to_line(PT a, PT b, PT c) {
    return a + (b - a) * dot(c - a, b - a) / (b - a).norm2();
}

// reflection point c onto line through a and b assuming a != b
PT reflection_from_point_to_line(PT a, PT b, PT c) {
    PT p = project_from_point_to_line(a, b, c);
    return p + p - c;
}

// minimum distance from point c to line through a and b
double dist_from_point_to_line(PT a, PT b, PT c) {
    return fabs(cross(b - a, c - a) / (b - a).norm());
}

```

```

// 0 if not parallel, 1 if parallel, 2 if collinear
int is_parallel(PT a, PT b, PT c, PT d) {
    double k = fabs(cross(b - a, d - c));
    if (k < eps) {
        if (fabs(cross(a - b, a - c)) < eps && fabs(cross(c - d, c - a)) < eps) return 2;
        else return 1;
    }
    else return 0;
}

// check if two lines are same
bool are_lines_same(PT a, PT b, PT c, PT d) {
    if (fabs(cross(a - c, c - d)) < eps && fabs(cross(b - c, c - d)) < eps) return true;
    return false;
}

// 1 if point is ccw to the line, 2 if point is cw to the line,
// 3 if point is on the line
int point_line_relation(PT a, PT b, PT p) {
    int c = sign(cross(p - a, b - a));
    if (c < 0) return 1;
    if (c > 0) return 2;
    return 3;
}

```

5 Graph

5.1 BiconnectedComponents

```

struct BiconnectedComponent {
    vector<int> low, num, s;
    vector<vector<int>> components;
    int counter;

    BiconnectedComponent() : low(n, -1), num(n, -1), counter(0) {
        for (int i = 0; i < n; i++)
            if (num[i] < 0) dfs(i, 1);
    }

    void dfs(int x, int isRoot) {
        low[x] = num[x] = ++counter;
        if (g[x].empty()) {
            components.push_back(vector<int>(1, x));
            return;
        }
        s.push_back(x);

        for (int i = 0; i < (int)g[x].size(); i++) {
            int y = g[x][i];
            if (num[y] > -1)
                low[x] = min(low[x], num[y]);
            else {
                dfs(y, 0);
                low[x] = min(low[x], low[y]);
            }
        }
    }
}

```

```

if (isRoot || low[y] >= num[x]) {
    components.push_back(vector<int>(1, x));
    while (1) {
        int u = s.back();
        s.pop_back();
        components.back().push_back(u);
        if (u == y) break;
    }
}
}
}
};

int find_centroid(const vector<vector<int>> &G, const vector<bool> &used, int v) {
    vector<tuple<int, int, int>> sz;
    function<void(int, int)> dfs = [&](int a, int p) {
        int S = 1, mx = 0;
        for (int x : G[a]) if (x != p && !used[x]) {
            dfs(x, a);
            int c = get<1>(sz.back());
            S += c, mx = max(mx, c);
        }
        sz.emplace_back(a, S, mx);
    };
    dfs(v, -1);
    int S = get<1>(sz.back());
    for (auto [i, s, mx] : sz) if (2 * max(S - s, mx) <= S)
        return i;
}

answer_type solve(const vector<vector<int>> &G) {
    vector<bool> used(size(G), 0);
    answer_type answer;
    auto work = [&](int c) {
        /* Do something on rooted tree c
        DFS with !used[x] (See above) */
    };
    queue<int> Q; Q.emplace(0);
    while (!Q.empty()) {
        int x = Q.front();
        Q.pop();
        int c = find_centroid(G, used, x);
        work(c);
        used[c] = 1;
        for (int x : G[c]) if (!used[x]) Q.emplace(x);
    }
    return answer;
}

```

5.3 Dinic


```

const ll INF = 1e18;
struct Dinic {
    const static bool SCALING = false; // scaling = EV log(max C)
    with larger constant
    ll lim = 1;

    struct Edge {
        int u, v;
        ll cap, flow;
    };

    int n, s, t;
    vector<int> level, ptr;
    vector<Edge> e;
    vector<vector<int>> g;

    Dinic(int _n) : n(_n), level(_n), ptr(_n), g(_n) {
        e.clear();
        for (int i = 0; i < n; ++i) {
            ptr[i] = 0;
            g[i].clear();
        }
    }

    void add_edge(int u, int v, ll c) {
        debug(u, v, c);
        g[u].push_back(sz(e));
        e.push_back({u, v, c, 0});
        g[v].push_back(sz(e));
        e.push_back({v, u, 0, 0});
    }

    ll get_max_flow(int _s, int _t) {
        s = _s, t = _t;
        ll flow = 0;
        for (lim = SCALING ? (1 << 30) : 1; lim > 0; lim >= 1) {
            while (1) {
                if (!bfs()) break;
                fill(all(ptr), 0);
                while (ll pushed = dfs(s, INF)) flow += pushed;
            }
        }
        return flow;
    }

private:
    bool bfs() {
        queue<int> q;
        q.push(s);
        fill(all(level), -1);
        level[s] = 0;
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (int id : g[u]) {
                if (e[id].cap - e[id].flow < 1) continue;
                if (level[e[id].v] != -1) continue;
                if (SCALING and e[id].cap - e[id].flow < lim) continue;
                level[e[id].v] = level[u] + 1;
            }
        }
    }

```

```

        q.push(e[id].v);
    }
}
return level[t] != -1;
}

ll dfs(int u, ll flow) {
    if (!flow) return 0;
    if (u == t) return flow;
    for (; ptr[u] < sz(g[u]); ++ptr[u]) {
        int id = g[u][ptr[u]], to = e[id].v;
        if (level[to] != level[u] + 1) continue;
        ll pushed = dfs(to, min(flow, e[id].cap - e[id].flow));
        if (pushed) {
            e[id].flow += pushed;
            e[id ^ 1].flow -= pushed;
            return pushed;
        }
    }
    return 0;
}
};

```

5.4 EulerPath

```

struct EulerUndirected {
    EulerUndirected(int _n) : n(_n), m(0), adj(_n), deg(_n, 0) {}

    void add_edge(int u, int v) {
        adj[u].push_front(Edge(v));
        auto it1 = adj[u].begin();
        adj[v].push_front(Edge(u));
        auto it2 = adj[v].begin();

        it1->rev = it2;
        it2->rev = it1;

        ++deg[u];
        ++deg[v];
        ++m;
    }

    std::pair<bool, std::vector<int>> solve() {
        int cntOdd = 0;
        int start = -1;
        for (int i = 0; i < n; i++) {
            if (deg[i] % 2) {
                ++cntOdd;
                if (cntOdd > 2) return {false, {}};
            }
            if (start < 0) start = i;
        }

        // no odd vertex -> start from any vertex with positive degree
    }
}

```

```

    if (start < 0) {
        for (int i = 0; i < n; i++) {
            if (deg[i]) {
                start = i;
                break;
            }
        }
        if (start < 0) {
            // no edge -> empty path
            return {true, {}};
        }
    }

    std::vector<int> path;
    find_path(start, path);

    if (m + 1 != static_cast<int>(path.size())) {
        return {false, {}};
    }

    return {true, path};
}

struct Edge {
    int to;
    std::list<Edge>::iterator rev;

    Edge(int _to) : to(_to) {}
};

//private:
int n, m;
std::vector<std::list<Edge>> adj;
std::vector<int> deg;

void find_path(int v, std::vector<int>& path) {
    while (adj[v].size() > 0) {
        int next = adj[v].front().to;
        adj[next].erase(adj[v].front().rev);
        adj[v].pop_front();
        find_path(next, path);
    }
    path.push_back(v);
}
};

```

5.5 EulerPathDirected

```

struct EulerDirected {
    EulerDirected(int _n) : n(_n), adj(n), in_deg(n, 0), out_deg(n, 0) {}

    void add_edge(int u, int v) { // directed edge
        assert(0 <= u && u < n);
        assert(0 <= v && v < n);
        adj[u].push_front(v);
        in_deg[v]++;
    }
}

```



```

    out_deg[u]++;
}

std::pair<bool, std::vector<int>> solve() {
    int start = -1, last = -1;
    for (int i = 0; i < n; i++) {
        // for all u, |in_deg(u) - out_deg(u)| <= 1
        if (std::abs(in_deg[i] - out_deg[i]) > 1) return
            {false, {}};

        if (out_deg[i] > in_deg[i]) {
            // At most 1 vertex with out_deg[u] - in_deg[u]
            // = 1 (start vertex)
            if (start >= 0) return {false, {}};
            start = i;
        }

        if (in_deg[i] > out_deg[i]) {
            // At most 1 vertex with in_deg[u] - out_deg[u]
            // = 1 (last vertex)
            if (last >= 0) return {false, {}};
            last = i;
        }
    }

    // can start at any vertex with degree > 0
    if (start < 0) {
        for (int i = 0; i < n; i++) {
            if (in_deg[i]) {
                start = i;
                break;
            }
        }
        // no start vertex --> all vertices have degree == 0
        if (start < 0) return {true, {}};
    }

    std::vector<int> path;
    find_path(start, path);
    std::reverse(path.begin(), path.end());

    // check that we visited all vertices with degree > 0
    std::vector<bool> visited(n, false);
    for (int u : path) visited[u] = true;

    for (int u = 0; u < n; u++) {
        if (in_deg[u] && !visited[u]) {
            return {false, {}};
        }
    }

    return {true, path};
}

private:
    int n;
    std::vector<std::list<int>> adj;
    std::vector<int> in_deg, out_deg;

    void find_path(int v, std::vector<int>& path) {

```

```

        while (adj[v].size() > 0) {
            int next = adj[v].front();
            adj[v].pop_front();
            find_path(next, path);
        }
        path.push_back(v);
    }
};

5.6 GeneralMatching

const int MAXN = 2020 + 1;
struct GM { // 1-based Vertex index
    int vis[MAXN], par[MAXN], orig[MAXN], match[MAXN],
        aux[MAXN], t, N;
    vector<int> conn[MAXN];
    queue<int> Q;
    void addEdge(int u, int v) {
        conn[u].push_back(v); conn[v].push_back(u);
    }
    void init(int n) {
        N = n; t = 0;
        for (int i=0; i<n; ++i) {
            conn[i].clear();
            match[i] = aux[i] = par[i] = 0;
        }
    }
    void augment(int u, int v) {
        int pv = v, nv;
        do {
            pv = par[pv]; nv = match[pv];
            match[pv] = pv; match[pv] = v;
            v = nv;
        } while (u != pv);
    }
    int lca(int v, int w) {
        ++t;
        while (true) {
            if (v) {
                if (aux[v] == t) return v; aux[v] =
                    t;
                v = orig[par[match[v]]];
            }
            swap(v, w);
        }
    }
    void blossom(int v, int w, int a) {
        while (orig[v] != a) {
            par[v] = w; w = match[v];
            if (vis[w] == 1) Q.push(w), vis[w] = 0;
            orig[v] = orig[w] = a;
            v = par[w];
        }
    }
    bool bfs(int u) {
        fill(vis+1, vis+1+N, -1); iota(orig + 1, orig +
            N + 1, 1);

```

```

        Q = queue<int> (); Q.push(u); vis[u] = 0;
        while (!Q.empty()) {
            int v = Q.front(); Q.pop();
            for (int x: conn[v]) {
                if (vis[x] == -1) {
                    par[x] = v; vis[x] = 1;
                    if (!match[x]) return
                        augment(u, x), true;
                    Q.push(match[x]);
                    vis[match[x]] = 0;
                }
                else if (vis[x] == 0 && orig[v] !=
                    orig[x]) {
                    int a = lca(orig[v],
                        orig[x]);
                    blossom(x, v, a);
                    blossom(v, x, a);
                }
            }
        }
        return false;
    }
    int Match() {
        int ans = 0;
        //find random matching (not necessary, constant
        //improvement)
        vector<int> V(N-1); iota(V.begin(), V.end(), 1);
        shuffle(V.begin(), V.end(), mt19937(0x94949));
        for (auto x: V) if (!match[x]) {
            for (auto y: conn[x]) if (!match[y]) {
                match[x] = y, match[y] = x;
                ++ans; break;
            }
        }
        for (int i=1; i<=N; ++i) if (!match[i] && bfs(i))
            ++ans;
        return ans;
    }
};

```

5.7 GlobalMinCut

```

pair<int, vi> GetMinCut(vector<vi>& weights) {
    int N = sz(weights);
    vi used(N), cut, best_cut;
    int best_weight = -1;
    for (int phase = N - 1; phase >= 0; phase--) {
        vi w = weights[0], added = used;
        int prev, k = 0;
        rep(i, 0, phase) {
            prev = k;
            k = -1;
            rep(j, 1, N) if (!added[j] && (k == -1 || w[j] > w[k])) k
                = j;
            if (i == phase - 1) {
                rep(j, 0, N) weights[prev][j] += weights[k][j];
                rep(j, 0, N) weights[j][prev] = weights[prev][j];
            }
        }
    }
}

```

```

        used[k] = true;
        cut.push_back(k);
        if (best_weight == -1 || w[k] < best_weight) {
            best_cut = cut;
            best_weight = w[k];
        }
    } else {
        rep(j, 0, N) w[j] += weights[k][j];
        added[k] = true;
    }
}
}
return {best_weight, best_cut};
}

```

5.8 KhopCau

```

#include <bits/stdc++.h>

using namespace std;

const int maxN = 10010;

int n, m;
bool joint[maxN];
int timeDfs = 0, bridge = 0;
int low[maxN], num[maxN];
vector<int> g[maxN];

void dfs(int u, int pre) {
    int child = 0; // So luong con truc tiep cua dinh u trong cy DFS
    num[u] = low[u] = ++timeDfs;
    for (int v : g[u]) {
        if (v == pre) continue;
        if (!num[v]) {
            dfs(v, u);
            low[u] = min(low[u], low[v]);
            if (low[v] == num[v]) bridge++;
            child++;
            if (u == pre) { // Neu u l dinh goc cua cy DFS
                if (child > 1) joint[u] = true;
            }
            else if (low[v] >= num[u]) joint[u] = true;
        }
        else low[u] = min(low[u], num[v]);
    }
}

int main() {
    cin >> n >> m;
    for (int i = 1; i <= m; i++) {
        int u, v;
        cin >> u >> v;
        g[u].push_back(v);
        g[v].push_back(u);
    }
}

```

```

for (int i = 1; i <= n; i++)
    if (!num[i]) dfs(i, i);

int cntJoint = 0;
for (int i = 1; i <= n; i++) cntJoint += joint[i];

cout << cntJoint << ' ' << bridge;
}

```

5.9 MCMF

```

#include <bits/extc++.h>
const ll INF = numeric_limits<ll>::max() / 4;
typedef vector<ll> VL;
struct MCMF {
    int N;
    vector<vi> ed, red;
    vector<VL> cap, flow, cost;
    vi seen;
    VL dist, pi;
    vector<pii> par;
    MCMF(int N) : N(N), ed(N), red(N), cap(N, VL(N)), flow(cap),
        cost(cap), seen(N), dist(N), pi(N), par(N) {}
    void addEdge(int from, int to, ll cap, ll cost) {
        this->cap[from][to] = cap;
        this->cost[from][to] = cost;
        ed[from].push_back(to);
        red[to].push_back(from);
    }
    void path(int s) {
        fill(all(seen), 0);
        fill(all(dist), INF);
        dist[s] = 0;
        ll di;
        __gnu_pbds::priority_queue<pair<ll, int>> q;
        vector<decltype(q)::point_iterator> its(N);
        q.push({0, s});
        auto relax = [&](int i, ll cap, ll cost, int dir) {
            ll val = di - pi[i] + cost;
            if (cap && val < dist[i]) {
                dist[i] = val;
                par[i] = {s, dir};
                if (its[i] == q.end())
                    its[i] = q.push({-dist[i], i});
                else
                    q.modify(its[i], {-dist[i], i});
            }
        };
        while (!q.empty()) {
            s = q.top().second;
            q.pop();
            seen[s] = 1;
            di = dist[s] + pi[s];
            trav(i, ed[s]) if (!seen[i]) relax(i, cap[s][i] -
                flow[s][i], cost[s][i], 1);
            trav(i, red[s]) if (!seen[i]) relax(i, flow[i][s],
                -cost[i][s], 0);
        }
    }
};

```

```

}
rep(i, 0, N) pi[i] = min(pi[i] + dist[i], INF);
}
pair<ll, ll> maxflow(int s, int t) {
    ll totflow = 0, totcost = 0;
    while (path(s), seen[t]) {
        ll fl = INF;
        for (int p, r, x = t; tie(p, r) = par[x], x != s; x = p)
            fl = min(fl, r ? cap[p][x] - flow[p][x] :
                flow[x][p]);
        totflow += fl;
        for (int p, r, x = t; tie(p, r) = par[x], x != s; x = p)
            if (r)
                flow[p][x] += fl;
            else
                flow[x][p] -= fl;
    }
    rep(i, 0, N) rep(j, 0, N) totcost += cost[i][j] *
        flow[i][j];
    return {totflow, totcost};
}
// I f some costs can be negative , call this before maxflow:
void setpi(int s) { // (otherwise , leave this out)
    fill(all(pi), INF);
    pi[s] = 0;
    int it = N, ch = 1;
    ll v;
    while (ch-- && it--) rep(i, 0, N) if (pi[i] != INF)
        trav(to, ed[i]) if (cap[i][to] && ((v = pi[i] +
            cost[i][to]) < pi[to]) pi[to] = v, ch = 1;
        assert(it >= 0); // negative cost cycle
    }
};

```

5.10 StronglyConnected

```

struct DirectedDfs {
    vector<vector<int>> g;
    int n;
    vector<int> num, low, current, S;
    int counter;
    vector<int> comp_ids;
    vector<vector<int>> scc;

    DirectedDfs(const vector<vector<int>>& _g)
        : g(_g),
          n(g.size()),
          num(n, -1),
          low(n, 0),
          current(n, 0),
          counter(0),
          comp_ids(n, -1) {
        for (int i = 0; i < n; i++) {
            if (num[i] == -1) dfs(i);
        }
    }
};

```

```

void dfs(int u) {
    low[u] = num[u] = counter++;
    S.push_back(u);
    current[u] = 1;
    for (auto v : g[u]) {
        if (num[v] == -1) dfs(v);
        if (current[v]) low[u] = min(low[u], low[v]);
    }
    if (low[u] == num[u]) {
        scc.push_back(vector<int>());
        while (1) {
            int v = S.back();
            S.pop_back();
            current[v] = 0;
            scc.back().push_back(v);
            comp_ids[v] = ((int)scc.size()) - 1;
            if (u == v) break;
        }
    }
}

// build DAG of strongly connected components
// Returns: adjacency list of DAG
std::vector<std::vector<int>>> build_scc_dag() {
    std::vector<std::vector<int>>> dag(scc.size());
    for (int u = 0; u < n; u++) {
        int x = comp_ids[u];
        for (int v : g[u]) {
            int y = comp_ids[v];
            if (x != y) {
                dag[x].push_back(y);
            }
        }
    }
    return dag;
}
};

```

5.11 TopoSort

```

std::pair<bool, std::vector<int>>> topo_sort(const
    std::vector<std::vector<int>>>& g) {
    int n = g.size();
    // init in_deg
    std::vector<int> in_deg(n, 0);
    for (int u = 0; u < n; u++) {
        for (int v : g[u]) {
            in_deg[v]++;
        }
    }

    // find topo order
    std::vector<int> res;
    std::queue<int> qu;
    for (int u = 0; u < n; u++) {
        if (in_deg[u] == 0) {
            qu.push(u);

```

```

    }
}

while (!qu.empty()) {
    int u = qu.front();
    qu.pop();
    res.push_back(u);
    for (int v : g[u]) {
        in_deg[v]--;
        if (in_deg[v] == 0) {
            qu.push(v);
        }
    }
}

if ((int)res.size() < n) {
    return {false, {}};
}
return {true, res};
}

```

6 Math

6.1 Euclid

```

ll gcd(ll a, ll b) { return __gcd(a, b); }
ll euclid(ll a, ll b, ll &x, ll &y) {
    if (b) {
        ll d = euclid(b, a % b, y, x);
        return y -= a / b * x, d;
    }
    return x = 1, y = 0, a;
}

```

6.2 Factorization

```

inline long long qpow(long long a, int b) {
    long long ans = 1;
    while (b) {
        if (b & 1) ans = ans * a % mod;
        a = a * a % mod;
        b >>= 1;
    }
    return ans;
}

inline long long rv(int x) {
    return qpow(x, mod - 2) % mod;
}

bool is_prime(long long n) {
    if (n <= 1) return false;
    for (int a : {2, 3, 5, 13, 19, 73, 193, 407521,
        299210837}) {
        if (n == a) return true;

```

```

        if (n % a == 0) return false;
    }
    long long d = n - 1;
    while (!(d & 1)) d >>= 1;
    for (int a : {2, 325, 9375, 28178, 450775, 9780504,
        1795265022}) {
        long long t = d, y = ipow(a, t, n);
        while (t != n - 1 && y != 1 && y != n - 1) y =
            mul(y, y, n), t <<= 1;
        if (y != n - 1 && !(t & 1)) return false;
    }
    return true;
}

long long pollard(long n) {
    auto f = [n](long x) { return mul(x, x, n) + 1; };
    long long x = 0, y = 0, t = 0, prd = 2, i = 1, q;
    while (t++ % 40 || gcd(prd, n) == 1) {
        if (x == y) x = ++i, y = f(x);
        if ((q = mul(prd, max(x, y) - min(x, y), n)))
            prd = q;
        x = f(x), y = f(f(y));
    }
    return gcd(prd, n);
}

vector<long long> factor(long n)
{
    if (n == 1) return {};
    if (is_prime(n)) return {n};
    long x = pollard(n);
    auto l = factor(x), r = factor(n / x);
    l.insert(l.end(), r.begin(), r.end());
    return l;
}

```

6.3 FFT

```

using ld = double;
// Can use std::complex<ld> instead to make code shorter (but
// it will be slightly slower)
struct Complex {
    ld x[2];

    Complex() { x[0] = x[1] = 0.0; }
    Complex(ld a) { x[0] = a; }
    Complex(ld a, ld b) {
        x[0] = a;
        x[1] = b;
    }

    Complex(const std::complex<ld>& c) {
        x[0] = c.real();
        x[1] = c.imag();
    }

    Complex conj() const { return Complex(x[0], -x[1]); }

    Complex operator+(const Complex& c) const {

```

```

    return Complex{
        x[0] + c.x[0],
        x[1] + c.x[1],
    };
}
Complex operator-(const Complex& c) const {
    return Complex{
        x[0] - c.x[0],
        x[1] - c.x[1],
    };
}
Complex operator*(const Complex& c) const { return
    Complex(x[0] * c.x[0] - x[1] * c.x[1], x[0] * c.x[1] +
        x[1] * c.x[0]); }

Complex& operator+=(const Complex& c) { return *this = *this
    + c; }
Complex& operator-=(const Complex& c) { return *this = *this
    - c; }
Complex& operator*=(const Complex& c) { return *this = *this
    * c; }
};
void fft(vector<Complex>& a) {
    int n = a.size();
    int L = 31 - __builtin_clz(n);
    static vector<Complex> R(2, 1);
    static vector<Complex> rt(2, 1);
    for (static int k = 2; k < n; k *= 2) {
        R.resize(n);
        rt.resize(n);
        auto x = Complex(polar(ld(1.0), acos(ld(-1.0)) / k));
        for (int i = k; i < 2 * k; ++i) {
            rt[i] = R[i] = i & 1 ? R[i / 2] * x : R[i / 2];
        }
    }
    vector<int> rev(n);
    for (int i = 0; i < n; ++i) rev[i] = (rev[i / 2] | (i & 1) <<
        L) / 2;
    for (int i = 0; i < n; ++i)
        if (i < rev[i]) swap(a[i], a[rev[i]]);

    for (int k = 1; k < n; k *= 2) {
        for (int i = 0; i < n; i += 2 * k) {
            for (int j = 0; j < k; ++j) {
                auto x = (ld*)&rt[j + k].x, y = (ld*)&a[i + j + k].x;
                Complex z(x[0] * y[0] - x[1] * y[1], x[0] * y[1] + x[1]
                    * y[0]);
                a[i + j + k] = a[i + j] - z;
                a[i + j] += z;
            }
        }
    }
}
vector<ld> multiply(const vector<ld>& a, const vector<ld>& b) {
    if (a.empty() || b.empty()) return {};
    vector<ld> res(a.size() + b.size() - 1);
    int L = 32 - __builtin_clz(res.size());
    vector<Complex> in(n), out(n);

    for (size_t i = 0; i < a.size(); ++i) in[i].x[0] = a[i];

```

```

    for (size_t i = 0; i < b.size(); ++i) in[i].x[1] = b[i];

    fft(in);
    for (Complex& x : in) x *= x;

    for (int i = 0; i < n; ++i) out[i] = in[-i & (n - 1)] -
        in[i].conj();
    fft(out);

    for (size_t i = 0; i < res.size(); ++i) res[i] = out[i].x[1]
        / (4 * n);
    return res;
}
long long my_round(ld x) {
    if (x < 0) return -my_round(-x);
    return (long long)(x + 1e-2);
}
vector<long long> multiply(const vector<int>& a, const
    vector<int>& b) {
    vector<ld> ad(a.begin(), a.end());
    vector<ld> bd(b.begin(), b.end());
    auto rd = multiply(ad, bd);
    vector<long long> res(rd.size());
    for (int i = 0; i < (int)res.size(); ++i) {
        res[i] = my_round(rd[i]);
    }
    return res;
}

```

6.4 Interpolate

```

const int mod = 1e9 + 7;
const int N = 1e6 + 6;

long long inv[N], po[N], pre[N], suf[N], dakdak[N];
long long ans, num;

inline long long qpow(long long a, int b) {
    long long ans = 1;
    while (b) {
        if (b & 1) ans = ans * a % mod;
        a = a * a % mod;
        b >>= 1;
    }
    return ans;
}
inline long long rv(int x) { return qpow(x, mod - 2) % mod; }
void prec() {
    inv[0] = 1;
    for (int i = 1; i <= k + 1; ++i) {
        inv[i] = (1LL * inv[i - 1] * rv(i)) % mod;
        po[i] = (po[i - 1] + qpow(i, k)) % mod;
    }
    for (int i = 1; i <= k + 1; ++i) {
        dakdak[i] = (inv[i] * inv[k + 1 - i]) % mod;
    }
}

```

```

inline long long interpolate(int x, int k, bool bf = false) {
    if (k == 0) return x;
    if (x <= k + 1 || bf) {
        return po[x];
    }
    pre[0] = x;
    suf[k + 1] = x - (k + 1);
    for (int i = 1; i <= k; i++) pre[i] = (pre[i - 1] * (x - i))
        % mod;
    for (int i = k; i >= 1; i--) suf[i] = (suf[i + 1] * (x - i))
        % mod;
    ans = 0;
    for (int i = 0; i <= k + 1; i++) {
        if (i == 0)
            num = suf[1];
        else if (i == k + 1)
            num = pre[k];
        else
            num = (pre[i - 1] * suf[i + 1]) % mod; // numerator

        if ((i + k) & 1)
            ans = (ans + ((po[i] * num % mod) * dakdak[i])) % mod;
        else
            ans = (ans - ((po[i] * num % mod) * dakdak[i])) % mod;

        ans = (ans + mod) % mod;
    }
    return ans;
}

```

6.5 LinearDeterminant

```

template <typename T>
vector<T> char_poly(vector<vector<T>> M) {
    int N = M.size();
    for (int i = 0; i < N - 2; i++) {
        int p = -1;
        for (int j = i + 1; j < N; j++)
            if (M[j][i] != T(0)) {
                p = j; break;
            }
        if (p == -1) continue;
        M[i + 1].swap(M[p]);
        for (int j = 0; j < N; j++) swap(M[j][i + 1],
            M[j][p]);

        T r = T(1) / M[i + 1][i];
        for (int j = i + 2; j < N; j++) {
            T c = M[j][i] * r;
            for (int k = 0; k < N; k++) M[j][k] -=
                M[i + 1][k] * c;
            for (int k = 0; k < N; k++) M[k][i + 1]
                += M[k][j] * c;
        }
    }
    vector<vector<T>> P = {{T(1)}};
    for (int i = 0; i < N; i++) {

```

```

vector<T> f(i + 2, 0);
for (int j = 0; j <= i; j++) f[j + 1] += P[i][j];
for (int j = 0; j <= i; j++) f[j] -= P[i][j] *
    M[i][i];

T b = 1;
for (int j = i - 1; j >= 0; j--) {
    b *= M[j + 1][j];
    T h = -M[j][i] * b;
    for (int k = 0; k <= j; k++) f[k] += h *
        P[j][k];
}
P.push_back(f);
return P.back();
}

template <typename T>
vector<T> det_linear(vector<vector<T>> A, vector<vector<T>> B) {
    int N = A.size(), nu = 0; T det = 1;
    for (int i = 0; i < N; i++) {
        int p = -1;
        for (int j = i; j < N; j++)
            if (A[j][i] != T(0)) {
                p = j; break;
            }
        if (p == -1) {
            if (++nu > N) return vector<T>(N + 1, 0);
            for (int j = 0; j < i; j++) {
                for (int k = 0; k < N; k++)
                    B[k][i] -= B[k][j] * A[j][i];
                A[j][i] = 0;
            }
            for (int j = 0; j < N; j++) swap(A[j][i],
                B[j][i]);
            --i; continue;
        }
        if (p != i) A[i].swap(A[p]), B[i].swap(B[p]),
            det = -det;
        det *= A[i][i];

        T c = T(1) / A[i][i];
        for (int j = 0; j < N; j++) A[i][j] *= c,
            B[i][j] *= c;
        for (int j = 0; j < N; j++) if (j != i) {
            T c = A[j][i];
            for (int k = 0; k < N; k++)
                A[j][k] -= A[i][k] * c, B[j][k] -=
                    B[i][k] * c;
        }
    }
    for (auto &y : B) for (T &x : y) x = -x;
    auto f = char_poly(B);
    for (T &x : f) x *= det;
    f.erase(f.begin(), f.begin() + nu);
    f.resize(N + 1);
    return f;
}

```

6.6 Lucas

```

ll lucas(ll n, ll m, int p, vi& fact, vi& invfact) {
    ll c = 1;
    while (n || m) {
        ll a = n % p, b = m % p;
        if (a < b) return 0;
        c = c * fact[a] % p * invfact[b] % p * invfact[a - b] % p;
        n /= p;
        m /= p;
    }
    return c;
}

```

6.7 Matrix

```

template <class T, int N>
struct Matrix {
    typedef Matrix M;
    array<array<T, N>, N> d{};
    M operator*(const M& m) const {
        M a;
        rep(i, 0, N) rep(j, 0, N) rep(k, 0, N) a.d[i][j] += d[i][k]
            * m.d[k][j];
        return a;
    }
    vector<T> operator*(const vector<T>& vec) const {
        vector<T> ret(N);
        rep(i, 0, N) rep(j, 0, N) ret[i] += d[i][j] * vec[j];
        return ret;
    }
    M operator(ll p) const {
        assert(p >= 0);
        M a, b(*this);
        rep(i, 0, N) a.d[i][i] = 1;
        while (p) {
            if (p & 1) a = a * b;
            b = b * b;
            p >>= 1;
        }
        return a;
    }
};

```

6.8 MillerRabin

```

inline uint64_t mod_mult64(uint64_t a, uint64_t b, uint64_t m)
    { return __int128_t(a) * b % m; }
uint64_t mod_pow64(uint64_t a, uint64_t b, uint64_t m) {
    uint64_t ret = (m > 1);
    for (;;) {
        if (b & 1) ret = mod_mult64(ret, a, m);
        if (!(b >>= 1)) return ret;
    }
}

```

```

a = mod_mult64(a, a, m);
}
}

// Works for all primes p < 2^64
bool is_prime(uint64_t n) {
    if (n <= 3) return (n >= 2);
    static const uint64_t small[] = {
        2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41,
        43, 47, 53, 59, 61, 67, 71, 73, 79, 83,
        89, 97, 101, 103, 107, 109, 113, 127, 131, 137, 139, 149,
        151, 157, 163, 167, 173, 179, 181, 191, 193, 197,
        199,
    };
    for (size_t i = 0; i < sizeof(small) / sizeof(uint64_t); ++i)
        if (n % small[i] == 0) return n == small[i];
}

// Makes use of the known bounds for Miller-Rabin
// pseudoprimes.
static const uint64_t millerrabin[] = {
    2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37,
};
static const uint64_t A014233[] = {
    // From OEIS.
    2047LL, 1373653LL, 25326001LL, 3215031751LL,
    2152302898747LL, 3474749660383LL, 341550071728321LL,
    341550071728321LL, 3825123056546413051LL,
    3825123056546413051LL, 3825123056546413051LL, 0,
};
uint64_t s = n - 1, r = 0;
while (s % 2 == 0) {
    s /= 2;
    r++;
}
for (size_t i = 0, j; i < sizeof(millerrabin) /
    sizeof(uint64_t); i++) {
    uint64_t md = mod_pow64(millerrabin[i], s, n);
    if (md != 1) {
        for (j = 1; j < r; j++) {
            if (md == n - 1) break;
            md = mod_mult64(md, md, n);
        }
        if (md != n - 1) return false;
    }
    if (n < A014233[i]) return true;
}
return true;
}

```

6.9 Mobius

```

mobius[1] = 1;
for (int i = 2; i < N; ++i) {
    --mobius[i];
    for (int j = i + i; j < N; j += i) mobius[j] -= mobius[i];
}

```

}

6.10 ModInverse

```
const ll mod = 1000000007, LIM = 200000;
ll* inv = new ll[LIM] - 1; inv[1] = 1;
for(ll i = 2; i < LIM; ++i) inv[i] = mod - (mod / i) * inv[mod
    % i] % mod;
```

6.11 ModMulLL

```
typedef unsigned long long ull;
const int bits = 10; // i f a l l numbers are less than 2^k ,
    set bits = 64k
const ull po = 1 << bits;
ull mod_mul(ull a, ull b, ull &c) {
    ull x = a * (b & (po - 1)) % c;
    while ((b >= bits) > 0) {
        a = (a << bits) % c;
        x += (a * (b & (po - 1))) % c;
    }
    return x % c;
}
ull mod_pow(ull a, ull b, ull mod) {
    if (b == 0) return 1;
    ull res = mod_pow(a, b / 2, mod);
    res = mod_mul(res, res, mod);
    if (b & 1) return mod_mul(res, a, mod);
    return res;
}
```

6.12 ModularArithmetic

```
const ll mod = 17; // change to something else
struct Mod {
    ll x;
    Mod(ll xx) : x(xx) {}
    Mod operator+(Mod b) { return Mod((x + b.x) % mod); }
    Mod operator-(Mod b) { return Mod((x - b.x + mod) % mod); }
    Mod operator*(Mod b) { return Mod((x * b.x) % mod); }
    Mod operator/(Mod b) { return *this * invert(b); }
    Mod invert(Mod a) {
        ll x, y, g = euclid(a.x, mod, x, y);
        assert(g == 1);
        return Mod((x + mod) % mod);
    }
    Mod operator(ll e) {
        if (!e) return Mod(1);
        Mod r = *this (e / 2);
        r = r * r;
        return e & 1 ? *this * r : r;
    }
}
```

}
};

6.13 Notes

6.13.1 Cycles

Let $g_S(n)$ be the number of n -permutations whose cycle lengths all belong to the set S . Then

$$\sum_{n=0}^{\infty} g_S(n) \frac{x^n}{n!} = \exp \left(\sum_{n \in S} \frac{x^n}{n} \right)$$

6.13.2 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n-1)(D(n-1) + D(n-2)) = nD(n-1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rfloor$$

6.13.3 Burnside's lemma

Given a group G of symmetries and a set X , the number of elements of X up to symmetry equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).

If $f(n)$ counts “configurations” (of some sort) of length n , we can ignore rotational symmetry using $G = Z_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n, k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k).$$

6.13.4 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1, p(n) = \sum_{k \in Z \setminus \{0\}} (-1)^{k+1} p(n - k(3k-1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

n	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	~2e5	~2e8

6.13.5 Lucas' Theorem

Let n, m be non-negative integers and p a prime. Write $n = n_k p^k + \dots + n_1 p + n_0$ and $m = m_k p^k + \dots + m_1 p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^k \binom{n_i}{m_i} \pmod{p}$.

6.13.6 Bernoulli numbers

EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t - 1}$ (FFT-able).
 $B[0, \dots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \dots]$

Sums of powers:

$$\sum_{i=1}^n i^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\begin{aligned} \sum_{i=m}^{\infty} f(i) &= \int_m^{\infty} f(x) dx - \sum_{k=1}^{\infty} \frac{B_k}{k!} f^{(k-1)}(m) \\ &\approx \int_m^{\infty} f(x) dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m)) \end{aligned}$$

6.13.7 Stirling numbers of the first kind

Number of permutations on n items with k cycles.

$$c(n, k) = c(n-1, k-1) + (n-1)c(n-1, k), \quad c(0, 0) = 1$$

$$\sum_{k=0}^n c(n, k) x^k = x(x+1) \dots (x+n-1)$$

$$\begin{aligned} c(8, k) &= 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1 \\ c(n, 2) &= 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \dots \end{aligned}$$

6.13.8 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j :s s.t. $\pi(j) > \pi(j+1)$, $k+1$ j :s s.t. $\pi(j) \geq j$, k j :s s.t. $\pi(j) > j$.

$$E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k)$$

$$E(n, 0) = E(n, n-1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

6.13.9 Stirling numbers of the second kind

Partitions of n distinct elements into exactly k groups.

$$S(n, k) = S(n-1, k-1) + kS(n-1, k)$$

$$S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$

6.13.10 Bell numbers

Total number of partitions of n distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \dots$ For p prime,

$$B(p^m + n) \equiv mB(n) + B(n+1) \pmod{p}$$

6.13.11 Labeled unrooted trees

on n vertices: n^{n-2}
 # on k existing trees of size n_i : $n_1 n_2 \dots n_k n^{k-2}$
 # with degrees d_i : $(n-2)! / ((d_1-1)! \dots (d_n-1)!)$

6.13.12 Catalan numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1, C_{n+1} = \frac{2(2n+1)}{n+2} C_n, C_{n+1} = \sum C_i C_{n-i}$$

$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \dots$

- sub-diagonal monotone paths in an $n \times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with $n+1$ leaves (0 or 2 children).
- ordered trees with $n+1$ vertices.
- ways a convex polygon with $n+2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

6.14 NTT

```
/* NTT with modulo 998244353
notes:
NTT with mod m
g is any primitive root modulo m (g = 3 works well for
998244353)
n divides m - 1 evenly
wn = g^((m - 1) / n)
https://codeforces.com/blog/entry/75326
*/
```

```
const int N = 1 << 21;
const ll mod = 998244353;
const ll g = 3;
```

```
int rev[N];
ll w[N], iw[N], wt[N], inv_n;
```

```
ll binpow(ll a, ll b){
```

```
    ll res = 1;
    for(; b >= 1, a = (1ll * a * a) % mod;
        if(b & 1)
            res = (1ll * res * a) % mod;
    return res;
}

void precalc(int lg){
    int n = 1 << lg;

    inv_n = binpow(n, mod - 2);

    for(int i = 0; i < n; ++i){
        rev[i] = 0;
        for(int j = 0; j < lg; ++j)
            if(i & (1 << j))
                rev[i] |= (1 << (lg - j - 1));
    }

    ll wn = binpow(g, (mod - 1) / n);
    w[0] = 1;
    for(int i = 1; i < n; ++i)
        w[i] = (1ll * w[i - 1] * wn) % mod;

    ll iwn = binpow(wn, mod - 2);
    iw[0] = 1;
    for(int i = 1; i < n; ++i)
        iw[i] = (1ll * iw[i - 1] * iwn) % mod;
}

void ntt(vector<ll> &a, int lg, bool inv = 0){
    int n = (1 << lg);

    for(int i = 0; i < n; ++i)
        if(i < rev[i])
            swap(a[i], a[rev[i]]);

    for(int len = 2; len <= n; len <= 1){
        int d = n / len;
        for(int j = 0; j < (len >> 1); ++j)
            wt[j] = (inv ? iw[d * j] : w[d * j]);
        for(int i = 0; i < n; i += len){
            for(int j = 0; j < (len >> 1); ++j){
                ll x = a[i + j], y = (1ll * a[i + j + (len >> 1)] * wt[j]) % mod;
                a[i + j] = (x + y) % mod;
                a[i + j + (len >> 1)] = (x - y + mod) % mod;
            }
        }
    }

    if(inv)
        for(int i = 0; i < n; ++i)
            a[i] = (1ll * a[i] * inv_n) % mod;
}

vector<ll> multiply(vector<ll> a, vector<ll> b){
    int n = 1, lg = 0;
    int na = sz(a), nb = sz(b);
```

```
    while(n < na + nb)
        n <= 1, ++lg;

    precalc(lg);

    a.resize(n);
    b.resize(n);

    ntt(a, lg);
    ntt(b, lg);

    for(int i = 0; i < n; ++i)
        a[i] = (1ll * a[i] * b[i]) % mod;

    ntt(a, lg, 1);

    vector<ll> c;
    for(int i = 0; i < na + nb - 1; ++i)
        c.push_back(a[i]);

    // while(!c.empty() and c.back() == 0)
    //     c.pop_back();

    return c;
}
```

6.15 PhiFunction

```
const int LIM = 5000000;
int phi[LIM];
void calculatePhi() {
    rep(i, 0, LIM) phi[i] = i & 1 ? i : i / 2;
    for (int i = 3; i < LIM; i += 2)
        if (phi[i] == i)
            for (int j = i; j < LIM; j += i) (phi[j] /= i) *= i - 1;
```

6.16 PollardFactorize

```
using ll = long long;
using ull = unsigned long long;
using ld = long double;
ll mult(ll x, ll y, ll md) {
    ull q = (ld)x * y / md;
    ll res = ((ull)x * y - q * md);
    if (res >= md) res -= md;
    if (res < 0) res += md;
    return res;
}

ll powMod(ll x, ll p, ll md) {
    if (p == 0) return 1;
    if (p & 1) return mult(x, powMod(x, p - 1, md), md);
    return powMod(mult(x, x, md), p / 2, md);
}
```



```

bool checkMillerRabin(ll x, ll md, ll s, int k) {
    x = powMod(x, s, md);
    if (x == 1) return true;
    while (k--) {
        if (x == md - 1) return true;
        x = mult(x, x, md);
        if (x == 1) return false;
    }
    return false;
}

bool isPrime(ll x) {
    if (x == 2 || x == 3 || x == 5 || x == 7) return true;
    if (x % 2 == 0 || x % 3 == 0 || x % 5 == 0 || x % 7 == 0)
        return false;
    if (x < 121) return x > 1;
    ll s = x - 1;
    int k = 0;
    while (s % 2 == 0) {
        s >>= 1;
        k++;
    }
    if (x < 1LL << 32) {
        for (ll z : {2, 7, 61}) {
            if (!checkMillerRabin(z, x, s, k)) return false;
        }
    } else {
        for (ll z : {2, 325, 9375, 28178, 450775, 9780504,
                    1795265022}) {
            if (!checkMillerRabin(z, x, s, k)) return false;
        }
    }
    return true;
}

ll gcd(ll x, ll y) { return y == 0 ? x : gcd(y, x % y); }

void pollard(ll x, vector<ll> &ans) {
    if (isPrime(x)) {
        ans.push_back(x);
        return;
    }
    ll c = 1;
    while (true) {
        c = 1 + get_rand(x - 1);
        auto f = [&](ll y) {
            ll res = mult(y, y, x) + c;
            if (res >= x) res -= x;
            return res;
        };
        ll y = 2;
        int B = 100;
        int len = 1;
        ll g = 1;
        while (g == 1) {
            ll z = y;
            for (int i = 0; i < len; i++) {
                z = f(z);
            }
            ll zs = -1;

```

```

        int lft = len;
        while (g == 1 && lft > 0) {
            zs = z;
            ll p = 1;
            for (int i = 0; i < B && i < lft; i++) {
                p = mult(p, abs(z - y), x);
                z = f(z);
            }
            g = gcd(p, x);
            lft -= B;
        }
        if (g == 1) {
            y = z;
            len <<= 1;
            continue;
        }
        if (g == x) {
            g = 1;
            z = zs;
            while (g == 1) {
                g = gcd(abs(z - y), x);
                z = f(z);
            }
        }
        if (g == x) break;
        assert(g != 1);
        pollard(g, ans);
        pollard(x / g, ans);
        return;
    }
}

// return list of all prime factors of x (can have duplicates)
vector<ll> factorize(ll x) {
    vector<ll> ans;
    for (ll p : {2, 3, 5, 7, 11, 13, 17, 19}) {
        while (x % p == 0) {
            x /= p;
            ans.push_back(p);
        }
    }
    if (x != 1) {
        pollard(x, ans);
    }
    sort(ans.begin(), ans.end());
    return ans;
}

// return pairs of (p, k) where x = product(p^k)
vector<pair<ll, int>> factorize_pk(ll x) {
    auto ps = factorize(x);
    ll last = -1, cnt = 0;
    vector<pair<ll, int>> res;
    for (auto p : ps) {
        if (p == last)
            ++cnt;
        else {
            if (last > 0) res.emplace_back(last, cnt);
            last = p;
            cnt = 1;
        }
    }
}

```

```

    }
    if (cnt > 0) {
        res.emplace_back(last, cnt);
    }
    return res;
}

vector<ll> get_all_divisors(ll n) {
    auto pks = factorize_pk(n);

    vector<ll> res;
    function<void(int, ll)> gen = [&](int i, ll prod) {
        if (i == static_cast<int>(pks.size())) {
            res.push_back(prod);
            return;
        }

        ll cur_power = 1;
        for (int cur = 0; cur <= pks[i].second; ++cur) {
            gen(i + 1, prod * cur_power);
            cur_power *= pks[i].first;
        }
    };

    gen(0, 1LL);
    sort(res.begin(), res.end());
    return res;
}

```

6.17 PrimitiveRoot

```

// Primitive root of modulo n is integer g iff for all a < n &
// gcd(a, n) == 1, there exist k: g^k = a mod n
// k is called discrete log of a (in case P is prime, can find
// in O(sqrt(P)) by noting that (P-1) is divisible by k)
//
// Exist if:
// - n is 1, 2, 4
// - n = p^k for odd prime p
// - n = 2*p^k for odd prime p
int powmod(int a, int b, int p) {
    int res = 1;
    while (b)
        if (b & 1)
            res = int(res * 1ll * a % p), --b;
        else
            a = int(a * 1ll * a % p), b >>= 1;
    return res;
}

int generator(int p) {
    vector<int> fact;
    int phi = p-1, n = phi;
    for (int i=2; i*i<=n; ++i)
        if (n % i == 0) {
            fact.push_back(i);
            while (n % i == 0)
                n /= i;
        }
}

```

```

    }
    if (n > 1)
        fact.push_back (n);

    for (int res=2; res<=p; ++res) {
        bool ok = true;
        for (size_t i=0; i<fact.size() && ok; ++i)
            ok &= powmod (res, phi / fact[i], p) != 1;
        if (ok) return res;
    }
    return -1;
}

```

6.18 TwoSat

```

struct TwoSatSolver {
    TwoSatSolver(int _n_vars) : n_vars(_n_vars), g(2 * n_vars) {}

    void x_or_y_constraint(bool is_x_true, int x, bool is_y_true,
        int y) {
        assert(x >= 0 && x < n_vars);
        assert(y >= 0 && y < n_vars);
        if (!is_x_true) x += n_vars;
        if (!is_y_true) y += n_vars;
        // x || y
        // !x -> y
        // !y -> x
        g[(x + n_vars) % (2 * n_vars)].push_back(y);
        g[(y + n_vars) % (2 * n_vars)].push_back(x);
    }

    // Returns:
    // If no solution -> returns {false, {}}
    // If has solution -> returns {true, solution}
    // where |solution| = n_vars, solution = true / false
    pair<bool, vector<bool>> solve() {
        DirectedDfs tree(g);
        vector<bool> solution(n_vars);
        for (int i = 0; i < n_vars; i++) {
            if (tree.comp_ids[i] == tree.comp_ids[i + n_vars]) {
                return {false, {}};
            }
            // Note that reverse(tree.scc) is topo sorted
            solution[i] = tree.comp_ids[i] < tree.comp_ids[i +
                n_vars];
        }
        return {true, solution};
    }

    // number of variables
    int n_vars;
    // vertex 0 -> n_vars - 1: Ai is true
    // vertex n_vars -> 2*n_vars - 1: Ai is false
    vector<vector<int>> g;
};

```

6.19 XorBasis

```

struct Basis {
    const int LGX = 19;

    vector<int> a;

    Basis() : a(LGX + 1, 0) {}

    void add(int x) {
        for(int i = LGX; i >= 0; --i){
            if(x & (1 << i)){
                if(a[i]) x ^= a[i];
                else{
                    a[i] = x;
                    break;
                }
            }
        }
    }

    void add(Basis o){
        for(int i = LGX; i >= 0; --i)
            add(o.a[i]);
    }

    bool is_spannable(int x) {
        for(int i = LGX; i >= 0; --i)
            if(x & (1 << i))
                x ^= a[i];
        return (x == 0);
    }
};

```

7 String

7.1 AhoCorasick

```

template <int MAXC = 26> struct AhoCorasick {
    vector<array<int, MAXC>> C;
    vector<int> F;
    vector<vector<int>> FG;
    vector<bool> E;

    int node() {
        int r = C.size();
        E.push_back(0);
        F.push_back(-1);
        C.emplace_back();
        fill(C.back().begin(), C.back().end(), -1);
        return r;
    }

    int ctrans(int n, int c) {
        if (C[n][c] == -1) C[n][c] = node();
        return C[n][c];
    }
};

```

```

}

int ftrans(int n, int c) const {
    while (n && C[n][c] == -1) n = F[n];
    return C[n][c] != -1 ? C[n][c] : 0;
}

AhoCorasick(vector<vector<int>> P) {
    node();
    for (int i = 0; i < (int)P.size(); i++) {
        int n = 0;
        for (int c : P[i]) n = ctrans(n, c);
        E[n] = 1;
    }
    queue<int> Q;
    F[0] = 0;
    for (int c : C[0]) if (c != -1) Q.push(c), F[c] = 0;
    while (!Q.empty()) {
        int n = Q.front(); Q.pop();
        for (int c = 0; c < MAXC; ++c) if
            (C[n][c] != -1) {
                int f = F[n];
                while (f && C[f][c] == -1) f =
                    F[f];
                F[C[n][c]] = C[f][c] != -1 ?
                    C[f][c] : 0;
                Q.emplace(C[n][c]);
            }
    }
    FG.resize(F.size());
    for (int i = 1; i < (int)F.size(); i++) {
        FG[F[i]].push_back(i);
        if (E[i]) Q.push(i);
    }
    while (!Q.empty()) {
        int n = Q.front();
        Q.pop();
        for (int f : FG[n]) E[f] = 1, Q.push(f);
    }
}

bool check(vector<int> V) {
    if (E[0]) return 1;
    int n = 0;
    for (int c : V) {
        n = ftrans(n, c);
        if (E[n]) return 1;
    }
    return 0;
}
};

```

7.2 KMP

```

// prefix function: *length* of longest prefix which is also
// suffix:
// pi[i] = max(k: s[0..k-1] == s[i-(k-1)..i]
//
// KMP {{{

```

```

template <typename Container>
std::vector<int> prefix_function(const Container& s) {
    int n = s.size();
    std::vector<int> pi(n);
    for (int i = 1; i < n; ++i) {
        int j = pi[i - 1];
        while (j > 0 && s[i] != s[j]) j = pi[j - 1];
        if (s[i] == s[j]) ++j;
        pi[i] = j;
    }
    return pi;
}

// Tested: https://oj.vnoi.info/problem/substr
// Return all positions (0-based) that pattern 'pat' appears in
// 'text'
std::vector<int> kmp(const std::string& pat, const std::string&
    text) {
    auto pi = prefix_function(pat + '\0' + text);
    std::vector<int> res;
    for (size_t i = pi.size() - text.size(); i < pi.size(); ++i) {
        if (pi[i] == (int)pat.size()) {
            res.push_back(i - 2 * pat.size());
        }
    }
    return res;
}

// Tested: https://oj.vnoi.info/problem/icpc22_mt_b
// Returns cnt[i] = # occurrences of prefix of length-i
// NOTE: cnt[0] = n+1 (0-length prefix appears n+1 times)
std::vector<int> prefix_occurrences(const string& s) {
    int n = s.size();
    auto pi = prefix_function(s);
    std::vector<int> res(n + 1);
    for (int i = 0; i < n; ++i) res[pi[i]]++;
    for (int i = n - 1; i > 0; --i) res[pi[i - 1]] += res[i];
    for (int i = 0; i <= n; ++i) res[i]++;
    return res;
}

```

7.3 Manacher

```

std::array<vector<int>, 2> manacher(const string& s) {
    int n = s.size();
    std::array res = {vector<int>(n + 1, 0), vector<int>(n, 0)};

    for (int z = 0; z < 2; z++) {
        for (int i = 0, l = 0, r = 0; i < n; i++) {
            int t = r - i + 1;
            if (i < r) res[z][i] = min(t, res[z][l + t]);

            int l2 = i - res[z][i], r2 = i + res[z][i] - 1;
            while (l2 && r2 + 1 < n && s[l2 - 1] == s[r2 + 1]) {
                ++res[z][i];
                --l2;
                ++r2;
            }
        }
    }
}

```

```

    }
    if (r2 > r) {
        l = l2;
        r = r2;
    }
}
for (int i = 0; i < n; i++) {
    res[z][i] = 2 * res[z][i] + z;
}
}
res[0].erase(res[0].begin(), res[0].begin() + 1);
res[0].pop_back();
return res;
}

```

7.4 StringHashing

```

int power(long long n, long long k, const int mod) {
    int ans = 1 % mod;
    n %= mod;
    if (n < 0) n += mod;
    while (k) {
        if (k & 1) ans = (long long) ans * n % mod;
        n = (long long) n * n % mod;
        k >>= 1;
    }
    return ans;
}

const int MOD1 = 127657753, MOD2 = 987654319;
const int p1 = 137, p2 = 277;
int ip1, ip2;
pair<int, int> pw[N], ipw[N];
void prec() {
    pw[0] = {1, 1};
    for (int i = 1; i < N; i++) {
        pw[i].first = 1LL * pw[i - 1].first * p1 % MOD1;
        pw[i].second = 1LL * pw[i - 1].second * p2 % MOD2;
    }
    ip1 = power(p1, MOD1 - 2, MOD1);
    ip2 = power(p2, MOD2 - 2, MOD2);
    ipw[0] = {1, 1};
    for (int i = 1; i < N; i++) {
        ipw[i].first = 1LL * ipw[i - 1].first * ip1 % MOD1;
        ipw[i].second = 1LL * ipw[i - 1].second * ip2 % MOD2;
    }
}

struct Hashing {
    int n;
    string s; // 0 - indexed
    vector<pair<int, int>> hs; // 1 - indexed
    Hashing() {}
    Hashing(string _s) {
        n = _s.size();
        s = _s;
        hs.emplace_back(0, 0);
    }
}

```

```

for (int i = 0; i < n; i++) {
    pair<int, int> p;
    p.first = (hs[i].first + 1LL * pw[i].first * s[i] % MOD1)
        % MOD1;
    p.second = (hs[i].second + 1LL * pw[i].second * s[i] %
        MOD2) % MOD2;
    hs.push_back(p);
}
}
pair<int, int> get_hash(int l, int r) { // 1 - indexed
    assert(1 <= l && l <= r && r <= n);
    pair<int, int> ans;
    ans.first = (hs[r].first - hs[l - 1].first + MOD1) * 1LL *
        ipw[l - 1].first % MOD1;
    ans.second = (hs[r].second - hs[l - 1].second + MOD2) * 1LL *
        ipw[l - 1].second % MOD2;
    return ans;
}
pair<int, int> get_hash() {
    return get_hash(1, n);
}
}
};

```

7.5 SuffixArray

```

vector<int> SA(const vector<int>& s, int upper) {
    int n=s.size();
    if (n == 0) return {};
    if (n == 1) return {0};
    if (n == 2) {
        if (s[0] < s[1]) return {0, 1};
        else return {1, 0};
    }
    vector<int> sa(n), sum_l(upper+1), sum_s(upper+1);
    vector<bool> ls(n);
    for (int i=n-2; i>=0; i--)
        ls[i]=(s[i] == s[i+1]) ? ls[i+1] : (s[i] <
            s[i+1]);
    for (int i = 0; i<n; i++)
        if (!ls[i]) sum_s[s[i]]++;
        else sum_l[s[i]+1]++;
    for (int i=0; i<upper; i++) {
        sum_s[i] += sum_l[i];
        if (i < upper) sum_l[i+1] += sum_s[i];
    }
    auto induce=[&](const vector<int>& lms) {
        fill(sa.begin(), sa.end(), -1);
        vector<int> buf(upper+1);
        copy(sum_s.begin(), sum_s.end(), buf.begin());
        for (auto d : lms) {
            if (d == n) continue;
            sa[buf[s[d]]++] = d;
        }
        copy(sum_l.begin(), sum_l.end(), buf.begin());
        sa[buf[s[n-1]]++] = n-1;
        for (int i=0; i<n; i++) {
            int v=sa[i];

```

```

        if (v>=1 && !ls[v-1]) sa[buf[s[v-1]]++] =
            v-1;
    }
    copy(sum_l.begin(), sum_l.end(), buf.begin());
    for (int i=n-1; i>=0; i--) {
        int v=sa[i];
        if (v>=1 && ls[v-1]) sa[--buf[s[v-1]+1]]
            = v-1;
    }
};
vector<int> lms_map(n+1, -1), lms;
int m=0;
for (int i=1; i<n; i++) if (!ls[i-1] && ls[i]) {
    lms_map[i]=m++;
    lms.push_back(i);
}
induce(lms);
if (m) {
    vector<int> sorted_lms, rec_s(m);
    for (int v : sa) if (lms_map[v] != -1)
        sorted_lms.push_back(v);
    int rec_upper=0;
    rec_s[lms_map[sorted_lms[0]]]=0;
    for (int i=1; i<m; i++) {
        int l=sorted_lms[i-1], r=sorted_lms[i];
        int end_l = (lms_map[l]+1 < m) ?
            lms[lms_map[l]+1] : n;
        int end_r = (lms_map[r]+1 < m) ?
            lms[lms_map[r]+1] : n;
        bool same=true;
        if (end_l-1 != end_r-r) same=false;
        else {
            while (l < end_l) {
                if (s[l] != s[r]) break;
                l++, r++;
            }
            if (l == n || s[l] != s[r])
                same=false;
        }
        if (!same) rec_upper++;
        rec_s[lms_map[sorted_lms[i]]]=rec_upper;
    }
    auto rec_sa = SA(rec_s, rec_upper);
    for (int i=0; i<m; i++) sorted_lms[i] =
        lms[rec_sa[i]];
    induce(sorted_lms);
}

```

```

    }
    return sa;
}

vector<int> lcp_array(const vector<int>& s, const vector<int>&
sa) {
    int n=int(s.size());
    assert(n>=1);
    vector<int> rnk(n), lcp(n-1);
    for (int i=0; i<n; i++) rnk[sa[i]] = i;
    int h=0;
    for (int i=0; i<n; i++) {
        if (h > 0) h--;
        if (rnk[i] == 0) continue;
        int j=sa[rnk[i]-1];
        for (; j+h < n && i+h < n; h++)
            if (s[j+h] != s[i+h]) break;
        lcp[rnk[i]-1]=h;
    }
    return lcp;
}

```

7.6 Z

```

vector<int> zfunc(const string& s) {
    int n = (int)s.length();
    vector<int> z(n);
    z[0] = n;
    for (int i = 1, l = 0, r = 0; i < n; ++i) {
        if (i <= r) z[i] = min(r - i + 1, z[i - l]);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]]) ++z[i];
        if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
    }
    return z;
}

```

8 template

```

#include "bits/stdc++.h"
using namespace std;

```

```

#ifdef LOCAL
#include "debug.h"
#else
#define debug(...)
#endif

using ll = long long;
using pii = pair<int, int>;

#define F first
#define S second
#define sz(x) (int)(x).size()
#define all(x) (x).begin(), (x).end()

mt19937_64
    rng(chrono::steady_clock::now().time_since_epoch().count());
ll get_rand(ll l, ll r) {
    assert(l <= r);
    return uniform_int_distribution<ll> (l, r)(rng);
}

void solve(){
}

int32_t main() {
    cin.tie(nullptr)->sync_with_stdio(0);
    #define task "troll"
    if(fopen(task".inp", "r")){
        freopen(task".inp", "r", stdin);
        freopen(task".out", "w", stdout);
    }
    int test = 1;
    // cin >> test;
    for(int i = 1; i <= test; ++i){
        // cout << "Case #" << i << ": ";
        solve();
    }
    #ifdef LOCAL
        cerr << "\n[Time]: " << 1000.0 * clock() /
            CLOCKS_PER_SEC << " ms.\n";
    #endif
    return 0;
}

```