
# Lesson 3

- HTTP
- Routes
- Controllers
- Views.
- database.yml
- Version Control System

# Internet.




#### Url.

```
<протокол>://<хост>:<порт>/<путь>?<парам.>
```

#### Examples:

- . http://www.flatstack.com:80
- http://www.flatstack.com:80/projects
- . http://www.flatstack.com:80/projects?q='le'

# DNS. (Domain name system)



## Why you no give me ip?

- GET / HTTP/1.1
- · Host: google.com
- RequestUrl: google.com/search
- User-Agent: Web-Kit
- Accept-Encoding: gzip
- Accept-Charset: ISO-8859-1, UTF-8;
- · Cache-Control: no-cache
- Accept-Language:en; q=0.7, en-us;


### Response.

- Status: HTTP/1.1 200 OK
- Location: http://www.google.com
- Content-type: text/html; charset=UTF-8
- Content-length: 219

# **HTML Content**

```
<HTML><HEAD><meta http-equiv="content-type" content="
text/html;charset=utf-8">
<TITLE>301 Moved</TITLE></HEAD><BODY>
<H1>301 Moved</H1>
The document has moved
<A HREF="http://www.google.com/">here</A>.
</BODY></HTML>
```

# HTTP Methods. Why?



- GET
- POST
- PUT
- DELETE
- ...

#### Rails routes.

# confir/routes.rb

resources:comments

# app/controllers/comments\_controller.rb class CommentsController < ApplicationController end

## Routes to Actions.

GET	/comments	index
GET	/comments/new	new
POST	/comments	create
GET	/comments/:id	show
GET	/comments/:id/edit	edit
PUT	/comments/:id	update
DELETE	/comments/:id	destroy

## \$ rake routes

```
comments#index
                    /comments(.:format)
   comments GET
                    /comments(.:format)
             POST 
                                                   comments#create
new_comment GET
                    /comments/new(.:format)
                                                  comments#new
edit comment GET
                    /comments/:id/edit(.:format)
                                                   comments#edit
                    /comments/:id(.:format)
    comment GET
                                                   comments#show
             PUT
                    /comments/:id(.:format)
                                                   comments#update
             DELETE /comments/:id(.:format)
                                                  comments#destroy
```

#### Generate controller.

### \$ rails generate controller comments.

```
1 class CommentsController < ApplicationController
    def index
      # поведение
      # Рендерим app/views/comments/index.html.erb
    end
    def show
      # поведение
     end
11
    def edit
      # поведение
    end
15
    def update
      # поведение
17
    end
    def new
      # поведение
21
    end
22
23
    def create
      # поведение
    end
27
    def destroy
28
      # поведение
    end
30 end
```

#### Render views.



#### Instance variables.

```
1 class CommentsController < ApplicationController
2  def show
3    @comment = Comment.find(1)
4  end
5 end</pre>
```

#### Erb.

### Slim.

```
1 = link_to 'Back', comments_path
2
3 h1= @comment.subject
4 .coment-content
5 = @coment.message
6 p Created at: #{ @coment.created_at.to_s(:long) }
```

### Render partials. And Dry.

```
# app/views/comments/new.html.erb
# app/views/comments/edit.html.erb
```

# app/views/comments/\_form.html.erb

## Form partial.

```
<%= form for(@comment) do |f| %>
 2
     <% if @comment.errors.any? %>
 3
       <div id="error explanation">
 4
5
6
7
         <h2><%= pluralize(@comment.errors.count, "error") %>
         prohibited this post from being saved:</h2>
         <l
8
         <% @comment.errors.full_messages.each do |msg| %>
 9
           <\si msq \( \si \) /\li>
10
         <% end %>
11
         12
       </div>
13
     <% end %>
14
15
     <div class="field">
16
       <%= f.label :subject %><br />
17
       <%= f.text field :subject %>
18
     </div>
19
     <div class="field">
20
       <%= f.label :message %><br />
21
       <%= f.text area :message %>
22
    </div>
23
     <div class="actions">
```

#### Form for.

```
<= form_for @comment do |f| %>
  <%= f.label :subject %>
  <%= f.text_field :subject %>
  <% end %>
```

```
<form action="comments/1" method="POST">
    <label_for="comment_subject>Subj.</label>
    <input type="text" name="comment[:subject]>
    ...
</form>
```

### Put. Delete.

```
< input type="text" name = "_method" value="
put">
```

#### Link to.

```
<%= link_to 'Label',
```

- comments\_path
- comment\_path(@comment)
- o new\_comment\_path
- edit\_comment\_path(@comment)

%>

### Layouts.

- Asset tags
- yield and content\_for
- Partials

- javascript\_include\_tag
- stylesheet\_link\_tag

## Application layout. Head.

```
<!DOCTYPE html>
<html>
  <head>
  <%= stylesheet_link_tag "application" %>
  <%= javascript_include_tag "application" %>
  <%= csrf_meta_tags %>
  <%= yield(:head) if content_for?(:head) %>
```

## Application layout. Body.

```
<body>
     <%= yield %>
  </body>
</html>
```

## Apply application layout.

# app/views/comments/show.html.erb

```
<h1><h1></= @comment.subject %></h1>
```

```
<% content_for(:head) do %>
    <%= javascript_include_tag "comments" %>
<% end %>
```