Collaborative Wind Tunnel Flight Investigation

Multi-Variable Functional Scaling of Aerodynamic Stall

$$\alpha_{\text{stall}} = f(\alpha,\, m,\, t/c,\, Re)$$

Platform: NCSSM *WindTunnel lab* (GPU-Accelerated 2D Lattice Boltzmann Simulator)

Developed by F. Santibanez, Ph.D.
Honors Aerospace Engineering · NCSSM Connect Program
North Carolina School of Science and Mathematics

Academic Year 2026–2027

Mission Briefing & Research Objective

In aerodynamics, **stall** represents the sudden loss of lift and surge in drag when airflow separates from the upper surface of a wing. Using **Dimensional Analysis**, we can show that the critical stall angle depends on three fundamental dimensionless parameters: airfoil camber (m), thickness ratio (t/c), and the Reynolds number (Re):

$$\alpha_{\text{stall}} = \Phi\left(m,\, \frac{t}{c},\, Re\right), \quad \text{and the peak lift capability} \quad C_{L,\max} = \Psi\left(m,\, \frac{t}{c},\, Re\right). \tag{1}$$

As an aerospace research consortium, our class will systematically explore this multi-variable relationship using the GPU-accelerated **WindTunnel lab**. Four specialized student research divisions will each interrogate one parameter, gather high-precision digital telemetry, and collaborate to construct a unified empirical scaling model for aircraft design.

1 Dimensional Analysis & The Aerodynamics of Stall

1.1 Physical Nature of Aerodynamic Stall

When an airfoil moves through air at an angle of attack α, fluid streams smoothly over both surfaces, generating lift. However, as α increases, air flowing over the upper surface must turn sharply around the nose and decelerate into an increasing pressure hill (known as an *adverse pressure gradient*). At a critical angle called the **stall angle** (α_{stall}), the sluggish air near the surface can no longer overcome this hill. The flow detaches (separates) from the upper surface, spilling into an unsteady, turbulent wake. Lift collapses, drag surges, and the wing stalls.

1.2 Formulating the Physical Problem with Dimensional Analysis

Before running expensive wind tunnel tests or computer simulations, aerospace engineers use **Dimensional Analysis** (the Buckingham Π Theorem) to determine which variables truly govern the physics, reducing complex systems of units into universal, dimensionless parameters.

To determine what governs the stall angle α_{stall}, we list every physical variable that could influence the onset of flow separation:

Physical Variable	**Symbol**	**SI Units**	**Dimensions** $[M, L, T]$
Stall Angle of Attack	α_{stall}	rad or deg	[1] (dimensionless)
Airfoil Chord Length	c	m	$[L]$
Maximum Camber Height	h	m	$[L]$
Maximum Thickness	t	m	$[L]$
Freestream Air Speed	U_∞	m/s	$[LT^{-1}]$
Air Density	ρ	kg/m^3	$[ML^{-3}]$
Air Dynamic Viscosity	μ	$\text{Pa} \cdot \text{s}$	$[ML^{-1}T^{-1}]$

1.3 Applying the Buckingham Π Theorem

We have $n = 7$ physical variables expressed in $k = 3$ fundamental dimensions: mass $[M]$, length $[L]$, and time $[T]$. According to the Buckingham Π Theorem, the physical relationship can be expressed by exactly $n - k = 7 - 3 = 4$ independent dimensionless groups (Π-groups).

Selecting the fluid dynamic reference scale (ρ, U_∞, c) as repeating variables, we construct the dimensionless Π-groups:

1. **Group 1 ($\Pi_1 = \alpha_{\text{stall}}$):** The dependent parameter of interest, the critical stall angle (dimensionless).
2. **Group 2 ($\Pi_2 = h/c = m$):** The **Airfoil Camber Ratio** (maximum camber expressed as a percentage or fraction of chord).
3. **Group 3 ($\Pi_3 = t/c$):** The **Airfoil Thickness Ratio** (maximum thickness as a percentage or fraction of chord).
4. **Group 4 ($\Pi_4 = \frac{\rho U_\infty c}{\mu} = \frac{U_\infty c}{\nu} = Re$):** The **Reynolds Number**, which scales the ratio of fluid inertia (momentum) to viscous friction.

Therefore, dimensional analysis proves that the stall angle does not depend on arbitrary combinations of meters, kilograms, or seconds independently. Rather, it is strictly governed by a universal functional relationship:

$$\alpha_{\text{stall}} = \mathbf{\Phi}\left(\mathbf{m},\, \frac{\mathbf{t}}{\mathbf{c}},\, \mathbf{Re}\right) \tag{2}$$

Furthermore, during an angle of attack sweep, the dimensionless lift coefficient $C_L = \frac{L}{\frac{1}{2}\rho U_\infty^2 c}$ traces an aerodynamic curve:

$$C_L = g\left(\alpha;\, m,\, \frac{t}{c},\, Re\right) \tag{3}$$

whose peak defines $C_{L,\max}$ occurring at $\alpha = \alpha_{\text{stall}}$.

1.4 Physical Intuition Behind the Dimensionless Groups

- **Angle of Attack (α):** The operational variable. In the attached regime, lift increases linearly ($C_L \approx 2\pi(\alpha - \alpha_0)$). As α increases, the suction peak near the leading edge intensifies until near-wall air runs out of momentum, triggering separation.
- **Airfoil Thickness (t/c):** Controls the roundness of the nose (leading-edge radius $r_{\text{le}} \propto (t/c)^2$). A sharp, thin airfoil ($t/c = 6\%$) forces air around an abrupt corner, causing early, violent bubble separation. A blunt, thick airfoil ($t/c = 18\%$) smooths out this curve, delaying separation to higher angles.

- **Airfoil Camber (m):** Asymmetry shifts the zero-lift angle to negative values ($\alpha_0 \approx -1.1m$), boosting lift at zero degrees. However, extra upper-surface curvature makes the pressure hill steeper, altering when separation occurs.
- **Reynolds Number (Re):** Measures how fast and energetic the fluid is compared to its internal stickiness. High-Re air has high momentum and thinner boundary layers ($\delta \propto 1/\sqrt{Re}$), enabling it to resist separation and climb steeper pressure hills, which delays stall to higher angles.




Figure 1: Anatomy of an aerodynamic lift polar: Linear attached regime, non-linear separation onset, peak lift $C_{L,\max}$ at critical stall angle α_{stall}, and post-stall periodic vortex shedding.

2 Experimental Testing Platform: NCSSM *WindTunnel lab*

Tests are conducted using NCSSM's **WindTunnel lab**, a real-time GPU-accelerated numerical wind tunnel powered by the Lattice Boltzmann Method (LBM D2Q9) and Smagorinsky subgrid-scale turbulence modeling.

2.1 Standardized Data Acquisition (DAQ) Protocol

To ensure reproducibility across all student research teams, each data point must be collected according to the **5-Second Integer Vortex Shedding Integration Protocol**:

1. **Geometry Configuration:** Enter the 4-digit NACA profile (e.g., `2412`) in the control panel.
2. **Flow Conditioning:** Set the target Reynolds number (Re) slider and verify that *Smagorinsky LES* is checked.
3. **Angle Dialing:** Adjust α using the slider for coarse sweeping (2.0° increments) and the stepper buttons (`[<]` / `[>]`) for high-resolution refinement (0.5° increments) in the vicinity of stall.
4. **Flow Settling Verification:** Observe the telemetry status indicator. When flow is altered, the indicator displays **Flow Settling**. Wait 3–5 seconds until the badge turns **Flow Settled · Ready**.

5. **Execute 5s Cycle Acquisition:** Click `[Acquire (5s)]` or press hotkey `L`. The system integrates instantaneous momentum-exchange forces across full shedding periods ($\int \sin(\omega t)dt \equiv 0$), completely filtering phase bias.
6. **Telemetry Logging:** The polar graph displays the cycle-averaged C_L, accompanied by dynamic error whiskers representing the shedding envelope $[C_{L,\min}, C_{L,\max}]$.
7. **CSV Export:** Upon completing an angle sweep, click `[CSV]` to save the raw laboratory dataset.

3 Consortium Division Assignments

The class is partitioned into four research divisions. Each division is responsible for executing high-density angle of attack sweeps across their assigned parameter matrix.

3.1 Division 1: Airfoil Thickness (t/c) & Nose Curvature Division

Primary Objective: Quantify the impact of leading-edge radius and airfoil thickness on stall onset angle and determine whether thicker profiles experience sudden or docile stall.

- **Fixed Controls:** Baseline Reynolds number $Re = 1000$, Camber $m = 0\%$ (Symmetric Series).
- **Airfoil Sweep Matrix:**
  1. **NACA 0006:** Ultra-thin ($t/c = 6\%$) — Sharp leading edge, high susceptibility to separation bubble burst.
  2. **NACA 0009:** Moderately thin ($t/c = 9\%$) — Classic high-speed profile.
  3. **NACA 0012:** Standard benchmark ($t/c = 12\%$) — NASA calibration standard.
  4. **NACA 0018:** Thick subsonic ($t/c = 18\%$) — High structural depth, blunt nose.
  5. **NACA 0024:** Very thick ($t/c = 24\%$) — Low-speed strut/root section.
- **Angle Sweep Range:** $\alpha \in [-2.0°, +24.0°]$. Sweep in 2.0° steps from $-2°$ to 8°, then 0.5° steps from 8° to 20°.
- **Deliverable Plot 1.1:** Composite polar plot (C_L vs α) overlaying all five thickness ratios.
- **Deliverable Plot 1.2:** Functional curve of α_{stall} vs (t/c) and $C_{L,\max}$ vs (t/c).

3.2 Division 2: Airfoil Camber (m) & Zero-Lift Asymmetry Division

Primary Objective: Determine how mean camber line curvature shifts the zero-lift angle α_0, alters maximum lift $C_{L,\max}$, and affects the stall angle α_{stall}.

- **Fixed Controls:** Baseline Reynolds number $Re = 1000$, Thickness $t/c = 12\%$, Maximum Camber Location $p = 0.4c$ (`NACA X412` Family).
- **Airfoil Sweep Matrix:**
  1. **NACA 0012:** Symmetric reference ($m = 0\%$).
  2. **NACA 1412:** Mild camber ($m = 1\%$).
  3. **NACA 2412:** Benchmark camber ($m = 2\%$, typical general aviation wing).
  4. **NACA 4412:** High-lift camber ($m = 4\%$).
  5. **NACA 6412:** Extreme aggressive camber ($m = 6\%$, STOL/cargo section).
- **Angle Sweep Range:** $\alpha \in [-8.0°, +22.0°]$. Sweep in 2.0° steps from $-8°$ to 4°, then 0.5° steps through stall.
- **Deliverable Plot 2.1:** Experimental lift slope verification: verify linear slope $dC_L/d\alpha$ against 2π and plot experimental α_0 vs theoretical prediction $\alpha_0 \approx -1.1m$.
- **Deliverable Plot 2.2:** Functional curve of α_{stall} vs m and $C_{L,\max}$ vs m. Does increasing camber delay or advance stall onset?

3.3 Division 3: Reynolds Number (Re) & Viscous Scale Division

Primary Objective: Determine the empirical scaling law connecting Reynolds number to boundary layer energization and stall angle delay.

- **Fixed Controls:** Standard NACA 2412 airfoil profile ($m = 2\%$, $p = 0.4c$, $t/c = 12\%$).
- **Reynolds Number Sweep Matrix:**
  1. $Re = 300$**:** Viscous-dominated flow (thick laminar boundary layer, micro-aerial scale).
  2. $Re = 600$**:** Low Reynolds number transitional regime.
  3. $Re = 1200$**:** Standard baseline tunnel scale.
  4. $Re = 2500$**:** Moderate Reynolds number with elevated momentum transport.
  5. $Re = 5000$**:** High Reynolds number testing (energized boundary layer).
- **Angle Sweep Range:** $\alpha \in [-4.0^\circ, +22.0^\circ]$ for each Reynolds number. Focus 0.5° resolution in the $[8^\circ, 18^\circ]$ stall zone.
- **Deliverable Plot 3.1:** Family of $C_L(\alpha)$ curves showing the progression of stall softening and delay with increasing Re.
- **Deliverable Plot 3.2:** Semilogarithmic scaling plot: α_{stall} vs $\ln(Re)$ and test for power-law correlation $\alpha_{\text{stall}} \propto Re^k$.

3.4 Division 4: Coupled Interaction & Post-Stall Shedding Dynamics Division

Primary Objective: Investigate coupled camber-thickness interactions and quantify dynamic vortex shedding oscillation amplitudes and inverted stall asymmetry.

- **Sweep Matrix A (Coupled Geometry Matrix):**
  1. **NACA 4406:** High camber (4%) + Ultra-thin (6%) — Severe suction peak combined with sharp nose.
  2. **NACA 4418:** High camber (4%) + Thick (18%) — Camber-thickness synergy.
  3. **NACA 0006 vs NACA 0018:** Thickness extremes under symmetric conditions.
- **Sweep Matrix B (Bidirectional Inverted Stall Exploration):**
  1. Execute a continuous bidirectional sweep on **NACA 2412** from $\alpha = -16.0^\circ$ to $+20.0^\circ$.
  2. Locate positive stall $(\alpha^+_{\text{stall}}, C^+_{L,\max})$ and inverted negative stall $(\alpha^-_{\text{stall}}, C^-_{L,\min})$.
- **Deliverable Plot 4.1:** Dynamic shedding envelope diagram: plot oscillation amplitude $\Delta C_L = C_{L,\max} - C_{L,\min}$ (error whiskers) as a function of degrees past stall $(\alpha - \alpha_{\text{stall}})$.
- **Deliverable Plot 4.2:** Cambered airfoil stall asymmetry comparison: contrast positive vs inverted stall modes.

4 Classroom Consortium: Multi-Variable Data Pooling

Following data acquisition, each division will deposit their calibrated data points into the **Consortium Master Telemetry Database**. Every team will then have access to the complete 4D matrix.

Div.	Airfoil / Case	m	t/c	Re	Meas. α_{stall} (°)	Meas. $C_{L,\max}$
1	NACA 0006	0.00	0.06	1000	_____	_____
1	NACA 0009	0.00	0.09	1000	_____	_____
1	NACA 0012	0.00	0.12	1000	_____	_____
1	NACA 0018	0.00	0.18	1000	_____	_____
1	NACA 0024	0.00	0.24	1000	_____	_____
2	NACA 1412	0.01	0.12	1000	_____	_____
2	NACA 2412	0.02	0.12	1000	_____	_____
2	NACA 4412	0.04	0.12	1000	_____	_____
2	NACA 6412	0.06	0.12	1000	_____	_____
3	NACA 2412 ($Re = 300$)	0.02	0.12	300	_____	_____
3	NACA 2412 ($Re = 600$)	0.02	0.12	600	_____	_____
3	NACA 2412 ($Re = 1200$)	0.02	0.12	1200	_____	_____
3	NACA 2412 ($Re = 2500$)	0.02	0.12	2500	_____	_____
3	NACA 2412 ($Re = 5000$)	0.02	0.12	5000	_____	_____
4	NACA 4406	0.04	0.06	1000	_____	_____
4	NACA 4418	0.04	0.18	1000	_____	_____
4	NACA 2412 (Inverted)	0.02	0.12	1000	_____	_____

Table 1: Consortium Master Parametric Telemetry Table for class-wide regression.

5 Analysis & Discussion Prompts

Each research division will author a technical report synthesizing their primary domain and the global consortium dataset. Address the following analytical prompts:

1. **Thickness Scaling & Optimal Slenderness:** Plot α_{stall} against (t/c) for the symmetric NACA 00XX series.
   - At what thickness ratio does α_{stall} peak?
   - Physically explain the stall mechanism transition between NACA 0006 (thin-airfoil bubble bursting) and NACA 0018 (progressive trailing-edge stall).
   - Why does increasing thickness beyond $t/c \approx 0.18$ eventually degrade aerodynamic performance?
2. **Camber Effect on Stall vs Lift Capability:** Contrast the effect of camber m on $C_{L,\max}$ versus its effect on α_{stall}.
   - Does adding camber increase or decrease the stall angle α_{stall}?
   - Why does NACA 6412 achieve higher $C_{L,\max}$ than NACA 0012 despite intense suction peaks?
   - Verify Thin Airfoil Theory: calculate the linear regression slope $dC_L/d\alpha$ and compare to 2π. Calculate the zero-lift angle α_0 and compare to theoretical $-1.1m$.

3. **Reynolds Scaling and Boundary Layer Energization:** Examine the five Reynolds number test points.
   - Fit an empirical logarithmic model: $\alpha_{\text{stall}} = A + B\ln(Re/1000)$. Report constants A and B and R^2.
   - Relate your findings to the laminar boundary layer thickness $\delta \propto 1/\sqrt{Re}$. Why does an energized, thinner boundary layer delay separation?
4. **Post-Stall Dynamics & Force Vector Behavior:** Observe the real-time vector overlay $(\vec{L}, \vec{D}, \vec{R})$ and smoke streamlines across stall.
   - How does the orientation of the resultant force vector $\vec{R}$ rotate as the airfoil transitions into deep stall?
   - In deep stall, how does the shedding oscillation envelope $[C_{L,\min}, C_{L,\max}]$ relate to the formation and shedding of von Kármán vortex street structures in the wake?
5. **Global Multi-Variable Regression Model:** Using the pooled class dataset from Table 1, fit a multi-linear response surface:

$$\alpha_{\text{stall}}\left(m,\, \frac{t}{c},\, Re\right) \approx C_0 + C_m \cdot m + C_t \cdot \left(\frac{t}{c}\right) + C_{Re} \cdot \ln\left(\frac{Re}{1000}\right). \tag{4}$$

   Determine the regression coefficients C_0, C_m, C_t, C_{Re} and discuss the dominant sensitivity governing stall onset in subsonic flight.

6 Grading Rubric (100 Points Total)

Criterion	Performance Expectations	Points
Experimental Protocol & DAQ Rigor	Correct execution of 5s burst integration protocol; flow settled state verified; appropriate angle density (0.5° near stall); complete CSV exports.	20
Data Visualization & Polar Curves	Clear, publication-grade polar plots (C_L vs α, C_D vs α, L/D vs α) with error whiskers, stall points clearly identified, theoretical references included.	20
Physical Mechanisms & Fluid Dynamics	Sound, thorough physical reasoning explaining separation, suction peaks, boundary layer energy, vortex shedding, and thin vs trailing-edge stall.	25
Consortium Synthesis & Regression	Successful integration with class dataset; formulation and statistical evaluation of the multi-variable scaling model $\alpha_{\text{stall}} = \Phi(m, t/c, Re)$.	20
Technical Communication & Formatting	Clear engineering report organization; proper unit annotations; professional tables, diagrams, and executive summary.	15
Total		**100**

Table 2: Laboratory Evaluation and Assessment Rubric.