When a screened pattern search spends more simulator calls: evidence from mineral-processing circuit cases

Felipe Santibáñez-Leal, ORCID 0000-0002-0150-3246

Preprint · v1.1, 1 November 2026 · Licence CC BY 4.0
CAOS open-research programme · mineral-processing optimization
Version DOI 10.5281/zenodo.23852504 · concept DOI (always latest) 10.5281/zenodo.23833134
Not peer reviewed. Source code, data and computational records:
github.com/fsantibanezleal/CAOS_OreFlow

Abstract

Surrogate screening can add trial evaluations as well as avoid them. We evaluate a neural-surrogate search step, with a reconstruction guard and a Gaussian-process interval-width filter, within multistart generalized pattern search with a progressive barrier. Its unscreened control uses the same fixed objective weight, starts, bounds, stopping rules and circuit evaluator. Across 72 target-mode variants from twelve authored mineral-processing cases, the screened searches recorded 26,367 distinct cached trial states versus 22,487 without screening, a 17.25% increase. These counters exclude the later weight-path study, uncached audits and model costs. Counts were higher in 68 variants, tied in four and lower in none. Both procedures found feasible endpoints in 70 variants and no feasible endpoint in two; terminal outcomes matched in 65. The seven different feasible decisions differed by at most 0.0027 t/h (0.017%) in recovered primary metal. Of 5,811 evaluated surrogate-selected proposals, 901 improved the incumbent; absolute recovery error had mean 0.71, median 0.48 and maximum 38.16 percentage points. The screen did not reduce the recorded search workload on this suite. These finite-search results do not establish global optimality, elapsed-time savings or performance on operating plants.

1 Introduction

Grinding, classification and flotation decisions interact through nonlinear balances, equipment limits and product-quality constraints. Direct simulation can be expensive when an optimizer repeatedly evaluates a complete flowsheet. A learned approximation may reduce that cost by ranking candidates before exact simulation, but only if the number of avoided simulator calls exceeds the number of additional calls caused by the screening rule. Prediction accuracy alone is insufficient: optimization depends on errors near competing candidates and on the geometry of the feasible region.

Surrogate models have been used to approximate phenomenological comminution circuits. Koh et al. report a neural-network surrogate for simulator throughput with substantial speedup on their studied circuit and data design [3]. More generally, surrogate management methods combine approximate models with exact evaluations and retain convergence safeguards for the original problem [2]. Generalized pattern search provides derivative-free search with convergence results under specified smoothness and direction-set assumptions [4, 1]. These results motivate guarded screening, but do not imply that a particular screen reduces calls or preserves a particular finite-budget solution.

This study evaluates one integrated procedure on OreFlow's committed case records. It asks two bounded questions: does screening reduce exact engine evaluations, and how closely do the screened and unscreened searches agree on feasibility and recovered metal? The cases are authored scenarios rather than measured operating data. The result is therefore an algorithmic comparison within a declared simulator domain, not a plant-performance claim.

2 Related work

Koh et al. trained a deep neural model to reproduce a phenomenological comminution-circuit simulator and used the approximation to accelerate scenario evaluation [3]. That work addresses approximation of simulator outputs. Here, the object of evaluation is the effect of a surrogate-driven search step inside a bounded derivative-free optimizer, including the exact-call cost and terminal decision relative to an unscreened control.

The surrogate management framework formalizes the interplay between approximation models and exact objective evaluations [2]. Generalized pattern search methods offer convergence properties for suitable objective functions and generating directions; those properties do not automatically transfer to a modified search step without the relevant assumptions and proof [4, 1]. Accordingly, this experiment reports finite-suite behavior and makes no global-convergence claim for the screened implementation.

3 Method

3.1 Process decision problem

The search varies the grind target within the case contract and, for circuits with flotation, the collector dose and rougher gas velocity. The evaluator returns recovered primary metal M in t/h, recovery, concentrate grade, total specific energy E in kWh/t, power and water use. For a selected recovery weight $w \in [0, 1]$, the normalized objective is

$$J(x; w) = w\frac{M(x)}{M_0} - (1 - w)\frac{E(x)}{E_0}, \tag{1}$$

where M_0 and E_0 are the values at the variant's base operating point. Grade, installed power and water limits are treated as relaxable constraints through a progressive barrier; contract bounds on decisions are unrelaxable. The paired searches use the same fixed objective weight, starts and stopping rules. The subsequent warm-started weight-path calculation is a separate descriptive study.

3.2 Exact and screened searches

The baseline is a generalized pattern search with a progressive feasibility barrier. The screened procedure uses the same engine, objective, starts, mesh, bounds, constraints and stopping budget. At each iteration, the exported neural evaluator predicts candidate responses one and two mesh steps from feasible and infeasible incumbents. A proposal is eligible only when its reconstruction error is below the learned guard threshold and the Gaussian-process 95% recovery half-width does not exceed five percentage points. That interval belongs to the Gaussian process, not to the neural prediction used for ranking, and neither filter guarantees accuracy. The eligible candidate with the highest predicted objective is evaluated by the exact circuit engine. Only an engine result can update an incumbent or become a reported endpoint; the ordinary poll remains available when the search step does not improve it.

Each case record contains screen counts, accepted proposals, the surrogate and engine results for each proposal, the evaluation count, the terminal outcome and a paired unscreened search from the same starts. This paired design isolates the computational effect of the screen within the simulator and its finite search settings. It does not estimate runtime on a plant control system.

3.3 Evaluation set and measures

The baked suite contains 96 variants: 72 target-mode variants and 24 classifier-cut variants. The latter are intentionally unscreened because the learned screen's features do not cover that circuit mode. Both searches find no feasible endpoint in two target-mode iron-magnetite variants under their declared settings. We report paired evaluation counts over all 72 target-mode records and compare feasible decisions for the 70 records where both searches find one. A matching infeasible status counts as a matching terminal outcome; it is neither a feasible endpoint nor a proof of global infeasibility.

The primary cost measure compares the recorded `evaluations` counters after the fixed-weight multistart searches. Each is the number of distinct trial states stored in that search's cache; repeated states across starts count once. Screened and unscreened runs use separate caches. Refused trial states remain recorded outcomes. These counters exclude uncached base/endpoint audits, the subsequent weight path, fitting, loading and screening inference, so they do not instrument every simulator invocation or measure wall-clock cost. Secondary measures are per-variant count ordering, terminal-outcome agreement, recovered-metal difference, number of proposals that improve the incumbent and absolute recovery error at proposed points. Percentage-point errors are differences between recovery percentages, not relative percentage errors.

4 Results

4.1 Exact evaluation cost

Across the 72 paired target-mode variants, screening recorded 26,367 cached trial evaluations; the baseline recorded 22,487. The relative increase is

$$100\left(\frac{26{,}367}{22{,}487}-1\right)=17.25\%. \tag{2}$$

Screening cost more in 68 variants and tied in four; it saved recorded evaluations in none. The comparison includes the fixed-weight multistart run for each variant. The counters are captured before the separate weight-path study. They are not a wall-clock benchmark and exclude the one-time training and export cost of the surrogate.




Figure 1: Recorded search evaluations for the 72 target-mode variants. Each counter measures distinct cached trial states in a fixed-weight multistart run. Points above the identity line have a larger screened count. The aggregate compares the same paired records; the later weight path and uncached audits are excluded.

4.2 Decision agreement

Both procedures find feasible endpoints in 70 variants and return infeasible search statuses in the remaining two. They return the same terminal outcome in 65 of 72 variants: the 63 exactly matching feasible decision vectors plus the two matching infeasible statuses. Seven feasible variants select different decision vectors. Across those seven, the largest absolute difference in recovered primary metal is 0.002653 t/h, or 0.0168% relative to the larger value. Five favor the unscreened result in recovered metal and two favor the screened

Table 1: Paired optimization results on the 72 target-mode variants.

Measure	Result
Authored cases	12
Target-mode variants	72
Feasible endpoints in both searches	70
Infeasible outcomes in both searches	2
Recorded search evaluations, screened	26,367
Recorded search evaluations, unscreened	22,487
Cost change	+17.25%
More / tied / fewer evaluations	68 / 4 / 0
Same terminal outcome	65 / 72

result. This close numerical agreement on these cases does not show that screening is safe for other inputs, constraints or stopping budgets.

4.3 Proposal behavior and prediction errors

The screened search records 79,034 candidate evaluations by the screening logic. Nineteen are rejected by the learned-state guard and 48,268 by the uncertainty-width rule. The algorithm sends 5,811 selected proposals to the engine; 901, or 15.5%, improve the incumbent. For those evaluated proposals, the mean absolute recovery error is 0.712 percentage points, the median is 0.483 points and the maximum is 38.158 points. The large maximum is material: the width filter did not eliminate every large pointwise error in the proposal record. The evidence does not support describing the surrogate as uniformly accurate where it is used.

5 Discussion

For this suite, screening yields a striking separation between decision agreement and computational efficiency. The selected decisions are usually identical and the measured metal differences are small, yet the screened search evaluates the circuit more often. This is consistent with a mechanism in which the screen adds exact evaluations at selected candidates without removing enough ordinary polling evaluations. Close final decisions do not compensate for a 17.25% increase in the measured call count when the objective of screening is to reduce simulator work.

The result also illustrates why average prediction error is not a sufficient screen diagnostic. Optimization depends on candidate ranking near the incumbent, uncertainty calibration in the feasible region and how many candidates the screen makes the exact evaluator inspect. The observed maximum recovery error of 38.16 percentage points cautions against treating a nominal confidence-width threshold as a universal safety guarantee. Independent calibration on the exact region of use and a prospective test on new cases would be needed before relying on the screen outside this authored suite.

The comparator is deliberately narrow: the same fixed-weight multistart generalized pattern search with screening switched off. The experiment does not compare global optimization methods, alternative surrogate-management strategies or wall-clock performance on a calibrated plant model. Evaluation counts exclude the later weight path, uncached audits and surrogate fitting time. The case suite uses authored inputs and simulator-generated values, so it cannot establish transfer to unseen plants or ores.

6 Limitations

All optimization outcomes are generated by an authored, steady-state process simulator. They are not measurements from operating plants. Model-form error, changing ore, plant instrumentation error, control-system

latency and economic uncertainty are outside this experiment. The finite set of twelve cases does not represent the full mineral-processing design space.

The paired searches share a finite starting set, mesh and evaluation budget. Agreement is conditional on those choices and does not establish global optimality. The progressive-barrier method has established convergence analyses under their stated assumptions; this implementation's surrogate-selected search modification is not accompanied by a new convergence proof. The call-count measure also omits time spent fitting, loading and evaluating the surrogate, as well as parallel execution effects.

7 Conclusions

The neural-surrogate search step, with a reconstruction guard and Gaussian-process width filter, did not reduce recorded search evaluations on OreFlow's 72 target-mode optimization records. Its count was 17.25% higher than the paired unscreened procedure, lower in no variant, and terminal outcomes matched in 65 cases. Seven feasible endpoints differed, with at most 0.002653 t/h difference in recovered primary metal. The maximum observed proposal recovery error was 38.16 percentage points despite the uncertainty-width filter. These findings support retaining the screen as a reproducible comparison method while rejecting its use as a demonstrated compute-saving accelerator on this suite. A further evaluation would require a separately specified screening design, calibration checks on candidate regions and validation on cases not used to design the rule.

Data and code availability

The case-level optimization records are committed under `https://github.com/fsantibanezleal/CAOS_OreFlow/tree/main/data/derived/cases`; the implementation and tests are in the same public repository. Each record stores paired search counts, proposals, engine outcomes and terminal decisions. The records are simulator outputs from authored scenarios and are not plant data.

References

[1] C. Audet and J. E. Dennis, Jr., "Mesh adaptive direct search algorithms for constrained optimization," *SIAM Journal on Optimization*, vol. 17, no. 1, pp. 188–217, 2006. doi: 10.1137/040603371.

[2] A. J. Booker, J. E. Dennis, Jr., P. D. Frank, D. B. Serafini, V. Torczon, and M. W. Trosset, "A rigorous framework for optimization of expensive functions by surrogates," *Structural Optimization*, vol. 17, pp. 1–13, 1999. doi: 10.1007/BF01197708.

[3] E. J. Y. Koh, E. Amini, G. J. McLachlan, and N. Beaton, "Utilising a deep neural network as a surrogate model to approximate phenomenological models of a comminution circuit for faster simulations," *Minerals Engineering*, vol. 170, article 107026, 2021. doi: 10.1016/j.mineng.2021.107026.

[4] V. Torczon, "On the convergence of pattern search algorithms," *SIAM Journal on Optimization*, vol. 7, no. 1, pp. 1–25, 1997. doi: 10.1137/S1052623493250780.