

Visual Symbols

Álvaro Figueira, PhD.

MSc in Data Science - Data Visualization



DEPARTAMENTO DE CIÊNCIA DE COMPUTADORES
FACULDADE DE CIÊNCIAS DA UNIVERSIDADE DO PORTO



42

Symbols and Visualization

- The patterns and relationships discovery start by **mapping data** into **graphical symbols**

SOME SIMPLE RULES:

- Any **screen pattern** should imply into a **data pattern**, otherwise it is an **artifact**
- Any **order perceived** in the visual representation should reflect some **data property**
- **Similarity** between **data** instances should imply **similarity** between the **visual symbols** representing them

43

43

The Eight Visual Variables



- A common way to **translate data** into visual representations is to **map** each data **attribute** into a different **visual marker**
- It is possible to use up to **eight visual variables**
 1. Position
 2. Shape
 3. Size
 4. Brightness
 5. Color
 6. Orientation
 7. Texture
 8. Movement

44

44

Position

- **Position** (1D, 2D, or 3D) is the **most important variable**
 - Spatial arrangement is the first to be read on a visualization



45

45

Shape

- Any graphical element can be used as a marker, including symbols, letters and words



In R the shapes are:


0	1	2	3	4	
□	○	△	+	×	
5	6	7	8	9	
◇	▽	⊠	✱	⬠	
10	11	12	13	14	
⊕	⊗	⊞	⊗	⊞	
15	16	17	18	19	
■	●	▲	◆	●	
20	21	22	23	24	25
●	●	■	◆	▲	▼

46

46

Shape

- Markers should be **as different as possible** between themselves but with similar area and complexities



47

47

Size (length, area and volume)

- Position and shape are the most important variables, the other only affect the way these are displayed, e.g., changing the size of the markers




48

48

Size (length, area, and volume)

- Size can be used to map continuous and categorical variables, but for the second case only few categories can be considered



49

49

Examples:

```
library(ggplot2)
```

```
# Scatter plot with multiple groups
```

```
# Shape depends on cyl
```


```
ggplot(df, aes(x=wt, y=mpg, group=cyl)) +  
  geom_point(aes(shape=cyl))
```

```
# Change point shapes and colors
```

```
ggplot(df, aes(x=wt, y=mpg, group=cyl)) +  
  geom_point(aes(shape=cyl, color=cyl))
```

```
# change point shapes, colors and sizes
```

```
ggplot(df, aes(x=wt, y=mpg, group=cyl)) +  
  geom_point(aes(shape=cyl, color=cyl, size=cyl))
```



50

50

Brightness


- **Brightness** can be used for **continuous attributes**, but only a few categorical values can be distinguished by humans



51

51

Brightness



52

52

Color


- Values are mapped to colors normally using a [colormap](#)
 - There are [specific colormaps](#) for continuous and categorical values (but only few classes)



53

53

Color



Color is car size

54

54

Orientation


- **Orientation** or direction is pre-attentively processed
 - Cannot be used for all markers, **problems** with **more than one natural axis**



55

55

Orientation




Orientation is price average

56

56

Texture


- **Texture** can be understood as a combination of other variables, such as shape, color and orientation



57

57

Texture



Texture is type of car
(SUV, compact, etc)

58

58

Movement

- **Movement** can be associated with other visual variables
 - Important to indicate **temporal variation**
- Read suggestion:
 - G. Robertson, R. Fernandez, D. Fisher, B. Lee, J. Stasko. **Effectiveness of Animation in Trend Visualization**. *IEEE Transactions on Visualization and Computer Graphics*, vol. 14, no. 6, pp. 1325-1332, November/December, 2008

59

59