



QUAIL-B IMDB, Qwen3 4B FP8, sf=0.1, one H100

Quail Stock vLLM Pipelined vLLM Pipelined SGLang SoL estimate


Latency




Fresh input tokens



Recomputed KV tokens



Answer agreement with Qwen3 32B



QUAIL-B IMDB: input documents before filtering

Query	Relation alias (set): input documents
IMDB-1	r (reviews): 5,000
IMDB-2	r (reviews): 5,000; a (aspects): 12
IMDB-3	r (reviews): 5,000; a (aspects): 12
IMDB-4	r (reviews): 5,000; a (aspects): 12
IMDB-5	r (reviews): 5,000; a (aspects): 12
IMDB-6	r (reviews): 5,000
IMDB-7	r (reviews): 5,000
IMDB-8	r (reviews): 5,000; a (aspects): 12; a2 (aspects): 12
IMDB-9	r1 (reviews): 5,000; a1 (aspects): 12; r2 (reviews): 5,000; a2 (aspects): 12
IMDB-10	r1 (reviews): 5,000; a1 (aspects): 12; r2 (reviews): 5,000; a2 (aspects): 12

Each alias lists its full input before filters. Repeated aliases can refer to the same underlying set.
Counts come from the saved corpus manifest. SoL uses the same inputs and the saved reference labels for survivors.