Open clusters: inclusion criteria

Catalogue: wenu_open_clusters_v0.2.ecsv

513 selected open clusters. These plots show the accepted population, not the excluded parent catalogue.

Mandatory lists: messier, caldwell, sac_urban, rasc_finest_ngc, sac_best_ngc

All resolved cluster rows and unresolved claims retained; mandatory rows bypass all numeric cuts.

Intersection: positive source radius/member_count, finite Hunt V10, strict V10 below sloping boundary and max_v10; source-specific reddening cut.

V10 < 17.5 - (12.5/3) * log10(radius_arcmin); extrapolated outside 1..1000 arcmin.

Numeric limits: V10 < 12.5; E(B-V) limit: 3.0; available-source policy: all.

Depuration: retain Hunt type o and Dias-only open clusters. Single-source objects need other compilation or observing-list evidence; masked claims remain for review.

Excluded counts: {"hunt_type_g": 48, "hunt_type_m": 17, "single_source_no_other_compilation": 5}

Hunt V10 is the tenth brightest accepted member, not integrated cluster magnitude. Identifier-matched Dias points share Hunt V10; no independent Dias V10 is supplied. Filled symbols use Dias data, hollow symbols Hunt data.

Strict separation < both published radii; reciprocal unique unmatched pairs are provisional and retain unresolved alias review flags.

Parent selection SHA-256: c072f225548889da195fb7a33fe94707a2b638db45af8c38f28b4406ff7223fc