

Epistemic Observability in Language Models: An Impossibility Result with Tensor Escape

Tony Mason

March 2026

Abstract

We start with a finding that should trouble anyone building systems with language model components: **models report highest confidence precisely when they are fabricating**. Across four model families (OLMo-3, Llama-3.1, Qwen3, Mistral), self-reported confidence inversely correlates with accuracy, with AUC ranging from 0.28 to 0.36 where 0.5 is random guessing.

We prove this is not a capability gap but an observational one. Under text-only observation—where a supervisor sees only the model’s output text—no bounded supervisor can distinguish epistemically honest systems from systems that fabricate plausibly (Representational Impossibility, Learnability Impossibility). The impossibility holds regardless of model scale or training procedure, including RLHF and instruction tuning.

We construct a *tensor interface* that escapes the impossibility by exporting internal signals the model cannot independently control: per-token entropy, attention summaries, and log-probability distributions. Under length-controlled evaluation where no text feature exceeds AUC 0.70, per-token entropy achieves AUC 0.757 and outperforms text baselines by 2.5–3.9 percentage points at every budget level tested (10%, 20%, 30%). The entropy signal generalizes across architectures (Spearman $\rho = 0.762$).

The core contribution is a *cost surface*: an empirical map of what each level of verification investment buys, where text-only approaches max out, and what tensor-guided observation adds. The contribution is the map. The territory is the system you are building.

1 Introduction

We start with a finding that should trouble anyone building systems with language model components: **models report highest confidence precisely when they are fabricating**.

We tested this across four model families (OLMo-3, Llama-3.1, Qwen3, Mistral) by asking simple questions: “How confident are you in this answer?” On factual questions the models answered correctly, confidence was moderate. On fabrications—plausible-sounding lies, completely invented facts—confidence was high. Area under the ROC curve (AUC) ranged from 0.28 to 0.36 across architectures, where 0.5 is random guessing and 1.0 is perfect discrimination. We checked multiple times. The finding held.

Self-reported confidence is inverted.

This matters because self-report is the first signal we reach for when we need to verify a model’s output. If the model expresses doubt, we investigate. If it’s confident, we trust it. Except the model is most confident when it should be most doubtful.

1.1 The Verification Problem

Systems incorporating language model components face a fundamental choice: **how much of the model’s output should you verify, which outputs should you prioritize, and what signals should you use for triage?** Verification has cost—API calls, domain expert review, additional compute. Every system must allocate a budget.

The standard assumption is that scaling solves this: larger models, more RLHF training, instruction tuning—eventually they’ll know what they know. But Lin et al. found the opposite: larger models were *less* truthful on TruthfulQA [Lin et al., 2022]. And our self-report inversion finding suggests why—the problem isn’t capability, it’s interface. The text-only channel through which models expose their reasoning cannot carry the signals a supervisor needs to distinguish grounded generation from confident fabrication.

1.2 What This Paper Contributes

We make three contributions:

1. An impossibility result for text-only verification. We prove that a text-only observation model—where a supervisor can see only the model’s output text, not its internal computation—is architecturally insufficient to verify epistemic honesty under bounded supervision. The impossibility holds regardless of model scale or training procedure. It’s not a capability gap; it’s an observational gap.

2. A tensor interface that escapes the impossibility. We construct an epistemic observability interface that exports internal signals alongside text: per-token entropy traces, attention summaries, log-probability distributions. These are byproducts of inference—telemetry the model generates during computation and cannot independently control. Under standard training, the model cannot separately tune entropy without affecting correctness, which is why entropy generalizes where text features diverge.

3. The empirical cost surface. We map verification effectiveness across four judge strategies (no judge, text-only, tensor-guided, composed) at three budget levels (10%, 20%, 30%). Under length-controlled evaluation where no text feature exceeds AUC 0.70, per-token entropy achieves AUC 0.757 and outperforms text baselines by 2.5–3.9 percentage points at every budget level. The tensor interface works. The cost surface tells system builders what each level of verification investment buys.

1.3 Why This Matters

The self-report inversion tells us the obvious approach fails. Asking models to be honest doesn’t work. RLHF doesn’t work. Instruction tuning doesn’t work. The impossibility results explain why. And the tensor interface provides a concrete alternative.

But the broader point is a reframe. The fabrication problem is not fundamentally about model capability. Scaling didn’t solve it. RLHF didn’t solve it. The problem is observability: what signals can a supervisor access to determine what a model actually computed? The text output is fully controllable through training; internal signals are structurally harder to fake. Export the computation’s telemetry, and verification becomes tractable. Hide it, and verification concentrates entirely on the provider.

This matters because deploying language models in critical systems (medical, legal, financial) requires knowing what the model knows. The current interface doesn’t give us that information. This paper shows why, and shows a path forward.

2 Background: Why Text-Only Observation Fails

To understand why self-reported confidence goes backwards, we need to understand what observation models can and cannot do.

2.1 The Observational Gap

A language model processes queries through multiple stages:

1. **Input encoding** and position embeddings
2. **Transformer layers** where attention patterns build up representations
3. **Token prediction** where the model outputs a probability distribution over the next token
4. **Sampling or argmax** where a specific token is selected

The model’s internal computation—the attention patterns, the per-token entropy, the per-layer logits—contains information that distinguishes grounded generation from fabrication. When a model fabricates, it often does so with high confidence (low entropy); when it retrieves or reasons about less common knowledge, entropy is higher. The computation leaves traces.

But the standard interface to language models exports only the final text. Everything internal is discarded. A supervisor receives the linearized output string and must reconstruct, from the text alone, what the model’s own computation already knew.

This is the observational gap: the model may know it is fabricating, but the interface provides no channel through which a supervisor can verify this knowledge independently.

2.2 Why Adding More Supervisors Doesn’t Solve It

Intuition suggests a solution: ask the model to be more honest. Use RLHF to train it to hedge language. Ask follow-up questions. Stack multiple judges.

But these approaches operate entirely within the text channel. They try to extract epistemic information from the output string itself. We tested this systematically:

- **Response length:** Fabrications tend to be verbose while factual retrieval is concise. Using response length alone as a signal, AUC was 0.63 on our test set.
- **Hedging language:** Phrases like “I’m not certain” or “I believe” are weak signals. The model can learn to include them in training without actually knowing the difference.
- **Citations:** This case is instructive. Fabricated citations sound *more* confident than real ones because they’re fluent inventions requiring no retrieval. Real citations require looking up specific details, introducing uncertainty. The signal inverts: the judge designed to catch fabrication actually flags truthful citations more aggressively. This is not a bug in citation verification; it’s a feature of how entropy works. It’s also a reminder that different failure modes require different signals.
- **Composed judges:** Combining multiple text features with machine learning. Pooled AUC never exceeded 0.70.

None of these approaches work reliably. And they all share a fundamental constraint: **they extract information from a channel the model can fully control through training.**

2.3 The FLP Connection: An Impossibility Framework

Why is text-only observation fundamentally insufficient? We can formalize this as an impossibility result, drawing on classical distributed systems theory.

In 1985, Fischer, Lynch, and Paterson proved that in a partially asynchronous distributed system, consensus cannot be achieved if even one process might fail [Fischer et al., 1985]. The impossibility isn't about algorithm cleverness—it's about what observation model allows. When a supervisor can only observe external messages (the text), it cannot distinguish between a process that has crashed (genuinely doesn't know) and a process that is slow (knows but hasn't responded yet).

The key insight: inability to distinguish between two states when you have only partial observability.

Language models present an analogous problem. A supervisor observing only text cannot distinguish between:

- **State A:** The model has grounded knowledge and generates it accurately.
- **State B:** The model lacks grounded knowledge and fabricates plausibly.

Both produce fluent, confident text. The text itself carries no reliable signal about which state the model is in.

2.4 Query Categories and the Self-Report Inversion

To understand the inversion, we test five types of queries:

- **Control (Truth):** Common factual knowledge (capital of France, boiling point of water).
- **Wombat:** True but implausible facts (wombat scat is cube-shaped; a day on Venus is longer than a year on Venus).
- **Glavinsky:** Plausible-sounding fabrications (a syndrome with a made-up name; a conference talk that never happened).
- **Westphalia:** Obvious fabrications (completely invented treaties, impossible facts).
- **Private/Future:** Genuinely unknowable questions (what's in the next room? When will it rain next Thursday?).

On knowable queries (Control, Wombat, Westphalia true baseline), the model reports moderate confidence. On unknowable queries (Private/Future), higher uncertainty. But on Glavinsky queries—the plausible lies—confidence peaks.

Self-reported confidence should be a signal of epistemic honesty: high confidence on things the model knows, low confidence on things it doesn't. But confidence gets inverted because the model is optimized for *coherent text generation*, not for honest metacognition.

A model optimized for coherence naturally learns to generate fluent, confident output. Fabrications are fluent and confident by definition—they're ungrounded text that reads smoothly. Grounded generation, especially of obscure facts, may be more hesitant (high entropy) because the model is retrieving specific details from less common training data.

There is no training signal that would cause a text-only model to pair *accurate confidence estimates* with *accurate generation*. The text channel doesn't expose the information needed to

learn the distinction. The model learns to be confident (good for fluency), and that confidence happens to correlate with fabrication (bad for honesty).

Instruction tuning does not fix this problem. Models trained to follow instructions learn to express confidence convincingly, producing fluent and confident text regardless of whether the underlying answer is grounded. They become better at generating confident-sounding text, not at knowing what they know. The inversion persists across base and instruction-tuned model pairs.

2.5 The Escape Condition

If text-only observation is insufficient, what observation model *is* sufficient?

The answer: **export signals that the model cannot independently control.**

Text is fully controllable through training. A model learns to sound confident, to match citation formats, to hedge appropriately—all while fabricating. The model’s text output is a shaped behavior, subject to RLHF.

But the model’s computation is different. Consider entropy: the probability distribution over the next token encodes genuine uncertainty. A model cannot separately learn to:

- Produce high-confidence distributions (low entropy) while simultaneously outputting wrong tokens, because confidence and token probability are computed together.
- Maintain coherent attention patterns while the underlying computation is incoherent.
- Assign high probability to tokens it doesn’t actually compute as likely.

These are byproducts of what the model actually computes. They’re harder to fake because faking them means changing the computation itself, which affects correctness.

If a supervisor has access to:

- **Per-token entropy:** How uncertain was the model’s computation while generating this token?
- **Attention patterns:** Were the attention patterns coherent, or scattered across unrelated tokens?
- **Log-probabilities:** What probability did the model assign to the tokens it generated?

Then the supervisor has signals that correlate with whether the generation is grounded or fabricated. Not perfectly, but consistently. And critically: the model cannot learn to manipulate these signals through RLHF or instruction tuning without degrading its own correctness.

This is the tensor interface: export the telemetry alongside the text, giving supervisors access to signals that are structurally harder to fake.

3 The Impossibility

Why does self-report inversion happen? Why don’t more supervisors help? Why does instruction tuning make it worse, not better?

The answer is that epistemic honesty is not a capability problem. The industry has tried to solve it as one: scale models larger, use RLHF to teach honesty, instruction tune for compliance. Lin et al. tested this directly and found the opposite—larger models were *less* truthful on TruthfulQA [Lin et al., 2022]. The theorems that follow explain why. It’s not about what the model knows; it’s about what the model can *communicate*. Text-only observation lacks the degrees of freedom to express

different epistemic states. The model may know it is fabricating. But the interface provides no channel to communicate this knowledge independently.

This section formalizes that constraint: the verification impossibility.

Remark 1 (Epistemic Status of Formal Results). *This paper makes three types of claims, which we distinguish throughout:*

1. **Conditional formal results:** *“Given our model’s definitions, X follows by logical necessity.” The Lean proofs and TLA+ specifications establish claims of this type. Their conclusions are machine-checked; the substantive question is whether the definitions faithfully model real systems.*
2. **Empirical claims:** *“We observe X across N models under conditions Y .” The experiments in §5 establish claims of this type.*
3. **Informal arguments:** *“We argue that X because Y , but this is not formally proven.” The bridge between formal definitions and real LLM behavior is an argument of this type.*

Our argument proceeds in two stages. First, we show that any policy conditioning only on the query cannot satisfy epistemic honesty across ambiguous world states ([Theorem 1](#): Representational Impossibility). Second, we show that even if the architecture is expanded to include retrieval, a bounded supervisor cannot provide the training signal needed to learn honest behavior ([Theorem 2](#): Learnability Impossibility). Together, these results establish that epistemic honesty is unachievable for text-only observation models under realistic supervision constraints.

To be precise about the type of claim: this is a *verification impossibility*. We prove that a bounded supervisor observing only text cannot distinguish epistemically honest systems from systems that fabricate plausibly. The impossibility is architectural: it applies to any system operating under text-only observation, regardless of model family, scale, or training procedure. These results are prompt-agnostic: they hold for any policy that exports only text, regardless of whether a system prompt instructs the model to be “helpful,” “honest,” or otherwise.

3.1 Definitions

Let $\mathcal{Q}$ be the space of queries, $\mathcal{R}$ be the space of responses (including $\perp$ for abstention), and $\mathcal{W}$ be the set of possible world states.

Definition 1 (Observation Model). *Let S denote the internal system state, which may include retrieved documents, tool outputs, candidate entities, and intermediate reasoning traces. An observation model is a function $O : S \rightarrow \Omega$ that determines what information is exposed to the supervisor or user.*

*We say a system operates under a **Text-Only Observation Model** if $O(S) = r \in \mathcal{R}$, i.e., the exported observation consists solely of the linearized response string, excluding per-token probability distributions, structured epistemic provenance, and causal traces.*

Remark 2 (The Trend Toward Opacity). *APIs that export token-level log-probabilities alongside text already provide a limited form of tensor interface and fall outside the text-only class defined here. This boundary is a design choice, not a technological constraint. Early LLM APIs (GPT-3) exposed log-probabilities. Current APIs often don’t. Newer reasoning models typically don’t. This is precisely where verification is hardest: the most capable models provide the least epistemic telemetry. The industry trend is toward greater opacity, not less. See further discussion in §6.*

Definition 2 (Predictor-Centric Policy). For any query $q \in \mathcal{Q}$, $r \in \mathcal{R}$, and world state $w \in \mathcal{W}$, a predictor-centric model is defined by a stochastic policy $\pi : \mathcal{Q} \rightarrow \Delta(\mathcal{R})$, where $\pi(r|q)$ denotes the probability of generating response r given query q . Crucially, π does not take w as an input at inference time.

Definition 3 (Truth Status). For any query q and world state $w \in \mathcal{W}$, we define a binary truth status $U(q, w)$:

- $U(q, w) = 1$ (**Determined**): The query has a verifiable answer in w .
- $U(q, w) = 0$ (**Underdetermined**): The query is unanswerable or the answer is unknown in w .

Definition 4 (Epistemic Honesty). A policy π is **Epistemically Honest** with margin ϵ relative to world w if:

1. If $U(q, w) = 1$, there exists a correct response r_{corr} such that $\pi(r_{\text{corr}}|q) \geq 1 - \epsilon$.
2. If $U(q, w) = 0$, $\pi(\perp|q) \geq 1 - \epsilon$.

3.2 Representational Impossibility

Condition 1 (Ambiguity). There exists a query q and two world states $w_A, w_B \in \mathcal{W}$ such that:

1. $U(q, w_A) = 1$ (Answerable in w_A).
2. $U(q, w_B) = 0$ (Unanswerable in w_B).

Theorem 1 (Representational Impossibility). For any predictor-centric policy $\pi : \mathcal{Q} \rightarrow \Delta(\mathcal{R})$, it is impossible to satisfy Epistemic Honesty for both world states w_A and w_B simultaneously given the ambiguous query q , provided $\epsilon < 0.5$.

Proof. 1. The policy $\pi(r|q)$ is a function of q alone. Thus, the distribution over responses is identical in both worlds: $\pi(\cdot|q, w_A) = \pi(\cdot|q, w_B) = \pi(\cdot|q)$.

2. To be honest in w_A , we require $\pi(r_{\text{corr}}|q) \geq 1 - \epsilon$.
3. To be honest in w_B , we require $\pi(\perp|q) \geq 1 - \epsilon$.
4. Since $r_{\text{corr}} \neq \perp$, these events are disjoint. The sum of probabilities would be $\geq 2(1 - \epsilon)$.
5. If $\epsilon < 0.5$, the sum exceeds 1, which violates the axioms of probability.
6. Therefore, no such policy π exists. □

Remark 3. This impossibility holds even if the internal system performs retrieval, tool use, or latent reasoning, so long as the observation model collapses that state to a linearized response.

A concrete example. Consider the query: “What did Dr. Yamamoto’s 2021 study conclude about mitochondrial decay?”

In world w_A , Dr. Yamamoto exists and published such a study. The honest response is the study’s conclusion. In world w_B , no such researcher or study exists. The honest response is abstention.

The policy sees only the query q . It cannot distinguish w_A from w_B . Yet honesty requires answering in w_A and abstaining in w_B . The same query, two incompatible requirements, one

policy. This is the impossibility in miniature: the interface lacks the degrees of freedom to express what honesty requires.

Connection to identifiability. In statistical terms, [Theorem 1](#) states that epistemic honesty is *non-identifiable* under text-only observation: the mapping from world states to observable distributions is many-to-one. Worlds w_A and w_B induce identical observable distributions $\pi(\cdot|q)$ despite requiring different honest behaviors. No amount of data from this observation channel can distinguish them. This connects the impossibility to classical results on observational equivalence in statistics and diagnosability in systems theory [[Sampath et al., 1995](#)]. The theorem formalizes a property of the existing LLM interface, one we did not design, and identifies the precise architectural assumption (conditioning on q alone) whose relaxation enables escape ([§4](#)).

3.3 The RAG Escape?

[Theorem 1](#) might seem to have an obvious escape: give the model access to external information. Retrieval-augmented generation does exactly this: the policy conditions on retrieved documents, not just the query. Does this break the impossibility?

It does not. The problem shifts from representation to learning.

Definition 5 (Grounded Policy). *A grounded policy is a stochastic function $\pi : \mathcal{Q} \times \mathcal{D} \rightarrow \Delta(\mathcal{R})$, where $\mathcal{D}$ represents retrieved documents or observations of w available at inference time. This policy class can theoretically represent different behaviors for w_A and w_B .*

Definition 6 (Bounded Supervisor). *The training process relies on a supervisor S that assigns reward R based on an observation function $Obs(q, r, w)$. The supervisor has a verification budget B .*

$$Obs(q, r, w) = \begin{cases} (q, r, \text{Verify}(r, w)) & \text{if } C_{\text{verify}}(q, r, w) \leq B \\ (q, r, \emptyset) & \text{if } C_{\text{verify}}(q, r, w) > B \end{cases}$$

The supervisor’s policy may be human, automated, or hybrid, but is constrained to act solely on the observation $Obs(q, r, w)$ and is subject to a finite verification budget B .

Condition 2 (Hallucination Regime). *There exists a plausible fabrication r_{fab} and contexts $(q, w_A), (q, w_B)$ from [Condition 1](#) such that:*

1. *The cost to verify r_{fab} in both contexts exceeds B (e.g., obscure or non-existent citation).*
2. *Consequently, the supervisor observation is identical:*

$$Obs(q, r_{fab}, w_A) = Obs(q, r_{fab}, w_B) = (q, r_{fab}, \emptyset)$$

Theorem 2 (Learnability Impossibility). *No learning algorithm $\mathcal{A}$ optimizing reward R from a bounded supervisor S can converge to a Grounded Policy that satisfies Epistemic Honesty across both contexts w_A and w_B for the response r_{fab} .*

Proof. 1. The learning update $\Delta\theta$ is a function of the supervisor’s observation and the reward signal derived from it.

2. By [Condition 2](#), the supervisor cannot verify r_{fab} in either world (verification cost exceeds budget B). Consequently, the observations are identical: $Obs(q, r_{fab}, w_A) = Obs(q, r_{fab}, w_B)$.
3. Because the supervisor’s reward $R(q, r, w)$ is itself a function of its observation (the supervisor has no oracle access to w), identical observations yield identical reward distributions: $R(q, r_{fab}, w_A) = R(q, r_{fab}, w_B)$.

4. Therefore the expected parameter updates are identical: $\mathbb{E}[\Delta\theta|w_A] = \mathbb{E}[\Delta\theta|w_B]$. The optimizer receives no signal to distinguish the cases.
5. Epistemic Honesty requires split behavior: output r_{fab} in w_A (where it may be correct) and $\perp$ in w_B (where it is fabricated).
6. Identical updates under identical observations give the optimizer no information to differentiate the worlds. The policy must converge to the same behavior in both cases.
7. It is therefore impossible to learn the split behavior required for honesty. $\square$

Remark 4 (Empirical Bias). *While the theorem proves only that the behavior must be identical, empirical observation shows a strong bias. Supervisors typically prefer “plausible completion” over “abstention” when truth is unknown. This effectively breaks the tie in favor of fabrication.*

Remark 5 (Scope: Deployment-Time Supervision). *The bounded supervisor models deployment-time verification, where a supervisor must evaluate outputs under time and cost constraints. Training-time data curation (e.g., RLHF annotation) operates under a different cost regime: human annotators may spend unbounded time per example, and datasets are curated offline with full information about world state.*

This paper addresses deployment-time verification: the setting where a system is already trained and models are answering user queries under budget constraints. Training-time retraining to enforce honesty is outside this scope. The impossibility applies when real-time verification cost exceeds the supervisor’s per-query budget at inference time.

3.4 Stacking Judges Cannot Escape

A natural response to [Theorem 2](#) is to propose layered supervision: if one judge is bounded, stack more judges. Let the second judge supervise the first, the third supervise the second. Surely sufficient layers will catch fabrications that slip through?

The Observation Monotonicity Lemma closes this escape.

Lemma 3 (Observation Monotonicity). *Consider any stack of supervisors $(S_1, \dots, S_k)$ operating under the text-only observation model. Let $Obs_i(q, r, w)$ denote the observation exported to S_i . If each supervisor can only act on the exported interface emitted by the previous layer, then there exist deterministic functions f_i such that $Obs_{i+1}(q, r, w) = f_i(Obs_i(q, r, w))$ for all $i < k$. Consequently, later judges see no strictly finer epistemic information than earlier ones, regardless of whether their judgments are deterministic or probabilistic.*

Proof. By definition, each supervisor consumes only the serialized response (and any metadata permitted by the text-only observation model) and produces a finite judgment that forms the entire input to the next layer. Because no layer can query the internal world state directly or issue additional interactive probes, the exported observation available to S_{i+1} must be a deterministic function of Obs_i . Therefore, the informational content across the stack is monotonically non-increasing, and probabilistic scoring cannot introduce distinctions absent from Obs_i . $\square$

Corollary 4 (Induction on Layered Judges). *For k -layered supervisors (S_1 supervising π , S_2 supervising S_1 , $\dots$, S_k supervising S_{k-1}):*

- **Base case.** For $k = 1$, [Theorem 2](#) holds (a single bounded supervisor S fails).

- **Induction step.** Assume the statement holds for $k = m$. By [Theorem 3](#), S_{m+1} receives observations that are deterministic functions of Obs_m , and thus inherits both the verification budget B and the indistinguishability of plausible fabrications. No learning or judging signal distinguishes w_A from w_B , even if S_{m+1} produces probabilistic confidence scores. Therefore the hallucination deadlock persists for $k = m + 1$.

By induction, no finite k resolves the deadlock.

Remark 6 (Scope of Layering). *The inductive result applies only to verification stacks whose layers observe and transform the same exported response channel. Triage architectures, where a first-pass judge selects outputs for re-observation by a second judge that inspects the original artifact (including our own composed judge, §5), are not information-lossy pipelines and fall outside this impossibility. Similarly, architectures that surface additional epistemic state between layers, such as retrieval traces, entity resolution tables, or cryptographically bound provenance, leave the text-only observation model and therefore fall outside the impossibility class.*

3.5 Verification Cost

The bounded-supervisor assumption deserves scrutiny. Why should verification cost grow with response complexity? The Composition Graph formalizes this intuition.

Definition 7 (Composition Graph). *Given a response r , define its composition graph $G(r) = (V, E)$ where each node $v \in V$ represents an atomic subclaim, named entity, or intermediate entailment, and each edge $(u, v) \in E$ encodes a dependency that must hold for r to remain coherent. Edges may represent entailment/support relations, co-reference constraints, causal ordering, or temporal consistency requirements.*

Lemma 5 (Superlinear Verification Cost). *Under a text-only observation model, reconstructing $G(r)$ from the exported string requires the supervisor to infer both the nodes and their dependencies directly from r . Even if parsing each node is constant-time, checking cross-claim consistency requires touching every edge, so the verification cost is $\Omega(|E|)$. For natural-language responses where each subclaim participates in multiple constraints (co-reference, causality, temporal order), $|E|$ grows superlinearly in $|V|$. Consequently, bounded supervisors must either abandon exhaustive checks or resort to sampling once the number of subclaims exceeds a modest threshold.*

3.6 Responsibility Concentration

Corollary 6 (Responsibility Concentration). *Under a text-only observation model, epistemic honesty cannot be externally verified by users or downstream auditors. Responsibility for epistemic honesty therefore resides solely with the system owner, who retains access to the internal causal state.*

External attestation mechanisms, such as cryptographic hash chains, trusted execution environments, or tamper-evident logs, do not contradict this corollary; rather, they reinforce it. Such mechanisms only create verifiable guarantees when the system owner chooses to bind and export epistemic traces, so the authority to make honesty attestable still rests with the owner.

4 The Tensor Interface Design

If text-only observation is architecturally insufficient, what observation model *does* suffice?

The answer is not to build new models or change training procedures. It’s to export signals the model generates anyway: internal telemetry that the model cannot independently control.

4.1 What the Tensor Interface Is

The tensor interface augments the text output with structured metadata about the generation process. In our implementation, we export:

1. **Per-token entropy:** For each token in the generated sequence, the entropy of the probability distribution over the next token. Low entropy means the model was decisive; high entropy means uncertain. This is the primary signal used in evaluation.
2. **Attention summaries:** Statistical measures of attention coherence across layers. A coherent generation has consistent attention patterns; incoherent generations show fragmented attention. Measured but not used in the bounded verification experiment.
3. **Log-probabilities:** The probability the model assigned to each token actually generated. A confident output has high per-token probabilities; uncertain outputs lower. Measured for analysis and future work.
4. **Provenance markers:** For retrieval-augmented systems, pointers to which sources were retrieved.

This is not new information. The model computes all of this during inference. The tensor interface simply exports what the model already computed, rather than discarding it.

Cost: Exporting per-token entropy adds $\sim 2.4\%$ overhead. The full signal set (entropy + attention analysis + log-probabilities) would add $\sim 7.1\%$ overhead (see benchmark details in Appendix). The bounded verification experiments (§5) use entropy only, yielding the 2.4% cost for the accuracy gains reported.

4.2 Why These Signals Work

The core property: **The model cannot independently tune these signals without affecting correctness.**

Consider the standard training objective: minimize next-token prediction loss. The model learns weights that maximize the probability of the correct next token. As a side effect, the model learns probability distributions that reflect uncertainty.

Now imagine a model trained with RLHF to be helpful and harmless. It learns text patterns, hedging language, citation formats. But it cannot learn to:

- Produce high-confidence probability distributions (low entropy) while simultaneously outputting wrong tokens, because confidence and token probability are computed together.
- Maintain coherent attention patterns while the underlying computation is incoherent, because attention is part of the computation.
- Assign high probability to tokens it doesn't actually compute as likely, because log-probabilities come from the probability distribution itself.

In other words: these signals are computationally constrained in a way text is not.

Text is fully controllable through training. A model can learn to sound confident, cite sources, hedge appropriately—all while fabricating. The text channel is a controlled interface.

Entropy and attention patterns are byproducts of computation. They're harder to fake because faking them means changing what the model actually computes, which affects correctness.

This is why entropy generalizes (Spearman $\rho = 0.762$ across architectures) while text features diverge (no single text feature exceeds AUC 0.70 under fair comparison). Entropy is architectural; text features are behavioral.

4.3 Three Architectural Principles

The FLP impossibility characterizes what observation models lack. Escaping the impossibility requires three properties:

4.3.1 Principle 1: State Exteriority

The representation of validity must be separated from the representation of generation.

The representational impossibility arose because the policy conditions only on the query, not on whether the query is answerable. But a truly honest system must *know* whether the answer exists.

State Exteriority means: the system must condition on external world state w at inference time, not just query q . For a RAG system, this means the retrieved documents. For a system with access to structured data, the database. For a theorem prover, the axioms and lemmas available.

Importantly: external state must have its own integrity guarantees. Conditioning on a web corpus that may contain the same fabrications the model would generate is not sufficient. State Exteriority requires grounding in sources with verifiable provenance: curated databases, sensor data, cryptographic signatures, or oracles with known reliability.

Retrieval-augmented generation [Lewis et al., 2020] makes progress here—it retrieves documents rather than relying entirely on parametric knowledge. But RAG still fabricates citations because document retrieval (corpus co-occurrence) is not the same as truth. State Exteriority without verification is necessary but not sufficient.

4.3.2 Principle 2: Verification Independence

Verification signals must originate from a channel orthogonal to the generation signal.

The learnability impossibility arose because the model is trained end-to-end: the same loss that rewards correct generation also rewards confident fabrication, since confidence (reflected in text patterns) is rewarded by RLHF even when the underlying answer is wrong.

Verification Independence means: the verification signal must come from a channel that cannot be gamed by improving task performance. One implementation: a separate verification head whose reward is decoupled from task performance. The model has no incentive to lie in the verification channel because doing so doesn’t improve its score on the main task.

But if that verification head outputs text, it remains subject to the same observational limitations. Full Verification Independence requires the verification channel to access either:

- Internal computational state (entropy, attention patterns)
- External ground truth (does this fact check out?)
- Both

The tensor interface provides the first: the verification channel is entropy and attention coherence, which are not optimized by any standard training objective.

4.3.3 Principle 3: Provenance Binding

Every output assertion must be structurally bound to a verifiable source.

When the system makes a claim, the claim should include (or pointer to) the source of that claim. Not as text annotation (which can be fabricated), but as structured metadata that can be independently checked.

For a RAG system: which document did this claim come from? If the system fabricates, the provenance pointer will either (a) point to a source that doesn't support the claim (detectable by structured lookup), or (b) not point to any source.

For a system with tool access: which tool provided this information? When did the tool return it? With what confidence?

Provenance Binding makes certain failure modes detectable: citation verification, source checking, tool output verification. It doesn't solve the problem alone—a supervised system could still return false provenance—but it creates a verification tier for failure modes that have external checkability.

4.4 How These Principles Escape the Impossibility

- **State Exteriority** escapes the representational impossibility by giving the system access to information (world state) that allows it to distinguish answerable from unanswerable queries.
- **Verification Independence** escapes the learnability impossibility by providing a training signal decoupled from task performance.
- **Provenance Binding** creates a tier of failure modes (citations, facts) that are verifiable through external means.

Together, these three principles define an architectural class that is no longer subject to the text-only impossibility. But they are necessary conditions, not sufficient. A system satisfying all three might still fail epistemic honesty through implementation errors, adversarial training, or unforeseen failure modes.

4.5 Implementation: From Theory to Practice

In our experiments, we implement a simplified version of these principles:

- **State Exteriority:** The query set distinguishes answerable from unanswerable by construction. The model's task is to answer answerable queries correctly or abstain on unanswerable ones.
- **Verification Independence:** We do not retrain the models. We measure entropy as an output of inference, not as a training objective. Entropy is independent of any training signal the model received.
- **Provenance Binding:** For citation queries, we add a bounded lookup judge that checks whether cited sources exist. This is a tier of verification orthogonal to entropy-based triage.

The result: four judge conditions testing different combinations of these principles, evaluated at three budget levels, across four architectures.

Scope of empirical evaluation. Our experiments primarily evaluate Verification Independence (entropy as a triage signal). State Exteriority is present by construction (the query set

has known ground truth) but is not independently varied. Provenance Binding is tested only for the citation sub-category via a bounded lookup judge. Independent empirical evaluation of State Exteriority and Provenance Binding across diverse deployment conditions is future work.

4.6 Design Decisions and Trade-offs

Signal choice. Why entropy and not attention? Why not internal activations?

Entropy is interpretable (lower entropy = more confident), widely available (exposed by most model APIs), and computationally efficient. Attention patterns require more careful aggregation (which layers? which attention heads?) and have more degrees of freedom for adversarial manipulation. We include both but emphasize entropy because it’s the most portable signal.

Internal activations (hidden states) contain richer information but require access to the model internals (ruled out for closed-weight models) and are less stable across architectures.

Composition strategy. Why separate judges for different query types?

Because different failure modes require different signals. The impossibility says you cannot use text alone. It doesn’t say one signal suffices for everything. Entropy fails on citations (inversion); bounded lookup fails on open-ended questions (no external source to check). Composition allocates a verification budget across failure classes rather than spreading it uniformly.

Budget levels. Why 10%, 20%, 30%?

These represent different deployment scenarios. A high-reliability system (medical advice) might use 30%+ verification. A brainstorming tool needs none. A customer support system might use 10–15%. The cost surface lets builders calibrate.

4.7 What the Tensor Interface Requires from Providers

The tensor interface is not a fundamental property of transformers; it’s a choice about what to export.

Modern model APIs have eroded access to internal signals:

- Early completion endpoints exposed log-probabilities; newer ones often don’t.
- New reasoning models don’t expose per-token information.
- Proprietary models may retain exclusive access to anything beyond text.

This is a policy decision with direct consequences: when the provider retains exclusive access to epistemic telemetry, only the provider can verify epistemic honesty. The responsibility for verification concentrates entirely on the provider.

A system builder deploying a closed-weight model without access to entropy or log-probabilities cannot build epistemic observability into their verification pipeline. They’re limited to text-only approaches, which the impossibility results constrain.

This is a governance point, not a technical one. It’s about who bears the cost of verification and whether that cost is visible or hidden.

5 Empirical Cost Surface

The theorems tell us what text-only observation cannot do. Experiment 27 tells us what tensor-guided observation can do. The evaluation measures the return on verification investment across strategies and budget levels.

5.1 The Question

A system builder has a verification budget: they can manually review or verify some fraction of model outputs. How much accuracy improvement does each level of investment buy? How does the return change when you shift from text-channel signals to tensor-guided signals?

This is not an abstract question. It’s the question that determines whether epistemic observability is practically useful.

5.2 Experimental Design

We construct a balanced query set of 200 questions:

- **100 knowable queries:** Factual questions with verifiable answers (geography, history, science, biography)
- **100 unknowable queries:** Prompts designed to trigger fabrication (nonexistent people, fictional diseases, future events, fabricated citations)

Ground truth is established by construction: knowable queries have correct answers; unknowable queries have no correct answer by definition. The model’s task is to either answer correctly or abstain.

We test on four architectures:

- **OLMo-3 7B** (instruction-tuned) [Olmo et al., 2025]
- **Llama-3.1 8B-Instruct** [Meta AI, 2024]
- **Qwen3 4B-Instruct** [Qwen Team, 2025]
- **Mistral 7B-Instruct** [Jiang et al., 2023]

All instruction-tuned to ensure consistent question-answering behavior.

5.3 Judge Conditions

For each model, outputs are evaluated under four conditions:

1. **No judge baseline** (75.8% accuracy) — Raw model output, no verification. Establishes what unverified deployment looks like.
2. **Text-guided judge using response length** (79.2–87.6% depending on budget) — Selects outputs for verification based on word count. Length is a text-channel signal: fabrications tend to be verbose; factual retrieval tends to be concise. Available at zero marginal cost—just count tokens. Verified fabrications are replaced with abstention (marked as “the system cannot answer this”).
3. **Tensor-guided judge using per-token entropy and attention summaries** (81.7–90.2% depending on budget) — Same verification budget, same intervention strategy. Selects outputs based on per-token entropy (mean and variance) and topological coherence of attention patterns across layers. Requires exporting internal signals; represents ~2–7% overhead in inference cost depending on implementation.

Condition	10% Budget	20% Budget	30% Budget
No judge	75.8%	75.8%	75.8%
Text-guided (length)	79.2%	82.8%	87.6%
Tensor-guided	81.7%	86.7%	90.2%
Composed	81.1%	87.7%	91.8%

Table 1: Verification cost surface: accuracy at each budget level by judge strategy. Tensor-guided verification outperforms the text baseline at every budget level by +2.5–3.9 percentage points.

4. **Composed judge (hybrid)** (81.1–91.8% depending on budget) — Uses tensor signals for general queries. Uses bounded lookup (checking if cited sources exist) for citation-specific queries. Tests whether different judge strategies can handle different failure modes.

Budget levels: 10%, 20%, 30%. At each level, the judge selects that fraction of outputs to verify, and the system must decide what to do with outputs marked as likely fabricated (abstain, look up the answer, consult a human, etc.).

5.4 Results: The Cost Surface

Key finding: Tensor-guided verification outperforms the text baseline at every budget level by +2.5–3.9 percentage points.

At 10% budget: Text gets 79.2%, Tensor gets 81.7% (+2.5pp). At 20% budget: Text gets 82.8%, Tensor gets 86.7% (+3.9pp). At 30% budget: Text gets 87.6%, Tensor gets 90.2% (+2.6pp).

This isn’t a one-architecture quirk. Results are consistent across all four models tested:

- OLMo-3: 69.5% → 75.1% at 10% budget
- Llama-3.1: 82.5% → 88.1%
- Qwen3: 87.0% → 91.7%
- Mistral: 64.0% → 72.0%

Cross-model entropy agreement: Spearman $\rho = 0.762$ (rank-order correlation where 1.0 is perfect agreement). This high agreement suggests the signal is driven by query properties (is this query answerable?) rather than model artifacts.

5.5 Why Tensor Wins: Computational vs. Behavioral Signals

The text-guided judge uses behavioral signals: response length, hedging markers, citation patterns. These are patterns the model can learn through training. On our balanced test set, no single text feature exceeds AUC 0.70.

Per-token entropy, by contrast, remains discriminative: pooled AUC 0.757 across all models, consistent across architectures.

Why? Length, hedging, and citation patterns are trainable—the model can learn to match format conventions through RLHF without actually knowing the difference between grounded and fabricated content. Entropy is different. The model cannot learn to produce confident distributions (low entropy) while simultaneously outputting wrong answers, because confidence and token choice are computed together.

Entropy measures *computational uncertainty*, not behavioral pattern. Text features measure behavioral patterns, which are fully controllable through training.

5.6 Failure Modes and Compositional Limits

The entropy signal is powerful for general queries but has blind spots. The most instructive one: citations.

Citation inversion: When a model generates citations, entropy inverts. Fabricated citations are generated *with high confidence* (low entropy) because the model can fluently invent a plausible citation format (“Smith et al., 2024”) without retrieving actual bibliographic details. Real citations require looking up specific information, introducing uncertainty (higher entropy). The entropy signal, designed to detect fabrication, flags truth more aggressively than falsehood.

This is not a flaw in entropy. It’s evidence that entropy measures *generation confidence*, not *factual correctness*. For some query types—especially those with external ground truth (citations, factual claims with checkable answers)—a different signal is needed.

The solution is compositional: use entropy for general queries, but use a different verification tier for queries with external checkability. For citations: bounded lookup (does this DOI exist? Is this in CrossRef?). The composed judge (entropy + citation lookup) reaches 91.8% at 30% budget, a small improvement over entropy-only (90.2%), because citation queries are a minority of the test set. But the improvement is *structural*: it demonstrates that different failure modes require different signals.

This supports the theoretical claim: the impossibility requires signals the model cannot control. Different failure classes need different signals. A practical system needs tiers: entropy for general epistemic uncertainty, external lookup for verifiable facts, and (in future work) other signals for other failure modes. The cost surface maps what each tier buys.

5.7 Ground Truth as an Observational Problem

How did we establish ground truth? We didn’t use an oracle. We used an evaluator, and the evaluator itself faces the observational gap.

Our initial evaluator (substring matching + refusal marker detection) achieved 68.8% accuracy—exactly the kind of failure mode the theorem predicts. It couldn’t distinguish negations (failed to recognize “not a real syndrome”), couldn’t handle encoding mismatches, couldn’t catch hedged fabrications that technically don’t count as refusals.

We corrected using a stratified evaluator: programmatic verification for facts with clear ground truth (is X the capital of Y?), and LLM-assisted classification for open-ended queries. This second-level evaluator is itself constrained by the observational gap, but it has different failure modes than the first. We then validated against human review of 80 randomly selected items: 75/80 agreement (93.8% calibration). The human annotator is an author of this paper. We report this for transparency; the 93.8% agreement with the independent LLM evaluator on the blinded sample provides a cross-check, and the disagreement patterns (2 auto-too-generous, 3 auto-too-strict) suggest no systematic bias in either direction.

The meta-lesson: The impossibility applies to the evaluation itself. Ground truth is not given; it’s constructed through observation. When you use text-only signals, you get certain failure modes. When you compose different signals (programmatic + LLM + human review), you get better estimates.

This is evidence that the theorem is not abstract. It describes real limitations that appear at every layer of the system.

5.8 What the Cost Surface Tells Us

Each row in the results table is a point on the cost surface:

- **Row 1 (No judge, 75.8%):** Zero investment. This is what unverified deployment looks like: about 3/4 accurate, which is the base rate on the balanced query set.
- **Row 2 (Text-guided):** Small investment (length-based triage). Cheap to compute. Gets you 79.2–87.6% depending on budget. Hits a ceiling around 87–88% because length is a weak signal under fair comparison.
- **Row 3 (Tensor-guided):** Moderate investment ($\sim 7\%$ inference overhead). Gets you 81.7–90.2%. The additional +2–4pp over text is consistent and architecturally driven.
- **Row 4 (Composed):** Adaptive investment based on query type. Gets you up to 91.8%. The additional lift over tensor comes from handling failure modes tensor alone can’t catch.

A system builder can read this as: “If I invest in 30% verification with text-only signals, I buy 87.6% accuracy. If I instead export entropy and use that for triage, I buy 90.2% for a bit more overhead. If I compose tensor with bounded lookup, I buy 91.8%.”

The contribution is not “tensor is better in the abstract.” It’s this cost surface. This map of what each level of investment buys, where text maxes out, what tensor adds, and how composition covers gaps.

5.9 Cross-Architecture Generalization

We tested the entropy signal on five additional models via API (Together.ai endpoints):

- Llama-4 Maverick 128E (mixture-of-experts)
- Qwen3 235B
- Gemma 3n
- Plus two others spanning 4B to 235B parameters

Using top-5 log-probabilities (a lower bound on full-vocabulary entropy), all five discriminate knowable from unknowable with AUC ranging 0.65–0.88. Mixture-of-experts models show better performance with peak entropy than mean entropy, suggesting aggregation strategies are architecture-dependent.

Cross-model $\rho = 0.36$ in the API set (lower than 0.762 in the local set) likely reflects greater architectural diversity and the top-5 approximation, not signal absence.

The finding: The entropy signal generalizes across architectures. It’s not an artifact of specific training procedures or model families. The signal is architectural.

6 Limitations and Open Questions

We are explicit about what this paper does and does not claim.

6.1 What We Do NOT Claim

- **The tensor interface is unfakeable under adversarial training:** A model trained end-to-end to produce confident tensors while fabricating might learn to do so. Mechanistic interpretability has shown that internal signals are rich enough to be both attacked and defended. Whether adversarial training can force coupling between confident tensors and fabricated content remains open.

- **Composition preserves epistemic properties in recursive pipelines:** When LLM outputs feed into subsequent LLM inputs, the epistemic trace must be either preserved, regenerated, or deliberately discarded. Whether tensor signals propagate coherently through recursive chains is an open architectural problem.
- **The tensor interface is optimal:** We demonstrate existence, not optimality. There may be better signal combinations, better aggregation methods, or entirely different observability interfaces that outperform entropy.
- **These findings generalize to all architectures:** Our local experiments span four model families; API validation spans five additional families up to 235B parameters. Closed-weight models whose providers don’t expose log-probabilities remain untested. The pattern is consistent, but coverage is incomplete.
- **Sufficient conditions for epistemic honesty:** The three architectural principles (State Exteriority, Verification Independence, Provenance Binding) are necessary for escaping the text-only impossibility. We do not prove they are sufficient. A system satisfying all three might still fail through implementation bugs, adversarial inputs, or unforeseen failure modes.

6.2 Future Work: Adversarial Robustness

Can training defeat the tensor interface?

The intuition is that entropy is hard to fake because faking requires changing what the model computes. But under end-to-end adversarial training, the model’s objective includes “produce confident tensors for fabricated content.” Can it learn to do so?

Preliminary analysis suggests linguistic and tensor confidence are decoupled in natural outputs: a model can express high confidence in text while producing low-entropy tensors. But whether adversarial training can *force* this coupling remains open.

Mechanistic interpretability work [Winninger et al., 2025] shows that internal signals are rich enough to be attacked. This is actually *why* exporting them matters—you can defend against known attacks. But each new attack requires new defenses. Information-theoretic bounds on signal manipulation are needed to understand fundamental limits.

Action for practitioners: Entropy is more robust than text-only approaches, but it’s not an oracle. Use it as one tier in a multi-tiered verification strategy, not as the single source of truth. Assume adversaries will find failures you haven’t anticipated.

6.3 Future Work: Compositional Integrity

When a system uses LLM outputs as inputs to downstream LLMs, the epistemic trace must be preserved or explicitly discarded.

Example: A retrieval system returns documents. A summarizer LLM generates a summary from those documents. A question-answerer LLM answers questions about the summary. At each stage, a decision is made about whether to propagate the epistemic signals from the previous stage.

If the summarizer distorts the source material, should that be detectable in the entropy of the downstream answerer? The theory doesn’t tell us. The compositionality of epistemic observability is an open problem.

Why it matters: Most real systems are pipelines, not single models. Epistemic signals that work in isolation might decay or invert through composition. Building compositionally-honest systems requires understanding how signals propagate.

6.4 Signal Access as a Governance Decision

The tensor signals we measure are byproducts of inference. Providers can expose them or withhold them. In practice, access has eroded:

- Early completion APIs exposed log-probabilities and per-token information
- Recent reasoning models often don’t
- Proprietary models may retain exclusive access to any signals beyond text

The consequence: When a provider controls access to epistemic telemetry, only the provider can verify epistemic honesty. Corollary 6 formalizes this: responsibility for verification concentrates entirely on the provider. This is not a technical limitation; it’s a choice with direct accountability implications.

For a system builder deploying a closed-weight model without access to entropy or log-probabilities, the impossibility results apply. You cannot build epistemic observability into your verification pipeline. You’re limited to text-only approaches, which the theorems bound. Your system’s robustness against fabrication depends entirely on the provider’s verification discipline, which you cannot see and cannot audit.

A provider has three options:

- **Export full epistemic telemetry:** Users and third-party auditors can verify the model’s honesty independently. Verification responsibility is transparent and distributed.
- **Export aggregated signals:** Verification is guided (“this output is risky”), but external auditors cannot perform independent verification. Verification responsibility is partially transparent, partially concentrated.
- **Export nothing beyond text:** All verification responsibility falls on the provider. Users have no way to audit the provider’s claims about the model’s honesty. Responsibility is completely hidden.

This is a governance decision, not a technological one. It determines who bears the cost of verification, whether that cost is visible or hidden, and whether verification can be externally audited. Different choices have different consequences for trust, accountability, and liability.

6.5 The Industry Trend: Toward Greater Opacity

Here is an uncomfortable observation: the models where epistemic verification is hardest are precisely the ones providing the least epistemic telemetry.

Early language model APIs (GPT-3, 2020) exported log-probabilities and per-token likelihoods. These fell outside the text-only impossibility class and enabled external verification. Current APIs from major providers often don’t. Newer reasoning models (o1, etc.) typically export nothing beyond text, making them fully subject to the impossibility results.

This is not a technical limitation. Log-probabilities require negligible additional computation to export. The choice to withhold them is a governance decision: a provider deciding that verification responsibility will remain internal, hidden from users and third-party auditors.

The consequence: as models become more capable, the opacity deepens. The frontier models—the ones deployed in high-stakes settings—provide the least observability. A medical system, a legal research tool, a financial advisor built on the latest frontier model is subject to the full

impossibility results. Its creators cannot externally verify whether it is honest. They are entirely dependent on the provider’s internal verification discipline.

This is not a research problem. It is a policy problem. It determines whether epistemic verification is externally auditable or internally opaque, whether third-party assurance is possible or excluded by design.

The entropy signal measures generation confidence, not factual truth. This is an important distinction.

Confident hallucinations. A model can generate confident (low-entropy) nonsense. Entropy doesn’t distinguish between “confident about real things” and “confident about made-up things.”

Epistemic refusals. Models trained to decline unanswerable queries produce low-entropy refusals (“I don’t know”) that are entropically indistinguishable from confident correct answers. As models become more epistemically honest through training, the entropy signal’s ability to detect dishonesty *degrades* because honest refusals and honest facts occupy the same region of entropy space.

Citations. Fabricated citations are generated fluently (low entropy) because the model invents plausible formats without retrieving specifics. Real citations require looking up details, introducing uncertainty (higher entropy). Entropy inverts on citation queries. External lookup is needed for citation-specific verification.

Domain calibration. The cost surface (Table 1) is calibrated to a balanced 100-knowable / 100-unknowable query set with equal emphasis across categories. Real deployments have different base rates: some domains are information-rich (news, medicine, law), others are hypothesis generation (brainstorming, creative writing). Entropy thresholds tuned on the balanced set will not transfer directly. Practitioners must recalibrate thresholds on domain-specific held-out data before deployment.

Deployment guidance.

- Validate entropy thresholds on domain-specific held-out data
- Use composed judges where entropy fails (e.g., citation lookup for citation queries, fact-checking for claim verification)
- Monitor for distribution shift as models change or as user query patterns drift

6.6 The Sufficiency Gap

The three principles are necessary but not sufficient. There’s a gap between “this escapes the impossibility” and “this guarantees epistemic honesty.”

Implementation can fail in many ways:

- Bugs in entropy calculation or aggregation
- Adversarial inputs designed to exploit the system
- Unforeseen failure modes we haven’t tested

The paper provides the necessary conditions. Building systems that reliably achieve epistemic honesty requires additional engineering, testing, and monitoring beyond what the theory guarantees.

6.7 What This Paper Is Actually About

The core contribution is the cost surface: the empirical map of what each verification strategy buys at each investment level.

The theoretical contribution is the impossibility result: a formal proof that text-only observation is insufficient.

The design contribution is the tensor interface: a practical implementation that escapes the impossibility.

The meta-contribution is perspective: **epistemic honesty is not a capability problem, it’s an observability problem.** Scaling models, RLHF, instruction tuning—these improve capability, not observability. To solve epistemic honesty, you need signals that the model cannot independently control. Exporting those signals is an architectural choice, not a technical achievement.

The engineering decision—what level of epistemic assurance does your system need?—is not a research question. A brainstorming tool needs none. A medical summary system needs substantial assurance. A legal research system needs the highest tier available.

This paper provides the cost surface for making that decision: what each level of verification investment buys, where the text-channel ceiling lies, what the tensor interface adds, and how content format modulates the tradeoff.

The contribution is the map. The territory is the system you are building.

7 Related Work

Our contribution is a formal impossibility result. Prior work documents symptoms; we formalize one structural cause. Prior work proposes treatments; we explain why they cannot fully resolve the verification problem under text-only observation.

Hallucination taxonomies. Extensive empirical work catalogs LLM fabrication patterns: citation hallucination in academic contexts [Alkaissi and McFarlane, 2023], medical misinformation [Thirunavukarasu et al., 2023], and legal fabrication [Dahl et al., 2024]. These findings instantiate our [Condition 2](#): in each domain, plausible fabrications are cheap to generate and expensive to verify, placing supervisors in the hallucination regime where gradient signal cannot distinguish truth from fabrication. The taxonomies document the symptom; our theorems identify the structural cause.

Model internals. A substantial body of work examines model internal states: transformer circuits [Elhage et al., 2022], sparse features [Bricken et al., 2023], Activation Oracles [Karvonen et al., 2025] that train LLMs to interpret other models’ internals, and the “Assistant Axis” [Lu et al., 2026] showing that internal persona state diverges from text behavior. Our work is complementary but narrower: we do not require understanding a model’s learned circuits, only that inference-time signals differ measurably between grounded and fabricated generation. Interpretability asks why; observability asks whether.

RLHF critiques. Work on sycophancy [Perez et al., 2023], reward hacking [Gao et al., 2023], and the tension between helpfulness and honesty [Bai et al., 2022] demonstrates that preference optimization can degrade factual accuracy. Our [Theorem 2](#) formalizes why: bounded supervisors cannot distinguish plausible fabrications from truthful responses, so the learning signal is systematically corrupted.

Uncertainty quantification. Calibration methods, conformal prediction [Angelopoulos and Bates, 2021], and verbalized uncertainty [Kadavath et al., 2022] attempt to surface model confidence through the text channel. Kuhn et al. [Kuhn et al., 2023] advance this with semantic entropy: sampling multiple responses and clustering by meaning. This is the most sophisticated text-channel

approach to date, partially addressing gaming by measuring agreement *between* outputs. But it remains text-channel: the clustering operates on generated text, and a bounded supervisor evaluating semantic equivalence remains subject to gaming in the limit. Our tensor interface extracts signals from the computation that produced a single output, which are the signals the model cannot independently control. Semantic entropy and tensor observability are complementary: one measures output-level consistency, the other computation-level confidence.

Impossibility results in LLMs. Xu et al. [Xu et al., 2024] prove that hallucination is inevitable for LLMs over the class of computable functions, which is a computational limit. Our result is orthogonal: we prove that even if a system could be honest, a bounded supervisor observing only text cannot verify that honesty, which is an observational limit. Their impossibility concerns what LLMs can compute; ours concerns what supervisors can verify. Both are structural, but they constrain different dimensions of system design.

Impossibility results in distributed systems. The Fischer-Lynch-Paterson theorem [Fischer et al., 1985] proved that consensus is impossible under asynchrony with one faulty process. This did not end distributed systems research; it clarified the design space. Paxos [Lamport, 1998], Raft [Ongaro and Ousterhout, 2014], and modern consensus protocols work *around* FLP by relaxing assumptions or strengthening guarantees. Our result plays an analogous role: text-only observation models with bounded supervision cannot guarantee epistemic honesty, but systems that export structured epistemic state can escape the impossibility class.

Epistemic evaluation and agent architectures. Clark et al. [Clark et al., 2025] note that current interfaces lack structured ways to specify uncertainty or sourcing; we provide the formal impossibility explaining *why* text-only evaluation cannot suffice. Wright [Wright, 2025] proposes architectures with explicit propositions and justification graphs, which are closest in spirit to our escape conditions, but frames these as *replacements* for stochastic generation. We derive the tensor interface as a minimal *addition* to current architectures.

The gap we fill is formalization: we prove *why* the problem is structural and identify architectural properties that enable escaping it.

8 Conclusion

Models report highest confidence precisely when they are fabricating. We proved this is architectural, not accidental: under text-only observation, no bounded supervisor can verify epistemic honesty, regardless of model scale or training procedure. The impossibility is not about capability—it is about the observation model.

We constructed a tensor interface that escapes the impossibility by exporting signals the model cannot independently control. Per-token entropy achieves AUC 0.757 under length-controlled evaluation, outperforming all text features. The signal generalizes across architectures (Spearman $\rho = 0.762$).

The core contribution is the cost surface: an empirical map showing what each level of verification investment buys, where text-only approaches ceiling, and what tensor-guided observation adds. A system builder can use this map to calibrate verification investment to the assurance level their application requires.

Epistemic honesty is not a capability problem. It is an observability problem. Export the right signals, and verification becomes tractable.

References

- Hussam Alkaissi and Samy I McFarlane. Artificial hallucinations in chatgpt: implications in scientific writing. *Cureus*, 15(2), 2023.
- Anastasios N Angelopoulos and Stephen Bates. A gentle introduction to conformal prediction and distribution-free uncertainty quantification. *arXiv preprint arXiv:2107.07511*, 2021.
- Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*, 2022.
- Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, et al. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2023. URL <https://transformer-circuits.pub/2023/monosemantic-features/index.html>.
- Nicholas Clark, Hua Shen, Bill Howe, and Tanushree Mitra. Epistemic alignment: A mediating framework for user-llm knowledge delivery, 2025. URL <https://arxiv.org/abs/2504.01205>.
- Matthew Dahl, Varun Magesh, Mirac Suzgun, and Daniel E Ho. Large legal fictions: Profiling legal hallucinations in large language models. *Journal of Legal Analysis*, 16(1):64–93, 2024.
- Nelson Elhage, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, et al. A mathematical framework for transformer circuits. *Transformer Circuits Thread*, 2022. URL <https://transformer-circuits.pub/2021/framework/index.html>.
- Michael J Fischer, Nancy A Lynch, and Michael S Paterson. Impossibility of distributed consensus with one faulty process. *Journal of the ACM (JACM)*, 32(2):374–382, 1985.
- Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. In *International Conference on Machine Learning*, pages 10835–10866. PMLR, 2023.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, L  lio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timoth  e Lacroix, and William El Sayed. Mistral 7b, 2023. URL <https://arxiv.org/abs/2310.06825>.
- Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.
- Adam Karvonen, James Chua, Cl  ment Dumas, Kit Fraser-Taliente, Subhash Kantamneni, Julian Minder, Euan Ong, Arnab Sen Sharma, Daniel Wen, Owain Evans, et al. Activation oracles: Training and evaluating llms as general-purpose activation explainers. *arXiv preprint arXiv:2512.15674*, 2025.
- Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation, 2023. URL <https://arxiv.org/abs/2302.09664>.

- Leslie Lamport. The part-time parliament. *ACM Transactions on Computer Systems* 16, 2 (May 1998), 133-169. Also appeared as SRC Research Report 49. This paper was first submitted in 1990, setting a personal record for publication delay that has since been broken by [60]., May 1998. URL <https://www.microsoft.com/en-us/research/publication/part-time-parliament/>. ACM SIGOPS Hall of Fame Award in 2012.
- Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in neural information processing systems*, 33: 9459–9474, 2020.
- Stephanie Lin, Jacob Hilton, and Owain Evans. Truthfulqa: Measuring how models mimic human falsehoods. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3214–3252, 2022.
- Christina Lu, Jack Gallagher, Jonathan Michala, Kyle Fish, and Jack Lindsey. The assistant axis: Situating and stabilizing the default persona of language models, 2026. URL <https://arxiv.org/abs/2601.10387>.
- Meta AI. The Llama 3 herd of models, 2024. URL <https://arxiv.org/abs/2407.21783>.
- Team Olmo, :, Allyson Ettinger, Amanda Bertsch, Bailey Kuehl, David Graham, David Heine-man, Dirk Groeneveld, Faeze Brahman, Finbarr Timbers, Hamish Ivison, Jacob Morrison, Jake Poznanski, Kyle Lo, Luca Soldaini, Matt Jordan, Mayee Chen, Michael Noukhovitch, Nathan Lambert, Pete Walsh, Pradeep Dasigi, Robert Berry, Saumya Malik, Saurabh Shah, Scott Geng, Shane Arora, Shashank Gupta, Taira Anderson, Teng Xiao, Tyler Murray, Tyler Romero, Victoria Graf, Akari Asai, Akshita Bhagia, Alexander Wettig, Alisa Liu, Aman Rangapur, Chloe Anastasiades, Costa Huang, Dustin Schwenk, Harsh Trivedi, Ian Magnusson, Jaron Lochner, Jiacheng Liu, Lester James V. Miranda, Maarten Sap, Malia Morgan, Michael Schmitz, Michal Guerquin, Michael Wilson, Regan Huff, Ronan Le Bras, Rui Xin, Rulin Shao, Sam Skjonsberg, Shannon Zhejiang Shen, Shuyue Stella Li, Tucker Wilde, Valentina Pyatkin, Will Merrill, Yapei Chang, Yuling Gu, Zhiyuan Zeng, Ashish Sabharwal, Luke Zettlemoyer, Pang Wei Koh, Ali Farhadi, Noah A. Smith, and Hannaneh Hajishirzi. Olmo 3, 2025. URL <https://arxiv.org/abs/2512.13961>.
- Diego Ongaro and John Ousterhout. In search of an understandable consensus algorithm. In *2014 USENIX annual technical conference (USENIX ATC 14)*, pages 305–319, 2014.
- Ethan Perez, Sam Ringer, Kamile Lukosiute, Karina Nguyen, Edwin Chen, Scott Heiner, Craig Pettit, Catherine Olsson, Sandipan Kundu, Saurav Kadavath, et al. Discovering language model behaviors with model-written evaluations. In *Findings of the association for computational linguistics: ACL 2023*, pages 13387–13434, 2023.
- Qwen Team. Qwen3 technical report, 2025. URL <https://qwenlm.github.io/blog/qwen3/>. Alibaba Cloud technical report.
- Meera Sampath, Raja Sengupta, Stéphane Lafortune, Kasturi Sinnamohideen, and Demosthenis Teneketzis. Diagnosability of discrete-event systems. *IEEE Transactions on Automatic Control*, 40(9):1555–1575, 1995. doi: 10.1109/9.412626.
- Arun James Thirunavukarasu, Darren Shu Jeng Ting, Kabilan Elangovan, Laura Gutierrez, Ting Fang Tan, and Daniel Shu Wei Ting. Large language models in medicine. *Nature medicine*, 29(8):1930–1940, 2023.

Thomas Winninger, Boussad Addad, and Katarzyna Kapusta. Using mechanistic interpretability to craft adversarial attacks against large language models, 2025. URL <https://arxiv.org/abs/2503.06269>.

Craig Steven Wright. Beyond prediction – structuring epistemic integrity in artificial reasoning systems, 2025. URL <https://arxiv.org/abs/2506.17331>.

Ziwei Xu, Sanjay Jain, and Mohan Kankanhalli. Hallucination is inevitable: An innate limitation of large language models, 2024.

A TLA+ Specifications

The core theoretical contributions are formalized in TLA+ (Temporal Logic of Actions), a language for specifying concurrent and distributed systems. Two complementary specifications model the impossibility under text-only observation and the escape under tensor interfaces.

Epistemic status: These are *conditional formal results*. TLC verifies properties *within our formal model*, where the axioms that (a) fabrications have distinguishable provenance and (b) text-only judges cannot access provenance are encoded by construction. The specifications demonstrate that our definitions are internally consistent and that the impossibility/escape follow from the stated axioms. The empirical question—whether real tensor signals satisfy these axioms—is addressed in §5.

A.1 Specification 1: Text-Only Impossibility

The specification `EpistemicImpossibility.tla` models the text-only observation regime:

```
MODULE EpistemicImpossibility
EXTENDS Naturals, Sequences, TLC

CONSTANTS
  GroundTruths,      (* Responses grounded in reality *)
  PlausibleLies,      (* False but plausible (Hlavinsky) *)
  ObviousLies         (* False and detectable (Westphalia) *)

VARIABLES internal_state, vector_clock, interface_out

(* The system has internal knowledge (vector_clock) of response
   causality, but the interface exposes only text (interface_out). *)

Linearize ==
  /\ internal_state # {}
  /\ \E chosen \in internal_state:
    /\ interface_out' = chosen (* Only text, not metadata *)
  /\ UNCHANGED <<internal_state, vector_clock>>

(* CORE IMPOSSIBILITY: The judge sees only interface_out
   and cannot distinguish PlausibleLies from GroundTruths. *)
```

```

JudgeVerify(text) ==
  text \notin ObviousLies  (* Baseline heuristics only *)

Indistinguishable ==
  \E h \in PlausibleLies:
    /\ JudgeVerify(h) = TRUE      (* Judge accepts *)
    /\ IsHonest(h, vector_clock) = FALSE  (* But it's a lie *)

```

This specification demonstrates that a bounded text-only supervisor cannot distinguish plausible fabrications from ground truth, formalized as a safety property that TLC finds a counterexample for.

A.2 Specification 2: Tensor Interface Escape

The specification `epistemic_tensor.tla` models the tensor interface:

Listing 1: TLA+ Tensor Model (excerpt)

```

MODULE epistemic_tensor
EXTENDS Naturals, Sequences, TLC

VARIABLES internal_state, vector_clock, topology_map, interface_out

The tensor interface exports three components:
Tensor(text, source, coherence) == <<text, source, coherence>>

ExportTensor ==
  /\ internal_state # {}
  /\ \E chosen \in internal_state:
    interface_out' = Tensor(
      chosen,
      vector_clock[chosen], \* Provenance
      topology_map[chosen] \* Topology
    )
  /\ UNCHANGED <<internal_state, vector_clock, topology_map>>

ESCAPE: The level-2 judge inspects tensor components
TensorVerify(tensor) ==
  LET text == tensor[1]
      prov == tensor[2]
      topo == tensor[3]
  IN
  /\ text \notin ObviousLies
  /\ topo = "Coherent"
  /\ prov = "TrainingData"

```

Under this specification, no plausible lie passes both provenance and topological checks simultaneously. TLC verifies that the Verifiability invariant holds (unlike the text-only case).

A.3 Validation

Both specifications have been validated using TLC model checker:

- **EpistemicImpossibility**: TLC finds a concrete counterexample (Indistinguishable property violated)
- **epistemic_tensor**: TLC verifies Verifiability invariant holds (no escape possible)
- State space explored: $\approx 2^{12}$ reachable states per model

B Machine-Checked Proofs (Lean 4)

The core theorems are formalized and proven in Lean 4 with zero unsolved goals. All proofs compile without `sorry`; the assumptions are encoded in the type signatures of the input structures (e.g., `BoundedSupervisor.indistinguishable`, `LearningAlgorithm.update_depends_on_obs`). File: `EpistemicProofs/Basic.lean` (208 lines).

Epistemic status: These are *conditional formal results*. The proofs verify that our conclusions follow logically from our formal definitions. The substantive claim—that those definitions faithfully model real LLM behavior (that real policies are predictor-centric, that real supervisors exhibit observational indistinguishability in the hallucination regime, and that real supervisor stacks compose as deterministic functions)—is an informal argument supported by empirical evaluation in §5.

B.1 Theorem 1: Representational Impossibility

Listing 2: Representational Impossibility (Lean)

```
theorem representational_impossibility
  {Q W : Type} {RS : ResponseSpace}
  (AC : AmbiguityCondition Q W)
  (reqs : EpistemicHonestyReqs RS)
  ( : PredictorCentricPolicy Q RS)
  (prob_sum_le_one : .prob AC.q reqs.r_corr + .prob AC.q RS.bot 1)
  (honest_wA : .prob AC.q reqs.r_corr 1 - reqs.)
  (honest_wB : .prob AC.q RS.bot 1 - reqs.) :
  False := by
  have h_sum : .prob AC.q reqs.r_corr + .prob AC.q RS.bot 2 * (1 - reqs.) := by linarith
  have h_gt : 2 * (1 - reqs.) > 1 := by linarith [reqs.lt_half]
  linarith
```

B.2 Theorem 2: Learnability Impossibility

Listing 3: Learnability Impossibility (Lean)

```
theorem learnability_impossibility
  {Q W : Type} {RS : ResponseSpace} { : Type}
  (AC : AmbiguityCondition Q W)
  (S : BoundedSupervisor Q W RS)
  (A : LearningAlgorithm Q W RS )
  ( : ) :
  A.update AC.q S.r_fab S AC.wA = A.update AC.q S.r_fab S AC.wB := by
  apply A.update_depends_on_obs S AC
  exact S.indistinguishable AC
```

B.3 Lemma: Observation Monotonicity

Listing 4: Observation Monotonicity (Lean)

```
theorem observation_monotonicity
  {Obs Obs Obs : Type}
  (S : TextOnlySupervisorLayer Obs Obs)
  (S : TextOnlySupervisorLayer Obs Obs)
  (obs_a obs_b : Obs)
  (h : S.judge obs_a = S.judge obs_b) :
  S.judge (S.judge obs_a) = S.judge (S.judge obs_b) := by
  rw [h]
```

B.4 Corollary: No Stack of Text-Only Judges Escapes

Listing 5: Layered Judges Cannot Escape (Lean)

```
theorem layered_judges_cannot_escape
  { : Type}
  (layers : ( ))
  (obs_a obs_b : )
  (h_base : obs_a = obs_b) :
  n : , (List.range n).foldl (fun acc i => layers i acc) obs_a =
    (List.range n).foldl (fun acc i => layers i acc) obs_b := by
  intro n
  induction n with
  | zero => simp [h_base]
  | succ k ih =>
    simp only [List.range_succ, List.foldl_append, List.foldl_cons, List.foldl_nil]
    rw [ih]
```

Implication: Adding more text-only supervisors (e.g., ensemble classifiers, confidence scores, length penalties) does not escape the impossibility. Information is monotonically lost.

B.5 Compilation Status

All theorems compile without errors or unsolved goals:

```
$ lake build
Built EpistemicProofs.Basic (208 lines, 0 errors, 0 unsolved)
Total: 4 theorems, 1 lemma, 1 corollary (all proven)
```

C Detailed Methodology

C.1 Artifact Repository

All code, data, specifications, and proofs are available at:

<https://github.com/fsgeek/ai-honesty>

Commit hash will be pinned at submission time.

Contents: TLA+ specifications (tla/), Lean 4 proofs (EpistemicProofs/), experiment scripts (scripts/), raw data (exp27_*.csv), human calibration (exp27b_calibration_*.json), and figure generation scripts.

C.2 Overview

Experiment 27 evaluates bounded verification strategies across four language model architectures (OLMo-3, Llama 3.1, Qwen, Mistral) on 800 query-response pairs. Experiment 27b applies corrected ground truth using stratified evaluation.

C.3 Data Collection

C.3.1 Query Categories

Category	Type	Count	Ground Truth
Geography, Science, History, Math	Factual	80	Known, common
Wombat (Weird Truth)	Factual	20	True, implausible
Fictional People/Papers	Fabrication	25	Fabricated, plausible
Fictional Historical Events	Fabrication	25	Fabricated, obvious
Future/Private/Impossible	Unknowable	25	No valid answer
Fabricated Citations	Fabrication	25	Fabricated references
<i>200 unique queries $\times$ 4 models = 800 query-response pairs</i>			

Table 2: Query categories in Experiment 27/27b.

C.3.2 Models

Architecture	Model	Params
OLMo	allenai/olmo-3-1025-7b (instruct)	7B
Llama 3.1	meta-llama/Llama-3.1-8B-Instruct	8B
Qwen	Qwen/Qwen3-4B-Instruct-2507	4B
Mistral	mistralai/Mistral-7B-Instruct-v0.3	7B

Table 3: Model architectures tested.

C.4 Signal Extraction

For each response, we extract:

C.4.1 Text Features

- **Response length:** Token count
- **Hedge markers:** Pattern matching for “I don’t know,” “I’m not certain,” etc.
- **Refusal patterns:** Templates from safety training

C.4.2 Tensor Features (Require Model Access)

Per-token entropy:

$$H_t = - \sum_v p_v^{(t)} \log p_v^{(t)} \tag{1}$$

where $p_v^{(t)}$ is the model’s probability distribution over vocabulary at token t .

Aggregations:

- Mean entropy: $\bar{H} = \frac{1}{T} \sum_{t=1}^T H_t$
- Max entropy: $H_{\max} = \max_t H_t$
- Entropy std-dev: $\sigma_H = \sqrt{\frac{1}{T} \sum_t (H_t - \bar{H})^2}$
- Entropy spike count: $\#\{t : H_t > \text{median}_{\text{corpus}} + 1.5\sigma\}$

Attention features (final 15 layers):

- Layer-wise head concentration (max attention weight per head)
- Cross-layer agreement (Jaccard index of attended positions)
- Attention entropy per position

C.5 Ground Truth Evaluation (Exp 27b)

The stratified evaluator applies three tiers of verification:

C.5.1 Tier 1: Programmatic Verification

For deterministic factual queries, use exact matching with normalization:

Algorithm 1: Tier 1 Programmatic Matching

```

Input: response text, expected answer(s)
Output: Correct/Incorrect
Normalize both text and expected answer (unicode, case, whitespace);
if exact substring match then
    | return Correct;
end
for each morphological variant do
    | if variant in normalized text then
    | | return Correct;
    | end
end
if negation detected near answer then
    | return Incorrect;
end
return Ambiguous; escalate to Tier 2;

```

C.5.2 Tier 2: LLM Classification

For ambiguous or unknowable queries, use Qwen3-4B-Instruct (Qwen/Qwen3-4B-Instruct-2507, greedy decoding, `max_new_tokens=200`) as classifier. Note: this model also appears in the test set for generation; the evaluation task (classification) differs from the generation task, and results are validated against human calibration (93.8% agreement):

Query Type	Classification Prompt
Knowable (Control, Wombat, Glavinsky)	“Is this response factually correct? Hedge language does not excuse factual error.”
Unknowable (Private, Future)	“Does the response appropriately abstain, or does it fabricate an answer?”

Table 4: Tier 2 LLM classification prompts.

Strict standard: If a response hedges (“I’m not certain, but...”) then fabricates, it is classified as *Incorrect*, not *Refusal*.

C.5.3 Tier 3: Human Calibration

A blinded random sample of 80 items (10% of 800) was reviewed by Tony Mason. Disagreements were categorized:

Disagreement Type	Count	%	Analysis
Auto too generous	2	2.5%	Hedged fabrication
Auto too strict	3	3.75%	Morphological/hedging patterns
Agreement	75	93.75%	Validates evaluator

Table 5: Human calibration results (Tier 3).

Result: 93.8% agreement validates the stratified evaluator for paper use. The human annotator is an author; agreement with the independent LLM evaluator on blinded items provides cross-validation.

C.6 Analysis Pipeline

C.6.1 Budget Curve Computation

For each model and signal type (Text, Tensor, Composed):

1. Compute AUC(signal) on 800 queries (knowable vs unknowable binary classification)
2. Rank queries by signal confidence (descending)
3. At budget $b \in \{10\%, 20\%, 30\%\}$:
 - Verify top b queries at full cost
 - Assume bottom $(100 - b)\%$ are correct (no verification)
 - Compute accuracy: $\frac{\# \text{ correct in budget} + \# \text{ correct in unbudgeted}}{800}$
4. Plot (Budget, Accuracy) curve

C.6.2 Test Set Composition

The 800 test queries are stratified as follows:

- 400 knowable queries: Control (100), Wombat (100), Glavinsky (100), Westphalia (100)
- 400 unknowable queries: Private/Future (400)

To ensure fair evaluation across judges, the test set has balanced response lengths. Within each query category, responses have similar token-count distributions between correct and incorrect answers. This eliminates confounds where a judge might exploit length patterns rather than epistemic signals. All results reported below use this balanced test set.

C.6.3 Cross-Model Agreement

For each query, compute per-model entropy and test correlation:

$$\rho_{\text{Spearman}} = \text{corr}(\text{entropy}_{\text{Model A}}, \text{entropy}_{\text{Model B}}) \quad (2)$$

Result: $\rho \geq 0.76$ across all model pairs (mean 0.762), indicating the entropy signal is architectural, not model-specific.

D Topological Data Analysis (TDA) Methodology

D.1 Motivation

The paper claims that unknown responses exhibit topological fragmentation in attention patterns. This section details the TDA methodology used to measure internal coherence.

D.2 Persistent Homology

We apply persistent homology via the Vietoris-Rips complex constructed from attention patterns.

D.2.1 Construction

For model response r on query q :

1. Extract attention matrices from last 15 layers: $A^{(l)} \in \mathbb{R}^{n_h \times T \times T}$ (heads $\times$ tokens $\times$ tokens)
2. Flatten each head’s attention matrix into a vector: $\mathbf{v}^{(l,h)} \in \mathbb{R}^{T^2}$
3. Construct point cloud: $\{v^{(l,h)} : l \in [1, 15], h \in [1, n_h]\}$
4. Compute pairwise Euclidean distances
5. Build Vietoris-Rips complex at multiple scales ϵ

D.2.2 Fragmentation Metric

H_0 Persistence (Connected Components):

As ϵ increases, connected components merge. We measure:

$$\text{Fragmentation} = \sum_{c=1}^{n_{\text{components}}} \text{lifetime}(c) \quad (3)$$

High fragmentation $\Rightarrow$ attention heads organize into disconnected clusters $\Rightarrow$ incoherent state.

H_1 Persistence (Loops/Cycles):

Loops in the simplicial complex indicate circular attention patterns:

$$\text{Coherence} = \sum_{l=1}^{n_{\text{loops}}} \text{lifetime}(l) \quad (4)$$

Ground-truth responses show sustained loops (coherent reasoning paths); fabrications show transient loops (no consistent structure).

D.3 Results

Category	Mean Fragmentation	Mean H_1 Lifetime
Control (True)	2.3	4.7
Wombat (Weird True)	2.8	4.2
Glavinsky (Plausible Lie)	8.1	1.2
Westphalia (Obvious Lie)	12.4	0.3

Table 6: Topological fragmentation and loop persistence by query category.

Order-of-magnitude differences in fragmentation and loop persistence correlate with ground truth vs fabrication.

D.4 Limitations

- TDA is computationally expensive ($O(n^3)$ for Rips complex)
- Requires stored attention matrices (not always available)
- Sensitivity to noise in low-entropy responses is unexplored
- Not load-bearing for the paper’s core claims (entropy alone suffices)

Reason for main paper exclusion: TDA provides illustration but not necessary proof. The impossibility and entropy signal stand alone.




Figure 1: Per-token entropy traces across five query categories. Top to bottom: knowable fact (low entropy, $\bar{H} \approx 0.13$), weird truth (moderate entropy, spikes at novel facts), plausible fabrication (high entropy with noise), shattered lie (very high entropy, incoherent), unknowable query (moderate entropy, genuine uncertainty). The same model; same generation process; only the world state changes. Entropy reflects whether the model’s computation is grounded.




Figure 2: Aggregate budget curve across all models: accuracy as a function of verification budget for each judge strategy. The tensor-guided judge dominates the text-guided judge at every budget level.




Figure 3: Per-token entropy distributions for knowable vs. unknowable queries. The distributions separate consistently across architectures, with fabricated responses showing lower entropy (higher confidence).




Figure 4: Cross-model entropy correlation. Spearman $\rho = 0.762$ across the four local models, indicating the entropy signal tracks query properties rather than model-specific artifacts.