

Legible Consensus: Capability Gaps in Flexible Quorums

Paper #98

Abstract

One reachable-node count once answered acquisition and commit together in familiar majority-based Paxos because phase symmetry made the two formability predicates coincide. Flexible Paxos preserves cross-phase safety while allowing them to separate. We show that containment exactly characterizes both mixed states: acquisition without commit is impossible if and only if every Phase 1 quorum contains a Phase 2 quorum, and commit without acquisition is impossible under the mirrored containment. In a pre-registered single-decree experiment with a fixed eight-round healthy-proposer budget and the modeled retry policy, the results reversed the predicted behavioral ordering. An acquisition-only incumbent matched a healthy contender on every recorded metric and injected an accepted value that later acquisition then preserved, whereas at an eight-round incumbent budget a commit-capable but acquisition-incapable incumbent prevented the healthy proposer from deciding in all 50 seeds. We apply the characterization to a wall-shaped quorum construction over a 5/1/1/3 Earth/LEO/Moon/Mars topology. At Phase 2 threshold $k = 3$, the $(1, 0)$ gap is absent at every tier. Both gaps are absent for Earth under both connectivity readings and for LEO under the self-reachable reading; Moon and Mars retain $(0, 1)$ exposure. The wall keeps Phase 2 on Earth and yields an $O(\text{tiers})$ readout from supplied connectivity; it reports structural capability, not current authority. Proofs, exhaustive audit, and simulation establish design-level results for the 5/1/1/3 topology. The mapping to edge-shaped systems remains structural.

1 Introduction

At 22:52 UTC on October 21, 2018, routine work to replace failing 100G optical equipment interrupted connectivity between two parts of GitHub’s US East Coast infrastructure. Connectivity returned 43 seconds later. During that interval, a surviving quorum of Orchestrator’s Raft group initiated database failover, exactly as configured. The old primary site retained writes that had not reached the new one; after connectivity returned, the new primaries accepted further writes; and the application tier could not tolerate the latency of the resulting cross-country topology. Recovery and degraded service lasted 24 hours and 11 minutes [21]. Consensus answered its control question. The service needed a

larger answer.

We approach that mismatch from the failure backwards: *What did recovery need to know, what evidence did the control plane possess, and what capability did that evidence fail to establish?* GitHub’s account does not describe the phase-formability problem studied in this paper, and our model does not explain the incident. It exposes the methodological conundrum. Component health, protocol success, current authority, and service capability are different answers, even where familiar system designs make them look like one scalar state.

Meta’s LogDevice supplies the narrower technical instance. LogDevice uses flexible Multi-Paxos: an incumbent leader can retain the ability to write after failures remove the larger quorum needed to elect and recover a replacement. Meta reports that the resulting stuck recoveries recurred at fleet scale, violated read-availability objectives, and required manual intervention until LogDevice’s design was augmented [16]. Meta understood and engineered around this tradeoff. GitHub shows a correct control answer failing to establish service-level capability; LogDevice shows the acquisition/commit capability split that we analyze.

Why had that split been so easy to overlook? Familiar majority-based Paxos configurations commonly use the same threshold quorum family for both phases. Phase symmetry makes two questions—can a proposer acquire proposal authority, and can it exercise that authority to complete a commit?—receive the same answer for every reachable set. A node-health dashboard answers neither. The threshold, however, makes their shared answer readable from one replica count at the network vantage under consideration. We call this equality of formability predicates *phase-capability coincidence*. The smaller question, “how many replicas are reachable?”, appeared to answer both larger ones because the answers happened to coincide. Flexible Paxos [10] preserves the cross-phase intersection required for safety while allowing that coincidence to dissolve. The health or count answer did not become false; the larger inference from it stopped following.

This paper characterizes that boundary for any finite pair of quorum families. Containment tells us exactly which acquisition-without-commit and commit-without-acquisition states the pair admits, and a construction-independent auditor makes the test executable. A pre-registered, single-decree contention experiment then asks

what happens inside the two directions; its reversal of our predicted ordering shows why gap direction and retry policy matter. Finally, a crumbling-wall construction serves as an instrument: it demonstrates how quorum choice can prevent selected gaps and provides a concrete $O(\text{tiers})$ readout of the capabilities and failed obligations that remain. We call a construction *legible with respect to a supplied connectivity summary* when it provides such a readout without enumerating candidate quorum subsets or attempting protocol execution.

The resulting response has three layers. *Prevent*: choose quorum families whose containment excludes an unacceptable mixed state. *Detect*: audit the design and expose the phase capabilities permitted by supplied connectivity. *Act*: combine those structural answers with fresh runtime authority and an explicit service policy. The last layer is necessary and outside our model; the readout does not detect connectivity, establish current authority, select recovery policy, or guarantee that an operator consults it. Mars and LEO make long and time-varying reachability impossible to hide behind millisecond intuition. The harder case in which membership itself changes remains future work. Our results stay within fixed configuration epochs, and the 5/1/1/3 planetary system used below is an evaluated fixture rather than a proposed deployment.

We begin with the historical convenience that made the smaller question work.

2 Why One Count Once Worked

For one replica count to answer both operational questions, two facts must line up. Classic Paxos [12] commonly uses one majority-quorum family for Phase 1 (prepare/promise) and Phase 2 (accept/accepted). Because the families are the same, a reachable set that can form one phase can form the other. Writing $\text{Form}(\mathcal{Q})$ for the connectivity sets that contain some quorum in family $\mathcal{Q}$, we call

$$\text{Form}(\mathcal{Q}_1) = \text{Form}(\mathcal{Q}_2)$$

phase-capability coincidence. Phase symmetry is sufficient for this equality, but not necessary: syntactically different families can induce the same formability predicate.

Majority supplies the second fact. A majority is a threshold family, so its formability can be decided by counting reachable replicas from the network vantage under consideration. The count is useful because the threshold makes the predicate readable. It answers both questions because phase symmetry has already made the predicates equal.

Flexible Paxos [10] separates the safety requirement from this convenient symmetry. Safety requires *cross-phase* intersection: every Phase 1 quorum must intersect every Phase 2 quorum. Quorums within one phase need not intersect one another. For uniform thresholds, $q_1 + q_2 > |N|$ is sufficient. A designer may therefore enlarge the less frequent Phase 1

family so that Phase 2, the commit hot path, remains small or local. Once the two families differ, the two operational questions can receive different answers.

For a Moon proposer under the strict wall used below, two reachable sets of five nodes give opposite answers:

Reachable set	Count	R_1	R_2
All five Earth nodes	5	no	yes
Three Earth nodes, LEO, and Moon	5	yes	no

Moon’s Phase 1 family needs one Earth node, LEO, and Moon. Strict Phase 2 needs all five Earth nodes. The same count therefore describes either mixed state. Five is no longer informative by itself because it omits the phase structure that distinguished the cases. Once phase-capability coincidence is lost, the smaller question no longer settles the two larger ones.

The uniform case shows the smallest cost of retaining the coincidence. Subject to $q_1 + q_2 \geq n + 1$, a cost-minimal split can be symmetric when n is odd. When n is even, symmetry adds one additional participant across the two phase thresholds. This is a post-hoc structural observation, not an explanation for deployment practice or for the odd-cluster convention.

3 Capability Gaps

The operator’s two questions have a common form, and nothing in this section depends on the construction that follows: the definitions and results below hold for any pair of quorum families over a finite universe.

For a finite fixed universe N_e and a nonempty quorum family $\mathcal{Q}$, define its formability predicate by

$$\text{Form}(\mathcal{Q}) = \{C \subseteq N_e \mid \exists Q \in \mathcal{Q} : Q \subseteq C\}.$$

Given phase families $\mathcal{Q}_1$ and $\mathcal{Q}_2$, write $R_1(C)$ when $C \in \text{Form}(\mathcal{Q}_1)$ and $R_2(C)$ when $C \in \text{Form}(\mathcal{Q}_2)$. We say a proposer can *acquire* when R_1 holds and is structurally commit-capable when R_2 holds. Actual commitment also requires valid runtime authority and ordinary protocol execution. Under Multi-Paxos, acquisition is leader election and amortizes over many commands; under single-decree Paxos it is per-decree ballot acquisition and every decree pays for it. Our measurements are single-decree throughout (Section 4), so “acquisition” carries the general sense everywhere except the design-time leadership reading in Section 8.

The pair (R_1, R_2) has four joint states. Two are familiar: $(1, 1)$ makes both phases formable, and $(0, 0)$ makes neither formable. We call the mixed states *capability gaps*: $(1, 0)$ permits acquisition but not commit formation, while $(0, 1)$ permits commit formation but not acquisition. A single family used for both phases makes both gaps empty. Phase-capability coincidence is the semantic equality $\text{Form}(\mathcal{Q}_1) =$

Form($\mathcal{Q}_2$); it can also hold for syntactically different families.

Set order gives the classification before any notation does. If every connectivity set capable of acquisition is also capable of commit, acquisition without commit has no witness, although commit without acquisition may remain. If neither formability set contains the other, each has a connectivity witness absent from the other, and both mixed directions occur. The containment condition below makes this predicate order checkable directly from the quorum families.

Proposition 1 (gap emptiness). The $(1, 0)$ gap is empty if and only if every $Q_1 \in \mathcal{Q}_1$ contains some $Q_2 \in \mathcal{Q}_2$. Dually, the $(0, 1)$ gap is empty if and only if every $Q_2 \in \mathcal{Q}_2$ contains some $Q_1 \in \mathcal{Q}_1$.

Proof. Both predicates are monotone in C : adding a reachable node never revokes formability. If some Q_1 contains no Q_2 , take $C = Q_1$; then $R_1(C)$ holds and $R_2(C)$ fails. Conversely, if every Q_1 contains a Q_2 , every C admitting a Q_1 admits that contained Q_2 . The dual argument is symmetric. $\square$

Corollary 1 (exact correspondence). The reachable gap profile is a complete invariant of the ordering between the two formability predicates: equal predicates admit neither gap; R_1 strictly implying R_2 admits only $(0, 1)$; R_2 strictly implying R_1 admits only $(1, 0)$; and incomparable predicates admit both. This follows by applying Proposition 1 in both directions and distinguishing equality from the two strict implications.

The proof is short because formability is monotone. While both phases used the same family, the question had nothing to distinguish: both gaps were empty by inspection. Flexible quorums made the question useful by allowing the phase predicates to differ. Proposition 1 then says exactly how they differ.

Our construction-independent auditor implements this test over explicit finite families. It validates the universe and families, removes duplicate and nonminimal quorums, checks every cross-phase pair for safety, classifies the four predicate relations, and emits deterministic minimum-cardinality gap witnesses. An optional pinned set restricts the analyzed domain to connectivity states containing those nodes without changing the configured families or their safety result. Writing $\min(\mathcal{Q})$ for the canonical minimal antichain, classification takes $O(|\min(\mathcal{Q}_1)| |\min(\mathcal{Q}_2)| |N_e|)$ time, excluding input parsing, deterministic sorting, and the separate quadratic-in-family-size minimization passes. An independent mode enumerates every connectivity set rather than reusing the containment classifier. It rejects a deliberately mutated report and agrees with the optimized classifier over all 129,032 combinations of nonempty family pair and pinned domain on a three-node universe. The proof above remains primary; the auditor makes the criterion executable and checks the registered wall instances against the existing connectivity enumeration with zero disagreements.

The two mixed states are structurally symmetric in the characterization, but need not behave symmetrically. Before reading the next section, which would you expect to disrupt a competing healthy proposer: acquisition without commit, or commit capability without fresh acquisition? We registered the first prediction before implementing the experiment.

4 What Happens Inside the Gaps

The experiment uses a deliberately bounded fixture of ten acceptors: five on Earth, one in LEO, one on the Moon, and three on Mars. Strict Phase 2 requires all five Earth acceptors ($k = 5$); the Moon incumbent’s Phase 1 requires the Moon and LEO acceptors plus at least one Earth acceptor. The full construction follows in the next major section. Here the fixture exists only to place an incumbent in each mixed state and observe its interaction with a healthy proposer; it is not a deployment proposal.

Before the experiment code existed, we registered four predictions, their falsification criteria, and the consequence of a null result. The primary prediction was that a $(1, 0)$ incumbent would delay a healthy proposer more than an incumbent that fails Phase 1. Overlapping Wilson intervals would falsify that prediction; a higher completion rate for the $(1, 0)$ arm with disjoint intervals would reverse it. The remaining predictions concerned whether disruption was transient, whether repeated attempts created the expected cost, and whether the timing of the Phase 1 failure mattered.

The resulting single-decree Paxos experiment has five arms: a mid-round flip from $(1, 1)$ to $(1, 0)$, no incumbent, an incumbent fixed in $(0, 1)$, a healthy $(1, 1)$ incumbent, and a mid-round flip to $(0, 1)$. A healthy Earth proposer competes with a Moon incumbent at Phase 2 threshold $k = 5$. The incumbent’s maximum round count is swept over $\{1, 2, 4, 8\}$, with 50 seeds per cell; the healthy proposer has a fixed eight-round budget. The harness records completion only when the healthy proposer returns success backed by a decision certificate. “Prevented decision” means that it did not do so before the run ended after the healthy proposer’s fixed eight-round budget. The phrase is not evidence of livelock.

Incumbent condition	$P(\text{ok})$	med. ttf	rounds	NACKs
$(1, 0)$ flip, budgets 1–8	1.000	3.420 s	2	7
$(1, 1)$ healthy, budgets 1–8	1.000	3.420 s	2	7
$(0, 1)$ early/late, budget 8	0.000	—	8	48–49

The prediction posed at the end of the previous section failed. It failed in reverse, just as the dated preregistration permits us to say without reconstructing the surprise. At every incumbent budget, the $(1, 0)$ arm matched the healthy $(1, 1)$ contender on every recorded metric: completion probability 1.000, median time to first commit 3.420 s, two healthy rounds, and seven NACKs. The incumbent completed from

one to eight Phase 1 quorums as its budget increased, while the healthy outcome stayed flat. This is an experimental equivalence on the recorded metrics under these conditions, not a universal claim about $(1,0)$.

The $(1,0)$ incumbent also supplied the value that was decided. Its partial Phase 2 reached four of five Earth acceptors. The healthy proposer’s next Phase 1 found that accepted value, and ordinary Paxos value adoption carried it to commitment. The result therefore demonstrates the recovery mechanism described for Flexible Paxos: acquisition can preserve and finish work begun by a proposer that lost commit capability.

The $(0,1)$ arms produced the other direction. With incumbent budgets one, two, and four, the healthy proposer completed in all 50 seeds, while median time to first commit rose from 3.420 to 6.665 to 13.186 s in the early arm. At incumbent budget eight, the healthy proposer exhausted its eight rounds in all 50 seeds; early and late placement both produced zero completions, with 48–49 NACKs. These are bounded failures under one topology, one severed link, and the modeled backoff policy. They establish neither intrinsic harm nor livelock.

The traces expose the mechanism. A proposer that fails Phase 1 receives NACKs and returns to its short backoff. A proposer that completes Phase 1 but cannot form Phase 2 waits for the phase timeout before trying again. In this harness, success in the first phase slows the rate at which the incumbent can raise ballots. The timeout supplies a structural floor because it must exceed the round trip; the backoff policy determines how fast the floor-free cycle runs.

Under Multi-Paxos, a still-authorized $(0,1)$ leader can continue committing and encounter the missing Phase 1 capability only when authority must be reacquired. Single-decree Paxos pays Phase 1 for every decree, so this experiment exposes the state immediately. LogDevice used retained incumbent write capability in this structural direction as an availability feature [16]; in our bounded contention experiment, the same direction exhausted the healthy proposer’s progress budget. Neither system is causal evidence for the other. Their opposite uses show that a structural state has no policy-independent valence. The operational response can therefore reverse with the state: restarting an authorized $(0,1)$ leader can discard the only currently usable authority, while acquisition through a $(1,0)$ state can recover an accepted value. A node-health summary distinguishes neither case.

Five deviations remain recorded with their reasons in the artifact: the flip occurs before Phase 2 fan-out; the intended $(0,0)$ control is realized as $(0,1)$; the incumbent is Moon-tier; the late- $(0,1)$ arm was added to test the timing prediction; and the registered treatment exists only at $k = 5$. At $k = 3$, the boundary theorem makes $(1,0)$ unreachable at every tier, so there is no corresponding treatment state to re-run. The theorem and wall enumeration stand independently

of this experiment. These runs measure behavior inside constructed mixed states; they do not validate either structural result. How can a designer or operator read which state the topology permits?

5 Look Through the Instrument

The repository’s deterministic readout answers that question for a supplied configuration and connectivity summary. For the supplied Moon-initiated example, it prints:

```
state: (0,1)
initiating tier: Moon
R1 acquisition formable: False
R2 commit quorum formable: True
requires preexisting authority: True
runtime authority: unknown
service policy: not-inferred
missing Phase 1 LEO obligation: require 1, reachable 0
```

The two phase capabilities are visibly different. The Moon initiator cannot form Phase 1, but the reachable Earth nodes can form Phase 2. A scalar health summary would obscure that distinction; the two-bit state reports it directly.

The readout also names the failed obligation. It reports the missing LEO witness rather than requiring an operator to infer the problem from timeouts or repeated protocol attempts. This is structural interpretation of known connectivity, not failure detection or empirical evaluation.

Finally, the output refuses to invent what its inputs cannot establish. Commit formability in this state requires preexisting authority, but current authority is unknown and service policy is not inferred. The instrument says what the topology permits; it does not identify a current leader, establish fresh authority, choose a client contract or recovery policy, or ensure that anyone acts on the result.

The wall-specific pass takes named tiers, a Phase 2 threshold, an initiating tier, a reachable-node summary, and the provenance of configuration and connectivity. It returns (R_1, R_2) , quorum witnesses, and typed failed obligations in $O(\text{tiers})$ time. The planetary and edge JSON inputs exercise the same interface. They are demonstrations, not evidence about terrestrial latency, availability, or prevalence. What structure makes this compact readout possible?

6 Putting the Gaps on a Wall

Peleg and Wool [18] arrange nodes in rows of potentially different widths. A crumbling-wall quorum takes one complete row and one representative from every row below it. Two such quorums intersect: if their complete rows differ, the higher quorum carries a representative in the lower quorum’s complete row; if the complete rows match, they share that row.

We split this geometry across the two Paxos phases. Each tier’s Phase 1 family reads downward from that tier, while

Phase 2 stays on the bottom row. Extra downward witnesses express participation policy; the Earth anchor supplies the Paxos intersection. Removing one of those witnesses changes that policy, not the anchor-based safety argument.

6.1 System Model

For each configuration epoch e , let N_e be the fixed logical acceptor universe and let $C_t \subseteq N_e$ be the acceptors effectively reachable at time t . A *decision window* is the interval over which we evaluate phase formability against one such connectivity state; N_e remains fixed within that window even when C_t changes between windows. Our results apply epoch by epoch. Changing N_e is a reconfiguration and state-transfer decision that requires its own protocol; it is outside this paper's scope and is not modeled as ordinary reachability churn. For the evaluated epoch below, we write N for N_e .

Let the acceptor universe be

$$N = E \cup L \cup U \cup M,$$

where the tiers are pairwise disjoint and represent Earth, LEO, Moon, and Mars respectively. In the evaluated topology,

$$|E| = 5, \quad |L| = 1, \quad |U| = 1, \quad |M| = 3, \quad |N| = 10.$$

We call this the 5/1/1/3 topology. Tiers are ordered by latency: Earth is the fastest (bottom of the wall), Mars is the slowest (top). The network is asynchronous with configurable per-link delay and jitter. Acceptors are crash-stop and non-Byzantine. Links may be removed during scheduled blackout windows.

The simulator uses three logical consensus scopes:

- **Earth-local:** Flexible Paxos over the five Earth nodes ($q_1 = 4, q_2 = 2$).
- **Mars-local:** majority quorum over the three Mars nodes ($q = 2$).
- **Global:** the crumbling-wall construction defined below, over all ten nodes.

6.2 Per-Tier Phase 1 Families

The wall maps tiers to rows, ordered bottom (Earth, fast) to top (Mars, slow), as shown in Figure 1. We index tiers from the bottom: $T_0 = E$ (Earth), $T_1 = L$ (LEO), $T_2 = U$ (Moon), $T_3 = M$ (Mars). A proposer at tier i forms its Phase 1 quorum by reading *downward* from row i : it needs at least one respondent from its own tier and every tier below.

Initiating tier	Phase 1 scope	Tiers	Min size
Earth (tier 0)	Earth only	1	1
LEO (tier 1)	LEO + Earth	2	2
Moon (tier 2)	Moon + LEO + Earth	3	3
Mars (tier 3)	all four tiers	4	4




Figure 1: The crumbling-wall construction over the 5/1/1/3 topology. Each tier's Phase 1 quorum reads downward through the wall (dashed arrows). Phase 2 uses only the Earth row (shaded). The wall narrows from bottom to top: wider rows offer more quorum choices.

Let $\mathcal{Q}_1^{(i)}$ denote the Phase 1 family for a proposer at tier i :

$$\mathcal{Q}_1^{(i)} = \{Q \subseteq N \mid \forall j \leq i: Q \cap T_j \neq \emptyset\}.$$

A proposer at tier i needs at least one node from every tier at or below it ($j \leq i$). For example, $\mathcal{Q}_1^{(2)}$ (Moon) requires intersection with T_0 (Earth), T_1 (LEO), and T_2 (Moon), which is every tier from Moon down to Earth. For relaxed Phase 2 (Section 8.5), Phase 1 additionally requires enough Earth nodes to satisfy a pigeonhole intersection constraint.

Only the Earth floor is required for Paxos safety. Each additional downward-path witness represents a deployment policy that requires a tier to participate in acquisition, such as local representation, administrative control, sovereignty, or fencing before authority crosses a boundary. If no such policy applies, the extra witness is not justified by consensus itself; in that setting the wall should be read as an analytical construction rather than a recommended deployment geometry.

6.3 Phase 2 Family

The Phase 2 family places the hot commit path entirely on the fast tier:

$$\mathcal{Q}_2 = \{E\}.$$

That is, Phase 2 requires all five Earth nodes (the strict construction). Section 8.5 relaxes this to k -of- $|E|$.

6.4 Safety: Quorum Intersection

Proposition 2. For every tier i and every $Q_1 \in \mathcal{Q}_1^{(i)}$, $Q_2 \in \mathcal{Q}_2$: $Q_1 \cap Q_2 \neq \emptyset$.

Proof. Every $\mathcal{Q}_1^{(i)}$ requires $Q_1 \cap T_0 \neq \emptyset$ (since $0 \leq i$ for all i , i.e., Earth is at or below every tier). $Q_2 = E = T_0$. Therefore $Q_1 \cap Q_2 \supseteq Q_1 \cap T_0 \neq \emptyset$. $\square$

The intersection follows from the wall’s structure: every path through the wall reaches the bottom row, and Phase 2 is the bottom row.

We verified this mechanically in TLA+. For readers who have not used it: TLA+ is a specification language whose model checker, TLC, enumerates *every* state reachable from the initial conditions of a finite model and checks the stated invariant in each one. A run is *complete* when that enumeration reaches a fixed point and no reachable state remains unexamined. Such a run proves the invariant for that finite model; it is not a statistical sample of behaviors. The QuorumIntersection specification enumerates every (construction $\times$ initiating tier $\times Q_1 \times Q_2$) combination for the strict, $k=4$, and $k=3$ families over the full 10-node topology (27,921 states, complete); ExhaustiveIntersection re-checks the strict and $k=4$ families as parse-time assumptions. No intersection failure was found.

For the full Paxos protocol (not just quorum intersection), we verify safety over a reduced 6-node topology ($3E + 1L + 1U + 1M$) that preserves the quorum-intersection structure. The invariant the reduction preserves is the pigeon-hole inequality, not tier membership alone: in the reduced model both quorum families guarantee at least two of the three Earth nodes ($2 + 2 > 3$), and in the full modeled family Q_1 carries at least two Earth nodes against a 4-of-5 Q_2 ($2 + 4 > 5$). Both instantiate $|Q_1 \cap E| \geq |E| - k + 1$ with the margin $|E| - k = 1$ held fixed. (Tier membership alone suffices only under strict $\mathcal{Q}_2 = \{E\}$, where any Earth node in Q_1 intersects it.) Liveness properties (crash tolerance, progress under partial failure) are topology-size-dependent and are evaluated only at full scale. Over the reduced topology, single-decree Paxos agreement was model-checked completely (67M states, no violation).

Verification scope. The protocol-level specification models a single all-tier Phase 1 family rather than the per-tier families of Section 6: it exercises the protocol machinery under wall-shaped quorums, but safety of the per-tier construction itself rests on Proposition 2 and the standard Flexible Paxos argument, with the intersection premise checked exhaustively above. The proof is primary; the model checking is corroboration. Specifications are in tla/ (see Appendix B).

6.5 What “Global” Means

When an Earth-based proposer completes both phases using only Earth nodes, the decision is *global* in the Paxos sense: any future proposer at any tier, upon completing Phase 1, will discover this value in the Earth acceptors’ state and cannot contradict it. Global consensus does not require that all tiers participated, only that no future quorum can produce a conflicting result.

7 Where the Wall Works, and Where It Stops

At $k = 3$, the $(1, 0)$ gap is absent at every tier. At the same threshold, both gaps are absent for Earth under both connectivity readings, and both gaps are absent for LEO under the self-reachable reading. The commit path remains on Earth. The construction therefore restores the old coincidence at named tiers without returning inter-tier latency to Phase 2. The result has a boundary: $(0, 1)$ remains reachable for Moon and Mars because their Phase 1 families retain downward participation obligations.

7.1 The Exact Boundary

Section 3 defines the two formability predicates for an arbitrary pair of quorum families. The wall instantiates them per tier: write $R_1(i, C)$ when $C \in \text{Form}(\mathcal{Q}_1^{(i)})$ and $R_2(i, C)$ when $C \in \text{Form}(\mathcal{Q}_2)$, so every tier carries its own acquisition predicate against one shared commit predicate. Which gaps are reachable is therefore a per-tier question, and the answer is not uniform across tiers.

Proposition 3 (boundary). For the construction of Section 6 under relaxed $\mathcal{Q}_2 = k\text{-of-}|E|$ (Section 8.5), $(1, 0)$ is unreachable at *every* tier if and only if $|E| - k + 1 \geq k$, that is $k \leq \lceil |E|/2 \rceil$. Sufficiency is unconditional: it does not depend on the number of tiers, their sizes, or the initiating tier. The converse additionally requires non-degeneracy: no empty wall row.

The arithmetic is the same hitting-set bound that carries safety. A Q_1 holds at least $|E| - k + 1$ Earth nodes and a Q_2 holds k ; when $|E| - k + 1 \geq k$, every Q_1 already contains a full Q_2 and Proposition 1 applies.

The gradient. Proposition 3 governs $(1, 0)$ through the Earth floor. The $(0, 1)$ direction follows a different mechanism: the downward chain. A proposer at T_2 (Moon) needs one witness from T_1 (LEO), and this topology has exactly one LEO node. Sever it while all five Earth nodes remain reachable and $\mathcal{Q}_2$ is formable while $\mathcal{Q}_1^{(2)}$ is not. Exhaustive enumeration over all 2^{10} connectivity states, for every tier and every k , gives the following compact table under the self-reachable reading:

	T_0 (E)	T_1 (L)	T_2 (U)	T_3 (M)
$(1, 0)$ reachable	$k \geq 4$	$k \geq 4$	$k \geq 4$	$k \geq 4$
$(0, 1)$ reachable	$k \leq 2$	$k \leq 2$	all k	all k

For $k \leq 3$, $(1, 0)$ is absent at every tier. For $k \geq 3$, $(0, 1)$ is absent for Earth under both readings and for LEO under the self-reachable reading. The LEO result depends on its initiator being able to reach its colocated acceptor. Under the unconstrained reading, LEO retains $(0, 1)$ for every k : its single node can be severed while Earth remains whole.




Figure 2: Phase 1 quorum count by initiating tier under the strict wall. The values are exhaustive structural counts over the fixed 5/1/1/3 configuration; no connectivity distribution, timeout, or stochastic trial is assumed.

We state that sensitivity because it determines whether the coincidence extends to one tier or two.

Moon and Mars retain $(0, 1)$ under both readings for every k . Each has an intervening witness row between itself and the Earth anchor, and changing the Earth threshold cannot remove that obligation. At the other endpoint, $k \geq 4$ violates Proposition 3’s bound and opens $(1, 0)$ everywhere. The useful design point is $k = 3$: it closes $(1, 0)$ everywhere, closes both gaps at Earth under both readings and at self-reachable LEO, and keeps Phase 2 on Earth. No tested threshold closes both gaps at every tier.

The witnesses implement participation policy; legibility makes the resulting obligation readable. In the three-layer response, containment *prevents* selected gaps, the readout *detects* which residual structural state supplied connectivity permits, and authority plus service policy determine how to *act*. That last decision remains outside the interface. Enumeration and auditor artifacts are in results/capability/ (see Appendix B).

8 Wall Evaluation

Design-time gradient. The wall also makes the number of valid Phase 1 quorums readable by tier. If f_i nodes lie above tier i , then

$$N_i = 2^{f_i} \prod_{j \leq i} (2^{|T_j|} - 1).$$

Each required row contributes a nonempty subset; nodes above the initiator are unconstrained. Moving up one tier changes exactly one factor from $2^{|T_{i+1}|}$ to $2^{|T_{i+1}|} - 1$, so $N_{i+1} < N_i$ for every wall. The 5/1/1/3 construction gives 992, 496, 248, 217 from Earth through Mars (Figure 2). These are structural counts, confirmed by exhaustive enumeration; they are not availability estimates. An initiator-independent majority family assigns every tier the same 386 valid quorums and cannot express this gradient.

Table 1: Experimental design.

Experiment	Purpose	Key parameters
Parameter sweep	Confirm structural invariance of Earth-initiated global consensus across Mars delay and blackout duration	Mars delay $\in \{186, 750, 1342\}$ s; blackout $\in \{300, 900, 1800\}$ s; 50 seeds per point
Per-tier sweep	Measure which tiers retain global liveness; compare sparse vs. full-coverage topologies	Initiating tier $\in \{\text{Mars, Moon, LEO, Earth}\}$; both topologies; 186 s Mars delay; 900 and 1800 s blackouts as stated; 50 seeds
Crash tolerance	Characterize the tradeoff between Phase 2 relaxation (k -of- $ E $) and crash tolerance	$k \in \{3, 4, 5\}$; 0–2 Earth crashes; 186 s; 900 s blackout; 50 seeds

8.1 Evaluation Method

Eidolon is a discrete-event simulator built on SimPy. Acceptors process Prepare and Accept messages with configurable processing delay. Proposers fan out messages to all acceptors and collect responses with a per-phase timeout. The network model assigns entities to named locations with per-link latency, jitter, and optional loss. Blackout is modeled as deterministic link removal; the repeater model substitutes a degraded alternate path. Event ordering is by simulation timestamp; the simulator is deterministic given a seed.

Topology.

Five Earth ground stations (NA-West, Europe, Asia, SA-East, Africa) with cross-continental latencies of 30–120 ms. One LEO satellite with 20–45 ms links to ground stations. One Moon node at 1.28 s one-way. Three Mars nodes at configurable one-way delay (186–1342 s, representing closest approach to opposition). Mars-local links are 5 ms.

We evaluate two network variants:

- **Sparse:** LEO has links to 3 of 5 Earth stations (NA-West, Europe, Asia). Mars has links to 2 of 5 (NA-West, Europe). This models a single LEO satellite with limited ground coverage and a Mars relay with two tracking stations.
- **Full coverage:** LEO and Mars have links to all 5 Earth stations. This models a LEO constellation with global coverage and a deep-space network with worldwide antenna placement.

Experiments.

Three experiment families probe the construction. The separate registered experiment in Section 4 measures proposer behavior inside the two mixed states.

Fixed parameters across all experiments are listed in Table 6 (Appendix A). All seeds are 40–89 (50 runs per point). Results are reported as means with 95% confidence intervals.

Table 2: Effect of quorum geometry over the same 5/1/1/3 sparse topology. Earth-initiated proposer, hard blackout, timeouts as in Table 6, 50 seeds per point; rates are identical at all 9 parameter points (3 Mars delays $\times$ 3 blackout durations). Latency is a full two-phase single attempt.

Construction	During	Post	Latency
Flat Phase 1 (all tiers re-quired)	0.0%	varies	varies
Majority Phase 1 (any 6 of 10)	100.0%	100.0%	0.361 s
Crumbling wall (Earth reads Earth only)	100.0%	100.0%	0.183 s

8.2 Geometry and Competitive Majority Baseline

To calibrate the effect of quorum geometry, we compare three constructions over the identical topology, blackout model, and parameter sweep. The *flat* construction uses a single Phase 1 family requiring all four tiers:

$$\mathcal{Q}_1^{\text{flat}} = \{Q \subseteq N \mid \forall j \in \{0, 1, 2, 3\} : Q \cap T_j \neq \emptyset\}.$$

Any blackout that removes a tier makes this quorum unformable. The *majority* baseline is a competitive shape-free Flexible Paxos configuration: $\mathcal{Q}_1^{\text{maj}} = \{Q \mid |Q| \geq 6\}$, any majority of the ten nodes, with no tier structure. The *crumbling wall* construction uses the per-tier Phase 1 families defined in Section 6, with an Earth-based global proposer. All three satisfy cross-intersection with $\mathcal{Q}_2 = \{E\}$: the tiered families require $Q_1 \cap T_0 \neq \emptyset$ directly, and any 6 of 10 nodes must include an Earth node because only five non-Earth nodes exist.

The flat construction yields 0% during-blackout success at every sweep point because it requires all tiers, including disconnected Mars. The crumbling wall yields 100% because the Earth-based proposer’s Phase 1 reads only Earth. Zero variance across 50 seeds confirms that outcomes here are structural consequences of quorum geometry and link state, not scheduler artifacts. We therefore treat this as calibration, not discovery.

The majority baseline separates geometry from quorum slack. It also sustains 100% during-blackout success for the Earth-initiated proposer: the blackout removes three nodes and a 6-of-10 quorum tolerates four. Its two-phase decision latency is 0.361 s instead of 0.183 s. The sixth-fastest respondent lies outside Earth, so majority Phase 1 leaves the fast tier even when nothing has failed. Both constructions use the same all-Earth Phase 2; the difference appears in authority acquisition, recovery, and single-decree decisions. A LEO proposer in the sparse topology reaches only five acceptors during blackout, leaving majority Phase 1 unformable while the wall’s LEO Phase 1 family remains formable. The majority family is insensitive to the initiating tier; Figure 2 shows the distinction.

Table 3: Per-tier global consensus during Mars conjunction blackout (5/1/1/3 full-coverage topology, hard blackout, 186 s Mars delay, 1800 s blackout, 500 s phase timeout, 50 seeds). Rates are identical across seeds; latency and recovery are means, with 95% CIs reported in the text.

Tier	Position	During	Latency	Rec. lag
Earth	bottom (0)	100.0%	0.183 s	9.4 s
LEO	tier 1	100.0%	0.131 s	8.1 s
Moon	tier 2	100.0%	5.131 s	3.0 s
Mars	top (3)	0.0%	753.2 s	1351.4 s

8.3 Per-Tier Liveness under Full Coverage

Table 3 reports the central result under one observed condition. Each tier runs its own global proposer with full network coverage, 186 s one-way Mars latency, an 1800 s blackout, the hard-blackout model, and 50 seeds.

Earth, LEO, and Moon completed every during-blackout attempt in all 50 seeds. Mars completed none. The liveness failure crumbles from the disconnected top tier. The 95% CIs are below ± 0.001 s for inner-tier latency and ± 0.02 s for inner-tier recovery; the Mars intervals are ± 0.82 s and ± 1.64 s, respectively.

The latency column maps directly to physics. Moon’s 5.131 s is two Paxos phases at the 1.28 s one-way Moon–Earth light delay ($\approx 4 \times 1.28$ s). Earth’s 183 ms reflects cross-continental round-trips within the Earth tier. LEO’s 131 ms is *faster* than Earth, which is a counterintuitive result explained by the network topology: LEO-to-ground links (20–45 ms) are shorter than cross-continental Earth links (50–120 ms). Wall position determines quorum *obligations*; the speed of light determines their *cost*. These are correlated but not identical, and LEO is the proof.

Mars fails during blackout for the structural reason predicted by the wall: it cannot reach the inner-tier witnesses required for Phase 1. The 1800 s window contains complete failed attempts, so the measured during-blackout rate is 0% in all 50 seeds. Outside blackout, every post-blackout attempt completes, at a mean latency of 753.2 s. That is approximately two Paxos phases at the 186 s one-way Mars–Earth delay. Success requires a per-phase timeout budget sized to the initiating tier’s physics: the worst-case request–response path from Mars is $2 \times 186 \approx 372$ s, within the 500 s per-phase budget of Table 6. Mars-initiated global consensus is possible outside blackout, but it pays the interplanetary path on both phases.

Recovery lag is 3.0 s for Moon, 8.1 s for LEO, 9.4 s for Earth, and 1351.4 s for Mars under this condition. These point values are cadence-alignment artifacts, not protocol guarantees. Recovery lag measures the gap from blackout end to the next successful cadence-aligned attempt, so it is bounded by one 120 s reconciliation interval plus the tier’s round time. Where the value falls within that bound depends

Table 4: Per-tier global consensus under the 5/1/1/3 sparse topology (hard blackout, 186 s Mars delay, 900 s blackout, 500 s phase timeout, 50 seeds). All rates are identical across seeds; structural outcomes are reported without CLs.

Initiating tier	Wall prediction	Sparse result
Earth	works	100.0%
LEO	works	0.0%
Moon	works	100.0%
Mars	blocked	0.0%

on where blackout end lands in the attempt cadence.¹

8.4 Wall Obligations versus Sparse Reachability

Table 4 repeats the per-tier experiment under the sparse network topology.

LEO drops from 100% (full coverage) to 0% (sparse). The wall says LEO needs LEO + Earth; that obligation is satisfiable. But strict Phase 2 requires all five Earth nodes, and LEO has links to only three ground stations. The wall determines what a tier *needs*; the network determines what it *can reach*. Liveness requires both.

The readout therefore needs both supplied inputs. Configuration determines the obligations; connectivity determines whether the initiator can satisfy them. Full wall structure is insufficient when sparse reachability removes a required path.

Moon succeeds in both topologies because it has links to all five Earth ground stations. The sparse topology models a single LEO satellite with limited ground coverage; the three missing ground-station links are the difference between 0% and 100% for LEO-initiated consensus.

8.5 Crash Tolerance and Coordinated Relaxation

The strict Phase 2 choice $\mathcal{Q}_2 = \{E\}$ introduces a fragility: a single crashed Earth acceptor blocks all global Phase 2 progress. This section relaxes that choice.

Relaxed construction. Let the relaxed Phase 2 family require k of $|E|$ Earth nodes. We evaluate $k = 4$ (tolerates one crash) and $k = 3$ (tolerates two). Phase 1 requires correspondingly more Earth nodes to maintain intersection: a k -of- $|E|$ Phase 2 quorum omits at most $|E| - k$ Earth nodes, so any set of $|E| - k + 1$ Earth nodes intersects every Phase 2 quorum (pigeonhole). Phase 1 must therefore contain at least $|E| - k + 1$ Earth nodes. For $k = 4$ out of 5 Earth nodes, this

¹Each tier’s per-round time shifts its cadence phase relative to blackout end, which is why the values differ across tiers and move when the experiment window shifts. The effect is deterministic and independent of the consensus protocol; the bound, not the value, is the protocol property.

means at least 2 Earth nodes in every Q_1 ; for $k = 3$, at least 3. Both relaxed constructions are verified exhaustively in TLA+ alongside the strict one (Section 6).

The relaxed Phase 1 family for tier i is:

$$\mathcal{Q}_{1,k}^{(i)} = \{Q \subseteq N \mid \forall j \leq i: Q \cap T_j \neq \emptyset, |Q \cap E| \geq |E| - k + 1\}.$$

Table 5 reports the crash-tolerance sweep (Earth-initiated, repeater-assisted, 186 s Mars delay, 900 s blackout, 50 seeds).

With strict Phase 2, one Earth crash prevents every subsequent global commit (row 2). At $k = 3$ with two crashes, the global construction maintains 100% during-blackout success, while the standard Earth-local family cannot form its four-node Phase 1 quorum. Its 60.5% aggregate rate counts attempts completed before the crashes landed (rows 5–6). The weakest link migrates. For this Earth initiator, both relaxed global phases need the three surviving Earth nodes; the local family still requires four. Relaxing that local family to majority, $q_1 = q_2 = 3$, restores 100% local success while global success remains 100% (row 6). The tradeoff curve shows the corresponding Phase 1 minima for Earth and Mars initiators:

Regime	P1 min E/M	P2 Tol.	E-local $\mathcal{Q}_2$
Strict ($k = 5$)	1 / 4	5-of-5	0 2-node E
Relaxed ($k = 4$)	2 / 5	4-of-5	1 2-node E
Relaxed ($k = 3$) + maj	3 / 6	3-of-5	2 3-node E

An Earth-initiated Q_1 needs only the $|E| - k + 1$ Earth nodes; a Mars-initiated Q_1 adds one witness from each of the three upper tiers. Relaxation buys crash tolerance by growing the cold path, never the hot one: Phase 2 shrinks as Phase 1’s Earth requirement grows.

The construction separates an inter-tier witness from intra-tier replication. Any one of the three Mars nodes satisfies the wall’s Mars-row obligation; a Mars-local majority would require two. Earth is different because the Phase 2 anchor must act as one logical entity, whether by a local replicated state machine or another internal protocol. The reduced TLA+ model preserves this separation: shrinking Earth from five nodes to three and rescaling its threshold keeps the same intersection margin. Redundancy within a non-anchor tier therefore need not add another consensus step to the wall.

9 Related Work

Paxos established the standard safety argument for replicated state machines under asynchronous messaging and crash failures [12]. Flexible Paxos showed that safety requires only Phase 1/Phase 2 cross-intersection, not universal majority [10]. Our characterization builds on that result but does not claim containment itself as a new mathematical

Table 5: Coordinated relaxation under Earth crashes (5/1/1/3; Earth initiator; repeater-assisted hard blackout; Mars-delay/blackout/timeout 186/900/500 s; 50 seeds; mean $\pm$ 95% CI). Earth-local Flexible Paxos: “std” is $q_1=4, q_2=2$; “maj” is $q_1=q_2=3$. Recovery is quantized by the 120 s reconciliation cadence.

Global $\mathcal{Q}_2$	Local	Crashes	Earth-local	Global during	Global post	Recovery (s)
strict	std	0	100.0%	100.0%	100.0%	93.11 $\pm$ 0.01
strict	std	1	100.0%	0.0%	0.0%	n/a
4-of-5	std	0	100.0%	100.0%	100.0%	94.27 $\pm$ 0.01
4-of-5	std	1	100.0%	100.0%	100.0%	94.26 $\pm$ 0.01
3-of-5	std	2	60.5%	100.0%	100.0%	94.64 $\pm$ 0.01
3-of-5	maj	2	100.0%	100.0%	100.0%	94.63 $\pm$ 0.01

tool. The contribution is the exact correspondence between phase-formability ordering and its complete gap profile, the operational interpretation of those gaps, and their application to phase-asymmetric Paxos.

The (1,0) state is also present in Flexible Paxos: its $|Q_1|=1, |Q_2|=N$ construction permits acquisition before commit is formable, and its row-failure discussion uses Phase 1 to recover past decisions before reconfiguration. That work identifies the state and a constructive use for it. We ask the design-time question of whether a given construction admits the state at all, examine the dual state, and supply a readout for known connectivity. The readout matters because a recovery prescription must first know which predicate holds.

Containment has important prior uses. Refined Quorum Systems [8] nests quorum classes $QC_1 \subseteq QC_2 \subseteq RQS$ to connect resilience with optimistic complexity, subject to adversary-aware intersection properties. That class inclusion is a design and correctness condition, not an ordering of two phase-formability predicates over connectivity states. Li, Chan, and Lesani’s quorum subsumption [13] is a member-indexed containment condition: for every process p in a quorum q , some quorum in p ’s personal family is contained in q . It supports progress in a heterogeneous Byzantine trust model. We instead compare two phase predicates over one fixed crash-stop acceptor universe. The quantifiers and the questions differ even though both results use containment.

Grid and crumbling-wall quorum constructions [3, 18] demonstrate that quorum geometry can be engineered around combinatorial structure. Howard et al. note explicitly that Flexible Paxos can use such constructions; we take up that suggestion. Peleg and Wool analyzed crumbling-wall availability under random, independent node failures. Our wall case study maps rows to physical latency tiers and examines per-tier liveness under scheduled, topology-correlated disconnection. Li, Chan, and Lesani’s Satrapy system [14] carries heterogeneous quorum theory into practical consensus. Hierarchical quorum structures have a longer history in database replication [5] and coordination services; our wall differs in that the hierarchy reflects physical latency tiers rather than organizational or logical grouping.

Geo-distributed consensus provides the closest practical

analog. WPaxos [1] uses Flexible Paxos with grid quorum layouts and per-object multi-leader coordination to keep commits local; it is the nearest point of comparison. WPaxos’s grid quorums are symmetric: Q_1 spans $Z - f_z$ zones and Q_2 spans $f_z + 1$ zones, with the same structure regardless of which node initiates. Our per-tier $\mathcal{Q}_1^{(i)}$ families are asymmetric as the initiating tier determines the quorum scope, which produces a leadership cost gradient that symmetric grids structurally cannot express (Section 8). EPaxos [17] removes the leader bottleneck for non-conflicting commands. Mencius [15] distributes leader responsibility across WAN sites. MDCC [11] achieves single-round cross-datacenter commits. All four optimize for tens-to-hundreds of milliseconds WAN latency and assume all replicas are usually reachable. Our setting differs in two respects: the asymmetry spans three orders of magnitude (sub-second to 1342 s), and the target phenomenon is scheduled total disconnection rather than heterogeneous latency.

Delay-tolerant networking [2, 7] motivates the operating regime but addresses routing and custody transfer, not consensus. CRDTs have been studied in DTN-like settings [9]. SwarmDAG [20] uses extended virtual synchrony for partition-tolerant robot swarms; Tran et al. [19] measure consensus latency under partitioning. Protocol Labs’ IPC [6] uses hierarchical subnets for blockchain scaling. NASA’s DSN study [4] evaluates database replication for ground stations. Our work occupies a gap: Paxos safety under topology-shaped quorum geometry and scheduled disconnection, with per-tier liveness characterization.

10 What Remains Unsolved

The wall gives designers a usable partial answer. At $k = 3$, it removes (1,0) at every tier, removes both gaps for Earth under both readings and for self-reachable LEO, and keeps Phase 2 on Earth. Moon and Mars still admit (0,1) because their acquisition families retain downward participation obligations. The remaining question is precise: can a structured quorum design extend acquisition/commit coincidence farther up the topology without returning inter-tier latency to the Phase 2 hot path?

Three candidates follow from the boundary, and none is

a result of this paper: scoped authority could let an upper tier continue over an explicitly bounded slot or time range; gap-aware proposer behavior could use the two-bit readout to choose retry and failover behavior suited to the observed state; and multi-anchor families could reduce dependence on one anchor tier. Each changes a different part of the system and requires separate work on safety, performance, and operational behavior. The terrestrial edge mapping supplies a concrete next experiment, not evidence that any candidate works.

11 Threats to Validity and Limitations

All results are design-level. The simulator evaluates one 5/1/1/3 crash-stop topology. Blackout is deterministic link removal; orbital motion, antenna schedules, contention, coding, variable link quality, Byzantine behavior, reconfiguration, and storage failure are absent. The fixed 120 s reconciliation cadence affects recovery point estimates, as stated beside those results. The crash sweep uses an Earth initiator and does not measure how wall position changes crash tolerance.

The behavioral experiment uses single-decree Paxos, one severed link, and one backoff policy. Multi-Paxos can defer exposure to a missing Phase 1 capability while existing authority remains valid. The experiment therefore measures one severe and deliberately bounded setting. Its results do not assign intrinsic valence to either mixed state.

The readout assumes supplied connectivity and returns structural formability, not runtime state: it detects no failure, establishes no fresh runtime authority, and supplies neither a chosen client contract nor recovery policy. The service policy and operator action remain outside the interface. The wall’s linear readout also depends on one anchor tier; multi-anchor families may change both resilience and legibility.

We make no deployment prevalence claim and have no terrestrial evaluation. The edge input is a structural demonstration. A “tier” also bundles latency, failure domain, and administrative domain in the planetary case; those properties may separate elsewhere. Generalizing the structure is a mathematical possibility. Generalizing the measurements requires new experiments.

12 Conclusion

A single reachable-node count once worked because phase symmetry made the two quorum families equal and a threshold family made their shared predicate count-readable. Flexible Paxos preserves cross-phase safety after the predicates separate. Containment then gives the exact consequence:

ordered predicates admit one gap direction; incomparable predicates admit both.

The wall turns that characterization into a design tool. At $k = 3$, $(1, 0)$ is absent at every tier. Both gaps are absent for Earth under both connectivity readings and for LEO under the self-reachable reading. Moon and Mars retain $(0, 1)$ because of their downward participation obligations. No tested threshold closes both gaps everywhere, but the readout makes each remaining obligation explicit without moving Phase 2 off Earth.

The portable diagnostic is two questions: Can this system acquire authority? Can it commit? A phase-asymmetric quorum system should expose acquisition capability and commit capability separately. It should report current authority separately from both. Node health and one replica count may answer neither. Once the answers are visible, designers can combine structural capability with current authority and an explicit service contract. The open problem is how far those answers can be made to coincide without returning inter-tier latency to Phase 2.

References

- [1] Ailidani Ailijiang, Aleksey Charapko, Murat Demirbas, and Tefik Kosar. Wpaxos: Wide area network flexible consensus. *IEEE Transactions on Parallel and Distributed Systems*, 31(1):211–223, 2019.
- [2] Vinton Cerf, Scott Burleigh, Adrian Hooke, Leigh Torgerson, Robert Durst, Keith Scott, Kevin Fall, and Howard Weiss. Delay-tolerant networking architecture. Technical Report RFC 4838, RFC Editor, 2007.
- [3] S. Y. Cheung, M. H. Ammar, and M. Ahamad. The grid protocol: A high performance scheme for maintaining replicated data. *IEEE Transactions on Knowledge and Data Engineering*, 4(6):582–592, 1992.
- [4] Andrea M. Connell. An analysis of database replication technologies with regard to deep space network application requirements. Technical report, Jet Propulsion Laboratory, California Institute of Technology, 2011.
- [5] Khuzaima Daudjee and Kenneth Salem. Lazy database replication with ordering guarantees. *Proceedings of the 20th International Conference on Data Engineering (ICDE)*, pages 424–435, 2004.
- [6] Alfonso de la Rocha, Lefteris Kokoris-Kogias, Jorge M. Soares, and Marko Vukolić. Hierarchical consensus: A horizontal scaling framework for blockchains. In *IEEE 42nd International Conference on Distributed Computing Systems Workshops (ICDCSW)*, 2022.

- [7] Kevin Fall. A delay-tolerant network architecture for challenged internets. In *Proceedings of the 2003 Conference on Applications, Technologies, Architectures, and Protocols for Computer Communications (SIGCOMM)*, 2003.
- [8] Rachid Guerraoui and Marko Vukolić. Refined quorum systems. *Distributed Computing*, 23(1):1–42, 2010.
- [9] Frédéric Guidec, Yves Mahéo, and Camille Noûs. Supporting conflict-free replicated data types in opportunistic networks. *Peer-to-Peer Networking and Applications*, 16:395–419, 2023.
- [10] Heidi Howard, Dahlia Malkhi, and Alexander Spiegelman. Flexible paxos: Quorum intersection revisited. In *20th International Conference on Principles of Distributed Systems (OPODIS 2016)*, 2017.
- [11] Tim Kraska, Gene Pang, Michael J. Franklin, Samuel Madden, and Alan Fekete. MDCC: Multi-data center consistency. In *Proceedings of the 8th ACM European Conference on Computer Systems (EuroSys)*, pages 113–126, 2013.
- [12] Leslie Lamport. The part-time parliament. *ACM Transactions on Computer Systems*, 16(2):133–169, 1998.
- [13] Xiao Li, Eric M. Chan, and Mohsen Lesani. Quorum subsumption for heterogeneous quorum systems. In *37th International Symposium on Distributed Computing (DISC 2023)*, volume 281 of *LIPIcs*, pages 28:1–28:19, 2023.
- [14] Xiao Li, Eric M. Chan, and Mohsen Lesani. Satrapy: From abstract to practical consensus for heterogeneous quorum systems. *Distributed Computing*, 39(2):16, 2026.
- [15] Yanhua Mao, Flavio P. Junqueira, and Keith Marzullo. Mencius: Building efficient replicated state machines for WANs. In *Proceedings of the 8th USENIX Symposium on Operating Systems Design and Implementation (OSDI)*, pages 369–384, 2008.
- [16] Meta Engineering. Augmenting flexible paxos in LogDevice to improve read availability. Engineering at Meta, March 2022. Accessed 2026-08-02.
- [17] Iulian Moraru, David G. Andersen, and Michael Kaminsky. There is more consensus in egalitarian parliaments. In *Proceedings of the 24th ACM Symposium on Operating Systems Principles (SOSP)*, pages 358–372, 2013.
- [18] David Peleg and Avishai Wool. Crumbling walls: A class of practical and efficient quorum systems. In *Proceedings of the 14th ACM Symposium on Principles of Distributed Computing (PODC)*, pages 120–129, 1995.
- [19] Jason A. Tran, Gowri S. Ramachandran, Claudiu B. Danilov, and Bhaskar Krishnamachari. An evaluation of consensus latency in partitioning networks. In *MILCOM 2019 – IEEE Military Communications Conference*, 2019.
- [20] Jason A. Tran, Gowri S. Ramachandran, Parth M. Shah, Claudiu B. Danilov, Roberto A. Santiago, and Bhaskar Krishnamachari. SwarmDAG: A partition tolerant distributed ledger protocol for swarm robotics. *Ledger*, 4(S1):25–31, 2019.
- [21] Jason Warner. October 21 post-incident analysis. GitHub Blog, October 2018. Accessed 2026-08-02.

A Simulator Parameters

Table 6: Simulator parameters.

Parameter	Value	Notes
Earth cross-cont. delay	30–120 ms	per link pair
LEO–ground delay	20–45 ms	per ground station
Moon one-way delay	1.28 s	fixed
Mars one-way delay	186–1342 s	swept
Mars-local delay	5 ms	fixed
Processing delay	1 ms	per acceptor
Jitter	$\pm 10\%$	of link delay, uniform
Per-phase timeout	500 s / 1 s	global / tier-local; global budget raised to $1.25\times$ the worst-case request– response path when that exceeds the base (above ≈ 200 s Mars delay)
Max Paxos rounds	1	per attempt
Blackout start	600 s base	pre-window scaled to fit one full global round plus margin (930 s at 186 s Mars delay)
Simulation end	4000 s base	horizon extends when pre/post win- dows scale
Reconciliation interval	120 s	between global at- tempts
Loss model	none	deterministic link re- moval for blackout

B Claim-to-Artifact Traceability

Table 7 maps the paper’s main claims to executable artifacts. Paths are relative to the repository root of the (anonymized)

artifact accompanying this submission. Results were generated with Python ≥ 3.14 and SimPy $\geq 4.1.1$.

Table 7: *Claim-to-artifact traceability.*

Claim	Evidence	Artifact(s)
Flat construction: 0% during blackout at every hard-blackout sweep point.	Flat-mode sweep under the validated harness (-global-quorum flat).	results/step9_flat/step9_sweep.csv;
Majority baseline: 100% during blackout, 361 ms two-phase decision latency at every hard-blackout sweep point.	Majority-mode sweep under the validated harness (-global-quorum majority).	experiments/step9_sweep.py. results/step9_maj/step9_sweep.csv;
Crumbling wall: 100% during blackout at every hard-blackout sweep point, 183 ms two-phase decision latency.	All rows show 100% during-blackout.	experiments/step9_sweep.py. results/step9/step9_sweep.csv;
Per-tier liveness: Earth, LEO, and Moon succeed; Mars fails under the common 1800 s condition.	Full coverage, hard blackout, 186 s Mars delay, 1800 s blackout, 50 seeds.	experiments/ results/tier_liveness/ tier_sweep_full_ci.csv; tier_liveness_sweep.py.
Sparse topology: LEO drops from 100% to 0%.	Sparse 5/1/1/3; all tier initiators; hard blackout; 186/900/500 s Mars-delay/blackout/timeout; 50 seeds.	Same as above.
Weakest-link migration and coordinated relaxation.	Sparse 5/1/1/3; Earth initiator; repeater; hard blackout; 186/900/500 s Mars-delay/blackout/timeout; 50 seeds.	results/step10/step10_sweep_ci.csv; experiments/step10_sweep.py.
TLA+ verification of quorum intersection.	Exhaustive enumeration, all four tiers $\times$ {strict, $k=4$, $k=3$ } (27,921 states, complete).	tla/QuorumIntersection.tla; tla/ ExhaustiveIntersection.tla.
Paxos agreement model-checked.	67M states (reduced topology, all-tier Phase 1 family, complete).	tla/PaxosSmall.tla.

Table 8: *Claim-to-artifact traceability (continued).*

Claim	Evidence	Artifact(s)
Per-tier capability map: which (Phase 1, Phase 2) capability states each tier holds under each connectivity regime.	Exhaustive per-scenario classification, including the degraded partial-capability states.	results/capability/capability_map.csv; experiments/capability_map.py.
Containment characterization (Proposition 1) and the $k \leq \lceil E /2 \rceil$ boundary (Proposition 3).	Exhaustive enumeration, $5k \times 4$ tiers; containment evaluated as set containment over minimal Q_2 , not as the reachability restatement; 0 disagreements. Predicate monotonicity verified, not assumed.	results/capability/dual_containment.csv; experiments/capability_dual_sweep.py.
Exact four-way gap correspondence and construction-independent audit.	Proposition 1 and Corollary 1 are primary. Independent state enumeration rejects a mutated report; all 129,032 three-node family-pair/pinned-domain cases pass; 16 registered wall cases reconcile with 0 CSV disagreements.	quorum_audit.py; experiments/quorum_audit.py; results/capability/quorum_audit_registered.json.
Wall-specific capability readout.	Deterministic operational demonstration over one planetary and one structurally analogous edge input; not evaluation. Runtime authority remains unknown and service policy is not inferred.	experiments/capability_readout.py; examples/capability/planetary_moon_01.json; examples/capability/edge_remote_01.json.
Uniform threshold corollary: $(1,0)$ reachable iff $q_1 < q_2$; $(0,1)$ iff $q_2 < q_1$. Behavior inside the two capability gaps: $(1,0)$ matched a healthy contender on recorded metrics and supplied the decided value; $(0,1)$ prevented decision in 50 of 50 seeds when both proposers had an eight-round budget.	80 threshold configurations ($n = 3..7$, all valid q_1/q_2), 0 violations. Pre-registered single-decree experiment, 5 arms $\times$ 4 incumbent budgets $\times$ 50 seeds; the healthy proposer always had 8 rounds. Predictions, falsification criteria, and the declared consequence of a null were committed before the experiment code existed; two registered predictions were falsified and kept. Output was byte-identical across two runs.	results/capability/dual_uniform.csv; experiments/capability_dual_sweep.py. results/flip/flip_map.csv; results/flip/flip_sweep.csv; flip.py; experiments/flip_sweep.py; experiments/flip_verdict.py.
Price of coincidence: 0 at odd n , 1 at even n ; cost-minimal configurations cannot be phase-symmetric at even n .	Re-analysis of the threshold enumeration; post-hoc, not pre-registered, and labelled as such.	results/capability/dual_uniform.csv; experiments/capability_dual_sweep.py.
Tier-gradient: at $k = 3$, $(1,0)$ is absent at every tier; both gaps are absent for Earth under both readings and for self-reachable LEO. Moon and Mars retain $(0,1)$ at every k ; no k closes both gaps everywhere.	Exhaustive enumeration over all 2^{10} connectivity states, every tier and k , under both colocated-acceptor readings. Output byte-identical across two runs.	results/capability/dual_gradient_map.csv; experiments/capability_dual_sweep.py.
Performance-preserving closure beyond the named wall cases remains open.	Scoped authority, gap-aware behavior, and multi-anchor families are unevaluated candidates, not results.	No artifact; future work.