



Numeric Data

CS 18000

Sunil Prabhakar

Department of Computer Science

Purdue University

[Problem]

Write a program that reads in the radius of a circle and outputs the area and circumference of the circle.

- Requires that we perform operations on numbers
- Strings or other standard classes are not appropriate for this purpose.
- Instead, we will use a special type of data

[Why not Strings?]

- We could use strings, but
 - Strings are just encodings of characters
 - with 2 bytes of storage
 - a numeric string can only represent 0,1,..., or 9
 - but, there are potentially $2^{16} = 65,536$ combinations (numbers)
 - the String class has no methods for numeric operations
 - better to use a different *type* of representation
 - the same 2 bytes of data can be used to represent two different types of data.

[Primitive Data Types]

- As all matter is fundamentally composed of atoms, all Java objects are fundamentally composed of primitive data types.
- Primitive types are the building blocks of all data used in Java.
- Primitive data types are neither classes nor objects.
 - they are the simplest representations of data
- Each type can be processed using operators specific to that type

Primitive Data Types

- Numeric

- e.g., 2, 3, 3.1416, -334234.2343242
- for storing and operating on integer and real valued data

■ Character

- [illegible]

■ Boolean

- logic data type
- only two allowed values: **true**, **false**

■ This week we will study Numeric data.

[The Type **double**]

- The most general numeric data type is called **double**
- This is not a class, but a primitive data type
- The name refers to double precision numbers
- This type can store positive and negative integer and real valued numbers
- Important: note that the name begins with a lower case d

Area and Perimeter

```
import java.util.Scanner;

public class CircleCalculator {

    public static void main (String[] args){
        double radius, area, circumference; //declare variables

        Scanner scanner = new Scanner(System.in); //setup scanner

        System.out.println("Enter Radius"); //prompt for radius
        radius = scanner.nextDouble(); //read in radius
        //Calculate area and circumference
        circumference = 2.0 * 3.14 * radius;
        area = 3.14 * radius * radius;

        System.out.println("Given Radius: " + radius + "\n" +
                           "Area: " + area + "\n" +
                           "Circumference: " + circumference);
    }
}
```

Not a class

[Important Points]

- Note the use of =
 - do not confuse this with the = symbol from mathematics
 - `circumference = 2 * 3.14 * radius;`
 - computes the product of 2, 3.14, and the numeric value stored in `radius`,
 - and copies this value into `circumference`
 - This is an **assignment** statement. Causes the value stored in `circumference` to change.

[Variables]

- Data items such as `area` are called *variables*.
 - since we can change their values during program execution.
- A variable has three properties:
 - A memory location to store the value,
 - The type of data stored in the memory location, and
 - The name used to refer to the memory location.
- When the declaration **`double`** `area;` is made,
 - memory space is allocated to store a **real - number** value
 - `area` is a reference for this space.

Assignment Statements

- We set the value of a variable using an *assignment statement*.
 - Do not confuse with equality in Algebra!

```
double a, b, c;
```

```
a = 3.0;  
b = 2.0 * 2.3;  
c = a * b;
```

- Compute the value of the right (of =) and copy the result into the variable on the left.

```
a = 2 * a;
```

- Use the current value of a to compute result and copy the result back into a.
- Can also initialize when declaring

```
double a = 5.9, b = 34;
```

[Arithmetic Operators]

```
double x, y, z;  
x = 5.0;  
y = 2.5;
```

Multiplication

`z = x * y;` → `z = 12.5`

Addition

`z = x + y;` → `z = 7.5`

Subtraction

`z = x - y;` → `z = 2.5`

Division

`z = x / y;` → `z = 2.0`

Unary negation

`z = -y;` → `z = -2.5`

Examples of expressions

```
double tempC, tempF;
```

```
tempF = tempC * 9.0/5.0 + 32.0;
```

```
double x, y, z;
```

```
z = x * x + y * y / x;
```

```
z = x*x+y*y/x;
```

```
z = x *      x      + y  
    *      y      /  
x;
```

Whitespaces make no difference.

All these expressions are identical to the compiler.


[Arithmetic Expressions]

- How is the following expression evaluated?

```
double x, y, z;  
...  
z = x + 3 * y;
```

- Answer: x is added to $3*y$.
- We determine the order of evaluation by following *precedence rules*.
- Evaluation is in order of precedence.
 - Recall PEMDAS
- Operators at same level are evaluated *left to right* for most operators

1



[Precedence Examples]

$$x \overset{4}{+} \underbrace{4 * y}_1 \overset{5}{-} \underbrace{x / z}_2 \overset{6}{+} \underbrace{2 / x}_3$$

same as: $x + (4 * y) - (x / z) + (2 / x)$

$$(x \overset{6}{+} y \overset{*}{\underbrace{\quad}_3} (\underbrace{4 - x}_1) \overset{4}{/} z \overset{7}{+} 2 \overset{5}{/} \underbrace{-x}_2)$$

same as:

$$(x + ((y * (4 - x)) / z) + (2 / (-x)))$$

To be sure, use parentheses!


[Problem]

- *Write a program that reads in the lengths of two sides of a triangle, and the angle between these sides, then computes and outputs the length of the third side.*

- Recall:

$$c^2 = a^2 + b^2 - 2ab \cos C$$

$$c = \sqrt{a^2 + b^2 - 2ab \cos C}$$



[Solution]

- We know how to get the three inputs.
- But, how do we compute square roots and cosines?
 - Many common functions are available as methods of the Math class defined in the java.lang package.
 - Trigonometric methods require angles to be expressed in Radians (not degrees).
- Most methods take **double** arguments and their return type is **double**

Sample Math Class Methods

Method name	Description	Input type	Output type
<code>pow(x, y)</code>	Return x^y	double	double
<code>log(x)</code>	Return natural log of x.	double	double
<code>sqrt(x)</code>	Return the square root of x	double	double
<code>sin(a)</code>	Return sine of angle a (radians)	double	double
<code>asin(a)</code>	Return the arc sine of a (in radians)	double	double
<code>toRadians(d)</code>	Convert d from degrees to radians.	double	double
<code>exp(x)</code>	Return e^x	double	double
<code>max(x, y)</code>	Return larger of x or y.	*	*

See API for details

[Step 1: Input and Test]

```
import java.util.Scanner;
public class ThirdSideStep1 {

    public static void main (String[] args){
        double a, b, c; // the three sides of the triangle
        double angleCDegrees; //the angle C in degrees

        Scanner scanner = new Scanner(System.in); //setup scanner

        System.out.println("Enter the length of one side:");
        a = scanner.nextDouble();

        System.out.println("Enter the length of the other side:");
        b = scanner.nextDouble();

        System.out.println("Enter the angle between these two sides (in
degrees)");
        angleCDegrees = scanner.nextDouble();

        System.out.println("a: " + a + ", b: " + b + ", angle: " + angleCDegrees);
    }
}
```

[Step 2: Convert to Radians]

```
angleCRadians = Math.toRadians(angleCDegrees);  
  
//Step 2: output the converted angle and check.  
System.out.println("The angle " + angleCDegrees +  
                    " degrees equals: " + angleCRadians  
                    + " radians");
```

- The Math class expects arguments in Radians, not degrees
- Use the toRadians method of the Math class to convert, and check.

[Step 3: Compute Side and Output]

```
    .  
    .  
    .  
c = Math.sqrt(Math.pow(a,2) + Math.pow(b,2) - 2 * a * b *  
Math.cos(angleCRadians));  
  
//Step 3: output the length of the third side  
System.out.println("The length of the third side is: " + c);
```

- Recall: $c = \sqrt{a^2 + b^2 - 2ab \cos C}$
- Note how the method calls are used within the expression to compute parts of the expression.

[Numeric Data Types]

- The type **double** that we saw allows us to store a very wide range of real number values:
 - -1.7977×10^{308} to $+1.797 \times 10^{308}$
 - 8 bytes are used to store each double variable
 - How? (we will discuss on Friday)
- Sometimes, we don't need such a large range.
 - can use the type **float** instead
 - only 4 bytes, but smaller range
 - $-3.40282347 \times 10^{38}$ to $+ 3.40282347 \times 10^{38}$

[Primitive vs. Class assignment]

- For assignment, the behavior of primitive variables seems to be different from that of class (reference) variables.

```
String str1, str2;  
str1 = new String ("Hello");  
str2 = new String ("World");  
str2 = str1;
```

```
double x, y;  
x = 5.0;  
y = 10.0;  
y = x;
```

[Primitive Data: Declaration & Assignment]

```
double i, j;  
i = 5.0;  
j = 8.0;
```

i

5.0

j

8.0

Memory is
allocated.

Values are stored in those
locations.

[Primitive Data Assignment]

```
double i;  
i = 5.0;  
i = 85.0;
```

i

85.00

Memory is
allocated.


The value 5.0 is stored in i.

The value 85.0 is stored in i.
Old value is lost.

Object Assignment

```
Customer  customer;  
customer  = new Customer( );  
customer  = new Customer( );
```

customer




The identifier **customer** is allocated.

The **reference** to the first object is stored in **customer**.

The **reference** to the second object is stored in **customer**. The old reference is lost.

Assigning objects

```
Customer  cust1, cust2;  
cust1     = new Customer( );  
cust2     = cust1;
```



The identifiers
are allocated.

The **reference** to the object
is stored in **cust1**.

The **reference** stored in
cust1. is copied to **cust2**.

[Assigning Primitive Data]

```
double i, j;  
i = 5.0;  
j = i;
```




Memory is allocated.

The **value** stored in `i` is copied to `j`.

Really the same

```
Customer  cust1, cust2;  
cust1     = new Customer( );  
cust2     = cust1;
```



The **value** happens to be a reference to an object.



Hence **reference** type vs. **primitive** type.

The **value** stored in **cust1** is copied to **cust2**.



[Object Vs. Primitive Assignment]

→ String str1, str2;
str1 = new String ("Hello");
str2 = new String ("World");
str2 = str1;

str1



str2



```
double x, y;  
x = 5.0;  
y = 10.0;  
x = y;
```

x




y



[Object Vs. Primitive Assignment]

```
String str1, str2;  
str1 = new String ("Hello");  
str2 = new String ("World");  
str2 = str1;
```




```
double x, y;  
x = 5.0;  
y = 10.0;  
x = y;
```




[Object Vs. Primitive Assignment]

```
String str1, str2;  
str1 = new String ("Hello");  
str2 = new String ("World");  
str2 = str1;
```



```
double x, y;  
x = 5.0;  
y = 10.0;  
x = y;
```



Area and Perimeter w/ float

```
import java.util.Scanner;
```

```
public class CircleCalculator {
```

```
    public static void main (String[] args){
```

```
        float radius, area, circumference; ← Note type
```

```
        Scanner scanner = new Scanner(System.in);
```

```
        System.out.println("Enter Radius");
```

```
        radius = scanner.nextFloat(); ← Note method name
```

```
        circumference = 2.0F * 3.14F * radius; ← Note literal values with F  
        area = 3.14F * radius * radius;
```

```
        System.out.println("Given Radius: " + radius + "\n" +  
                           "Area: " + area + "\n" +  
                           "Circumference: " + circumference);
```

```
    }
```

```
}
```

[CAUTION: Imprecision]

- It is not possible to exactly represent every possible real valued number in a **double** or **float**
 - Fixed number of bits
 - **float**: 4 bytes -- 32 bits: 2^{32} (~1 billion) combinations
 - **double**: 8 bytes -- 64 bits: 2^{64} (~1 million trillion) combinations
 - BUT, how many real numbers
 - between, say 1.0 and 2.0? INFINITE!
- **float** and **double** sometimes only store an approximation of the actual number!!!!
- Do not rely on exact values!

[Integer data]

- If we are dealing with integer values only, using float or double is unwise:
 - operations are slower
 - maybe using too much space (memory)
 - sometimes there is a (small) error in representation (imprecision)
- Instead, we have completely separate numeric types for **integer** data
 - **byte, short, int, long**
 - differ in size and range

Numeric Data Types

Type	Content	Size (bytes)	Minimum Value	Maximum Value
byte	Integer	1	-128	127
short		2	-32768	32767
int		4	-2147483648	2147483647
long		8	-9, 223, 372, 036, 854, 780, 000	9, 223, 372, 036, 854, 780, 000
float	Real	4	$-3.40282347 \times 10^{38}$	$3.40282347 \times 10^{38}$
double		8	-1.7977×10^{308}	1.7977×10^{308}

Operators for Integer types

```
int x, y, z;  
x = 5;  
y = 2;
```

Multiplication

`z = x * y;` → `z = 10`

Addition

`z = x + y;` → `z = 7`

Subtraction

`z = x - y;` → `z = 3`

Division

`z = x / y;` → `z = 2`

Truncation!

Modulo

`z = x % y;` → `z = 1`

Remainder




Unary negation

`z = -y;` → `z = -2`

[Division Operator]

- It is important to note the behavior of division when the operands are both Integer types (**byte, short, int, long**)
 - in this case we get integer division (**truncation** of the decimal part)
- or, at least one is of type **float** or **double**
 - in this case we get regular division (no truncation).
 - there may be errors due to inherent problem with float and double representations.
- Division by 0 causes an error.

[Integer vs. Real Division]

```
...  
public static void main (String[] args){  
    int i, j, k;  
    float f, g, h;  
  
    i = 5;  
    j = 2;  
    k = i/j;  k = 2  
  
    k = j/i;  k = 0  
  
    f = 5;  
    g = 2;  
    h = f/g;  h = 2.5  
}
```

[Modulo Operator]

- This is simply a remainder operator
 - $x \% y$ computes the remainder when x is divided by y .
 - normally only used when both x and y are integer types (**byte**, **short**, **int** or **long**)
 - can be used with **float** and **double**, but results are not really meaningful

[Type Safety]

- Why so many different types for numeric data?
 - Integer types are more efficient and 100% accurate, BUT don't handle fractional values.
 - All types have a range
 - larger range implies more memory used
- Can we mix different types in expressions and assignments?
 - Yes, but have to be careful.

[Numeric Type Precision]

- The numeric types can be arranged in order of their ranges as follows:

byte < **short** < **int** < **long** < **float** < **double**

- The range of each type is strictly more precise than the range of each type to its left
 - E.g., any **byte** value can be stored in a **long** variable
 - Thus, there is no loss in assigning a smaller typed value to a larger typed variable
 - Going the other way causes losses!

Examples

```
byte b;  
short s;  
int i;  
long l;  
float f;  
double d;  
...
```

```
d = f;  
d = l;  
d = i;  
d = s;  
d = b;  
f = l;  
f = i;  
f = s;  
f = b;  
l = i;  
l = s;  
l = b;  
i = s;  
i = b;  
s = b;
```

Each of these assignments is legal -- no data loss.

```
byte b;  
short s;  
int i;  
long l;  
float f;  
double d;  
...
```

```
f = d;  
l = d;  
i = d;  
s = d;  
b = d;  
l = f;  
i = f;  
s = f;  
b = f;  
i = l;  
s = l;  
b = l;  
s = i;  
b = i;  
b = s;
```

ERROR!!
Each of these assignments is **illegal** -- could result in data loss.

[Type Casting]

- It is possible to explicitly change types (type casting)

```
d = (double) i;  
i = (int) d;
```

- Necessary when assigning a more precise type to a less precise one (Demotion).
 - possible data loss
 - assigning a **float** or **double** to an integer type results in truncation (not rounding)

```
i = (int) 3.5;
```

i will store 3, not 3.5

- Automatically done when assigning a less precise type to a more precise type (promotion). No data loss

[Expression Types]

- Each numeric expression also has a data type. What is the type of $i + j$?
- Depends on the types of i and j .
 - If they are both of the same type, then the expression is of the same type too
 - Otherwise the operand with the lower type will be automatically promoted to the higher type; the overall expression will be of this higher type too.

[Expression types]

```
byte b;  
short s;  
int i;  
long l;  
float f;  
double d;  
...  
l = b + i;  
  
l = (long) (f * d);  
  
s = (short) f / b;  
  
d = ((s/b) + (i*l))/f;
```

[Literal Numeric Values]

- What is the type of a literal value such as 3 or 3.45?
- If there is no decimal point, then the type is **int**
 - To make it a **long** type append L or l
 - For **byte** and **short** -- no special type. If the value is an integer within the range of **byte** (**short**), it can be assigned to a **byte** (**short**)
- If it has a decimal point, then its type is **double**.
 - To make it a **float** append F or f

```
byte b = 23;  
short s = 145;  
int i = -2345;  
long l = 234L;  
float f = -3.4556F;  
double d = 3.4564;
```

Area and Perimeter (again)

```
import java.util.Scanner;

public class CircleCalculator {

    public static void main (String[] args){
        double radius, area, circumference;

        Scanner scanner = new Scanner(System.in);
        System.out.println("Enter radius");
        radius = scanner.nextDouble();

        circumference = 2.0 * 3.1415926535897932 * radius;
        area = 3.1415926535891932 * radius * radius;

        System.out.println("Given Radius: " + radius + "\n" +
                           "Area: " + area + "\n" +
                           "Circumference: " + circumference);
    }
}
```


[Constants]

- Many programs use a constant value that should not be changed during execution.
- To avoid errors and reduce effort, we can define these once and reuse them.

```
final double PI =3.1415926535897932384626433832795;  
...  
area = PI * radius * radius;  
perimeter = 2 * PI * radius;
```

Note new
keyword

- The Math class defines PI and E
- Convention: all upper case for constants.

[Why use constants?]

- Consistent values
 - No errors due to mistyping
- Easy to manage
 - If we need to change the precision of PI, we need only change it in one place.
- Programs are more readable.

[Numeric Types vs. Strings]

- Numeric data types are not strings!
 - There are no quotes used for numeric types
- What is the difference between 20 and "20"?
 - They are represented very differently by the computer.
 - 20 is represented in binary equivalent of the value 20. "20" is simply two distinct characters.
 - Doing math on numeric types is direct and fast.
 - Numeric values have special formats.
- We can convert between the two types
 - `println()` automatically converts numbers to strings

[Parsing strings to numbers]

- Consider the following attempt to read in the radius value.

```
double radius, area, circumference;  
radius = JOptionPane.showInputDialog(null, "Enter radius");
```

- Not allowed by the compiler: wrong type.
- To convert we use a special method defined in a special class:

```
double radius, area, circumference;  
String inputString;  
  
inputString = JOptionPane.showInputDialog(null, "Enter radius");  
radius = Double.parseDouble(inputString);
```

[Wrapper classes]

- Useful methods and constants for each of the primitive types are defined in corresponding 'wrapper' classes

Primitive Type	Wrapper class	Sample Method	Constants
byte	Byte	parseByte()	MIN_VALUE MAX_VALUE SIZE
short	Short	parseShort()	
int	Integer	parseInt()	
long	Long	parseLong()	
float	Float	parseFloat()	
double	Double	parseDouble()	

See API for details

[CAUTION: + operator]

- Recall the + operator for strings?
- It is different than the + operator for numeric data.
- If BOTH operands are numeric data then it is numeric addition
- Otherwise, it is string concatenation
 - if one is numeric it will be converted to a string!

```
double x=5.0, y=6.0, z;  
String name = "234.5", str;
```

```
str = name + x + y; → str = "234.55.06.0"
```

```
str = x + y + name; → str = "11.0234.5"
```

```
z = name + x + y; → ERROR!
```

```
z = x + y + name; → ERROR!
```

[CAUTION: overflow & underflow]

```
byte b;  
b = 127;  
b += 1;
```

```
System.out.println("b is" + b);
```

b is -128

- Why?
- b went out of bounds and wrapped around!
 - Overflow.
- Similarly underflow can occur.
- Pick types wisely! Each has its own range -- be aware of it.
- Note: compiler can catch some problems.

```
byte b;  
b = 128;
```

will not compile!

[Shorthand operators]

- When the right hand side of an assignment uses the same operand as the left hand side, we often use a shorthand form for some operators:

Operator	Example	Shorthand For
<code>+=</code>	<code>x+=y;</code>	<code>x = x+y;</code>
<code>-=</code>	<code>x-=y;</code>	<code>x = x-y;</code>
<code>*=</code>	<code>x*=y;</code>	<code>x = x*y;</code>
<code>/=</code>	<code>x/=y;</code>	<code>x = x/y;</code>
<code>%=</code>	<code>x%=y;</code>	<code>x = x%y;</code>

Note: no spaces

[Problem]

On what day of the week were you born?

```

public class Birthday {

    public static void main(String[] args) {
        GregorianCalendar yourDateOfBirth;
        int year, month, day;
        Scanner scanner;
        String dayOfWeek;
        Locale locale = new Locale("EN");

        scanner = new Scanner(System.in);
        System.out.println("Enter the year of your birth");
        year = scanner.nextInt();

        System.out.println("Enter the month of your birth (0 for Jan, 1 for Feb, etc.)");
        month = scanner.nextInt();

        System.out.println("Enter the day of your birth");
        day = scanner.nextInt();

        yourDateOfBirth = new GregorianCalendar(year, month, day);
        dayOfWeek = yourDateOfBirth.getDisplayName(Calendar.DAY_OF_WEEK,
                                                    yourDateOfBirth.LONG, locale);
        System.out.println("You were born on a " + dayOfWeek);
    }
}

```