

DA 6891

36-inch countertop extractor

optional external or internal blower for maximum versatility.



- Striking design – telescopic canopy 36 1/8 (916) in (mm) inches wide.
- Powerful – 423.78 (720) ft³/min (m³/h) in Booster level
- Practical – 15-minute automatic blower run-on
- Suitable for every home – vented or recirculating
- For perfect functionality – accessories for proper venting

EAN: 4002515823972 / Material number: 10595910 /
Old Material Number: 28689150USA

General information	
Model number	DA 6891
Manufacturer material number	10595910
EAN number	4002515823972
Marketing class	Gold
Design	
Downdraft	•
Construction type and design	
Color	Stainless steel
Operating modes	
Recirculated mode	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 2900-900
OdorFree charcoal filter (order separately)	DKF18-900
Design	
Edge extraction	•
User convenience	
Electronic controls	•
Power levels (number excl. Intensive)	3
Booster levels	1
Run-on time 15 min.	•
Hood in Motion	•
Filter system	
Number of dishwasher-safe stainless steel grease filters	2
Lighting	
Number x W	1x6W
Light intensity in lx	280 lx
Color temperature in K	4000 Kelvin
Exhaust air	
Air throughput in CFM in Booster	240
Air throughput in Intensive setting (cfm)	423.78 (720)
Safety	
Safety shut-off	•
Single-ply safety glass (ESG)	•
Technical data	
Canopy width in in.(mm)	36 1/8 (916)
Overall min. height for vented and external in in. (mm)	41 3/8 (1052)
Overall max. height for vented and external in in. (mm)	41 3/8 (1052)
Canopy height in in.(mm)	25 3/8 (646)
Overall min. height for recirculation in in. (mm)	41 3/8 (1052)
Canopy depth in in.(mm)	13 7/8 (351)
Overall max. height for recirculation in in. (mm)	41 3/8 (1052)
Electrical plug	US grounded plug
Net weight in lbs. (kg)	60 (27.0)
Length of electrical wire in ft (m)	4 (1.5)
Standard plug fitted	•
Total connected load in kW	0.34
Voltage in V	120
Fuse rating in A	10

DA 6891

36-inch countertop extractor

optional external or internal blower for maximum versatility.



EAN: 4002515823972 / Material number: 10595910 /
Old Material Number: 28689150USA

Number of phases	1
Frequency in Hz	60

Installation note

Vent connection at top,rear,side,bottom	•
Diameter of vent connection in in.(mm)	6 (150)

Standard accessories

Reducer from 150 to 125 mm Ø	•
------------------------------	---

optional external or internal blower for maximum versatility.



DA 6881, DA 6891 Downdraft (Installation drawing)

DA 6881, DA 6891 Downdraft (Installation drawing)

1) Stepped cut-out for granite or marble worktops, 2) If downdraft system and hob are installed in separate cut-outs it is important to ensure sufficient stability of ridges.