

1. Classification
 - (a) K-Nearest Neighbor
2. Ensemble Algorithms
 - (a) Adaboost

Algorithm 1 k-Nearest Neighbor

Input: X: training data, Y: Class labels of X, x: unknown sample

Output: Class with the highest number of occurrence

```

1: function CLASSIFY( $X, Y, x$ )
2:   for  $i = 1$  to  $m$  do
3:     Compute distance  $d(X_i, x)$ 
4:   end for
5:   Compute set  $I$  containing indices for the  $k$  smallest distances  $d(X_i, x)$ 
6:   Return majority label  $\{Y_i \text{ where } i \in I\}$ 
7: end function
  
```

1. Ensemble Algorithm

Algorithm 2 Adaboost

Input:

Training data $\{(x_i, y_i)_{i=1}^N$ where $x_i \in \mathbb{R}^k$ and $y_i \in \{-1, 1\}\}$

Large number of classifiers denoted by $f_m(x) \in \{-1, 1\}$

0-1 loss function I defined as

$$I(f_m(x, y)) = \begin{cases} 0, & \text{if } f_m(x_i) = y_i \\ 1, & \text{if } f_m(x_i) \neq y_i \end{cases} \quad (1)$$

(2)

Output: The final classifier

```

1: for  $i = 1$  to  $N$  do
2:   for  $i = 1$  to  $M$  do
3:     Fit weak classifier  $m$  to minimize the objective function:
4:      $\epsilon_m = \frac{\sum_{i=1}^N w_i^m I(f_m(x_i) \neq y_i)}{x^2 + 2x + 1}$ 
5:     where  $I(f_m(x_i) \neq y_i) = 1$  if  $f_m(x_i) \neq y_i$  and 0 otherwise
6:      $\alpha_m = \ln \frac{1 - \epsilon_m}{\epsilon_m}$ 
7:   end for
8:   for all  $i$  do
9:      $w_i^{m+1} = w_i^{(m)} e^{\alpha_m I(f_m(x_i) \neq y_i)}$ 
10:  end for
11: end for
  
```

1. Another Pseudocode for Adaboost

1. Machine Learning Algorithms Pseudocode

1. Machine Learning Algorithms Pseudocode

1. Machine Learning Algorithms Pseudocode

1. Machine Learning Algorithms Pseudocode

1. Machine Learning Algorithms Pseudocode

1. Machine Learning Algorithms Pseudocode

1. Machine Learning Algorithms Pseudocode

1. Machine Learning Algorithms Pseudocode

Algorithm 3 Adaboost

Input:Training data $\{(x_i, y_i)_{i=1}^N$ where $x_i \in \mathbb{R}^k$ and $y_i \in \{-1, 1\}\}$ **Output:** The final classifier

- 1: Given Training data $\{(x_i, y_i) \text{ where } y_i \in \{-1, 1\}\}$
- 2: initialize D_1 = uniform distribution on training examples
- 3: **for** $t = 1$ to T **do**
- 4: Train weak classifier h_t on D_t
- 5: choose $\alpha_t > 0$
- 6: compute new distribution D_{t+1} :
- 7: **for** all i **do**
- 8: multiply $D_t(x)$ by

$$\begin{cases} e^{-\alpha_t}, & (< 1) \text{ if } y_i = h_t(x_i) \\ e^{\alpha_t}, & (> 1) \text{ if } y_i \neq h_t(x_i) \end{cases} \quad (3)$$

- 9: renormalize
 - 10: **end for**
 - 11: output final classifier $H_{final}(x) = \text{sign}(\sum \alpha_t h_t(x))$
 - 12: **end for**
-

Algorithm 4 Random forest

Input: S: training set, F:Features and number of trees in forest B **Output:** Constructed tree

- 1: **function** RANDOMFOREST(S, F)
 - 2: $H \leftarrow \emptyset$
 - 3: **for** $i \in 1, \dots, B$ **do**
 - 4: $S^{(i)} \leftarrow$ A bootstrap sample from S
 - 5: $h_i \leftarrow \text{RANDOMIZEDTREELEARN}(S^{(i)}, F)$
 - 6: $H \leftarrow H \cup \{h_i\}$
 - 7: **end for**
 - 8: return H
 - 9: **end function**
 - 10: **function** RANDOMIZEDTREELEARN(S, F)
 - 11: At each node:
 - 12: $f \leftarrow$ a very small subset of F
 - 13: Split on best feature in f
 - 14: return The learned tree
 - 15: **end function**
-

Algorithm 5 Iterative Dichotomiser 3

Input: D : Training Data, X : Set of Input Attributes

Output: A decision tree

```
1: function ID3( $D, X$ )
2:   Let  $T$  be a new tree
3:   if all instances in  $D$  have the same class  $c$  then
4:     Label( $T$ ) =  $c$ ; Return  $T$ 
5:   end if
6:   if  $X = \emptyset$  or no attribute has positive information gain then
7:     Label( $T$ ) = most common class in  $D$ ; Return  $T$ 
8:   end if
9:    $X \leftarrow$  attribute with highest information gain
10:  Label( $T$ ) =  $X$ 
11:  for each value  $x$  of  $X$  do
12:     $D_x \leftarrow$  instances in  $D$  with  $X = x$ 
13:    if  $D_x$  is empty then
14:      Let  $T_x$  be a new tree
15:      Label( $T_x$ ) = most common class in  $D$ 
16:    else
17:       $T_x = \text{ID3}(D_x, X - \{x\})$ 
18:    end if
19:    Add a branch from  $T$  to  $T_x$  labeled by  $x$ 
20:  end for
21:  return  $T$ 
end function
```

Algorithm 6 Perceptron

Input: $ProblemSize, InputPatterns, iterations_{max}, learn_{rate}$

Output: $Weights$

```
1: for  $i = 1$  to  $iterations_{max}$  do
2:    $Pattern_i \leftarrow \text{SelectInputPattern}(InputPatterns)$ 
3:    $Activation_i \leftarrow \text{ActivateNetwork}(Pattern_i, Weights)$ 
4:    $Output_i \leftarrow \text{TransferActivation}(Activation_i)$ 
5:    $UpdateWeights(Pattern_i, Output_i, learn_{rate})$ 
6: end for
7: Return  $Weights$ 
```

Algorithm 7 Back-propagation

Input: $ProblemSize, InputPatterns, iterations_{max}, learn_{rate}$

Output: $Network$

```
1:  $Network \leftarrow \text{ConstructNetworkLayers}()$ 
2:  $Network_{weights} \leftarrow \text{InitializeWeights}(Network, ProblemSize)$ 
3: for  $i = 1$  to  $iterations_{max}$  do
4:    $Pattern_i \leftarrow \text{SelectInputPattern}(InputPatterns)$ 
5:    $Output_i \leftarrow \text{ForwardPropagate}(Pattern_i, Network)$ 
6:    $\text{BackwardPropagateError}(Pattern_i, Output_i, Network)$ 
7:    $UpdateWeights(Pattern_i, Output_i, Network, learn_{rate})$ 
8: end for
9: Return  $Network$ 
```

Algorithm 8 Learning Vector Quantization

Input: $ProblemSize, InputPatterns, iterations_{max}, CodebookVectors_{num}, learn_{rate}$ **Output:** $CodebookVectors$

```
1:  $CodebookVectors \leftarrow InitializeCodebookVectors(CodebookVectors_{num}, ProblemSize)$ 
2: for  $i = 1$  to  $iterations_{max}$  do
3:    $Pattern_i \leftarrow SelectInputPattern(InputPatterns)$ 
4:    $Bmu_i \leftarrow SelectBestMatchingUnit(Pattern_i, CodebookVectors)$ 
5:   for  $Bmu_i^{attribute} \in Bmu_i$  do
6:     if  $Bmu_i^{class} \equiv Pattern_i^{class}$  then
7:        $Bmu_i^{attribute} \leftarrow Bmu_i^{attribute} + learn_{rate} \times (Pattern_i^{attribute} - Bmu_i^{attribute})$ 
8:     else
9:        $Bmu_i^{attribute} \leftarrow Bmu_i^{attribute} - learn_{rate} \times (Pattern_i^{attribute} - Bmu_i^{attribute})$ 
10:    end if
11:  end for
12: end for
13: Return  $CodebookVectors$ 
```

Algorithm 9 Self Organizing Map

Input: $InputPatterns, iterations_{max}, learn_{rate}, Grid_{width}, Grid_{height}$ **Output:** $CodebookVectors$

```
1:  $CodebookVectors \leftarrow InitializeCodebookVectors(Grid_{width}, Grid_{height}, InputPatterns)$ 
2: for  $i = 1$  to  $iterations_{max}$  do
3:    $Learn_{rate}^i \leftarrow CalculateLearningRate(i, learn_{rate}^{init})$ 
4:    $neighborhood_{size}^i \leftarrow CalculateNeighborhoodSize(i, neighborhood_{init}^{size})$ 
5:    $Pattern_i \leftarrow SelectInputPattern(InputPatterns)$ 
6:    $Bmu_i \leftarrow SelectBestMatchingUnit(Pattern_i, CodebookVectors)$ 
7:    $Neighborhood \leftarrow Bmu_i$ 
8:    $Neighborhood \leftarrow SelectNeighbors(Bmu_i, CodebookVectors, neighborhood_{size}^i)$ 
9:   for  $Vector_i \in Neighborhood$  do
10:    for  $Vector_i^{attribute} \in Vector_i$  do
11:       $Vector_i^{attribute} \leftarrow Vector_i^{attribute} + learn_{rate} \times (Pattern_i^{attribute} - Vector_i^{attribute})$ 
12:    end for
13:  end for
14: end for
15: Return  $CodebookVectors$ 
```

Algorithm 10 Hierarchial Agglomerative Algorithm

Input: $\langle V, E, w \rangle$. Weighted graph d_c . Distance measure for two clusters**Output:** $\langle V_T, E_T \rangle$. Cluster hierarchy or dendrogram

```
1:  $C = \{\{v \mid v \in V\}\}$  ▷ Initial Clustering
2:  $V_t = \{v_C \mid C \in C\}, E_T = \emptyset$  ▷ Initial Dendrogram
3: while  $|C| > 1$  do
4:    $update\_distance\_matrix(C, G, d_c)$ 
5:    $\{C, C'\} = \underset{\{C_i, C_j\} \in C: C_i \neq C_j}{argmin} d_c(C_i, C_j)$ 
6:    $C = (C \setminus \{C, C'\}) \cup \{C \cup C'\}$  ▷ Merging
7:    $V_T = V_T \cup \{v_{C, C'}\}, E_T = E_T \cup \{\{v_{C, C'}, v_C\}, \{v_{C, C'}, v_{C'}\}\}$  ▷ Dendrogram
8: end while
9: Return  $T$ 
```

Algorithm 11 Hierarchial Divisive Algorithm

Input: $\langle V, E, w \rangle$. Weighted graph d_c . Distance measure for two clusters**Output:** $\langle V_T, E_T \rangle$. Cluster hierarchy or dendogram1: $C = \{V\}$

▷ Initial Clustering

2: $V_t = \{v_C \mid C \in C\}, E_T = \emptyset$

▷ Initial Dendogram

3: **while** $\exists C_x : (C_x \in C \wedge |C_x| > 1)$ **do**4: $update_distance_matrix(C, G, d_c)$ 5: $\{C, C'\} = \underset{\{C_i, C_j\} : C_i \cup C_j = C_x \wedge C_i \cap C_j = \emptyset}{argmax} d_c(C_i, C_j)$ 6: $C = (C \setminus \{C, C'\}) \cup \{C \cup C'\}$

▷ Merging

7: $V_T = V_T \cup \{v_{C, C'}\}, E_T = E_T \cup \{\{v_{C, C'}, v_C\}, \{v_{C, C'}, v_{C'}\}\}$

▷ Dendogram

8: **end while**9: Return T
