

Modelling Complex Systems

Self-propelled particles

This lecture is adapted from Vicsek, T. & Zafeiris, A. (2012)
Collective Motion. And slides of David Sumpter

See: arXiv:1010.5017v2





Why do animals move together?

- Increased accuracy (many estimates)
- Increased awareness (many eyes)
- Confuse predators and reduce encounters

How do animals move together?

- Group formation usually seems to be *spontaneous*.
- Based on local interactions
- Phenomenological models
- Can ignore 'first principles' physics!
e.g. Conservation of momentum
- Use biological principles and limits instead.

Random walk in one dimension

- Run ‘RandomWalk1D’

$$\begin{aligned} \text{future position} & \rightarrow x_i(t+1) = x_i(t) + v_0 u_i(t) \\ \text{current position} & \quad \downarrow \\ \text{current velocity} & \quad \searrow \\ u_i(t+1) &= au_i(t) + e_i(t) \\ \text{future velocity} & \quad \nearrow \\ \text{current velocity} & \quad \nearrow \\ \text{stochastic effect} & \quad \swarrow \end{aligned}$$

$e_i(t)$ is a random number selected uniformly at random from a range $[-\eta/2, \eta/2]$

Attraction in one dimension

- Run 'Aggregate1D'

$$x_i(t+1) = x_i(t) + v_0 u_i(t)$$
$$u_i(t+1) = a u_i(t) + (1-a) s_i(t) + e_i(t)$$

future position current position current velocity

future velocity current velocity stochastic effect


Direction to most neighbours

$$s_i(t) = \frac{1}{|R_i|} \sum_{j \in R_i} \text{sign}(x_i(t) - x_j(t))$$


$e_i(t)$ is a random number selected uniformly at random from a range $[-\eta/2, \eta/2]$

Cockroach aggregation


Cockroaches



Model



Radakov's fish



Alignment model in one dimension

- Run 'Align1D'


$$\begin{aligned} \text{future position} & \rightarrow x_i(t+1) = x_i(t) + v_0 u_i(t) \\ \text{future velocity} & \nearrow \\ u_i(t+1) &= au_i(t) + (1-a) s_i(t) + e_i(t) \\ \text{current position} & \downarrow \\ \text{current velocity} & \nearrow \\ \text{velocity of neighbours} & \nearrow \\ \text{stochastic effect} & \swarrow \end{aligned}$$

$$s_i = G\left(\frac{1}{|R_i|} \sum_{j \in R_i} u_j(t)\right)$$


$$G(u) = \begin{cases} (u+1)/2 & \text{for } u > 0 \\ (u-1)/2 & \text{for } u < 0 \end{cases}$$

e is a random number selected uniformly at random from a range $[-\eta/2, \eta/2]$

Alignment


$$\phi = \frac{1}{n} \sum_{i=1}^n \underline{u}_i(t) \quad \text{measures order in the system.}$$

1D self-propelled particles



$\phi = \frac{1}{n} \sum_{i=1}^n \underline{u}_i(t)$ measures order in the system (alignment).







Buhl et al. (2006), *Science*
Yates et al. (2009), *PNAS*

Buhl et al. (2006), *Science*
Yates et al. (2009), *PNAS*





7 locusts




25 locusts




50 locusts







Model vs Experiment



Model vs Experiment



Vicsek Model


N: number of particles

η : noise parameter

L: size of domain

R : radius of interaction

v: speed



Angular update rule:

$$\theta_i(t+1) = \tan^{-1} \left(\frac{\sum_{j \in R_i} \sin(\theta_j(t))}{\sum_{j \in R_i} \cos(\theta_j(t))} \right) + e(t)$$

$e(t)$ is a random number selected uniformly at random from a range $[-\eta/2, \eta/2]$

2D Alignment

- Run ‘Align2D’

Measure of Alignment: Polarisation



High polarisation



Low Polarisation

Measure of Alignment: Polarisation



High polarisation




Low Polarisation



Measure of Alignment: Polarisation



High polarisation



Low Polarisation




Measure of Alignment: Polarisation



High polarisation





Low Polarisation



$$\text{Polarisation of: } \theta_1, \theta_2, \dots, \theta_N = \frac{1}{N} \sqrt{(\sum_j \sin(\theta_j))^2 + (\sum_j \cos(\theta_j))^2}$$


Vicsek Model




Vicsek et al., PRL 75 (1995)

Attraction/Repulsion


“Boids” model



Alternative distance measures



Alternative distance measures



Metric: all individuals within a certain distance.

Topological: a fixed number of nearest neighbors.

Voronoi: those individuals sharing a boundary in a Voronoi tessellation of the group.

Visual: all individuals that occupy an angular area on the retina of the focal fish that is greater than a threshold value.


Even more options

- Maximum turning angles
- Blind angles
- Attraction/repulsion potentials
- Reaction times
- Wall interactions
- Variable speed
- Variation in individuals
- Pheromone trails
- Etc....




Sheepdog model

(b)



Drive and collect



Next: when humans go ballistic

PRL 110, 228701 (2013)

PHYSICAL REVIEW LETTERS

week ending
31 MAY 2013




Collective Motion of Humans in Mosh and Circle Pits at Heavy Metal Concerts


Jesse L. Silverberg,* Matthew Bierbaum, James P. Sethna, and Itai Cohen

Department of Physics and Laboratory of Atomic and Solid State Physics, Cornell University, Ithaca, New York 14853, USA

(Received 13 February 2013; published 29 May 2013)






Moshpit model




Rules of motion




Using data to fit models



The modelling cycle





Can you tell the difference between real and simulated fish?

The image is a collage of screenshots from a computer application. At the top left is a grayscale video frame showing many fish swimming, with a black 'Play' button overlaid. To its right is a circular interface with two halves: a white half containing green dots and a gray half containing one dot, with a 'Make your choice' label and a 'Next' button. Below these is a large central window showing a fish silhouette with the text 'Congratulations! You have answered 5 out of 6 questions correctly.' and a 'Click refresh button to play again' link. To the left of this window is a smaller video frame showing a container of fish, with a 'Skip' button at the bottom. To the right is a window with a 'Begin' button. A bottom banner at the very bottom of the collage reads 'Get playing!' and provides a URL: <http://www.collective-behavior.com/apps/>.

Play

Congratulations!
You have answered 5 out of 6 questions correctly.

Click refresh button to play again




Skip

Begin


Get playing!

<http://www.collective-behavior.com/apps/>


Get playing!
<http://www.collective-behavior.com/apps/>



Can people tell the difference between real and simulated fish?



Evolving prey





<http://collective-behavior.com/apps/fishindanger/webgl>

Project - Particle Swarm Optimisation

Optimisation problem.

Find global minimum/local minima.



Benchmark: Rastrigin function

$$F(x_1, x_2) = 10n + \sum_{i=1}^2 x_i^2 - 10 \cos(2\pi x_i) \quad x_i \in [-5.12, 5.12]$$

Recall: attraction in one dimension

$$\begin{aligned} \text{future position} & \quad \text{current position} & \text{current velocity} \\ \xrightarrow{\hspace{1cm}} & x_i(t+1) = x_i(t) + v_0 u_i(t) & \xrightarrow{\hspace{1cm}} \\ & u_i(t+1) = a u_i(t) + (1-a) s_i(t) + e_i(t) & \\ \text{future velocity} & \quad \text{current velocity} & \quad \text{stochastic effect} \\ & \nearrow & \nearrow & \nearrow \\ & & & \text{Direction to most neighbours} \end{aligned}$$

$$s_i(t) = \frac{1}{|R_i|} \sum_{j \in R_i} \text{sign}(x_i(t) - x_j(t))$$

$e_i(t)$ is a random number selected uniformly at random from a range $[-\eta/2, \eta/2]$

Extension: Particle swarm optimisation

$$x_i^{(t)} = x_i^{(t-1)} + v_i^{(t)}$$
$$v_i^{(t)} = v_i^{(t-1)} + c_1 U(0, 1) \odot (p_i - x_i^{(t-1)}) + c_2 U(0, 1) \odot (p_g - x_i^{(t-1)})$$

future position → $x_i^{(t-1)}$

current position → p_i

current velocity → $v_i^{(t-1)}$

future velocity → $v_i^{(t-1)}$

current velocity → p_g

stochastic effect → $c_1 U(0, 1)$

stochastic effect → $c_2 U(0, 1)$

N particles. p_1, \dots, p_N best positions of each particle.

p_g - best position of particles in neighbourhood

Extension: Particle swarm optimisation

$$x_i^{(t)} = x_i^{(t-1)} + v_i^{(t)}$$
$$v_i^{(t)} = v_i^{(t-1)} + c_1 U(0, 1) \odot (p_i - x_i^{(t-1)}) + c_2 U(0, 1) \odot (p_g - x_i^{(t-1)})$$

The diagram illustrates the components of the PSO update equations. It shows the flow of information from labels to the corresponding terms in the equations.

- future position** points to the term $x_i^{(t-1)}$ in the first equation.
- current position** points to the term $x_i^{(t-1)}$ in the second equation.
- current velocity** points to the term $v_i^{(t-1)}$ in the second equation.
- future velocity** points to the term $v_i^{(t-1)}$ in the second equation.
- current velocity** points to the term $v_i^{(t-1)}$ in the second equation.
- cognitive** points to the term $(p_i - x_i^{(t-1)})$ in the second equation.
- social** points to the term $(p_g - x_i^{(t-1)})$ in the second equation.

N particles. p_1, \dots, p_N best positions of each particle.

p_g - best position of particles in neighbourhood

c_1 Cognitive - pulls particle towards best position it has had so far

c_2 Social - pulls particle towards best position so far of those in its neighbourhood

```
x = rand(N, d)      # positions
v = rand(N, d)      # velocities
p = rand(N, d)      # previous best position
pbest = infinity(N) # best function value
g = 0                # index of best in neighborhood

# Run some amount of iterations
for t in range(iter):

    # Update all particles
    for i in range(N):


        # Check if F at current x is better than previous and update pbest, p.
        if F(x[i]) < pbest[i]:
            pbest[i] = F(x[i])
            p[i] = x[i]

        # Get neighbors and get index of best performing particle
        neighbors = get_neighbors(i)
        g = best_performer(neighbors)

        # Update velocity and position
        v[i] += mult_elem(c1*rand(d), (p[i] - x[i])) +
                mult_elem(c2*rand(d), (p[g] - x[i]))
        x[i] += v[i]
```

Extension: Particle swarm optimisation

Jonas Olsson




$$c_1 = 1.49618, c_2 = 1.49618$$

c_1 Cognitive - pulls particle towards best position it has had so far

c_2 Social - pulls particle towards best position so far of those in its neighbourhood

Extension: Particle swarm optimisation

Jonas Olsson




$$c_1 = 0, c_2 = 1.49618$$

c_1 Cognitive - pulls particle towards best position it has had so far

c_2 Social - pulls particle towards best position so far of those in its neighbourhood

Extension: Particle swarm optimisation

Jonas Olsson



$$c_1 = 1.49618, c_2 = 1.49618, w = 0.7298$$

c_1 Cognitive - pulls particle towards best position it has had so far

c_2 Social - pulls particle towards best position so far of those in its neighbourhood


w inertia/constriction/viscosity,

large w - viscosity low, particles move easily - favours global min

Small w - viscosity high particles move slower - favours local min

Extension: Particle swarm optimisation

Jonas Olsson



$$c_1 = 0, c_2 = 1.49618, w = 0.7298$$

c_1 Cognitive - pulls particle towards best position it has had so far

c_2 Social - pulls particle towards best position so far of those in its neighbourhood


w inertia/constriction/viscosity,

large w - viscosity low, particles move easily - favours global min

Small w - viscosity high particles move slower - favours local min

Extension: Particle swarm optimisation

Jonas Olsson



$$c_1 = 1.49618, c_2 = 0, w = 0.7298$$

c_1 Cognitive - pulls particle towards best position it has had so far

c_2 Social - pulls particle towards best position so far of those in its neighbourhood



w inertia/constriction/viscosity,

large w - viscosity low, particles move easily - favours global min

Small w - viscosity high particles move slower - favours local min

Prc

future



$$u_i(t+1) = \alpha u_i(t) + (1-\alpha) s_i(t) + e_i(t)$$

future velocity

current velocity

stochastic effect

Direction to most neighbours

$$s_i(t) = \frac{1}{|R_i|} \sum_{j \in R_i} \text{sign}(x_i(t) - x_j(t))$$

$e_i(t)$ is a random number selected uniformly at random from a range $[-\eta/2, \eta/2]$