

```
141 6.614792      71.192.34.104      64.233.169.104      TCP      66      4338 → 80 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=4
SACK_PERM=1
Frame 141: 66 bytes on wire (528 bits), 66 bytes captured (528 bits)
  Encapsulation type: Ethernet (1)
  Arrival Time: Sep 20, 2009 16:43:08.345856000 Eastern Daylight Time
  [Time shift for this packet: 0.000000000 seconds]
  Epoch Time: 1253479388.345856000 seconds
  [Time delta from previous captured frame: 0.001102000 seconds]
  [Time delta from previous displayed frame: 0.001102000 seconds]
  [Time since reference or first frame: 6.614792000 seconds]
  Frame Number: 141
  Frame Length: 66 bytes (528 bits)
  Capture Length: 66 bytes (528 bits)
  [Frame is marked: False]
  [Frame is ignored: False]
  [Protocols in frame: eth:ethertype:ip:tcp]
  [Coloring Rule Name: HTTP]
  [Coloring Rule String: http || tcp.port == 80 || http2]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: Cisco_bf:6c:01 (00:0e:d6:bf:6c:01)
  Destination: Cisco_bf:6c:01 (00:0e:d6:bf:6c:01)
    Address: Cisco_bf:6c:01 (00:0e:d6:bf:6c:01)
      ....0. .... = LG bit: Globally unique address (factory default)
      ....0. .... = IG bit: Individual address (unicast)
  Source: Dell_4f:36:23 (00:08:74:4f:36:23)
    Address: Dell_4f:36:23 (00:08:74:4f:36:23)
      ....0. .... = LG bit: Globally unique address (factory default)
      ....0. .... = IG bit: Individual address (unicast)
  Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 71.192.34.104, Dst: 64.233.169.104
  0100 .... = Version: 4
  ....0101 = Header Length: 20 bytes (5)
  Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    0000 00.. = Differentiated Services Codepoint: Default (0)
    ....00.. = Explicit Congestion Notification: Not ECN-Capable Transport (0)
  Total Length: 52
  Identification: 0xa2eb (41707)
  Flags: 0x02 (Don't Fragment)
    0... .... = Reserved bit: Not set
    .1.. .... = Don't fragment: Set
    ..0. .... = More fragments: Not set
  Fragment offset: 0
  Time to live: 127
  Protocol: TCP (6)
  Header checksum: 0x045f [validation disabled]
  [Header checksum status: Unverified]
  Source: 71.192.34.104
  Destination: 64.233.169.104
  [Source GeoIP: Unknown]
  [Destination GeoIP: Unknown]
Transmission Control Protocol, Src Port: 4338, Dst Port: 80, Seq: 0, Len: 0
  Source Port: 4338
  Destination Port: 80
  [Stream index: 5]
  [TCP Segment Len: 0]
  Sequence number: 0 (relative sequence number)
  Acknowledgment number: 0
  1000 .... = Header Length: 32 bytes (8)
  Flags: 0x002 (SYN)
    000. .... = Reserved: Not set
    ...0 .... = Nonce: Not set
    ....0... = Congestion Window Reduced (CWR): Not set
    ....0... = ECN-Echo: Not set
    ....0... = Urgent: Not set
    ....0... = Acknowledgment: Not set
    ....0... = Push: Not set
    ....0... = Reset: Not set
    ....0... = Syn: Set
    [Expert Info (Chat/Sequence): Connection establish request (SYN): server port 80]
    [Connection establish request (SYN): server port 80]
    [Severity level: Chat]
    [Group: Sequence]
    ....0... = Fin: Not set
  [TCP Flags: .....S.]
  Window size value: 65535
  [Calculated window size: 65535]
  Checksum: 0xc034 [unverified]
  [Checksum Status: Unverified]
  Urgent pointer: 0
  Options: (12 bytes), Maximum segment size, No-Operation (NOP), Window scale, No-Operation (NOP), No-Operation (NOP), SACK permitted
  TCP Option - Maximum segment size: 1460 bytes
```

TCP Option - No-Operation (NOP)  
TCP Option - Window scale: 2 (multiply by 4)  
TCP Option - No-Operation (NOP)  
TCP Option - No-Operation (NOP)  
TCP Option - SACK permitted