

```
379 54.967184      128.59.23.100      192.168.1.102      IPv4      1514      Fragmented IP protocol (proto=ICMP 1, off=1480,
ID=0959) [Reassembled in #380]
Frame 379: 1514 bytes on wire (12112 bits), 1514 bytes captured (12112 bits)
  Encapsulation type: Ethernet (1)
  Arrival Time: Aug 21, 2004 21:48:51.625536000 Eastern Daylight Time
  [Time shift for this packet: 0.000000000 seconds]
  Epoch Time: 1093139331.625536000 seconds
  [Time delta from previous captured frame: 0.008797000 seconds]
  [Time delta from previous displayed frame: 0.008797000 seconds]
  [Time since reference or first frame: 54.967184000 seconds]
  Frame Number: 379
  Frame Length: 1514 bytes (12112 bits)
  Capture Length: 1514 bytes (12112 bits)
  [Frame is marked: False]
  [Frame is ignored: False]
  [Protocols in frame: eth:ethertype:ip:data]
Ethernet II, Src: LinksysG_da:af:73 (00:06:25:da:af:73), Dst: PremaxPe_8a:70:1a (00:20:e0:8a:70:1a)
  Destination: PremaxPe_8a:70:1a (00:20:e0:8a:70:1a)
    Address: PremaxPe_8a:70:1a (00:20:e0:8a:70:1a)
      .... ..0. .... .. = LG bit: Globally unique address (factory default)
      .... ...0 .... .. = IG bit: Individual address (unicast)
  Source: LinksysG_da:af:73 (00:06:25:da:af:73)
    Address: LinksysG_da:af:73 (00:06:25:da:af:73)
      .... ..0. .... .. = LG bit: Globally unique address (factory default)
      .... ...0 .... .. = IG bit: Individual address (unicast)
  Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 128.59.23.100, Dst: 192.168.1.102
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    0000 00.. = Differentiated Services Codepoint: Default (0)
    .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
  Total Length: 1500
  Identification: 0x0959 (2393)
  Flags: 0x03 (Don't Fragment) (More Fragments)
    0... .... = Reserved bit: Not set
    .1.. .... = Don't fragment: Set
    ..1. .... = More fragments: Set
  Fragment offset: 1480
  Time to live: 242
  Protocol: ICMP (1)
  Header checksum: 0xff60 [validation disabled]
  [Header checksum status: Unverified]
  Source: 128.59.23.100
  Destination: 192.168.1.102
  [Source GeoIP: Unknown]
  [Destination GeoIP: Unknown]
  Reassembled IPv4 in frame: 380
Data (1480 bytes)
0000 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0010 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0020 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0030 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0040 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0050 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0060 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0070 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0080 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0090 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00a0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00b0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00c0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00d0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00e0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00f0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0100 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0110 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0120 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0130 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0140 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0150 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0160 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0170 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0180 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0190 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
01a0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
01b0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
01c0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
01d0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
01e0 aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
```

[illegible]