

```
92 28.441511      192.168.1.102      128.59.23.100      IPv4      1514      Fragmented IP protocol (proto=ICMP 1, off=0, ID=32f9)
[Reassembled in #93]
Frame 92: 1514 bytes on wire (12112 bits), 1514 bytes captured (12112 bits)
  Encapsulation type: Ethernet (1)
  Arrival Time: Aug 21, 2004 21:48:25.099863000 Eastern Daylight Time
  [Time shift for this packet: 0.000000000 seconds]
  Epoch Time: 1093139305.099863000 seconds
  [Time delta from previous captured frame: 5.488773000 seconds]
  [Time delta from previous displayed frame: 5.488773000 seconds]
  [Time since reference or first frame: 28.441511000 seconds]
  Frame Number: 92
  Frame Length: 1514 bytes (12112 bits)
  Capture Length: 1514 bytes (12112 bits)
  [Frame is marked: False]
  [Frame is ignored: False]
  [Protocols in frame: eth:ethertype:ip:data]
  [Coloring Rule Name: TTL low or unexpected]
  [Coloring Rule String: ( ! ip.dst == 224.0.0.0/4 && ip.ttl < 5 && !pim && !ospf) || (ip.dst == 224.0.0.0/24 && ip.dst != 224.0.0.251
&& ip.ttl != 1 && !(vrrp || carp))]
Ethernet II, Src: PremaxPe_8a:70:1a (00:20:e0:8a:70:1a), Dst: LinksysG_da:af:73 (00:06:25:da:af:73)
  Destination: LinksysG_da:af:73 (00:06:25:da:af:73)
    Address: LinksysG_da:af:73 (00:06:25:da:af:73)
      ....0. .... = LG bit: Globally unique address (factory default)
      ....0. .... = IG bit: Individual address (unicast)
  Source: PremaxPe_8a:70:1a (00:20:e0:8a:70:1a)
    Address: PremaxPe_8a:70:1a (00:20:e0:8a:70:1a)
      ....0. .... = LG bit: Globally unique address (factory default)
      ....0. .... = IG bit: Individual address (unicast)
  Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 128.59.23.100
  0100 .... = Version: 4
  ....0101 = Header Length: 20 bytes (5)
  Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    0000 00.. = Differentiated Services Codepoint: Default (0)
    ....00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
  Total Length: 1500
  Identification: 0x32f9 (13049)
  Flags: 0x01 (More Fragments)
    0... .... = Reserved bit: Not set
    .0.. .... = Don't fragment: Not set
    ..1. .... = More fragments: Set
  Fragment offset: 0
  Time to live: 1
    [Expert Info (Note/Sequence): "Time To Live" only 1]
      ["Time To Live" only 1]
      [Severity level: Note]
      [Group: Sequence]
  Protocol: ICMP (1)
  Header checksum: 0x077b [validation disabled]
  [Header checksum status: Unverified]
  Source: 192.168.1.102
  Destination: 128.59.23.100
  [Source GeoIP: Unknown]
  [Destination GeoIP: Unknown]
  Reassembled IPv4 in frame: 93
Data (1480 bytes)
0000  08 00 d0 c6 03 00 77 03 37 36 20 aa aa aa aa aa .....w.76 .....
0010  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0020  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0030  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0040  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0050  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0060  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0070  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0080  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0090  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00a0  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00b0  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00c0  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00d0  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00e0  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
00f0  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0100  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0110  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0120  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0130  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0140  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0150  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0160  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
0170  aa aa aa aa aa aa aa aa aa aa aa aa aa aa aa .....
```

[Length: 1480]