



Harnessing Hydropower's Energy Storage and Flexibility for the Energy Transition: Introduction

Prof. Dr. Fabrizio Sossan

Gridlab, Institut Energie et environnement
Haute École d'Ingénierie
HES-SO Valais-Wallis
Switzerland

> Welcome! Bienvenue! Wilkommen!

Program

- 16:45 Welcome
- 17:00 Hydropower Innovation for the European Electrical System (B. Valluy, Alpiq)
- 17:20 Innovative storage technology and operations in hydropower (A. Presas, UPC)
- 17:40 Transformation from an energy producer to a grid stabilizer (D. Fischlin, KWO)
- 18:00 Shaping the Future of Hydropower with Numerical Simulations: Hydraulic short circuit and Sediment Erosion Challenges (C. Münch, HES-SO Valais-Wallis)
- 18:20 Industrial round table: M. Neuhauser (Andritz), J. August (EDF), A. Aires De Matos (EDP), R. Subira (Sener), Patrick Boissonneau (GE Vernova). Moderated by P. Roduit (HES-SO Valais-Wallis)

> Energy storage: yesterday

- Either costly, immature, or scarcely available (except for hydro, where available)
- Applications mostly limited to isolated microgrids:



+




+


Energy storage = Stable Power supply

> Energy storage: today

- Increased needs due to integrating more renewables in the grid




Dunkelflaute (and seasonal energy storage)



Duck curve

> Energy storage: today (cont'd)

- Improved technologies (including second life battery) and lower costs:



[NREL data]

- Diverse applications encouraged, energy storage's economics improve by providing multiple services

> (Bidirectional) energy storage technologies

Bidirectional technologies:

- Pumped-storage hydropower
- Batteries and second-life batteries
- Flywheels
- Ultracapacitors
- Power-to-x-to-power (fuel cells/electrolyser)

Attributes:

- Round-trip efficiency
- Response time
- Calendar and cycle ageing
- Power and energy density
- Cost
- Modularity / Adaptability / Scalability

Other grid-oriented flexible resources:


- Electric vehicles (V1G and V2G)
- Flexible demand

> From techs, to grid applications and integration

Example for a battery system

Tech and product development

- Materials and manufacturing
- Cell stack engineering
- Battery Management System (BMS)
- Power converter



Prof. Fabrizio Sossan

- | Application | Integration |
|---|---|
| <ul style="list-style-type: none"> • Definition of the application requirements • Definition of revenue streams • Sizing, siting, and technology selection • Grid connection • Energy Management System (EMS) • Real-time control | <ul style="list-style-type: none"> • Electricity and ancillary services markets • Policies to foster development inline with energy transition plans • Regulatory aspects, compensation schemes and subsidies (eg, RCP, CEL) |



Edwards & Sanborn 3 GWh battery, California

Integration

- Electricity and ancillary services markets
- Policies to foster development inline with energy transition plans
- Regulatory aspects, compensation schemes and subsidies (eg, RCP, CEL)




Schweizerische Eidgenossenschaft
Confédération suisse
Confederazione Svizzera
Confederaziun svizra



swissgrid
et al.

Energy Storage Grid Applications



> Challenges ahead

Today, storage grows spontaneously (market-driven) → no guarantee this yields a functional, system-level storage infrastructure.

Potential issues:

- Insufficient short-term/seasonal energy storage capacity, or nominal power
- Conflicting revenue streams (business model not sustainable in the long term)
- Inappropriate mix of technologies (quickly obsolete)

> Questions still unaddressed





Energy Storage: **what** techs mix, **where**, and **how** much to reach 100% renewables?



Time coupling across time scales



Many systems to coordinate at different voltage levels



> Increasing flexibility of hydropower

Increased regulation needs (due to more renewables) and ageing infrastructure, **more flexibility** is needed.

Several options to increase flexibility: one is coupling the hydropower plant with a local battery system (**hybrid hydropower plant**)

Three key tasks associated to **hybridization**:

1. Sizing (kVA, kWh) + technology selection (cycle and calendar ageing)
2. Scheduling, or energy management (hour-to-hour management of the state of charge)
3. Real-time control (sending set-point to the battery system, and integration in the SCADA system of the operator)

> The battery sizing problem in hybrid hydropower

Application requirements:

- Fatigue reduction
- Start & stop's reduction
- Hydropeaking mitigation

And, as it has always been,

- i, ii, iii frequency control
- energy arbitrage

Forecasts of the services to be provided and market signals
(or quantification of the uncertainty)


minimize { CAPEX + OPEX - revenues }
subject to:

- hydropower constraints
- battery system constraints
- Ancillary services and market commitments

BESS Energy capacity (MWh) and power (MVA)


Optimal BESS charging/discharging trajectories

> Control of a hybrid hydropower plant



> Control of a hybrid hydropower plant (cont'd)

Model predictive control (MPC) as an extension of the classic turbine governor (minimally invasive layout):



Reduced-order models to capture:

- Power dynamics
- Mechanical stress and impact of fatigue

> Acknowledgements

STORE.

Flagship
supported by



Schweizerische Eidgenossenschaft
Confédération suisse
Confederazione Svizzera
Confederaziun svizra

Swiss Confederation

Innosuisse – Swiss Innovation Agency



Novelis

FLASA
High Performance Yarns

OIKEN VALGRID^{SA}

RELL EMISSIUM

THELER

GRID LAB
ROMANDE ENERGIE

Natron Energy

PLANAIR
Ingénieurs de la transition énergétique


swissgrid

STOR-HY



Funded by
the European Union

Funded by the European Union under Grant Agreement No. 101172905. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the Climate, Infrastructure and Environment Executive Agency (CINEA). Neither the European Union nor the CINEA can be held responsible for them.

A blurred background image showing a close-up of various electrical components, including a large coil with orange and red wires, several black cables with yellow and blue insulation, and a metal bracket. The lighting is dramatic, with strong highlights and shadows.

Prof. Fabrizio Sossan
GridLab - <https://gridlab.hevs.ch>
HES-SO Valais-Wallis
 fabrizio.sossan@hevs.ch