



MyScoutee

OFFICIAL PRODUCT DOCUMENTATION

EXTERNAL INTEGRATION

MyScoutee Integration API Guide

A compact write API for creating asset and event batches, attaching optional image bytes, and correlating external records with MyScoutee resource IDs.

DOCUMENT ID MSC-API-001	DOCUMENT VERSION 1.0.1
APPLICABLE SOFTWARE VERSION MyScoutee 1.0.1	STATUS ● Released
RELEASE DATE 2026-09-19	LANGUAGE EN

Document Control

Document status and applicability

Document owner	MyScoutee project — integration documentation
Intended audience	External system developers, integration operators, and maintainers of the MyScoutee Java client
Normative API prefix	The deployment-specific Base URL shown in the profile API popup; its usual path is <code>/api/integrations/v1</code>
Reference implementation	<code>myscoutee-client</code> version 1.0.1, Java 17

Version History

Version	Date	Status	Change
1.0.1	2026-09-19	Released	Initial public batch API and Java client guide.


Small by design

This is not a general-purpose read API. It creates assets and events owned by the token owner and returns stable MyScoutee IDs for external correlation.

Table of Contents

- Integration Model**
- Base URL and Authentication**
- Endpoint Reference**
- ID Correlation and Retry Behaviour**
- Asset Batch**
- Event Batch**
- Optional Image Upload**
- Responses and Errors**
- Java Client and CLI**
- Security and Operational Rules**

1. Integration Model



Concept	Meaning
<code>id</code>	The caller-owned UUID sent in the request. It identifies the source-system record.
<code>externalId</code>	The stable MyScoutee asset or event UUID returned for that request item.
Ownership	Every created resource belongs only to the user who owns the integration token.
Batch	One request contains 1-1000 items. Further batches may be sent later.
Image	Optional local file bytes sent with the same POST. No remote image URL is accepted or downloaded.

2. Base URL and Authentication

Connect one external client

- 1 Open the API popup from the lower-right corner of the profile identity header.
- 2 Copy the full Base URL, including scheme, domain, and `/api/integrations/v1` path.
- 3 Generate an expiring client key. The complete token is shown only once.
- 4 Configure one stable client UUID and call `POST /connect`.

Header	Value	Required
<code>Authorization</code>	<code>Bearer msc_...</code>	Yes
<code>X-MyScoutee-Client-Id</code>	A stable UUID generated once by the external client	Yes
<code>Accept</code>	<code>application/json</code>	Recommended
<code>Content-Type</code>	<code>application/json</code> or <code>multipart/form-data</code>	Yes for batch POSTs

One key, one client

The first successful client UUID claims the key. Another client UUID cannot use it. A user may keep at most three active keys, and revocation blocks a key immediately.

3. Endpoint Reference

Method	Path	Purpose	Success
POST	/connect	Claim and validate a client key	200
POST	/assets	Create 1-1000 assets, optionally with images	200
POST	/events	Create 1-1000 events, optionally with images	200

There is no separate image endpoint and no booking query endpoint in this API version.

4. ID Correlation and Retry Behaviour

```
{
  "items": [
    {
      "id": "1066b61b-c0ac-43d5-ab28-f588f5a162f6",
      "externalId": "55fe8563-f360-48cf-af0e-7cfb0404ee84",
      "result": "created",
      "error": null
    }
  ]
}
```

The caller stores the pair above. Repeating the same resource type and caller `id` for the same token owner returns the same `externalId` with `result: "existing"`. It does not create or update a second resource.

Safe request retry

If a client times out before receiving the response, it may repeat the POST with the same item IDs and recover the same MyScoutee IDs.

5. Asset Batch

Field	Type	Required	Rule
id	UUID	Yes	Unique within the batch and stable in the caller system
type	string	Yes	Transport, Accommodation, or Supplies
title	string	Yes	Non-blank
capacityTotal	integer	Yes	At least 1
quantity	integer	Yes	At least 1
routes	string array	Accommodation only	At least one non-blank location for accommodation
subtitle, category, city, details	string	No	Asset description fields
sourceLink	URI string	No	Optional source reference; it is not used to download an image
visibility	string	No	Defaults through the ordinary asset model when omitted

```
{
  "items": [{
    "id": "7d857d7f-8d48-4cf1-95cc-cbf257640afa",
    "type": "Accommodation",
    "title": "Hotel room 101",
    "capacityTotal": 2,
    "quantity": 1,
    "routes": ["Bratislava"],
    "visibility": "Private"
  }]
}
```

6. Event Batch

Field	Type	Required	Rule
<code>id</code>	UUID	Yes	Unique within the batch and stable in the caller system
<code>title</code>	string	Yes	Non-blank
<code>subtitle</code>	string	Yes	Non-blank, matching the event editor requirement
<code>startAt</code> , <code>endAt</code>	ISO-8601 instant	Yes	<code>endAt</code> must be after <code>startAt</code>
<code>capacityMin</code>	integer	Yes	Zero or greater
<code>capacityMax</code>	integer	Yes	At least <code>capacityMin</code>
<code>location</code> , <code>sourceLink</code>	string	No	Optional display and source-reference fields
<code>visibility</code>	string	No	Ordinary event visibility; defaults when omitted
<code>status</code>	string	No	<code>draft</code> or <code>active</code> ; defaults to active
<code>topics</code>	string array	No	Optional event topics

```
{
  "items": [{
    "id": "1066b61b-c0ac-43d5-ab28-f588f5a162f6",
    "title": "Hotel evening",
    "subtitle": "Welcome event for hotel guests",
    "startAt": "2026-10-10T18:00:00Z",
    "endAt": "2026-10-10T20:00:00Z",
    "capacityMin": 1,
    "capacityMax": 30,
    "status": "draft"
  }]
}
```

7. Optional Image Upload

Use the same `POST /assets` or `POST /events` URL with `multipart/form-data`.

Part	Content type	Content
<code>request</code>	<code>application/json</code>	The complete batch object with its <code>items</code> array
Item UUID, for example <code>1066b61b-...</code>	<code>image/jpeg</code> , <code>image/png</code> , <code>image/webp</code> , or <code>image/gif</code>	One optional local image file for that item

Every file-part name must match an `id` in the JSON batch. At most one image may be attached to an item.

The server stores the original bytes and creates WebP variants whose maximum dimensions are 128 px, 640 px, and 1280 px. The resource points to the large variant.

No remote retrieval

Do not send an image URL. The client and this API never retrieve an image from another server; either send the file bytes in this request or omit the image.

8. Responses and Errors

HTTP/result	Meaning
<code>200 / created</code>	The resource was created; <code>externalId</code> contains its MyScoutee UUID.
<code>200 / existing</code>	The caller <code>id</code> was already mapped; the same <code>externalId</code> is returned.
<code>200 / rejected</code>	That item failed validation or creation; <code>error</code> contains a stable reason and <code>externalId</code> is null.
<code>400</code>	The batch envelope or multipart relationship is invalid.
<code>401</code>	The key is missing, invalid, expired, revoked, or claimed by another client UUID.

Common item errors include `id_must_be_uuid`, `duplicate_id_in_batch`, `title_required`, `subtitle_required`, `valid_start_and_end_required`, and the capacity-specific validation codes.

9. Java Client and CLI

```
./gradlew installDist

myscoutee-client configure \
  https://example.com/api/integrations/v1 \
  'msc_your_token'

myscoutee-client assets assets.json
myscoutee-client events events.json \
  1066b61b-c0ac-43d5-ab28-f588f5a162f6=event.webp
```

SDK method	Use
<code>connect()</code>	Validate and claim the configured key.
<code>createAssets(items)</code>	Send a JSON-only asset batch.
<code>createAssets(items, images)</code>	Send assets and a map from item UUID to local image path.
<code>createEvents(items)</code>	Send a JSON-only event batch.
<code>createEvents(items, images)</code>	Send events and optional local images.

The CLI stores the Base URL, token, and stable client UUID in `~/.myscoutee/client.properties`. The token is masked by `show-config`.

10. Security and Operational Rules

- ☐ Use HTTPS outside localhost development.
- ☐ Keep the complete key secret and use a distinct key for every connected client.
- ☐ Revoke a lost or retired key from the profile popup immediately.
- ☐ Retain both `id` and `externalId` in the external system.
- ☐ Split imports into batches of no more than 1000 items.
- ☐ Do not infer access to another user's records: the token fixes the resource owner.
- ☐ Do not include participant personal data in asset or event create requests.

Normative machine-readable contract: `myscoutee-client/openapi.yaml`. Reference client and versioned fixtures: `myscoutee-client/src/`.