

Greater Seattle Area Housing—Sales Price Prediction

Francis Tan

2017-02-27

Abstract

The goal of this project is to predict the sale price of a property by employing various predictive machine learning models in an ensemble given housing data such as the number of bedrooms/bathrooms, square footage, year built as well as other less intuitive variables as provided by the Zillow API.

Introduction

The Greater Seattle Area housing market has gone through a dramatic price increase in recent years with the median valuation at \$609,100, an 11.3% increase from last year and a 4.7% increase forecasted for the next year¹. Because of the dramatic change that has occurred in a short period of time, it has become increasingly difficult to predict property values. We believe that a machine learning model can predict a property value with reasonable accuracy given the property features and the time aspect (*lastSoldDate*).

Data Collection and Preprocessing

Data Collection Process

The most important element of any data science project is the data itself. This project heavily utilizes data from Zillow, a digital real estate destination for buyers, sellers, and agents. Fortunately, Zillow provides a public API which provides a convenience to an otherwise tedious task. Although the availability of a public API has made the data collection process simple, there are some limitations that we had to be cognizant of. Our vision was to start with a “seed” property which in turn would collect “comps” or comparables. Comps are simply other properties that have similar features to our seed property. This will provide a buyer an idea of what the value of the property should be.

The first limitation is that the full set of information that we were looking for cannot be extracted from one API endpoint. Zillow does not provide an endpoint which returns property information of comps given a seed property. What it provides instead is one endpoint that returns a list of comp property IDs (Zillow Property ID or ZPID) given a seed property address and a separate endpoint that returns property information given a ZPID. Furthermore, the comp endpoint returns a maximum of 25 comps per seed property. Thus the collection process is divided into three steps:

1. Collect comp IDs given a property address using *GetDeepSearchResults*.
2. Loop through each ZPID, collect 25 more comps for each, and append results to list of the other ZPIDs.
3. Collect property information for each ZPID collected using *GetDeepComps*.

The second limitation is that Zillow has limited the number of calls allowed per day to 1000. This poses a problem if one’s intent was to collect a significant amount of data. This limits our collection process further since we had to resort to making two calls. A simple solution was to include a sleep timer of 24 hours when a

¹Source: Zillow Data as of February 2017.

call encounters a rate limit warning. Although somewhat inconvenient, the solution achieved what we needed to accomplish.

Training Data

The table below is just a sample of what the training data looks like. We've removed many of the columns to make sure the table fits in the page. This is only to provide an idea of the formatting.

street	city	zip	finishedSqFt	lastSoldDate	lastSoldPrice
18314 48th Ave W	Lynnwood	98037	1223	11/07/2016	315000
19011 Grannis Rd	Bothell	98012	1296	10/06/2016	353000
2625 189th St SE	Bothell	98012	3226	02/01/2016	405000
719 John Bailey Rd	Bothell	98012	1200	07/22/2016	360000
5113 212th St SW	Lynnwood	98036	2300	05/12/2016	430000
21132 49th Ave W	Lynnwood	98036	1654	08/01/2016	305000
4715 212th St SW	Lynnwood	98036	1314	08/17/2016	315000
4717 212th St SW	Lynnwood	98036	2112	08/12/2016	445500
7525 Maltby Rd	Snohomish	98296	1936	09/30/2016	491000
22513 44th Ave W	Mountlake Terrace	98043	1344	05/12/2016	443190

Printing the *shape* attribute shows that we have 2826 observations and 23 columns.

```
>>> training_raw.shape
(2826, 23)
```

Finally, we have the following columns

```
>>> training_raw.dtypes
zpid                int64
street              object
city                object
state               object
zip                 object
FIPSCounty          object
useCode             object
taxAssessmentYear   object
taxAssessment       object
yearBuilt           object
lotSizeSqFt         object
finishedSqFt        int64
bathrooms           object
bedrooms            object
lastSoldDate        object
lastSoldPrice       int64
zestimate           object
zestimateLastUpdated object
zestimateValueChange object
zestimateValueLow    object
zestimateValueHigh   object
zestimatePercentile  int64
region              object
dtype: object
```

Since the goal of this project is to predict the sale price, it is obvious that the *lastSoldPrice* should be the response variable while the other columns can act as feature variables. Of course, some processing such as

dummy variable conversion is required before training begins.

Data Processing

The next step is to process and clean the data. First let's take a look at each variable and decide which ones need to be excluded. ZPID and street address logically do not affect sales price and thus can be excluded. Street address may explain some sale price variability, however it requires further processing for proper formatting, that is, we must eliminate unit numbers, suffix standardization (Dr. vs Drive), etc. This proves to be a difficult task that is beyond the scope of this project. Further, the effects of this variable is closely related to region. We have chosen to exclude it here but may be worth exploring further in the future. Finally, the state variable can also be excluded here as we are keeping the scope of this project to WA only.

```
>>> training = training_raw # Save original data intact
>>> training.drop(['zipid', 'street', 'state'], axis=1, inplace=True)
>>> training.dtypes
city                object
zip                 object
FIPScounty          object
useCode             object
taxAssessmentYear   object
taxAssessment       object
yearBuilt           object
lotSizeSqFt         object
finishedSqFt        int64
bathrooms           object
bedrooms            object
lastSoldDate        object
lastSoldPrice       int64
zestimate           object
zestimateLastUpdated object
zestimateValueChange object
zestimateValueLow    object
zestimateValueHigh   object
zestimatePercentile  int64
region              object
dtype: object
```

We can see that many of these variables are of type *object*. We'll need to convert these to the appropriate types. Most of these columns, excluding date columns, can be converted to numeric.

```
cols = training.columns[training.columns.isin([
    'taxAssessmentYear',
    'taxAssessment',
    'yearBuilt',
    'lotSizeSqFt',
    'finishedSqFt',
    'bathrooms',
    'bedrooms',
    'lastSoldPrice',
    'zestimate',
    'zestimateValueChange',
    'zestimateValueLow',
    'zestimateValueHigh',
    'zestimatePercentile'
```

```
]])
for col in cols:
    training[col] = pd.to_numeric(training[col])
```

Now let's convert *lastSoldDate* and *zestimateLastUpdated* to dates.

```
cols = training.columns[training.columns.isin([
    'lastSoldDate',
    'zestimateLastUpdated'
])]
for col in cols:
    training[col] = pd.to_datetime(training[col],
    infer_datetime_format=True)
```

One problem with the *datetime* data type is that it will not work with scikit-learn. So we need to convert this to a numerical type. One way to resolve this is to separate the date columns into year, month, and day.

```
training = training.assign(
    lastSoldDateYear=pd.DatetimeIndex(training['lastSoldDate']).year,
    lastSoldDateMonth=pd.DatetimeIndex(training['lastSoldDate']).month,
    lastSoldDateDay=pd.DatetimeIndex(training['lastSoldDate']).day,
    zestimateLastUpdatedYear=pd.DatetimeIndex(
        training['zestimateLastUpdated']
    ).year,
    zestimateLastUpdatedMonth=pd.DatetimeIndex(
        training['zestimateLastUpdated']
    ).month,
    zestimateLastUpdatedDay=pd.DatetimeIndex(
        training['zestimateLastUpdated']
    ).day
)
training.drop(['lastSoldDate', 'zestimateLastUpdated'], axis=1,
inplace=True)
training.dtypes
```

Next we need to see which of these variables need to be converted to factor variables. City, state, zip, FIPSCounty, useCode, and region all qualify. One thing to caution when creating dummy variables is the number of unique categories each column has. Large number of categories may be impractical for this project as it requires a significant amount of computing resources.

```
>>> training['city'] = training['city'].astype('category')
>>> training['city'].describe()
count      2826
unique       37
top      Seattle
freq       506
Name: city, dtype: object
>>> training['zip'] = training['zip'].astype('category')
>>> training['zip'].describe()
count      2826
unique       52
top     98033
freq       206
Name: zip, dtype: object
>>> training['FIPSCounty'] = training['FIPSCounty'].astype('category')
>>> training['FIPSCounty'].describe()
```

```

count      2826
unique      3
top      53033
freq      2127
Name: FIPSCounty, dtype: object
>>> training['useCode'] = training['useCode'].astype('category')
>>> training['useCode'].describe()
count      2826
unique      2
top      SingleFamily
freq      2785
Name: useCode, dtype: object
>>> training['region'] = training['region'].astype('category')
>>> training['region'].describe()
count      2826
unique     147
top      Bothell
freq      257
Name: region, dtype: object

```

We can see that none of these variables have an unreasonably high number of unique categories with the exception of region. It contains 147 categories which may be too high, however, we will assume that our machine can handle this for now.

Let's take a look at our columns now.

```

>>> training.dtypes
city                category
zip                category
FIPSCounty          category
useCode             category
taxAssessmentYear   float64
taxAssessment        float64
yearBuilt           float64
lotSizeSqFt         float64
finishedSqFt        int64
bathrooms           float64
bedrooms            float64
lastSoldPrice        int64
zestimate            float64
zestimateValueChange float64
zestimateValueLow    float64
zestimateValueHigh   float64
zestimatePercentile  int64
region              category
lastSoldDateDay      int32
lastSoldDateMonth    int32
lastSoldDateYear     int32
zestimateLastUpdatedDay int32
zestimateLastUpdatedMonth int32
zestimateLastUpdatedYear int32
dtype: object

```

Before we convert the categorical columns to dummy variables, let's look at the correlations compared to the sales price.

```
>>> training.corr()['lastSoldPrice'].sort_values(ascending=False,
inplace=False)
lastSoldPrice          1.000000
zestimateValueLow      0.980385
zestimate              0.975082
zestimateValueHigh     0.970668
taxAssessment          0.882125
finishedSqFt           0.705464
bathrooms              0.529689
bedrooms               0.358294
zestimateLastUpdatedDay 0.236169
zestimateValueChange    0.231479
yearBuilt              0.168197
lotSizeSqFt            0.060767
lastSoldDateMonth      0.031076
lastSoldDateYear       0.023216
zestimateLastUpdatedYear 0.011326
taxAssessmentYear      0.002857
lastSoldDateDay        -0.037264
zestimatePercentile     NaN
zestimateLastUpdatedMonth NaN
Name: lastSoldPrice, dtype: float64
```

As suspected, *zestimate* columns are highly correlated to the sales price. A *zestimate* is essentially Zillow's predicted value. Since we are trying to achieve the same thing in this project, let's not include Zillow's efforts here.

```
training.drop(['zestimate', 'zestimateLastUpdatedYear',
              'zestimateLastUpdatedMonth', 'zestimateLastUpdatedDay',
              'zestimateValueChange', 'zestimateValueLow',
              'zestimateValueHigh', 'zestimatePercentile'],
              axis=1, inplace=True)
```

Here are the finished columns.

```
>>> training.dtypes
city          category
zip           category
FIPSCounty    category
useCode       category
taxAssessmentYear  float64
taxAssessment    float64
yearBuilt      float64
lotSizeSqFt    float64
finishedSqFt   int64
bathrooms      float64
bedrooms       float64
lastSoldPrice  int64
region         category
lastSoldDateDay   int32
lastSoldDateMonth int32
lastSoldDateYear  int32
dtype: object
>>> training.describe()
      taxAssessmentYear  taxAssessment  yearBuilt  lotSizeSqFt  \
```

count	2823.000000	2.823000e+03	2824.000000	2810.000000
mean	2014.983351	5.323108e+05	1969.516289	11807.443772
std	0.317356	3.862534e+05	24.165808	17980.249333
min	2008.000000	9.700000e+04	1900.000000	814.000000
25%	2015.000000	3.186000e+05	1955.000000	7200.000000
50%	2015.000000	4.277000e+05	1971.000000	8738.000000
75%	2015.000000	6.080000e+05	1987.000000	11884.000000
max	2015.000000	5.776000e+06	2016.000000	765236.000000

	finishedSqFt	bathrooms	bedrooms	lastSoldPrice
lastSoldDateDay \				
count	2826.000000	2810.000000	2824.000000	2.826000e+03
	2826.000000			
mean	2168.015216	2.355338	3.495397	7.165524e+05
	17.213376			
std	914.006470	0.887511	0.833232	4.927167e+05
	9.022143			
min	520.000000	0.100000	0.000000	1.500000e+05
	1.000000			
25%	1520.000000	2.000000	3.000000	4.270000e+05
	10.000000			
50%	2000.000000	2.100000	3.000000	5.772500e+05
	17.000000			
75%	2600.000000	3.000000	4.000000	8.250000e+05
	25.000000			
max	6753.000000	7.000000	9.000000	5.800000e+06
	31.000000			

	lastSoldDateMonth	lastSoldDateYear
count	2826.000000	2826.000000
mean	6.523355	2015.995046
std	3.016119	0.070223
min	1.000000	2015.000000
25%	4.000000	2016.000000
50%	6.500000	2016.000000
75%	9.000000	2016.000000
max	12.000000	2016.000000

	taxAssessmentYear	taxAssessment	yearBuilt	lotSizeSqFt	finishedSqFt	bathrooms
count	2823.000000	2.823000e+03	2824.000000	2810.000000	2826.000000	2810.000000
mean	2014.983351	5.323108e+05	1969.516289	11807.443772	2168.015216	2.355338
std	0.317356	3.862534e+05	24.165808	17980.249333	914.006470	0.887511
min	2008.000000	9.700000e+04	1900.000000	814.000000	520.000000	0.100000
25%	2015.000000	3.186000e+05	1955.000000	7200.000000	1520.000000	2.000000
50%	2015.000000	4.277000e+05	1971.000000	8738.000000	2000.000000	2.100000
75%	2015.000000	6.080000e+05	1987.000000	11884.000000	2600.000000	3.000000
max	2015.000000	5.776000e+06	2016.000000	765236.000000	6753.000000	7.000000

	bedrooms	lastSoldPrice
count	2824.000000	2.826000e+03
mean	3.495397	7.165524e+05
std	0.833232	4.927167e+05
min	0.000000	1.500000e+05
25%	3.000000	4.270000e+05
50%	3.000000	5.772500e+05
75%	4.000000	8.250000e+05
max	9.000000	5.800000e+06

We can see that the median price in our data set is \$577,000 which is quite high!

As it turns out, we have NaNs in our data as seen below:

```
print(training.isnull().any())
```

```
city                False
zip                 False
FIPSCounty          False
useCode             False
taxAssessmentYear   True
taxAssessment        True
yearBuilt           True
lotSizeSqFt         True
finishedSqFt        False
bathrooms           True
bedrooms            True
lastSoldPrice        False
region              False
lastSoldDateDay      False
lastSoldDateMonth    False
lastSoldDateYear     False
dtype: bool
```

We need to remove these as NaNs will not work in the training process.

```
training.dropna(inplace=True)
print(training.isnull().any())
```

```
city                False
zip                 False
FIPSCounty          False
useCode             False
taxAssessmentYear   False
taxAssessment        False
yearBuilt           False
lotSizeSqFt         False
finishedSqFt        False
bathrooms           False
bedrooms            False
lastSoldPrice        False
region              False
lastSoldDateDay      False
lastSoldDateMonth    False
lastSoldDateYear     False
dtype: bool
```


Dummy Variables

Finally, let's make the dummy variable conversion. This can easily be achieved using the *get_dummies* function.

```
training = pd.get_dummies(training, columns=['city', 'zip',
      'FIPSCounty',
      'useCode', 'region'],
      drop_first=True)
print(training.shape)

(2794, 247)
```

We have 245 columns as shown above, which we can verify by adding the number of unique categories - 1 with the number of non-categorical columns.

Training

Now that we have prepared the data, we can begin the training process. Since we do not have new test data on hand, we will need to split a portion for final evaluation. Let's set aside 20% of the data for just that. We achieve this using scikit-learn's *train_test_split* function.

```
>>> x_train, x_test, y_train, y_test = train_test_split(
...     training.drop('lastSoldPrice', axis=1),
...     training['lastSoldPrice'],
...     test_size=0.2,
...     random_state=1201980
... )
...
```

Ridge Regression

Ridge regression addresses some of the problems of Ordinary Least Squares by imposing a penalty on the size of coefficients²

```
ridge = linear_model.Ridge()
param_grid = {
    'alpha': np.arange(0.1, 10, 0.2)
}
grid = GridSearchCV(ridge, param_grid, cv=10, n_jobs=-1)
grid.fit(x_train, y_train)
print(grid.best_params_)

{'alpha': 6.7000000000000011}
```

²Scikit-learn Documentation (http://scikit-learn.org/stable/modules/linear_model.html#ridge-regression)