Campinas State University

Doctoral Thesis

Search of Z and Higgs boson decaying into $\Upsilon + \gamma$ in pp collisions at CMS/LHC

Author:
Felipe Torres da Silva de Araujo

Supervisor:
Dr. José Augusto Chinellato
Co-Supervisor:
Dr. Alberto Franco de Sá Santoro

A thesis submitted in fulfillment of the requirements
for the degree of Doctor of Physics

in the

Graduate Program of
"Gleb Wataghin" Institute of Physics

August 15, 2020

"*Sometimes science is a lot more art than science. A lot of people don't get that.*"

Rick Sanchez

"*Então, que seja doce. Repito todas as manhãs, ao abrir as janelas para deixar entrar o sol ou o cinza dos dias, bem assim, que seja doce. Quando há sol, e esse sol bate na minha cara amassada do sono ou da insônia, contemplando as partículas de poeira soltas no ar, feito um pequeno universo; repito sete vezes para dar sorte: que seja doce que seja doce que seja doce e assim por diante. Mas, se alguém me perguntasse o que deverá ser doce, talvez não saiba responder. Tudo é tão vago como se fosse nada.*"

Caio Fernando Abreu

CAMPINAS STATE UNIVERSITY

Abstract

"Gleb Wataghin" Institute of Physics

Doctor of Physics

Search of Z and Higgs boson decaying into $\Upsilon + \gamma$ in pp collisions at CMS/LHC

by Felipe Torres da Silva de Araujo

Searches for Standard Model Higgs and Z bosons decaying to a $\Upsilon(1S, 2S, 3S)$ and a photon, with subsequent decay of the $\Upsilon(1S, 2S, 3S)$ to $\mu^+\mu^-$ are presented. The analyses is performed using data recorded by CMS detector from proton-proton collisions at center-of-mass energy of 13 TeV corresponding to an integrated luminosity of 35.86 fb^{-1}. We put a limit, 95% confidence level, on $H \rightarrow \Upsilon(1S, 2S, 3S) + \gamma$ decay branching fraction at (6.8, 7.1, 6.0) $\times 10^{-4}$ and on $Z \rightarrow \Upsilon(1S, 2S, 3S) + \gamma$ decay branching fraction at (2.6, 2.3, 1.3) $\times 10^{-6}$. Contributions to operation, maintenance and R&D of Resistive Plate Chambers (RPC) of CMS are also presented. **EXPANDIR**

Acknowledgements

I would like to thank:

- the Campinas State University for providing the institutional support for this study;
- the Rio de Janerio State University for the cooperation with Campinas State University in their high-energy physics program. This was a key factor for this study;
- the National Council for Scientific and Technological Development (CNPq) for the financial support for this work;
- the European Laboratory for Particle Physics (CERN) for the construction and operation of the Large Hadron Collider (LHC);
- the Compact Muon Solenoid (CMS) collaboration for the construction, operation and provision of the instrumental means for this study.

Contents

1 Introduction

INTRODUÇÃO

USAR UM PAPER DE CMS MUON PERFORMANCE PARA DIZER PORQUE TRABALHAR COM DETECTORES DE MUONS

2 CMS Resistive Plate Chambers - RPC

In the course of this PhD study, there were a lot of opportunities to work for the RPC project, in the context of the CMS Collaboration. The main activities consists of shifts for the RPC operation and data certification, upgrade and maintenance of the online software, R&D activities for the RPC upgrade and detector maintenance during the LHC Long Shutdown 2 (2019 to 2020).

In this chapter, it is presented a summary of the Resistive Plate Chamber technology and the contributions to the RPC project at CMS.

2.1 Resistive Plate Chambers

The seminal paper on the Resistive Plate Chamber (RPC) technology was presented by R. Santonico and R. Cardarelli, in which they described a "dc operated particle detector (...) whose constituent elements are two parallel electrode Bakelite plates between" [1]. The key idea behind the RPC, with respect to other similar gaseous detectors, is the use of two resistive plates as anode an cathode, which makes possible to have a small localized region of dead time, achieving very good time resolution.

The working principle for RPCs relies on the idea that a ionizing particle crossing the detector, tend to interact with the gas gap between the two plates and form a ionizing cascade process, in which the the produced charged particle are driven by the strong uniform electrical field produced by the two plates.

The gas mixture is a key component of a RPC. Even though the first RPCs were produced with a mixture of argon and butane, nowadays RPCs use a mixture of gases that would enhance an ionization caused by the incident particle and quench secondary (background) effects.

Another feature of the RPCs is its construction simplicity and low cost. This allow the use RPC to cover larger at a reasonable cost.

A extensive review of the RPC technology and its application can be found in [2].

DESCREVER A TECNOLOGIA DAS RPCS

DESCEREVER OS PRINCÍPOS DE OPERACAO - TDR

2.2 CMS Resistive Plate Chambers

At CMS, the Resistive Plate Chamber are installed in both the barrel and endcap region, forming a redundant system with the DT (barrel) and CSC (endcap). As described in the CMS Muon Technical Design Report (Muon-TDR) [3], the RPC are composed of 423 endcap chambers and 633 barrel chambers.

Each chamber consists of two gas gaps (double gap), 2 mm tick each, made of Bakelite (phenolic resin) with bulk resistivity of 10^{10} - 10^{11} Ωm. The choice of the bulk resistivity of the electrode has high impact on the rate capability of the detector.

Each gap has its external surface is coated with a thin layer of graphite paint, which acts as conductive material, distributing the applied high-voltage (HV). On top of the graphite a PET film is used for isolation. A sheet of copper strips is sandwiched between the gaps. Everything is wrapped in aluminum case.

The double gap configuration increases the efficiency of the chamber, since the signal is picked up from the OR combination of the two gaps. A chamber with only one gap working, looses around 15% of efficiency, even though, this can be recovered by increasing the HV applied during operation mode (working point - WP).

A characteristic that differentiate the CMS RPC from from previous RPC application in HEP is the operation mode. A RPC at CMS, operates in avalanche mode, while previous experiments used the streamer mode. Both modes are related to the applied HV, in commitment with the strength of the generated signal, and are capable of generate a well localized signal, which can be picked up by the readout electronics, but the avalanche mode offer a higher rate capability around 1 kHZ/cm^2, while the streamer mode goes up to 100 HZ/cm^2. The high rate capability is a key factor in order to cope with requirements of the LHC luminosity, specially in the high background regions.

Besides the rate capability, the key factors that driven the CMS RPC design were: high efficiency ($> 95\%$), low cluster size (> 2) for better spatial resolution (this reflects in the momentum resolution) and good timing in order to do the readout of the signal within the 25 ns of a LHC bunch cross (BX) and provide it to the CMS trigger system. These requirements have implications in the choice of material, dimensions, electronics and gas mixture.

In the barrel, along the radial direction, there are 4 muon layers (called stations), MB1 to MB4. MB1 and MB2 is composed of a DT chamber sandwiched between two RPC chambers (RB1 and RB2) with rectangular shape. The stations MB3 and MB4 have only one RPC (RB3 and RB4) are composed by two RPC chambers (named - and + chambers with the increase of ϕ) attached to one DT chamber, except in sector 9 and 11, where there is only one RPC. RE4, sector 10 is a special case, since it is composed of four chambers (−, -, + and ++). These stations are replicated along the z direction in five different wheels of the CMS (W-2, W-1, W0, W+1 and W+2) and in twelve azimuthally distributed sectors (S1 to S12). Figure 2.1 show the different barrel stations and wheel.

In the endcap, the RPC chambers have a trapezoidal shape and are distributed in four disks (or stations) each side (RE±4, RE±3, RE±2, RE±1), each one with 72 chambers. CMS split up its disks in 3 rings, along the radial direction, and 36 sector in the azimuthal angle. RPCs are present in the two outer rings (R2 and R3), in all 36 sectors. The RE±4 are special cases, since these chambers were installed only in 2014, a design choice was made the mechanically attached R2 and R3 chambers, each sector, in what is called, a super-module. Figure 2.2 show the different endcap disks.

The length of the strips is chosen, for both barrel and endcap, in such a way to control the area of each strip, in order to reduce the fake muons, due to random coincidence. This has to do with the time-of-flight and signal propagation along the strip. In the barrel, each chamber readout is



Figure 2.1: R-ϕ (left) and R-Z (right) projections of the barrel Muon System.

divided in two regions (rolls), called forward and backward (along increasing $|\eta|$) [1]. In the endcap, the strips are divided in 3 regions, called partitions A, B and C (from inside the detector to outside).

The gas mixture used in the CMS RPCs is composed by C2H2F4 (Freon R-134a, tetrafluoroethane), C4H10 (isobutane), SF6 (sulphur hexafluoride) (95.2 : 4.5 : 0.3 ratio) and with controlled humidity of 40% at 20-22 °C. The Freon is used to enhance the ionization and charge multiplication that characterizes the avalanche, while the isobutane is introduced for quenching proposes, in order to reduce the secondary ionizations that could lead to formation of streamers and the SF6 is used to reduce the electron background. The choice of Freon over other gases, i.e. argon-based and helium-based, was motivated by previous studies [4, 5].

Since its R&D, the RPC have shown good performance over aging. This is even historical over previous RPC experiments [6–12]. Even the most recent studies of aging, taking into account future LHC conditions (High-Luminosity LHC - HL-LHC) plus a safety margin of 3 times the expected background (600 HZ/cm^2) have shown good aging hardness [13].

2.2.1 Performance

PERFORMANCE NO RUN2

2.3 Contribution to the CMS RPC project

During the curse of this study, a head collaboration of our research group and the CMS RPC project was established. Many contributions were given to the project as part of the graduation as a experimental particle physicist, with focus on getting acquaintance with a subsystem technology and give a meaningful collaboration to the detector operation. Those are considered by the community important steps on the student graduation.

Bellow it is described the contributions given to the CMS RPC project.

[1]Some chamber are divided in three rolls, forward, middle and backward, for trigger propose.



Figure 2.2: R-Z projections of the endcap Muon System (positive Z side). This is the same configuration for the 36 ϕ sectors.

2.3.1 RPC Operation - Shifts and Data Certification

The first activities done for the CMS RPC project were shifts for data certification of data taken. This certification is done by specialized people for different CMS subsystems and physics objects groups [2].

This certification is done in order to ensure the quality of the date recorded based on the well functionality of each system during the data taking and the reconstruction of the physics objects in the expected matter. A certain collection of data (run) is said certificate when all subsystems and object experts agrees on this.

Figure 2.3 shows, as an example of the luminosity delivered by the LHC, recorded one by CMS and the certified (validated), from the 22nd of April, 2016 to the 27th of October, 2016. Only certified data is available for physics analysis.

Shifts are a continuous weekly activity (specially during the data taking period), performed in a weekly basis, in order to ensure the availability of certified data, as soon as possible.

[2] Groups of reconstruction and performance experts for different high-level reconstructed objects from CMS, i.e. muons, taus, jets/MET, electrons/photons



(a)



CMS preliminary results: April 22nd - October 27th 2016								
Tracker		Calorimeters			Muon Spectrometer			Operational Issue
Pixel	SST	ECAL	ES	HCAL	CSC	DT	RPC	Tracker HV ramp
99.9	99.1	99.3	99.7	99.6	99.9	99.9	99.6	99.5
All good for physics: 96%								

Luminosity weighted fraction (in %) of data certified as good for physics analysis relative to 37.76 / fb of data recorded by the CMS experiment during 2016 proton-proton collisions at 13 TeV with magnet at 3.8T.

Figure 2.3: (a) Luminosity delivered by the LHC, recorded one by CMS and the certified (validated), from the 22nd of April, 2016 to the 27th of October, 2016. (b) Efficiency of the certification process for each subsystem, from the 22nd of April, 2016 to the 27th of October, 2016. Total CMS efficiency is above 90%. [14]

2.4 RPC Online Software

On what concerns the Online Software (OS) of the CMS RPC system, the main contribution given was the upgrade of the Trigger Supervisor libraries.

The Trigger Supervisor is a web-based software, which run over the xDAQ backend and provides, through a mudules organized in a tree system, called cells, a standard inferface for the operation and monitoring of different system at CMS. In principle only systems which contribute directly to the L1 trigger should have a Trigger Supervisor implementation. This was the case for the RPC during the Run1. Since Run2, RPC contributes to the trigger indirectly, by providing data to the muon processors (CPPF, OMTF and TwinMux). The Trigger Supervisor implementation is a legacy from that period.

Each subsystem is responsible for its own implementation of the Trigger Supervisor, based on the functionalities that it wants to have (requirements). The xDAQ [15] is a middleware, developed by CERN and widely used at CMS, as a tool for control and monitoring of data acquisition system in a distributed environment. It is capable of providing a software layer for direct access of hardware functionalities and monitoring.

The upgrade made (figure 2.4), consists in upgrade the higher level of the RPC online software. In summary, up to 2017, the online software, was using Scientific Linux 6 as operational system, which executed xDAQ 12, in turn, servers as backend for Trigger Supervisor 2. A upgrade of the operational system to Centos 7, demanded the upgrade to xDAQ 14. On top of that, Trigger Supervisor 2 would not work and had to be updated to Trigger Supervisor 5 in order to be functional in 2018.

Between versions 2 and 5 of Trigger Supervisor, part of the source-code had to be reworked, keep the majority of the code structures. Most of the changes were made in the front-end of the system. The standard JavaScript library Dojo [16], used in version2, was deprecated in favor of



Figure 2.4: Upgrade of the RPC online software.

Google's Polymer[17]. The main reason for this change was to isolate C++ code from HTML, which was impossible with Dojo. This implied to rewrite all the screen of the RPC Trigger Supervisor implementation, as in figure 2.5.

The upgrade was done in time to ensure the control and operation of the RPC for 2018 data taking.



Figure 2.5: Example of the updated screens, using Trigger Supervisor 5.

2.4.1 iRPC R&D

For the next 4 year of CMS activities it is foreseen the upgrade of the the Muon Systems [3]. These upgrades are planed in order to extend the pseudorapidity coverage (η) and to guarantee the operation conditions of the present system in the HL-LHC (High Luminosity LHC) era. The RPC (Resistive Plate Chambers) [3] subsystem, it will have maintenance of the present chambers and installation of new chambers in the region of $|\eta| < 1,8$ para $|\eta| < 2,4$ [18]. These new chambers (iRPC) will be added in the most internal part of the muon spectrometer, RE3/1 e RE4/1, as in Figure 2.6.

Even thought this region is covered by the CSC detectors CSC (Cathode Strip Chambers), there are some loss of efficiency due the the system geometry. The installation of additional chambers will mitigate this problem and potentially increase the global efficiency of the muon system. The new



Figure 2.6: η projection of the Muon System subdetectors. In purple, is labeled the iRPCS to be installed during the CMS upgrade.

chamber, called iRPC (*improved RPC*), will be different them the present one. For a luminosity of $5 \times 10^{34} cm^{-2}s^{-1}$ the neutrons, photons, electrons and positrons background in the high $|\eta|$ region is expected to by be around 700 Hz$/cm^2$ (for the chambers in RE3-4/1). Applying a safety factor of 3, the new chambers should support up to 2 Hz$/cm^2$ of gamma radiation and still keep more than 95% of efficiency. Studies indicate, so far, that the use of High Pressure Laminates (HPL) for the double gap chambers is the most suitable choice. In order to reduce the aging and increase the rate capability, the electrodes and the gap size should be reduced in comparison with the present system.

One of the challenges for the R&D of the iRPC chambers is measuring the their performance in a high radiation environment, as the one for HL-LHC. For this, the CMS RPC project uses the Gamma Irradiation Facility (GIF++) [19], at CERN. The GIF++ is located at the H4 beam line in EHN1 providing high energy charged particle beams (mainly muon beam with momentum up to 100 GeV/c), combined with a 14 TBq 137-Cesium source. In the GIFF++ it is possible to achieve the HL-LHC total dose in a much reasonable amount of time. With the shutdown of LHC, the muon beam source is also off and will stay like this for 3 years. This means that the only muon sources for studies in GIF++ are cosmic muons.

In order to create a trigger system for iRPC R&D, the usual procedure is to use scintillators, on the top and on the bottom of the chamber. This is effective, but in a high gamma radiation environment, scintillators can be very sensitive which could lead to an undesirable amount of fake triggers which can degrade the measurements. Also, if one wants to covers a large area with scintillators, this can be expensive and they will not provide any means of tracking to measuring not only the global, but also the local chamber performance.

To provide a solution, the CMS RPC got in agreement with the LHCb [20] Muon Project to use their Multiwire Proportional Chambers (MWPC) [21], which were removed from LHCb, to be replaced by new chambers, and use them as trigger and/or tracking system at GIF++. This chambers, by design, have relatively low gamma sensitivity, already have some 1-dimensional resolution (O(cm)) and, the biggest advantage, with respect to any other gaseous particle detector option: LHCb has hundreds of vacant chambers. Any other detector would have to be build.

Not going in details of the MWPC technology nor the LHCb chamber construction [22], these chambers have a total active area of 968 $\times$ 200 mm^2 divided 2 layers (top and bottom) of 24 wire pads (40 $\times$ 200 mm^2) composed of around 25 wires/channel, grouped by construction. Each chamber is equipped with 3 FEBs (Front-End Boards) with 16 pads each.

A channel is a logical combination of a top layer (pads) and a bottom layer readout. These readouts can be combined in AND or OR logics. One can have 8 channels per FEB, each channel being a logical combination of top and bottom pads. In this mode they are called AND2 and OR2. It is also possible to have the FEB configured in a 2 channels mode, each one corresponding to one sixth of the total readout pads. In this mode, all the pads can be combined in OR (called OR8) or they can be AND'ed in top and bottom pads and then group in OR (called OR4AND2). Figures 2.7 and 2.8 presents a logical diagram for each readout mode.



Figure 2.7: FEB configured 8 channels modes. Group should be understood as wire pad. Left: Logical diagram for OR2. Right: Logical diagram for AND2.

The nominal gas mixture for these chambers is Ar/CO2/CF4 (40:55:5). For a matter of simplicity, it was used an already available similar gas line in the same building, used by CMS CSC



Figure 2.8: FEB configured 2 channels modes. Left: Logical diagram for OR8. Group should be understood as wire pad. Right: Logical diagram for OR4AND2.

(Cathode Strip Chamber) [3], which has a similar composition (40:50:10). Optimal conditions are obtained with 2 to 4 liters/hour of gas flux and 2.65 kV of applied voltage.

Figure 2.9 shows the setup that was prepared for commissioning of this chambers. It was mounted two chambers on top of another (chambers A and B) above an RPC R&D chamber and two other chambers on the bottom (chambers C and D). These four MWPC will be used as telescope for the RPC chamber. All the services were mounted in rack, as in Figure 2.9. This includes power supply (low voltage and high voltage), distribution panel, VME crate and boards for FEB control, computer for control (high voltage, and FEB control) and NIM crate and boards for LVDS to NIM signal conversion, logics and counting.

Due to the short amount of time available for the commissioning, only two measurements measurements were made with these chambers. They were meant to be a proof of concept for future activities.

The first measurement was to measure the coincidence rate of two chambers as a function of the distance between the two top planes (Figure 2.10). This measurements were done with nominal working point, with one FEB configured in 2 channels mode with 7 pC threshold, in (160 mm x 160 mm) area per chamber. One can observe that, if we go for a telescope trigger in the order of 1 meter of separation between the chamber, the logical combination chosen has negligible effect in the coincidence rate. Also, the fits can be used to estimate the rate in a configuration with chamber on the roof and under the floor. This could be the case of a universal trigger, to be mounted in GIF++ with these chamber.

The second measurement consist on evaluate the impact of γ background by placing a small Cs-137 source on top of the chamber A (Figure 2.11). For this measurement, the distance between top planes of each pair of chamber (A to B and C to D) is 65 mm, while the distance between the



Figure 2.9: Left: Setup mounted for commissioning. Two MWPC chamber on the top (chambers A and B) and two (chambers C and D) on the bottom with a RPC R&D in the middle. Right: Rack with all the services for the operation of these chambers.

top planes of A and C is 570 mm. It is clear the the γ source has an impact on chamber A rate, but this is negligible when we take into account the coincidence between two chambers.

This two measurements were enough to validate this chambers as possible trigger pro RPC R&D with cosmic muons in the laboratory and at GIF++. The next steps would be use this MWPC chamber to implement a tracking system from triggering. This would demand some developments, since, due to bandwidth restrictions, the signal from each FEB would have to go to a programmable fast electronics, i.e. a FPGA, which would reconstruct muon tracks and provide the trigger to the DAQ system. This can be done by placing the two pair of chambers (AB and CD) in orthogonal configuration and read the signal in a CAEN V2495 board [23].



Figure 2.10: Coincidence rate of two chambers with respect to an arbitrary distance between the two top planes. Measured in 10 minutes, for 2 logical combinations (OR8 and OR4AND2). Applied high voltage: 2.65 kV. Threshold: 7 pC. Active area: readout of 160 mm x 160 mm per chamber.



Figure 2.11: Individual rates (chambers A, B, C and D) and coincidence rates for two chambers (A AND B, C AND D), for without γ source (blue), a shielded γ source (orange) and an unshielded γ source (green). Source sitting on top of chamber A. Applied high voltage: 2.65 kV. Threshold: 7 pC. Active area: readout of 160 mm x 320 mm per chamber. Logical combination: AND2

2.4.2 LS2 and the RPC Standard Maintenance

In December 2018, the LS2 (Long Shutdown 2) was started. This a period in which the LHC and its detectors (CMS included) stop their operation for maintenance and upgrade. The LS2 will go up to 2021, when LHC and CMS restart the data taking with the Run3.

During the LS2 it is being installed services for the new chambers (gas pipes, low voltage (LV), cables, signal and control optical fibers, high voltage (HV) cable and support equipment, and HV/LV power supplies), as well as continuity to the to the RPC R&D studies, besides the reparation of broken elements of the present system, i.e. chamber in the barrel region which present gas leak problems, maintenance of the LV and HV connectivity and power system, maintenance of the control system of problematic chambers (Front-Ends boards, cabling and Distribution Boards) and the dismount and reinstallation of four stations in the endcap (RE4) on both sides of CMS [24].

What concerns the standard maintenance of the present RPC system, the main LS2 activities in which the student was involved, can be divided in three main tasks: (a) HV maintenance, (b) LV and control maintenance and (c) detector commissioning.

HV maintenance

A key factor of and RPC performance is the applied high voltage (HV). The CMS RPC achieve their optimal performance with, around, 9.5 kV applied in each gap. This voltage is in the range of the dielectric breakdown of many gases, which could lead to potential current leakages, if some part of the system is damaged, poorly operated or badly installed. If the currents are high enough this can make impossible the operation of the chamber. In cases like this, during the operation period (data taking), the problematic HV channel is identified and turned off (each chamber has two channels, one for each lawyer of gaps). Chambers in this situation are said to be operating in single gap mode (SG).

The goal for the HV maintenance is to, now that the CMS is off and the chambers are accessible, identify which part of the HV supply system is causing the current leak and fix it the best way possible. Usually the problem is beyond the power supply, very often connectors or the gap itself are damaged.

The CMS RPCs uses two kind of HV connectors, monopolar and tripolar connector. The monopolar are used to connect the chamber to the power supply. If mounted properly, rarely they present problems. The connection to the chamber is made by tripolar connectors, in which the ground and the HV for both gaps arrives to the chamber in a single connector, for simplicity and to save space in the patch panel. Unfortunately these connectors are relatively fragile, and they could be a potential source of leak, specially if they were poorly mounted, badly operated or with aging itself. Also, since this was a connector made exclusively for the CMS RPC system, some design choices had to be improved after the installation of other chamber. Those installed with old batches of tripolar connectors are sensitive ones. The reparation of this connectors consists in isolate the connector from the chamber and power it up to 15 kV (maximum voltage allowed by the system). If the tested connector is broken one will observe a very fast increase in the current of the HV channel. The only solution to this kind of problem is to replace the connector.

On the other hand, if the connector is powered isolated and pass the test, the problem beyond the connector (assuming that the power system have already been tested), i.e. inside the chamber. When a chamber is in SG mode it means that a full layer is off, but not necessarily all the gaps in that layer are bad (a RPC can have up to three per layer). In this situation, the procedure consists in cutting the cables that comes from the gaps to the chamber side connector one by one and identify which gap of the problematic layer is the broken by powering it. Once identified, this gap should isolated and the other ones reconnected. The broken gap is unrecoverable, since it is inside the chamber, but 5% to 10 % of efficiency can be retaken, without changing the applied HV and increasing the longevity of the chamber.

Another contribution to the HV maintenance was the proposal of a procedure to replace the problematic tripolar connector by a monopolar (also called jupiter) connector, which are known for being much more stable and reliable. The figure 2.12 (left) show the designed adapter for the chamber patch panel which would made this change possible. Figure 2.12 (right) shows a tryout of a chamber in which this procedure was tested. The proposal was presented to the RPC community and approved to be used from now on. Technical drawings and instructions were provided.



Figure 2.12: Left: Proposed adapter the chamber patch panel which make it possible to replace a tripolar by a jupiter HV connector. Right: Try out of the proposed HV connector replacement.

LV and control maintenance

The low voltage (LV) and control maintenance consists in make sure that the Front-End Boards (FEBs) are powered and configurable, which means that the LV power system is working from supply board to the cable, that the signal cables are in good state and properly connected to the chamber and to the link boards and that the on-detector electronics (FEBs and Distribution Boards - DBs) are working fine.

Usually, this system is very reliable. The weak point, in most of the cases, is the detector electronics. When a FEB [25] (as in Figure 2.13) is problematic it can present regions of very high noise or no signal at all (silent), which can not be recovered by the threshold control. In cases like this, when the FEB is accessible, it can be replaced in order to recover efficiency in the problematic chamber. This procedure is done by extracting the chamber from inside the detector (only for barrel chamber) and opening its cover to have access to the problematic component. Removed boards are send back to production labs for refurbishment.



Figure 2.13: RPC Front-end board (FEB) used in the barrel chambers.

The most usual problem is a chamber in which the threshold control was lost. For those chamber, most probably, the problem is in the distribution board of the chamber, which is a piece of hardware responsible for distribute the LV power to the FEBs (3 to 6 per chamber) and send the threshold control signal to the FEBs via I2C line. If a chamber has no threshold control, it means that the RPC operation has no control over the signal selection, which can potentially induce performance issues.

For the barrel this maintenance happens concomitantly with the gas leak reparations on the barrel chamber, since both demands the chamber extraction, which is a complex procedure in terms of operation and demands specialized equipment and manpower. For technical reasons, the gas leak extractions have precedence over LV ones.

Detector commissioning

All the LS2 activities demands uncabling of the chamber to be repaired and possibly some neighbor chambers. Also, it can involve the replacement of components of the chamber. To avoid damage to the system a compromising procedure is needed after all this activities. Given the responsibilities of the commissioning it was necessary to: (a) make sure that the the RPC system keep tracks of all the interventions, (b) maintain all the algorithms used in the commissioning procedure, (c) together with the RPC Coordination, define a pool of people and a schedule to the commissioning of the system and (d) follow-up, with other CMS RPC experts, the availability of materials and resources for the commissioning operations.

Besides the organizational tasks, the commissioning demanded to establish procedures to ensure the connectivity and functionality of HV and LV connections. For the HV, it is needed to make sure that the chambers are properly connected, without miscabling [3] and that the currents at stand-by HV and working point HV are compatible with the ones in the end of last data-taking (end of 2018). This activity will start in November/2019, when the CMS RPC Standard Gas Mixture will be available again.

[3] Mixed cable connections.

For the LV point of view, the LV power cable and signal cables should also be properly connected, and presenting a noise profile compatible with last data-taking. One key point for this task is to make sure that that there are no miscabling of signal cable. One RPC chamber can have from 6 to 18 signal cable, which are connected very close one to another. There is a good chance that a chamber, after reparation, have its signal cables mixed. In order to diagnose situations like this, it was validated a algorithm present in the RPC Online Software, but never used since LS1, which, by changing the threshold of each component of the RPC system, from very high to very low values (component by component), can spot miscabled chambers. Since the control line is independent of the signal line, a misclabed will present a different noise from what is expected.

Besides the validation of this algorithm, it was also implemented a web system (Figure 2.14), developed in Flask [26] wich automatize the execution of the algorithm, making transparent to the shifter (or the one performing the commissioning) the procedure to get miscabling report.



FEB Connectivity Test - Analysis

Worker	Date (YY-MM-DD)	Time (HH:MM:SS)	Hash	
RBP2_Far	2019-06-20	23:43:19	387534dst	Run Analyzer
RBP1_Far	2019-06-20	20:12:20	458306dst	Run Analyzer
RBP1_Far	2019-06-20	20:04:46	336162dst	Run Analyzer
RBP1_Near	2019-06-20	19:02:00	377863dst	Run Analyzer
RBP1_Near	2019-06-19	18:59:00	858950dst	Run Analyzer
RBP1_Far	2019-06-19	18:58:26	994787dst	Run Analyzer
YEN3_Far	2019-05-07	10:28:23	176278dst	Run Analyzer
YEN3_Near	2019-05-07	10:28:08	347504dst	Run Analyzer
YEN1_Far	2018-12-07	15:03:24	575561	Run Analyzer
RB0_Far	2018-12-07	14:45:42	101463	Run Analyzer
RBP1_Far	2018-12-07	09:12:00	477689	Run Analyzer

Figure 2.14: RPC FEB Commissioning Analyzer.

The LV commissioning is ongoing, since it happens, as much as possible, right after the chamber reparation.

Bibliography

[1] R. Santonico and R. Cardarelli. “Development of resistive plate counters”. In: *Nuclear Instruments and Methods in Physics Research* 187.2 (1981), pp. 377–380. ISSN: 0167-5087. DOI: https://doi.org/10.1016/0029-554X(81)90363-3. URL: http://www.sciencedirect.com/science/article/pii/0029554X81903633.

[2] Marcello Abbrescia, Paulo Fonte, and Vladimir Peskov. *Resistive gaseous detectors: designs, performance, and perspectives.* Weinheim: Wiley-VCH, 2018. DOI: 10.1002/9783527698691.

[3] *The CMS muon project: Technical Design Report.* Technical Design Report CMS. Geneva: CERN, 1997. URL: https://cds.cern.ch/record/343814.

[4] P. Bernardini et al. “Precise measurements of drift velocities in helium gas mixtures”. In: *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment* 355.2 (1995), pp. 428–433. ISSN: 0168-9002. DOI: https://doi.org/10.1016/0168-9002(94)01144-3. URL: http://www.sciencedirect.com/science/article/pii/0168900294011443.

[5] E. Gorini et al. “Drift velocity measurements in C2H2F4 based mixtures”. In: *Proceedings of the 4th International Workshop on Resistive Plate Chamber and Related Detectors, in Napoli, Italy, 15-16 October* (1997).

[6] G. Bressi et al. “AN APPARATUS TO SEARCH FOR FREE NEUTRON ANTI-NEUTRON OSCILLATIONS”. In: *Nucl. Instrum. Meth. A* 261 (1987), pp. 449–461. DOI: 10.1016/0168-9002(87)90353-6.

[7] H.L. Ge et al. “The production of residual nuclides in Pb irradiated by 400 MeV/u carbon ions”. In: *Nucl. Instrum. Meth. B* 337 (2014), pp. 34–38. DOI: 10.1016/j.nimb.2014.07.024.

[8] M. Abbrescia et al. “A Horizontal muon telescope implemented with resistive plate chambers”. In: *Nucl. Instrum. Meth. A* 336 (1993), pp. 322–329. DOI: 10.1016/0168-9002(93)91116-5.

[9] L. Antoniazzi et al. “The E771 RPC muon detector”. In: *Nucl. Instrum. Meth. A* 315 (1992), pp. 92–94. DOI: 10.1016/0168-9002(92)90686-X.

[10] A. Di Ciaccio et al. “Muon tracking and hadron punchthrough measurements using resistive plate chambers”. In: *Nucl. Instrum. Meth. A* 315 (1992), pp. 102–108. DOI: 10.1016/0168-9002(92)90688-Z.

[11] R. de Asmundis. “Performances of the RPC trigger system in the L3 experiment”. In: *3rd International Workshop on Resistive Plate Chambers and Related Detectors (RPC 95)*. 1995, pp. 139–155.

[12] D. Boutigny et al. “BaBar technical design report”. In: (Mar. 1995).

[13] Andrea Gelmi. *Longevity studies for the CMS-RPC system.* Tech. rep. CMS-CR-2018-136. Geneva: CERN, July 2018. URL: `https://cds.cern.ch/record/2634505`.

[14] *Public CMS Data Quality Information.* twiki.cern.ch/twiki/bin/view/CMSPublic/DataQuality. Acessado em: 20/02/2018.

[15] Johannes Gutleber, Steven Murray, and Luciano Orsini. "Towards a homogeneous architecture for high-energy physics data acquisition systems". In: *Computer Physics Communications* 153.2 (2003), pp. 155–163. ISSN: 0010-4655. DOI: `https://doi.org/10.1016/S0010-4655(03)00161-9`. URL: `http://www.sciencedirect.com/science/article/pii/S0010465503001619`.

[16] *Dojo.* https://dojotoolkit.org/. Acessado em: 20/02/2018.

[17] *Polymer Project.* Acessado em: 20/02/2018.

[18] M. I. Pedraza-Morales. *RPC upgrade project for CMS Phase II.* 2018. arXiv: `1806.11503 [physics.ins-det]`.

[19] Dorothea Pfeiffer et al. "The radiation field in the Gamma Irradiation Facility GIF++ at CERN". In: *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment* 866 (2017), pp. 91–103. ISSN: 0168-9002. DOI: `https://doi.org/10.1016/j.nima.2017.05.045`. URL: `http://www.sciencedirect.com/science/article/pii/S0168900217306113`.

[20] A. Augusto Alves Jr. et al. "The LHCb Detector at the LHC". In: *JINST* 3 (2008), S08005. DOI: `10.1088/1748-0221/3/08/S08005`.

[21] Georges Charpak et al. "The Use of Multiwire Proportional Counters to Select and Localize Charged Particles". In: *Nucl. Instrum. Meth.* 62 (1968), pp. 262–268. DOI: `10.1016/0029-554X(68)90371-6`.

[22] *LHCb Muon Group Home Page.* [Online; accessed 1-October-2019]. 2019. URL: `http://lhcb-muon.web.cern.ch/lhcb-muon/`.

[23] *CAEN Programmable Logic Unit - V2495.* [Online; accessed 1-October-2019]. 2019. URL: `https://www.caen.it/products/v2495/`.

[24] *Resistive Plate Chambers are getting dolled up.* https://cms.cern/news/resistive-plate-chambers-are-getting-dolled. Acessado em: 20/09/2019.

[25] C. Binetti et al. "A new Front-End board for RPC detector of CMS". In: (Sept. 1999).

[26] *Flask (web framework).* [Online; accessed 1-October-2019]. 2019. URL: `https://palletsprojects.com/p/flask/`.