



INSTALACIÓN MYSQL + PHPMYADMIN

Despliegue de Aplicaciones Web

Javier Ruiz Muro

```
Ubuntu Server - VMware Workstation
File Edit View VM Tabs Help
root@javierrm:~# aptitude install mysql-server
Se instalarán los siguiente paquetes NUEVOS:
 libbcgi-fast-perl{a} libbcgi-pm-perl{a} libclone-perl{a} libencode-locale-perl{a}
 libevent-pthreads-2.1-7{a} libfcgi-bin{a} libfcgi-perl{a} libfcgi01db1{a}
 libhtml-parser-perl{a} libhtml-tagset-perl{a} libhtml-template-perl{a} libhttp-date-perl{a}
 libhttp-message-perl{a} libio-html-perl{a} liblwp-mediatypes-perl{a} libmecab2{a}
 libprotobuf-lite23{a} libtimedate-perl{a} liburi-perl{a} mecab-ipadic{a} mecab-ipadic-utf8{a}
 mecab-utils{a} mysql-client-8.0{a} mysql-client-core-8.0{a} mysql-common{a} mysql-server
 mysql-server-8.0{a} mysql-server-core-8.0{a}
0 paquetes actualizados, 28 nuevos instalados, 0 para eliminar y 14 sin actualizar.
Necesito descargar 29,3 MB de ficheros. Después de desempaquetar se usarán 242 MB.
¿Quiere continuar? [Y/n/?]
```

```
root@javierrm:~# /usr/bin/mysqladmin -u root password aa
mysqladmin: [Warning] Using a password on the command line interface can be
Warning: Since password will be sent to server in plain text, use ssl con
safety.
root@javierrm:~# mysql -u root mysql
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A
```

```
root@javierrm:~# aptitude install mysql-admin
No se puede encontrar ningún paquete cuyo nombre o descripción coincida con "mysql-admin"
Unable to apply some actions, aborting
```

```
root@javierrm:~# aptitude install mysql-query-browser
No se puede encontrar ningún paquete cuyo nombre o descripción coincida con "mysql-query-browser"
Unable to apply some actions, aborting
root@javierrm:~# _
```

```
root@javierrm:~# mysql -h localhost -u root
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 14
Server version: 8.0.32-0ubuntu0.22.10.2 (Ubuntu)

Copyright (c) 2000, 2023, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> create database javierDAW;
Query OK, 1 row affected (0,01 sec)

mysql> _
```

```
mysql> drop database javierDAW;
Query OK, 0 rows affected (0,02 sec)

mysql> _
```

```
root@javierrm:~# mysqldump -h localhost -u root javierDAW > backup.sql
root@javierrm:~# _
```

```
root@javierrm:~# mysqldump -h localhost -u root javierDAW < backup.sql
-- MySQL dump 10.13 Distrib 8.0.32, for Linux (x86_64)
--
-- Host: localhost    Database: javierDAW
--
-- Server version      8.0.32-0ubuntu0.22.10.2

/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
/*!50503 SET NAMES utf8mb4 */;
/*!40103 SET @OLD_TIME_ZONE=@@TIME_ZONE */;
/*!40103 SET TIME_ZONE='+00:00' */;
/*!40014 SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0 */;
/*!40014 SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS, FOREIGN_KEY_CHECKS=0 */;
/*!40101 SET @OLD_SQL_MODE=@@SQL_MODE, SQL_MODE='NO_AUTO_VALUE_ON_ZERO' */;
/*!40111 SET @OLD_SQL_NOTES=@@SQL_NOTES, SQL_NOTES=0 */;
/*!40103 SET TIME_ZONE=@OLD_TIME_ZONE */;

/*!40101 SET SQL_MODE=@OLD_SQL_MODE */;
/*!40014 SET FOREIGN_KEY_CHECKS=@OLD_FOREIGN_KEY_CHECKS */;
/*!40014 SET UNIQUE_CHECKS=@OLD_UNIQUE_CHECKS */;
/*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;
/*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;
/*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;
/*!40111 SET SQL_NOTES=@OLD_SQL_NOTES */;

-- Dump completed on 2023-02-13 15:48:20
root@javierrm:~#
```

```
root@javierrm:~# apt update
Obj:1 http://es.archive.ubuntu.com/ubuntu kinetic InRelease
Obj:2 http://es.archive.ubuntu.com/ubuntu kinetic-updates InRelease
Obj:3 http://es.archive.ubuntu.com/ubuntu kinetic-backports InRelease
Obj:4 http://es.archive.ubuntu.com/ubuntu kinetic-security InRelease
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
Se pueden actualizar 14 paquetes. Ejecute «apt list --upgradable» para verlos.
root@javierrm:~# apt install phpmyadmin php-mbstring php-zip php-gd php-json php-curl
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
php-mbstring ya está en su versión más reciente (2:8.1+92ubuntu1).
fijado php-mbstring como instalado manualmente.
php-zip ya está en su versión más reciente (2:8.1+92ubuntu1).
fijado php-zip como instalado manualmente.
php-gd ya está en su versión más reciente (2:8.1+92ubuntu1).
fijado php-gd como instalado manualmente.
php-curl ya está en su versión más reciente (2:8.1+92ubuntu1).
fijado php-curl como instalado manualmente.
Paquetes sugeridos:
  php-recode www-browser php-gd2 php-pragmarx-google2fa-qrcode php-code-its-u2f-php-server
  php-paragonie-sodium-compatible
Se instalarán los siguientes paquetes NUEVOS:
  php-json phpmyadmin
0 actualizados, 2 nuevos se instalarán, 0 para eliminar y 14 no actualizados.
Se necesita descargar 1.834 B/4.456 kB de archivos.
Se utilizarán 34,9 MB de espacio de disco adicional después de esta operación.
¿Desea continuar? [S/n] _
```

Configuración de paquetes

Configuración de phpmyadmin	
Por favor, elija el servidor web que se debería configurar automáticamente para que ejecute phpMyAdmin.	
Servidor web que desea reconfigurar automáticamente:	
<input checked="" type="checkbox"/>	apache2
<input type="checkbox"/>	lighttpd
<div><Ok> <Cancel></div>	

```
99 apt-get purge phpmyadmin
100 apt update
101 apt install phpmyadmin php-mbstring php-zip php-gd php-json php-curl
102 reboot
103 shutdown
104 apt install phpmyadmin
105 phpenmod mbstring
106 systemctl start apache2
107 systemctl status apache2
108 ifconfig
109 mysql -u root
110 nano /etc/apache2/conf-available/phpmyadmin.conf
111 systemctl restart apache2
112 gksu gedit /etc/apache2/apache2.conf
113 nano /etc/apache2/apache2.conf
114 systemctl restart apache2
115 systemctl status apache2
116 apt install php
117 systemctl stop apache2
118 apt install libapache2-mod-php
119 nano /etc/apache2/httpd.conf
120 systemctl start apache2
121 systemctl status apache2
122 history
```

```
GNU nano 6.4 /etc/apache2/apache2.conf
</FilesMatch>

#
# The following directives define some format nicknames for use with
# a CustomLog directive.
#
# These deviate from the Common Log Format definitions in that they use %0
# (the actual bytes sent including headers) instead of %b (the size of the
# requested file), because the latter makes it impossible to detect partial
# requests.
#
# Note that the use of %{X-Forwarded-For}i instead of %h is not recommended.
# Use mod_remoteip instead.
#
LogFormat "%v:%p %h %l %u %t \"%r\" %>s %0 \"%{Referer}i\" \"%{User-Agent}i\"" vhost_combined
LogFormat "%h %l %u %t \"%r\" %>s %0 \"%{Referer}i\" \"%{User-Agent}i\"" combined
LogFormat "%h %l %u %t \"%r\" %>s %0" common
LogFormat "%{Referer}i -> %U" referer
LogFormat "%{User-agent}i" agent

# Include of directories ignores editors' and dpkg's backup files,
# see README.Debian for details.


# Include generic snippets of statements
IncludeOptional conf-enabled/*.conf


# Include the virtual host configurations:
IncludeOptional sites-enabled/*.conf

# vim: syntax=apache ts=4 sw=4 sts=4 sr no
Include /etc/phpmyadmin/apache.conf
```

```
GNU nano 6.4 /etc/apache2/httpd.conf
DirectoryIndex index.php index.php3 index.html index.htm
```

[Read 1 line]




Bienvenido a phpMyAdmin

Mioma - Language
Español - Spanish

Iniciar sesión ⓘ

Usuario:

Contraseña: