

Package ‘GHAgricProductivityLab’

November 11, 2025

Type Package

Title Agricultural Productivity in Ghana

Version 0.0.0.9000

Author Francis Tsiboe [aut, cre] (<<https://orcid.org/0000-0001-5984-1072>>)

Maintainer Francis Tsiboe <ftsiboe@hotmail.com>

Contributor -

Reviewer -

Creator Francis Tsiboe

Description Provides tools and datasets for investigating the drivers of agricultural production short-falls in Ghana.

It compiles research studies that examine farmer-specific and institutional factors to assess whether inefficiencies arise from technical inefficiency, technology gaps, or both. The package offers empirical evidence to inform policy discussions and interventions aimed at improving agricultural productivity, particularly in contexts with limited access to modern technologies.

License GPL-3 + file LICENSE

URL <https://github.com/ftsiboe/GHAgricProductivityLab>

BugReports <https://github.com/ftsiboe/GHAgricProductivityLab/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

VignetteBuilder knitr

Depends R (>= 4.1.0)

Imports MatchIt, data.table, haven, stats

Remotes github::dylan-turner25/rfcip

Suggests dplyr, knitr, crayon, tidyr, withr, rmarkdown, cobalt, dplyr, doBy, stringr, testthat (>= 3.0.0)

LazyData true

Cite-us If you find it useful, please consider starring the repository and citing the following studies

- Tsiboe, F. and Turner, D. (2025). ``Incorporating buy-up price loss coverage into the United States farm safety net." Applied Economic Perspectives and Policy.
- Tsiboe, F., et al. (2025). ``Risk reduction impacts of crop insurance in the United States."

Applied Economic Perspectives and Policy.
- Gaku, S. and Tsiboe, F. (2024). Evaluation of alternative farm safety net program combination strategies. Agricultural Finance Review.

Contents

covariate_balance	2
draw_matched_samples	3
draw_match_sample_specifications	4
functional_forms	5
get_crop_area_list	6
harmonized_data_prep	6
sf_functional_forms	7
sf_model_specifications	8
study_setup	10
treatment_effect_calculation	10
treatment_effect_summary	12
write_match_formulas	13
Index	14

covariate_balance	<i>Compute Covariate Balance Summaries Across Matching Specs</i>
-------------------	--

Description

Compute Covariate Balance Summaries Across Matching Specs

Usage

```
covariate_balance(match_specifications, matching_output_directory)
```

Arguments

- match_specifications
data.frame/data.table with at least columns: boot, ARRAY, and the spec fields stored in RDS (e.g., method, distance, link).
- matching_output_directory
Directory containing RDS files named as "0001.rds", "0002.rds", etc.

Details

Reads each matching result RDS (expected to contain m.out and match_specifications), extracts balance via `cobalt::bal.tab`, reshapes, computes a composite balance $rate = mean((Diff - 0)^2, (KS - 0)^2, (V_{Ratio} - 1)^2)$, and averages by ARRAY, method, distance, link, sample.

Value

- A list with:
 - rate
data.frame of mean balance metrics by spec (Adj sample only) with a composite rate.
 - bal_tab
long-format balance table per covariate/stat/sample/spec.

draw_matched_samples *Draw matched samples (stratified bootstrap + matching)*

Description

Performs stratified resampling at the Surveyx, EaId level (excluding EaIds listed for the current bootstrap ID) and computes adjusted sampling weights used for matching. Then fits a matching model per match_specifications[i,] using **MatchIt**, with exact matching on Emch and distance/link from match_specifications.

Usage

```
draw_matched_samples(
  i,
  data,
  match_variables_exact,
  match_variables_scaler,
  match_variables_factor,
  match_specifications,
  sample_draw_list,
  verbose = FALSE
)
```

Arguments

i	Integer index selecting the row of match_specifications to use.
data	A data.frame/data.table containing at least: Surveyx, EaId, HhId, Mid, UID, Weight, Treat, plus columns named in Emch, Scle, Fixd.
match_variables_exact	A character vector of variable names to be included in the exact match component (e.g., "gender", "region").
match_variables_scaler	A character vector of continuous or scalar variable names to include as covariates in the general match formula (e.g., "age", "income").
match_variables_factor	A character vector of factor variable names to be included as dummy-coded categorical covariates in the general match formula.
match_specifications	Data frame of matching specifications with columns boot, method, distance, and optionally link.
sample_draw_list	Data frame where column ID identifies the bootstrap draw, and each remaining column corresponds to a Survey containing the sampled EaId.
verbose	Logical; if TRUE, prints the chosen matching method and timing. Default FALSE.

Details

Adjusted weights are computed as $pWeight = Weight \times (alloc/allocj)$, where alloc is the pre-exclusion sum of Weight by Surveyx, EaId and allocj is the post-exclusion sum.

Exact matching is performed on variables in Emch. The distance model formula is constructed as $\text{Treat} \sim \text{Scle} + \text{Fixd}$. When `distance == "glm"`, `m.order = "largest"` is used; otherwise `"closest"`.

Value

A list with:

`match_specifications` The selected row from `match_specifications`.
`m.out` The `matchit` object.
`md` Matched data: `Surveyx`, `EaId`, `HhId`, `Mid`, `UID`, `weights`, `pWeight`.
`df` The analysis data with adjusted weights: `Surveyx`, `EaId`, `HhId`, `Mid`, `UID`, `pWeight`.

`draw_match_sample_specifications`

Draw / Match Sample Specifications

Description

Generates (i) a draw list by sampling `EaId` within each unique Survey group and (ii) a grid of matching specifications for each bootstrap draw.

Usage

```
draw_match_sample_specifications(drawN, data, myseed = 3242025)
```

Arguments

<code>drawN</code>	Integer. The number of draws to perform per Survey.
<code>data</code>	A <code>data.frame</code> or <code>data.table</code> containing at least the columns <code>Survey</code> and <code>EaId</code> .
<code>myseed</code>	Integer. Seed for random number generation (default 03242025).

Details

Draw list: For each unique value of `Survey`, the function samples `drawN` `EaId` values with replacement and prepends a 0 row (`ID = 0`) for the baseline. The result is then spread to wide format with one column per `Survey`.

Matching specs: For each draw ID, creates a set of matching model specifications that include:

- Nearest neighbor with distances: `"euclidean"`, `"scaled_euclidean"`, `"mahalanobis"`, `"robust_mahalanobis"`.
- Nearest neighbor with distance `"glm"` and links: `"logit"`, `"probit"`, `"cloglog"`, `"cauchit"`.

An `ARRAY` index is added for convenience.

Value

A list with two elements:

`m.specs` A `data.frame` of matching specifications with columns `boot`, `method`, `distance`, `link`, `ARRAY`.
`drawlist` A `data.frame` in wide format where each `Survey` is a column and rows correspond to draw ID (0:`drawN`).

Note

Requires that data contain Survey and EaId. `tidyr::spread()` is used for wide reshaping (consider `tidyr::pivot_wider()` in new code).

functional_forms

*Generate Functional and Distribution Forms***Description**

Creates symbolic production function strings for stochastic frontier analysis (SFA), including Cobb-Douglas (CD) and Translog (TL) specifications, plus a set of candidate distributions for the inefficiency term.

Usage

```
functional_forms(nX = 5, trend = FALSE)
```

Arguments

nX	Integer. Number of input variables. Default is 5.
trend	Logical. If TRUE, adjusts the (optional) transcendental form (TP) by removing the last linear input term. Default is FALSE.

Details

The returned `fxnforms` list includes:

- CD: sum of log inputs ($\ln I_1 + \ln I_2 + \dots$).
- TL: CD terms plus second-order and pairwise interaction terms (e.g., $0.5 * \ln I_i^2$ and $\ln I_i * \ln I_j$ for $i < j$).

Additional forms (Linear, Quadratic, Generalized, Transcendental) are shown in the code as commented examples; uncomment to include them. The `trend` argument only affects TP when that form is enabled.

`distforms` lists common inefficiency distributions (e.g., half-normal, truncated normal, exponential, lognormal, Weibull) and whether a scaling property is assumed for each.

Value

A list with:

`fxnforms` Named character strings of functional forms.

`distforms` Named list of inefficiency distributions with a scaling flag.

get_crop_area_list	<i>Extract Matching Crop Area Columns from a Dataset</i>
--------------------	--

Description

Identifies and returns the column names in a dataset corresponding to crop area variables for a specified set of crops. The function looks for column names that start with "Area_" and match any of the crops provided in selected_crops.

Usage

```
get_crop_area_list(
  data,
  selected_crops = c("Beans", "Cassava", "Cocoa", "Cocoyam", "Maize", "Millet", "Okra",
    "Palm", "Peanut", "Pepper", "Plantain", "Rice", "Sorghum", "Tomatoe", "Yam")
)
```

Arguments

data	A data.frame or data.table containing crop-related variables. Column names are expected to include fields prefixed with "Area_", such as "Area_Maize".
selected_crops	A character vector specifying the crop names to filter. Defaults to a common set of crops including "Beans", "Cassava", "Cocoa", "Cocoyam", "Maize", "Millet", "Okra", "Palm", "Peanut", "Pepper", "Plantain", "Rice", "Sorghum", "Tomatoe", and "Yam".

Value

A character vector containing the names of columns in data that correspond to the specified crop area variables (e.g., "Area_Maize", "Area_Rice"). Returns an empty vector if no matching columns are found.

harmonized_data_prep	<i>Prepare Data for Agricultural Productivity Analysis</i>
----------------------	--

Description

Cleans and transforms a dataset by creating new variables, applying log transformations, converting selected variables to factors or characters, and recoding education levels. The function is designed to standardize inputs for further analysis of agricultural productivity.

Usage

```
harmonized_data_prep(data)
```

Arguments

data	A data.frame or data.table containing household- and farm-level variables such as weights, demographic information, and agricultural inputs.
------	--

Value

A cleaned and transformed `data.frame` or `data.table` with additional variables ready for analysis.

sf_functional_forms	<i>Generate Functional and Distribution Forms for MSF Models</i>
---------------------	--

Description

Builds algebraic strings for common production-function specifications and assembles a catalog of distributional assumptions for one-sided inefficiency terms used in stochastic frontier / multi-stage frontier (MSF) analysis.

Usage

```
sf_functional_forms(number_of_inputs = 5, include_trend = FALSE)
```

Arguments

number_of_inputs	Integer. Number of input variables to enumerate in the functional forms (creates symbols $I_1 \dots I_k$ and $\ln I_1 \dots \ln I_k$). Default 5.
include_trend	Logical. If TRUE, adjusts the Transcendental production form (TP) by dropping the last linear input term. See <i>Note</i> regarding when TP is present. Default FALSE.

Details**Functional forms (returned as character strings):**

- CD: Cobb-Douglas - sum of logs of inputs, e.g., $\ln I_1 + \ln I_2 + \dots + \ln I_k$.
- TL: Translog - CD plus all second-order log terms (squares and cross-products), e.g. %
- LN: Linear (commented out in current code). %
- QD: Quadratic (commented out). %
- GP: Generalized (commented out). %
- TP: Transcendental (commented out; see Note).

Terms are generated programmatically for $k = \text{number_of_inputs}$, with: I_i denoting input levels and $\ln I_i$ their logarithms.

Distributional forms (list of lists): Each entry is named and contains `list(name, scaling = <logical>)`. Included options: `hnormal`, `tnormal`, `exponential`, `tslaplace`, `genexponential`, `tnormal_scaled`, `rayleigh`, `uniform`, `gamma`, `lognormal`, `weibull`. The scaling flag indicates whether the Wang-Schmidt (2002) scaling property is used in that specification.

Value

A list with two components:

- `fxnforms`: named list of character strings for functional forms (e.g., `$CD`, `$TL`). Forms that are commented out in the implementation will not appear.
- `distforms`: named list of distribution specifications; each is a list with elements `[1]` = distribution name and `scaling` = logical.

Note

The current implementation defines CD and TL and removes NULL entries before returning. Other forms (LN, QD, GP, TP) are commented out. If you plan to set `include_trend = TRUE`, ensure TP is actually included in `fxnforms`; otherwise, modifying `fxnforms$TP` will not have any effect (and would error if TP is not defined).

sf_model_specifications

Build Model Specifications

Description

Construct a specification table for multi-stage frontier (MSF) analysis by combining alternative production-function forms and distributional assumptions with technology choices and disaggregation levels. The function first creates a pooled grid of functional forms (`fxnforms`) and distributions (`distforms`), then augments it with crop-specific and demographic splits, and finally expands technology choices.

Usage

```
sf_model_specifications(
  data,
  distforms = sf_functional_forms()$distforms,
  fxnforms = sf_functional_forms()$fxnforms,
  technology_variables,
  mainF = 2,
  mainD = 1,
  demographic_variables = c("Female", "Region", "Ecozon", "EduCat", "EduLevel", "AgeCat"),
  crop_list = c("Beans", "Cassava", "Cocoa", "Cocoyam", "Maize", "Millet", "Okra",
    "Palm", "Peanut", "Pepper", "Plantain", "Rice", "Sorghum", "Tomatoe", "Yam")
)
```

Arguments

<code>data</code>	data.frame or data.table. A dataset that (ideally) contains the columns named in <code>demographic_variables</code> . Note: The current implementation references a global object <code>DATA</code> (not <code>data</code>) when deriving demographic levels; ensure <code>DATA</code> exists with those columns or adapt your environment accordingly.
<code>distforms</code>	named list of distributional forms. If NULL, defaults to <code>functional_forms()\$distforms</code> .
<code>fxnforms</code>	named list of functional forms. If NULL, defaults to <code>functional_forms()\$fxnforms</code> .
<code>technology_variables</code>	character vector of technology variables. The first element is taken as the default/primary technology.
<code>mainF</code>	integer index of the preferred functional form (in <code>fxnforms</code>). Default is 2.
<code>mainD</code>	integer index of the preferred distribution (in <code>distforms</code>). Default is 1.
<code>demographic_variables</code>	character vector of column names used for demographic disaggregation. Defaults to <code>c("Female", "Region", "Ecozon", "EduCat", "EduLevel", "AgeCat")</code> .
<code>crop_list</code>	character vector of crop names for crop-level disaggregation. Defaults to a selection of common crops.

Details

Procedure (high level):

1. Build a pooled grid of all `fxnforms` * `distforms`.
2. Keep rows matching `mainF` and `mainD` and tag pooled specs.
3. Add crop-specific rows for `crop_list` (using the main form/dist).
4. Add demographic splits for each variable in `demographic_variables`, using unique levels in `DATA[, var]` (see note in *Warning*).
5. Set `TechVar` to the first element of `technology_variables`; if additional technology variables are provided, add pooled rows for them with the main form/dist.
6. Reorder to prioritize `mainD` and create an `nm` flag with values "fullset" and "optimal".
7. Remove demographic rows for the default demographic list and retain only `level == "Pooled"` in the final output.

Returned columns (final table):

- `disasg` - disaggregation variable (e.g., "CropID").
- `level` - disaggregation level (e.g., "Pooled" or a crop/level).
- `TechVar` - selected technology variable.
- `f` - index of functional form (position in `fxnforms`).
- `d` - index of distribution (position in `distforms`).
- `nm` - marker column ("fullset" / "optimal").

Value

A `data.frame` (`data.table`-compatible) of model specifications with columns `disasg`, `level`, `TechVar`, `f`, `d`, and `nm`.

Warning

The function calls `unique(DATA[, w])` inside a `tryCatch`; this requires a global object `DATA` containing the demographic columns. If `DATA` is absent or lacks a given variable, that split is skipped.

Assumptions

- `technology_variables` is non-empty; its first element is the default.
- `mainF` and `mainD` are valid indices within `fxnforms` and `distforms`, respectively.

study_setup	<i>Initialize Study Environment and Directory Structure</i>
-------------	---

Description

Initialize Study Environment and Directory Structure

Usage

```
study_setup(
  seed = 1980632,
  project_name,
  local_directories = list(output = file.path("replications", project_name, "output"),
    matching = file.path("replications", project_name, "output", "matching"),
    treatment_effects = file.path("replications", project_name, "output",
      "treatment_effects"), estimations = file.path("replications", project_name, "output",
      "estimations"), figure_data = file.path("replications", project_name, "output",
      "figure_data"), figure = file.path("replications", project_name, "output", "figure"))
)
```

Arguments

seed	Numeric/integer scalar seed. Will be coerced to integer. Default: 1980632.
project_name	Length-1, non-NA character project name (required).
local_directories	Named list of character paths to create. Defaults use project_name.

Value

List with wd (directories) and seed.

treatment_effect_calculation	<i>Compute log-linear treatment effects (ATE/ATET/ATEU) for multiple outcomes</i>
------------------------------	---

Description

For a given matching specification index *i*, this function:

1. loads the corresponding matched sample weights from disk,
2. merges them into the analysis data via UID,
3. normalizes selected inputs/outputs by plot Area,
4. fits a weighted log-linear model for each outcome with interactions between Treat and the provided matching covariate formulas,
5. transforms fitted differences to percentage effects, trims extreme values, and computes weighted ATE, ATET, and ATEU alongside model fit statistics.

Note: The function returns a long table of results (atet_scalar), not the index *i*.

Usage

```
treatment_effect_calculation(
  data,
  i,
  match_specifications,
  matching_output_directory,
  match_formulas
)
```

Arguments

data A data.frame containing at least:

- identifiers: UID
- treatment flag: Treat (logical or 0/1)
- plot size: Area (positive; used to area-normalize variables)
- outcomes: HrvstKg, Area, SeedKg, HHLaborAE, HirdHr, FertKg, PestLt
- any covariates referenced in match_formulas\$general_match and match_formulas\$exact_match

i Integer index selecting the row of match_specifications and the matching result file to load (zero-padded via ARRAY to "NNNN.rds").

match_specifications A data.frame with at least column ARRAY; the i-th row is used to locate the matching output file and is also cbind-ed to the results.

matching_output_directory Directory containing per-specification matching results named as "0001.rds", "0002.rds", etc. Each RDS should contain \$md with UID and weights.

match_formulas A list with:

- general_match: a **formula** (RHS accessed via as.character(...)[3])
- exact_match: a **formula** (RHS accessed via as.character(...)[2])

Details

For each outcome in `c("HrvstKg", "Area", "SeedKg", "HHLaborAE", "HirdHr", "FertKg", "PestLt")`, fits:

$$\log(\text{outcome} + \text{eps}) \sim \text{Treat} * (\text{general_match_rhs} + \text{exact_match_rhs})$$

where $\text{eps} = \min(\text{outcome}[\text{outcome} > 0]) * 1/100$. Treatment effect is

$$TE_{OLS} = (e^{\hat{y}_1 - \hat{y}_0} - 1) \times 100$$

trimmed to $[-100, 100]$.

Value

A data.frame (atet_scalar) with columns from match_specifications[i,] joined to rows:

- outcome, treatment
- level in {ATE, ATET, ATEU, aic, ll, R2, N, Ft, R2a}
- est (numeric estimate)

treatment_effect_summary

Summarize Treatment Effect Estimates Across Matching Specifications

Description

Aggregates and summarizes treatment effect results stored as .rds files in a specified output directory. The function reads each RDS file, combines all results into a single data frame, filters out invalid estimates, and computes jackknife-style summary statistics (mean, standard error, sample size, t-value, and p-value) by matching specification and outcome.

Usage

```
treatment_effect_summary(treatment_effects_output_directory)
```

Arguments

treatment_effects_output_directory

Character string giving the path to the directory containing .rds files with treatment effect results (e.g., outputs of treatment_effect_calculation() saved across specifications).

Details

The function proceeds through the following steps:

1. Lists and reads all .rds files in treatment_effects_output_directory.
2. Combines them into a single long-format data frame using `data.table::rbindlist()`.
3. Removes rows with invalid estimates (NA, NaN, Inf, or -Inf).
4. Separates base (non-bootstrap) results where `boot == 0` and joins these with jackknife summary statistics computed via `doBy::summaryBy()` across method, distance, link, outcome, and level.
5. Renames summary columns to:
 - `jack_mean`: mean estimate
 - `jack_se`: standard error
 - `jack_n`: sample size (number of replicates)
 - `jack_tv1`: t-value ($\text{jack_mean} / \text{jack_se}$)
 - `jack_pv1`: two-sided p-value

Value

A `data.frame` containing summarized treatment effect estimates with columns:

- `method`, `distance`, `link`, `outcome`, `level`
- `est` (original estimate for non-bootstrap sample)
- `jack_mean`, `jack_se`, `jack_n`, `jack_tv1`, `jack_pv1`

write_match_formulas *Construct Matching Formulas for Exact and General Matching*

Description

Builds two types of matching formulas commonly used in propensity score or covariate matching workflows:

- An **exact match** formula specifying categorical variables to match exactly.
- A **general match** formula specifying numeric and factor covariates for distance-based matching.

The function returns both formulas as character strings that can be used in matching functions such as `MatchIt::matchit()` or `Matching::Match()`.

Usage

```
write_match_formulas(
  match_variables_exact,
  match_variables_scaler,
  match_variables_factor
)
```

Arguments

`match_variables_exact`

A character vector of variable names to be included in the exact match component (e.g., "gender", "region").

`match_variables_scaler`

A character vector of continuous or scalar variable names to include as covariates in the general match formula (e.g., "age", "income").

`match_variables_factor`

A character vector of factor variable names to be included as dummy-coded categorical covariates in the general match formula.

Value

A named list with two elements:

`exact_match` A string representing the exact match formula (factor variables only).

`general_match` A string representing the general match formula, including both continuous and factor covariates on the right-hand side of `Treat ~`.

Index

covariate_balance, [2](#)

draw_match_sample_specifications, [4](#)

draw_matched_samples, [3](#)

functional_forms, [5](#)

get_crop_area_list, [6](#)

harmonized_data_prep, [6](#)

sf_functional_forms, [7](#)

sf_model_specifications, [8](#)

study_setup, [10](#)

treatment_effect_calculation, [10](#)

treatment_effect_summary, [12](#)

write_match_formulas, [13](#)