

Package ‘fcipSupplementalLab’

January 21, 2026

Type Package

Title Research Framework for Supplemental Crop Insurance in the FCIP

Version 0.0.0.9000

Author Francis Tsiboe [aut, cre] (<<https://orcid.org/0000-0001-5984-1072>>)

Maintainer Francis Tsiboe <ftsiboe@hotmail.com>

Creator Francis Tsiboe

Description Provides a research framework for analyzing supplemental crop insurance products in the United States Federal Crop Insurance Program (FCIP). The package supports reproducible workflows to evaluate adoption and demand, actuarial performance and program soundness, public-private risk transfer, fiscal exposure, risk reduction and income transfer, and basis risk and coverage quality. Functions emphasize transparent data preparation, diagnostic summaries, and modular analysis components suitable for reports and policy briefs.

License GPL-3 + file LICENSE

URL <https://github.com/ftsiboe/fcipSupplementalLab>

BugReports <https://github.com/ftsiboe/fcipSupplementalLab/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

VignetteBuilder knitr

Depends R (>= 4.1.0)

Imports data.table, rfcip, stringr, urbanmapr, matrixStats, ggplot2, devtools

Remotes github::dylan-turner25/rfcip, github::UrbanInstitute/urbanmapr, github::dylan-turner25/rfsa

Suggests dplyr, tidyr, knitr, rmarkdown, mockery, withr, testthat (>= 3.0.0), piggyback, purrr, readr

LazyData true

Contents

aggregate_expected_outcomes	2
build_agent_simulation_data	3
build_supplemental_offering_and_adoption	4
clean_agents_data	5

clean_eco_share_by_insurance_plan	6
clean_rma_sco_and_eco_adm	6
clean_rma_sobtpu	7
clean_sco_share_by_coverage_level	8
clean_supplemental_plan_shares	8
compute_base_policy_outcomes	9
compute_expected_outcomes	10
compute_supplemental_current	11
compute_supplemental_factors	12
compute_supplemental_full	13
compute_supplemental_incremental	13
dispatcher_supplemental_simulation	14
ers_theme	15
farm_performance_metrics	16
install_from_private_repo	18
setup_environment	18
study_scenarios	20

Index	21
--------------	-----------

aggregate_expected_outcomes

Aggregate and winsorize expected outcomes (year-level)

Description

Loads all per-task expected outcome files for a given year, aggregates them, winsorizes key relative metrics within groups (5th-95th percentiles), and saves a single cleaned file.

Usage

```
aggregate_expected_outcomes(
  year,
  expected_directory = NULL,
  output_directory = NULL,
  study_environment,
  agent_identifiers = c("commodity_year", "state_code", "county_code", "type_code"),
  disaggregate = NULL
)
```

Arguments

year	Integer. Year to aggregate.
expected_directory	Character or NULL. Directory containing per-task expected_*.rds files for the year. If NULL, uses file.path(study_environment\$wd\$dir_expected, year).
output_directory	Character or NULL. Directory to write the aggregated file. If NULL, uses study_environment\$wd\$dir_expected.

study_environment

List. Must provide \$wd\$dir_expected (and is used to resolve defaults when directories are NULL).

agent_identifiers

Character vector. Grouping keys used for by-group winsorization (default: c("commodity_year", "s

disaggregate

Character or NULL. Optional extra grouping column (e.g., "combination"). If provided but missing, it is created as "ALL".

Details

Reads all .rds files under expected_directory, binds them, computes 5th and 95th percentiles for Relmean, Relsd, Relcv, Rellapv, Relrpv, Relnlapv, Relnlrpv, Relvar within each group, caps values to that range, and writes expected_<year>.rds to output_directory.

Value

Invisibly returns the path to the saved file.

build_agent_simulation_data

Build agent simulation panel

Description

Read cleaned agent-level simulation data for a crop year, unnest per-draw outcomes, filter to the requested draw(s), compute county-level expected yields, and add per-row revenue.

Usage

```
build_agent_simulation_data(
  year,
  sim,
  agents_directory = "data/cleaned_agents_data"
)
```

Arguments

year Integer. Crop year.

sim Integer vector. Draw number(s) to keep.

agents_directory

Character. Directory containing cleaned agent data. Default: "data/cleaned_agents_data".

Details

The function:

1. Loads cleaned_agents_data_<year>.rds from agents_directory.
2. Unnests draw pools: number, farm yield/price, and county yield/price.
3. Filters to sim (matching rma_draw_number).
4. Renames simulated fields to canonical names and floors negative county yields at zero.
5. Computes a planted-acre-weighted expected_county_yield.
6. Computes row-level revenue = actual_farm_yield * actual_price * planted_acres.

Value

A [data.table](#) containing all original columns plus:

- expected_county_yield
- final_county_yield
- harvest_price
- revenue

build_supplemental_offering_and_adoption

Build panel of supplemental insurance availability (offering) and adoption (acres)

Description

Creates a county-year-commodity panel with availability flags for APH/SCO/ECO90/ECO95 and adoption/acreage measures from RMA SOB/TPU. Availability is sourced from the RMA ADM (A00030_InsuranceOffer). ECO availability applies starting in 2021.

Usage

```
build_supplemental_offering_and_adoption(
  cleaned_rma_sobtpu_file_path = "data/cleaned_rma_sobtpu.rds",
  output_directory = "data"
)
```

Arguments

cleaned_rma_sobtpu_file_path

Character. Path to cleaned RMA SOB/TPU RDS. Default: "data/cleaned_rma_sobtpu.rds".

output_directory

Character. Directory to save output RDS; created if missing. Default: "data".

Details

Output columns:

- commodity_year, state_code, county_code, commodity_code, county_fips
- avail_aph, avail_sco, avail_eco90, avail_eco95 (0/1 flags)
- insured_acres, sco, eco90, eco95 (adopted acres)

Availability aggregation uses max() (binary). Acreage aggregation uses sum(). Missing numeric values are replaced with 0.

Value

Invisibly returns the output file path. Also prints a brief summary.

Examples

```
## Not run:
  path <- build_supplemental_offering_and_adoption()
  readRDS(path)[1:5]

## End(Not run)
```

clean_agents_data	<i>Clean agent-level data for a given year</i>
-------------------	--

Description

Downloads, merges, and processes agent-level insurance data for the specified year. Combines revenue draws, calibrated yields, and RMA reference data, computes premium/subsidy measures, and saves the cleaned dataset as an RDS file.

Usage

```
clean_agents_data(
  year,
  cleaned_rma_sobtpu_file_path = "data/cleaned_rma_sobtpu.rds",
  cleaned_rma_sco_and_eco_adm_file_path = "data/cleaned_rma_sco_and_eco_adm.rds",
  output_directory = "data/cleaned_agents_data"
)
```

Arguments

year	Integer. Commodity year to process (e.g., 2015).
cleaned_rma_sobtpu_file_path	Path to cleaned RMA SOB/TPU RDS file. Default: "data-raw/data/cleaned_rma_sobtpu.rds".
cleaned_rma_sco_and_eco_adm_file_path	Path to cleaned RMA SCO & ECO admin RDS file. Default: "data-raw/data/cleaned_rma_sco_a
output_directory	Directory to save output RDS file. Created if missing. Default: "data/cleaned_agents_data".

Value

Returns the input year on success, with attributes for save_path and number of rows. Returns NULL on error.

Note

Requires **data.table**, access to GitHub-hosted RDS files, and the helper function get_compressed_adm().

clean_eco_share_by_insurance_plan
ECO share by insurance plan

Description

Computes Enhanced Coverage Option (ECO) **shares of insured acres** for base plans (1=YP, 2=RP, 3=RP-HPE), using ECO plan codes 87-89 mapped back to 1-3, and returns separate shares for ECO-90 and ECO-95.

Usage

```
clean_eco_share_by_insurance_plan(sob)
```

Arguments

sob	A data.table (or data.frame) of SOB records that already contain aggregated acre and dollar fields. Must include at least: insured_acres, endorsed_acres, insurance_plan_code, coverage_level_percent, commodity_year, state_code, county_code, commodity_code, type_code, practice_code.
-----	---

Details

- Base data are summed for plans 1:3.
- ECO records are selected via plan codes 87:89, remapped to 1:3 (subtract 86), and coverage levels are labeled as "eco90" / "eco95" (using coverage_level_percent * 100).
- ECO shares are computed as eco_endorsed_acres / insured_acres by key.

Value

A data.table with unique rows by commodity_year, state_code, county_code, commodity_code, type_code, practice_code, and columns: eco90, eco95 (shares in [0,1]); missing combinations may be NA.

clean_rma_sco_and_eco_adm
Build SCO/ECO/Area ADM table for a given year (adds SCO88/SCO90)

Description

Downloads yearly ADM fragments from GitHub Releases for *Supplemental SCO*, *Supplemental ECO*, and *Area* plans, aggregates key parameters by common grouping keys, linearly interpolates SCO rates to 88% and 90% (using AYP and, for years ≥ 2021 , ECO anchors), and returns the cleaned, stacked table.

Usage

```
clean_rma_sco_and_eco_adm(year)
```

Arguments

year Integer. commodity year (e.g., 2022).

Value

A [data.table](#) containing original SCO/ECO/Area ADM rows plus synthesized **SCO88** (insurance_plan_code + 10) and **SCO90** (insurance_plan_code + 20) rows with non-invalid base_rate.

Note

Requires internet access. Missing plan files for a year are skipped silently.

clean_rma_sobtpu	<i>Clean and aggregate RMA Summary of Business (SOB-TPU) data</i>
------------------	---

Description

Retrieves RMA SOB-TPU records for requested years, combining **live** years (last 5 years, fetched via [rfcipc::get_sob_data\(\)](#)) with **stable** years (downloaded from a prebuilt .rds release), then filters, harmonizes insurance plan codes, coverage levels, and unit structure codes, and returns an analysis-ready data.table aggregated to common keys.

Usage

```
clean_rma_sobtpu(
  years = as.numeric(format(Sys.Date(), "%Y")) - 1,
  insurance_plan = NULL,
  acres_only = TRUE,
  addon_only = TRUE,
  harmonize_insurance_plan_code = TRUE,
  harmonize_coverage_level_percent = TRUE,
  harmonize_unit_structure_code = TRUE
)
```

Arguments

years Integer vector of commodity years.

insurance_plan Optional integer vector of harmonized plan codes to keep after harmonization (1=YP, 2=RP, 3=RP-HPE). If NULL, keep all.

acres_only Logical; keep only acres-level records. Default TRUE.

addon_only Logical; exclude CAT (coverage_type_code == "C"). Default TRUE.

harmonize_insurance_plan_code Logical; recode plans to (1,2,3). Default TRUE.

harmonize_coverage_level_percent Logical; normalize coverage levels to decimal in 0.50 to 0.95 at 0.05 steps. Default TRUE.

harmonize_unit_structure_code Logical; recode unit structure to (OU, BU, and EU). Default TRUE.

Value

A `data.table` aggregated to the keys with columns: `insured_acres`, `endorsed_acres`, `liability_amount`, `total_premium_amount`, `subsidy_amount`, `indemnity_amount`.

`clean_sco_share_by_coverage_level`

SCO share by coverage level

Description

Computes the Supplemental Coverage Option (SCO) **share of insured acres** by coverage level for base plans (1=YP, 2=RP, 3=RP-HPE), using SCO plan codes 31-33 mapped back to 1-3.

Usage

```
clean_sco_share_by_coverage_level(sob)
```

Arguments

<code>sob</code>	A <code>data.table</code> (or <code>data.frame</code>) of SOB records that already contain aggregated acre and dollar fields. Must include at least: <code>insured_acres</code> , <code>endorsed_acres</code> , <code>insurance_plan_code</code> , <code>coverage_level_percent</code> , <code>commodity_year</code> , <code>state_code</code> , <code>county_code</code> , <code>commodity_code</code> , <code>type_code</code> , <code>practice_code</code> .
------------------	--

Details

- Base data are summed for plans 1:3.
- SCO records are selected via plan codes 31:33 and then remapped to 1:3 (subtract 30) to align with corresponding base plans.
- SCO share is computed as `endorsed_acres / insured_acres` by key and coverage level.

Value

A `data.table` with unique rows by `commodity_year`, `state_code`, `county_code`, `commodity_code`, `type_code`, `practice_code` and column: `sco` (share in [0,1]).

`clean_supplemental_plan_shares`

Supplemental plan shares (SCO/ECO)

Description

Aggregates base plan acres/dollars and (optionally) merges in Supplemental Coverage Option (SCO) and Enhanced Coverage Option (ECO) shares for each key.

Usage

```
clean_supplemental_plan_shares(
  sob,
  get_sco_shares = TRUE,
  get_eco_shares = TRUE
)
```

Arguments

sob A `data.table` or `data.frame` of SOB records. Expected columns: `insured_acres`, `endorsed_acres`, `insurance_plan_code`, `coverage_level_percent`, `commodity_year`, `state_code`, `county_code`, `commodity_code`, `type_code`, `practice_code`, `unit_structure_code`, `coverage_type_code`, `liability_amount`, `total_premium_amount`, `subsidy_amount`, `indemnity_amount`.

get_sco_shares Logical; if TRUE, merge SCO shares by coverage level.

get_eco_shares Logical; if TRUE, merge ECO-90/95 shares by plan.

Details

Assumes base plans are harmonized to 1=YP, 2=RP, 3=RP-HPE, and `coverage_level_percent` is in decimals (e.g., 0.90, 0.95). Relies on helpers: `clean_sco_share_by_coverage_level()` and `clean_eco_share_by_insurance_plan()`.

Value

A `data.frame` with aggregated acres/dollars and columns `sco`, `eco90`, `eco95` (shares in [0,1] where available).

```
compute_base_policy_outcomes
```

Compute base-policy outcomes

Description

Vectorized **data.table** implementation of base-policy guarantees, acres/liability, premium pieces (total/subsidy/producer), and indemnity, plus a tidy column subset for downstream joins.

Usage

```
compute_base_policy_outcomes(cleaned_agents_data)
```

Arguments

cleaned_agents_data

A `data.frame` or `data.table` with the required columns (see error message if any are missing).

Details

Requires a set of core inputs (e.g., yields, prices, coverages, acres) and returns the standard monetary outputs for each policy row. Price risk is handled via a `new_insurance_guarantee` that depends on plan code.

Value

A [data.table](#) with key fields and outputs: insured_acres, liability, total_premium, subsidy_amount, producer_premium, indemnity, revenue, and supporting fields such as harvest_price, expected_county_yield, final_county_yield, new_insurance_guarantee, projected_price.

compute_expected_outcomes

Compute expected outcomes and risk metrics from simulation outputs

Description

Joins cleaned agent records to simulation files, then computes expected (mean/sd) revenues, downside-risk measures (loss-side residual moments), relative improvements with insurance, and insurance performance statistics. Writes a single .rds result file and returns its path (invisibly).

Usage

```
compute_expected_outcomes(
  year,
  task_id,
  agents_directory = "data/cleaned_agents_data",
  simulation_directory = NULL,
  output_directory = NULL,
  study_environment,
  agent_identifiers = c("commodity_year", "state_code", "county_code", "commodity_code",
    "type_code", "practice_code", "unit_structure_code", "insurance_plan_code",
    "coverage_level_percent", "insured_acres"),
  disaggregate = NULL
)
```

Arguments

year	Integer (scalar). Analysis year (used to resolve input/output paths).
task_id	Integer or integer vector. Pseudo-task partition(s) to keep; the function cycles a 1..500 index over agent rows and filters to these values.
agents_directory	Character. Directory containing cleaned_agents_data_<year>.rds.
simulation_directory	Character or NULL. Directory with simulation .rds files; default is file.path(study_environment\$wd\$dir_simulation, year).
output_directory	Character or NULL. Directory to write results; default is file.path(study_environment\$wd\$dir_expected, year).
study_environment	List. Must include wd\$dir_sim and wd\$dir_expected if the corresponding directory arguments are NULL.
agent_identifiers	Character vector. Columns that identify agent units and define aggregation groups (used for joins and by); default includes year, location, crop, unit structure, plan, coverage, and acres.

disaggregate Character or NULL. Optional extra column to disaggregate by (for example, "combination"). If provided but missing after the join, the column is created and set to "ALL".

Details

Pipeline

1. Load agent data and keep only agent_identifiers; coerce to data.table.
2. Assign a pseudo task (cycles 1..500), then filter to task_id.
3. Guardrails:
 - Stop if no simulation files are found.
 - Stop if the combined join yields zero rows.
 - Validate required numeric columns: revenue, indemnity, producer_premium, liability, total_premium, subsidy_amount.
 - Use safe_div() to avoid Inf/NaN on zero or non-finite denominators.
4. Compute revenues (floored at 0): Revenue and Revenue_Inc (= revenue + indemnity
 - producer premium).
5. By uid (=agent_identifiers plus disaggregate if provided), compute means, sds, residual-based downside measures (loss-only squared residuals and their frequency), and derived statistics (variance, CV, LAPV, LRPV, normalized forms).
6. Compute **relative** metrics (insured vs. uninsured ratios): Relmean, Relsd, Relcv, Rellapv, Rellrpv, Relnlapv, Relnlrpv, Relvar. Base Revenue* statistics are dropped before the final merge to keep results compact.
7. Aggregate insurance performance by group: mean liability, total_premium, subsidy_amount, producer_premium, indemnity, premium and LCR rates (Simrate, SimrateP, Simsuby, Simlcr), and **group sums** for lr_indemnity and lr_premium. Merge with the relative metrics.

Join note The join uses data[simdt, on = <keys>, nomatch = 0], i.e., it returns rows aligned to the simulation table entries that match the agent keys.

Value

Invisibly returns the saved file path (expected_<year>_<task-range>.rds).

compute_supplemental_current

Aggregate supplemental results for the current environment

Description

Scale selected SCO/ECO factors by base-policy weights (sco, eco90, eco95), aggregate by policy keys, append base outcomes, and label the rollup as "Basic+CURRENT".

Usage

```
compute_supplemental_current(base_policy_data, supplemental_factors)
```

Arguments

`base_policy_data` [data.table](#). Base-policy outcomes (contains keys, weights, and monetary fields).

`supplemental_factors` [data.table](#). Supplemental outcomes from `compute_supplemental_factors` including `sup`.

Value

A [data.table](#) aggregated by policy keys with: `revenue`, `liability`, `total_premium`, `subsidy_amount`, `producer_premium`, `indemnity`, and `combination`.

`compute_supplemental_factors`
Compute supplemental policy factors (SCO/ECO)

Description

Compute shallow-loss protection, premiums, and indemnities for one SCO/ECO endorsement offering, aligning plan families and joining ADM rating inputs.

Usage

```
compute_supplemental_factors(base_policy, adm, plan, subsidy, trigger)
```

Arguments

`base_policy` [data.table](#). Base-policy rows (keys, yields, prices, liability, etc.).

`adm` [data.table](#). Rating inputs with `base_rate` and join keys.

`plan` Integer. Plan code in the offering (e.g., 31-33, 51-53, 87-89).

`subsidy` Numeric. Subsidy factor (e.g., 0.65, 0.80, 0.44).

`trigger` Numeric. Coverage trigger level (e.g., 0.86, 0.90, 0.95).

Details

Handles plan families via offsets (31-33, 41-43, 51-53, 87-89). For plans 87-89 (ECO), the `coverage_level_percent` for ADM is matched to the `trigger` (with a small tolerance), and the subsidy factor special-case is applied for underlying plan code 1. Emits a standard `sup` label like "SC08665" or "EC09544".

Value

A [data.table](#) with columns: `commodity_year`, `state_code`, `county_code`, `commodity_code`, `type_code`, `practice_code`, `unit_structure_code`, `insurance_plan_code`, `coverage_level_percent`, `liability`, `total_premium`, `subsidy_amount`, `producer_premium`, `indemnity`, `sup`.

 compute_supplemental_full

Aggregate supplemental full-participation results

Description

Given selected sup labels, sum their monetary fields, append base outcomes, and produce a final rollup by policy keys with a descriptive combination label.

Usage

```
compute_supplemental_full(
  base_policy_data,
  supplemental_factors,
  supplemental_pick
)
```

Arguments

`base_policy_data`
[data.table](#). Base-policy outcomes.

`supplemental_factors`
[data.table](#). Results from `compute_supplemental_factors`.

`supplemental_pick`
 Character vector of sup labels to include.

Details

The function self-filters `supplemental_factors` to the provided `supplemental_pick` (after dropping empties), aggregates within keys, appends base outcomes, and re-aggregates.

Value

A [data.table](#) aggregated by the policy keys with: revenue, liability, total_premium, subsidy_amount, producer_premium, indemnity, and combination.

 compute_supplemental_incremental

Compute incremental supplemental results at an adoption rate

Description

Build an incremental scenario by scaling SC08665 supplemental dollars by a user-specified adoption rate, aggregating by keys, and appending base outcomes.

Usage

```
compute_supplemental_incremental(
  base_policy_data,
  supplemental_factors,
  adoption_rate
)
```

Arguments

`base_policy_data` [data.table](#). Base-policy outcomes.

`supplemental_factors` [data.table](#). Output from `compute_supplemental_factors` filtered to `sup == "SC08665"`.

`adoption_rate` Numeric. Percentage (e.g., 10 for 10\ scale incremental supplemental amounts).

Value

A [data.table](#) aggregated by the policy keys with: revenue, liability, total_premium, subsidy_amount, producer_premium, indemnity, and combination.

dispatcher_supplemental_simulation

Dispatcher: simulate supplemental outcomes for one draw

Description

Orchestrate the full supplemental simulation workflow for a given crop year and draw: build the agent panel, compute base-policy results, generate supplemental factors, assemble *Current*, *Full*, and *Incremental* scenarios, and write the combined results to disk.

Usage

```
dispatcher_supplemental_simulation(
  sim,
  year,
  agents_directory = "data/cleaned_agents_data",
  cleaned_rma_sco_and_eco_adm_file_path = "data/cleaned_rma_sco_and_eco_adm.rds",
  output_directory = NULL
)
```

Arguments

`sim` Integer. Draw number used in data building and the filename.

`year` Integer. Crop year.

`agents_directory` Character. Directory for cleaned agents data.

`cleaned_rma_sco_and_eco_adm_file_path` Character. Path to RDS of SCO/ECO ADM with join keys and base_rate. Default: "data/cleaned_rma_sco_and_eco_adm.rds".

`output_directory` Character or NULL. Where to write results; see Details for default behavior.

Details

The pipeline:

1. `build_agent_simulation_data` to construct the panel.
2. `compute_base_policy_outcomes` for base outcomes.
3. `study_scenarios` to enumerate offerings/mixes.
4. Load SCO/ECO ADM; filter to `commodity_year == year`; average `base_rate` by key; drop invalid/zero rates.
5. Loop offerings through `compute_supplemental_factors`.
6. Build scenarios:
 - *Current*: `compute_supplemental_current`.
 - *Full*: `compute_supplemental_full`.
 - *Incremental*: `compute_supplemental_incremental`.
7. Aggregate base-only results, `rbind` all scenarios, and save as `simXXX.rds` in `output_directory`.

If `output_directory` is `NULL`, it defaults to `file.path(study_environmentwddir_sim, year)` (ensure `study_environmentwddir_sim` exists in the calling environment).

Value

Invisibly writes `simXXX.rds` to `output_directory`.

ers_theme	<i>ERS Theme</i>
-----------	------------------

Description

ERS Theme

Usage

```
ers_theme()
```

Source

copied from <https://github.com/USDA-REE-ERS/MTED-Theme> on 08/01/2025

Examples

```
ggplot2::ggplot() + ers_theme()
```

farm_performance_metrics

Farm performance metrics by scenario and disaggregate

Description

Load expected_<year>.rds, derive outcome variables, compute deltas vs. baselines, trim extremes using quantile limits, aggregate (weighted mean/median) by requested disaggregates, and save a summarized .rds. Returns the saved path invisibly.

Usage

```
farm_performance_metrics(
  year,
  agent_identifiers = c("commodity_year", "state_code", "county_code", "commodity_code",
    "type_code", "practice_code", "unit_structure_code", "insurance_plan_code",
    "coverage_level_percent"),
  outcome_list = c("its", "Iits", "rrs1", "rrs2", "rrs3", "Irrs1", "Irrs2", "Irrs3",
    "sner1", "sner2", "sner3", "Simrate", "SimrateP", "Simsuby", "Simlcr", "rrp1",
    "rrp2", "rrp3", "itp"),
  combo,
  weight_variable = NULL,
  expected_directory = NULL,
  draw = NULL,
  draw_list_file_path = NULL,
  disaggregates = NULL,
  output_file_path = NULL,
  distributional_limits = c(0.05, 0.95)
)
```

Arguments

year	Policy year used to locate expected_<year>.rds.
agent_identifiers	Character vector of ID columns for grouping prior to long-pivot and averaging.
outcome_list	Character vector of outcome columns to reshape and aggregate.
combo	Target scenario (e.g., "Basic+CURRENT", "Basic+SC08665", or another).
weight_variable	NULL for equal weights (=1) or a character name of a numeric weight column.
expected_directory	Directory containing expected_<year>.rds.
draw	Optional draw identifier used for filtering and filename tag.
draw_list_file_path	Optional path to an RDS (named list) with the draw table; required if draw is not NULL.
disaggregates	Optional character vector of additional disaggregate columns (alongside "FCIP").
output_file_path	Output file path

distributional_limits

Numeric length-2 vector of lower/upper probabilities (e.g., `c(0.05, 0.95)`); must satisfy $0 < p1 < p2 < 1$.

Details**Steps:**

1. Filter rows to combination `%in% {"Basic+CURRENT", combo, "Basic+SC08665"}`.
2. Create derived metrics: `rrs1/2/3`, `its`, `flags Irrs*/Iits`, `sner*`, `percent/level` transforms (`rrp*`, `itp`), and scale `Sim*` by 100.
3. Reshape to long on `outcome_list`, drop non-finite values, average within identifiers (`agent_identifiers`, and `weight_variable` if provided), `scenario`, `variable`.
4. Join baselines: if `combo != "Basic+CURRENT"`, add "Basic+CURRENT" as `base00`; if `combo = {"Basic+SC08665"}`, add "Basic+SC08665" as `base01`. Compute `chglvl00/01` and `chgpct00/01` (guard divide-by-zero).
5. Build labels `PLAN`, `RPYP`, `COV`, `STRUCT`.
6. Compute trimming limits per (`variable`, `combination`, `state_code`, `IRR`, `commodity_code`) using `distributional_limits` (default `c(0.05, 0.95)`), require `n` greater or equal to 20, and cap to `*T` columns.
7. For each of `c("FCIP", disaggregates)`, compute weighted mean and weighted median of raw and trimmed metrics; stack results and write output.

Value

Invisibly returns the character path of the saved `.rds`.

Required columns

All `agent_identifiers`, plus: `combination`, `state_code`, `county_code`, `commodity_code`, `type_code`, `practice_code`, `IRR`, `Relcv`, `Relnlrvp`, `Relnlapv`, `Relmean`, `Simrate`, `SimrateP`, `Simsby`, `Simlcr`, `coverage_level_percent`, `unit_structure_code`, `insurance_plan_code`. If `weight_variable` is not `NULL`, that column must exist and be numeric.

Note

Baseline joins use `nomatch = 0` by design, so rows missing in the baseline are dropped before delta computation. Change to `nomatch = NA` if you prefer to retain such rows with NA deltas.

See Also

`data.table::data.table`, `data.table::melt`, `matrixStats::weightedMedian`

```
install_from_private_repo
```

Conditionally Install a Private GitHub Package in CI

Description

This helper function installs a private R package from GitHub using a personal access token (PAT) during GitHub Actions runs. It checks if the package is installed and, if not, installs it using `devtools::install_github()` with authentication.

Usage

```
install_from_private_repo(user_name, package_name, secret_name)
```

Arguments

<code>user_name</code>	Character. The GitHub username or organization that owns the repository.
<code>package_name</code>	Character. The name of the package and repository.
<code>secret_name</code>	Character. The name of the environment variable holding the GitHub PAT (excluding the "github_pat_" prefix).

Details

This function runs only when the environment variable `GITHUB_ACTIONS` is "true", which indicates it is running in a GitHub Actions workflow. It assumes that the provided PAT is stored in an environment variable named `secret_name`, and the full token is formed as `paste0("github_pat_", Sys.getenv(secret_name))`.

If `devtools` is not available, it will be installed from CRAN first. If the target package is already loaded, it will be detached before reinstallation.

Value

NULL. Called for its side effect of installing a package.

Note

This function is intended for use in CI environments and should not be called during package loading. Ensure the secret specified by `secret_name` is configured in your GitHub repository settings.

```
setup_environment
```

Setup Project Environment

Description

Initializes the working environment for a project by creating required directories, setting useful global options, and fixing the random seed.

Usage

```
setup_environment(
  year_beg = 2001,
  year_end = as.numeric(format(Sys.Date(), "%Y")),
  seed = 1980632,
  project_name,
  local_directories = list(file.path("data-raw", "output"), file.path("data-raw",
    "scripts"), file.path("data")),
  fastscratch_root = NULL,
  fastscratch_directories = NULL
)
```

Arguments

year_beg Integer. Beginning year of the analysis (default: 2001).

year_end Integer. Ending year of the analysis (default: current system year).

seed Integer. Random seed for reproducibility (default: 1980632).

project_name Character. Project name (required). Used to build fast-scratch directory paths.

local_directories List of project-local directories to create (default: `list("data-raw/output", "data-raw/scripts", "data")`).

fastscratch_root Optional character. Root directory for fast-scratch files. If NULL, it is set automatically:

- Windows: "C:/fastscratch"
- Linux/macOS: "/fastscratch/<username>"

fastscratch_directories List of fast-scratch subdirectories (relative to <fastscratch_root>/<project_name>) to create. If NULL, no fast-scratch subdirectories are created and `wd` is returned as an empty list.

Details

The function ensures the requested directories exist, creating them if necessary. Directory keys in the returned `wd` list are the basenames of the provided `fastscratch_directories`.

It also sets the following options:

- `options(scipen = 999)` (turns off scientific notation)
- `options(future.globals.maxSize = 8 * 1024^3)` (~8 GiB)
- `options(dplyr.summarise.inform = FALSE)` (quiet **dplyr**)

Finally, the random number generator is seeded with the provided seed.

Value

A list with:

wd Named list of created fast-scratch directories. Empty if `fastscratch_directories = NULL`.

year_beg Starting year (integer).

year_end Ending year (integer).

seed Seed value used for RNG.

study_scenarios	<i>Build study scenarios (SCO/ECO offerings and mixes)</i>
-----------------	--

Description

Define the endorsement offerings (plan family - trigger - subsidy - label) and the full-participation SCO/ECO mixes to evaluate for a given year.

Usage

```
study_scenarios(year)
```

Arguments

year	Integer. Crop year used to determine available ECO variants.
------	--

Details

For years ≥ 2021 , ECO 90/44 and 95/44 variants are added and the participation set is expanded accordingly. Offerings create sup labels such as "SC08665", "SC09080", "EC09044", "EC09544".

Value

A named list with:

- offerings: [data.table](#) of insurance_plan_code, Trigger, plan, Subsidy_factor.
- full_participation: [data.table](#) of SCO/ECO label combinations to test (columns sco, eco).

Index

`aggregate_expected_outcomes`, [2](#)

`build_agent_simulation_data`, [3](#), [15](#)
`build_supplemental_offering_and_adoption`,
[4](#)

`clean_agents_data`, [5](#)
`clean_eco_share_by_insurance_plan`, [6](#)
`clean_rma_sco_and_eco_adm`, [6](#)
`clean_rma_sobtpu`, [7](#)
`clean_sco_share_by_coverage_level`, [8](#)
`clean_supplemental_plan_shares`, [8](#)
`compute_base_policy_outcomes`, [9](#), [15](#)
`compute_expected_outcomes`, [10](#)
`compute_supplemental_current`, [11](#), [15](#)
`compute_supplemental_factors`, [12](#), [12–15](#)
`compute_supplemental_full`, [13](#), [15](#)
`compute_supplemental_incremental`, [13](#),
[15](#)

`data.table`, [4](#), [7](#), [10](#), [12–14](#), [20](#)
`dispatcher_supplemental_simulation`, [14](#)

`ers_theme`, [15](#)

`farm_performance_metrics`, [16](#)

`install_from_private_repo`, [18](#)

`rfcip::get_sob_data()`, [7](#)

`setup_environment`, [18](#)
`study_scenarios`, [15](#), [20](#)