

Package ‘gwk’

July 8, 2026

Type Package

Title Convenience Wrappers and Workflows for Geographically Weighted Analysis

Version 0.0.0.9000

Author Francis Tsiboe [aut, cre] (<<https://orcid.org/0000-0001-5984-1072>>),
TERRA ANALYTICS LLC [cph, fnd]

Maintainer Francis Tsiboe <ftsiboe@hotmail.com>

Contributor -

Reviewer -

Creator Francis Tsiboe

Copyright TERRA ANALYTICS LLC (Kansas, USA)

Description A toolkit of convenience wrappers and reproducible workflows around 'GWmodel' and related spatial packages ('sf', 'terra', 'sp') for geographically weighted analysis. Provides point-, polygon-, and county-level geographically weighted summary-statistics pipelines, distance-metric presets, and utilities to reduce results estimated across a grid of kernel and distance-metric settings to a single per-unit consensus, with optional Queen-contiguity reconciliation. The package wraps, and does not replace, the underlying estimators.

License GPL-3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Depends R (>= 4.1.0)

Imports data.table,
GWmodel,
sp,
sf,
terra,
dplyr,
urbnmapr,
methods,
stats,
utils

Suggests testthat (>= 3.0.0),
knitr,
rmarkdown

Remotes `github::UrbanInstitute/urbnmapr`

URL <https://github.com/ftsiboe/gwkit>

BugReports <https://github.com/ftsiboe/gwkit/issues>

Config/testthat/edition 3

Contents

estimate_gwr_by_point	2
estimate_gwr_by_polygon	3
estimate_gwss_by_county	4
estimate_gwss_by_point	6
estimate_gwss_by_polygon	8
gw_distance_metric_names	11
gw_distance_metric_presets	11
gw_optimal_class_by_point	11
gw_optimal_class_by_polygon	12
PACKAGE_GLOBALVARIABLES	13
resolve_distance_metric	14

Index	15
--------------	-----------

estimate_gwr_by_point	<i>Geographically weighted local mean/variance regression at points</i>
-----------------------	---

Description

For each point-referenced unit, fits a geographically weighted regression of response on covariate (the local slope on the response mean) and, unless disabled, a second GWR of the log-squared residuals (the local slope on the response variance). Local slope standard errors, t-values, and normal- approximation p-values are computed directly (GWmodel returns no SE at supplied regression points). Distances and the fixed bandwidth use GWmodel.

Usage

```
estimate_gwr_by_point(
  data,
  unit,
  response,
  covariate = "trend",
  coords = c("longitude", "latitude"),
  kernel = "bisquare",
  adaptive = FALSE,
  distance_metric = "Great Circle",
  bw = NULL,
  bw_approach = "AICc",
  bw_sample = 1500L,
  chunk_size = 250L,
  eps = 0.00000001,
  variance = TRUE,
  verbose = FALSE
)
```

Arguments

data	A data.table/data frame with one row per observation, containing the unit id (unit), response, covariate, and the two coordinate columns named in coords. Multiple observations per unit (e.g. a time series) are expected for a meaningful slope.
unit	Character string naming the spatial-unit id column.
response	Character string naming the response column.
covariate	Character string naming the covariate (e.g. "trend"). Default "trend".
coords	Length-2 character vector naming the longitude/latitude columns. Default c("longitude", "latitude").
kernel	GW kernel for GWmodel::bw.gwr() and the local weights. One of "gaussian", "exponential", "bisquare", "boxcar", "tricube". Default "bisquare".
adaptive	Logical; adaptive (kNN) bandwidth if TRUE, fixed distance if FALSE. Default FALSE.
distance_metric	One of gw_distance_metric_names(). Default "Great Circle".
bw	Optional pre-computed bandwidth. If NULL it is selected once via GWmodel::bw.gwr() on a random subsample.
bw_approach	Bandwidth criterion for bw.gwr(). Default "AICc".
bw_sample	Observations sampled for bandwidth selection. Default 1500.
chunk_size	Regression points per distance-matrix chunk. Default 250.
eps	Added to squared residuals before the log. Default 1e-8.
variance	Logical; also estimate the local variance slope. Default TRUE.
verbose	Logical; print chunk progress. Default FALSE.

Value

A data.table with one row per unit: term, unit_id, unit_level, mean_estimate, mean_standard_error, mean_t_value, mean_p_value, (when variance) the var_* equivalents, and model_estimator ("gwr").

See Also

Other Geographically weighted regression: [estimate_gwr_by_polygon\(\)](#)

estimate_gwr_by_polygon

Geographically weighted local mean/variance regression on polygons

Description

As estimate_gwr_by_point(), but the spatial units are polygons: centroid coordinates are derived from a supplied geometry (terra SpatVector or sf) and joined to data by the unit id, then the GWR is run on the centroids.

Usage

```
estimate_gwr_by_polygon(
  data,
  unit,
  polygons,
  response,
  covariate = "trend",
  poly_id = unit,
  kernel = "bisquare",
  adaptive = FALSE,
  distance_metric = "Great Circle",
  bw = NULL,
  bw_approach = "AICc",
  bw_sample = 1500L,
  chunk_size = 250L,
  eps = 0.00000001,
  variance = TRUE,
  verbose = FALSE
)
```

Arguments

data	A data.table/data frame with one row per observation, containing the unit id (unit), response, and covariate.
unit	Character string naming the spatial-unit id column in data.
polygons	A terra SpatVector or sf polygon layer whose id field (poly_id) matches unit.
response	Character string naming the response column.
covariate	Character string naming the covariate. Default "trend".
poly_id	Name of the id field in polygons. Default: value of unit.
kernel, adaptive, distance_metric, bw, bw_approach, bw_sample, chunk_size, eps, variance, verbose	See estimate_gwr_by_point().

Value

A data.table with one row per unit (see estimate_gwr_by_point()).

See Also

Other Geographically weighted regression: [estimate_gwr_by_point\(\)](#)

estimate_gwss_by_county

Estimate geographically weighted summary statistics (GWSS) for counties

Description

Computes Geographically Weighted Summary Statistics (GWSS) for one or more scalar, county-level variables observed in a subset of counties, then evaluates the statistics at **all** county locations (points-on-surface). This is useful for spatial smoothing and gap-filling (imputation) when some counties are missing observations.

Usage

```
estimate_gwss_by_county(
  data,
  fip_col,
  variable_list,
  distance_metric = "Euclidean",
  kernel = "gaussian",
  target_crs = 5070,
  draw_rate = 0.5,
  approach = "CV",
  adaptive = TRUE,
  state_fips_limits = NULL
)
```

Arguments

data	A data.frame/data.table with at least fip_col and all columns listed in variable_list.
fip_col	Character. Name of the county ID column in data; copied to "county_fips" for joining with the county map.
variable_list	Character vector. Names of one or more numeric columns in data to summarize using GWSS.
distance_metric	Character. One of gw_distance_metric_names(). Default: "Euclidean".
kernel	Character. One of "gaussian", "exponential", "bisquare", "boxcar", "tricube". Default: "gaussian".
target_crs	Integer EPSG code used to project county geometries when longlat = FALSE. Default: 5070 (NAD83 / CONUS Albers, meters).
draw_rate	Numeric in (0, 1]. Fraction of observed counties used during bandwidth cross-validation. Default: 0.5 (50%).
approach	Character. Bandwidth selection approach passed to GWmodel::bw.gwr(). One of "CV", "AIC", "AICc". Default: "CV".
adaptive	Logical. Use adaptive (nearest-neighbour count) bandwidth instead of fixed distance. Default: TRUE.
state_fips_limits	Optional character or numeric vector of state FIPS codes. When supplied, GWSS is evaluated only for counties whose state_fips is in this set.

Details

The function:

1. pulls U.S. counties from **urbnmapr** and projects to a suitable CRS;

2. copies data[[fip_col]] into "county_fips" and joins to the map;
3. identifies **observed counties** (finite values of the first entry in variable_list), fits GWSS using those points, and selects an adaptive bandwidth by cross-validation on a random subsample sized by draw_rate;
4. optionally restricts the evaluation grid to a subset of states via state_fips_limits;
5. evaluates GWSS at **all counties in the evaluation set** and returns local summaries keyed by county_fips.

Inputs: data must contain a county identifier column referenced by fip_col and at least one numeric column referenced in variable_list. Internally, a column "county_fips" is created for joining with urbnmapr::get_urban_map("counties"). The data are reduced to a single row per county (by county_fips) before fitting.

Multiple variables: variable_list can contain one or more variable names. Bandwidth selection is performed using the first variable in variable_list, but the resulting bandwidth is then used to compute GWSS for all variables in variable_list via GWmodel::gwss().

Distance metric (distance_metric) defines (p, theta, longlat) for GWmodel::gw.dist() via resolve_distance_metric(). Use gw_distance_metric_names() to list valid options. If longlat = TRUE (e.g., "Great Circle"), counties are transformed to EPSG:4326; otherwise they are projected to target_crs (default 5070, meters).

Bandwidth selection: cross-validation (approach = "CV" by default) is run on a uniform random subsample of size ceiling(draw_rate * n_obs), bounded to [5, n_obs - 1], where n_obs is the number of counties with finite values for the first variable in variable_list. Call set.seed() beforehand for reproducibility. The function returns NULL (with a message) if fewer than 5 counties have finite values.

State filtering: if state_fips_limits is non-NULL, the evaluation grid is restricted to counties whose state_fips is in state_fips_limits. This affects both the set of locations at which GWSS is evaluated and the returned county_fips set.

Value

A data.table of GW summary statistics for **all counties in the evaluation set**, with a county_fips column for merging back to polygons. Column names follow **GWmodel** conventions for each variable in variable_list, e.g. for a variable x, columns such as x_LM, x_LSD, x_LCV, x_LSKe, x_LSSke, etc. are returned (depending on GWmodel::gwss() defaults). Attributes attached: "bandwidth", "distance_params", "kernel", "approach", "adaptive". Returns NULL when there are fewer than 5 observed counties.

```
estimate_gwss_by_point
```

Estimate geographically weighted summary statistics (GWSS) for points

Description

Computes geographically weighted summary statistics (via **GWmodel::gwss**) at specified prediction locations using a **single global bandwidth** determined from a subsample of observed points. All observed points are used for every prediction; group_variable only partitions the prediction set for organizational or computational reasons.

Usage

```
estimate_gwss_by_point(
  locat_observed,
  locat_predict,
  longitude_col,
  latitude_col,
  variable,
  distance_metric = "Euclidean",
  kernel = "gaussian",
  target_crs = 5070,
  draw_rate = 0.5,
  approach = "CV",
  adaptive = TRUE,
  feasible_radius = 100,
  group_variable = NULL,
  identifiers = NULL
)
```

Arguments

<code>locat_observed</code>	data.frame/data.table with columns named by <code>longitude_col</code> , <code>latitude_col</code> , and a numeric column named by <code>variable</code> . Must be in decimal degrees (EPSG:4326).
<code>locat_predict</code>	data.frame/data.table with columns named by <code>longitude_col</code> and <code>latitude_col</code> . Must be in decimal degrees (EPSG:4326). Rows with no nearby observations (within <code>feasible_radius</code>) are dropped.
<code>longitude_col</code> , <code>latitude_col</code>	character column names for coordinates.
<code>variable</code>	character name of numeric column in <code>locat_observed</code> to summarize.
<code>distance_metric</code>	character distance metric passed to <code>GWmodel::gw.dist()</code> via <code>resolve_distance_metric()</code> . Default "Euclidean".
<code>kernel</code>	character kernel for GWR/GWSS weights. One of "gaussian", "exponential", "bisquare", "boxcar", "tricube". Default "gaussian".
<code>target_crs</code>	integer EPSG code used for projection during radius pre-screening (in meters). Default 5070 (NAD83 / CONUS Albers).
<code>draw_rate</code>	numeric fraction (0,1] of observed points used for bandwidth selection. Default 0.5.
<code>approach</code>	character one of "CV", "AIC", "AICc", passed to <code>GWmodel::bw.gwr()</code> . Default "CV".
<code>adaptive</code>	logical whether to use adaptive (kNN) bandwidth. Default TRUE.
<code>feasible_radius</code>	numeric radius in miles for pre-screening prediction locations. Default 100.
<code>group_variable</code>	character or NULL. Optional column in <code>locat_predict</code> used to partition prediction points; observed points are always global.
<code>identifiers</code>	character vector of column names from <code>locat_predict</code> to carry through to the output.

Details

- Coordinates are assumed to be in **WGS84 (EPSG:4326)**.
- Prediction points without any observed points within feasible_radius miles are excluded.
- Bandwidth is estimated **once** via `GWmodel::bw.gwr()` on a random subsample (size = draw_rate * n_obs, bounded to 5, n_obs - 1).
- group_variable, if provided, splits the prediction set for parallel or modular computation, but the same global bandwidth and all observed points are used for each group.

Value

A data.table containing:

- GWSS summary statistics (e.g., local mean, SD, etc.)
- longitude, latitude - coordinates of prediction points
- block_variable - group label or 1L
- bandwidth - estimated global bandwidth
- p, theta, longlat, approach, adaptive, variable - metadata
- any columns from identifiers

Returns an empty data.table if no prediction locations pass the radius screen.

Implementation notes

- Coordinates must be valid WGS84 (longitude = x, latitude = y).
- Radius pre-screen is computed using projected distances (in meters).
- Global bandwidth ensures comparability across groups.
- Random seed (set.seed(1L)) ensures reproducibility of CV subsampling.

References

Fotheringham, A. S., Brunsdon, C., & Charlton, M. (2002). *Geographically Weighted Regression: The Analysis of Spatially Varying Relationships*. John Wiley & Sons.

```
estimate_gwss_by_polygon
```

Estimate geographically weighted summary statistics for polygons

Description

This function estimates Geographically Weighted Summary Statistics (GWSS) for one or more numeric variables observed for a subset of polygons, then evaluates the local summary statistics at all polygon locations in a supplied spatial polygon layer. It is useful for spatial smoothing and gap-filling when some polygons do not have observed values.

Usage

```
estimate_gwss_by_polygon(
  data,
  shape_file,
  fip_col,
  variable_list,
  distance_metric = "Euclidean",
  kernel = "gaussian",
  target_crs = 5070,
  draw_rate = 0.5,
  approach = "CV",
  adaptive = TRUE
)
```

Arguments

<code>data</code>	A <code>data.frame</code> or <code>data.table</code> containing the polygon identifier column specified by <code>fip_col</code> and all numeric columns listed in <code>variable_list</code> .
<code>shape_file</code>	An <code>sf</code> polygon object containing the polygon geometries. This object must contain the polygon identifier column specified by <code>fip_col</code> .
<code>fip_col</code>	Character. Name of the polygon identifier column shared by <code>data</code> and <code>shape_file</code> . This column is copied internally to <code>polygon_fips</code> and used for joining the observed data to the polygon layer.
<code>variable_list</code>	Character vector. Names of one or more numeric columns in <code>data</code> to summarize using GWSS. The first variable in this vector is also used to define the observed polygons and to select the bandwidth.
<code>distance_metric</code>	Character. Name of the distance metric to use. Must be one of the values supported by <code>gw_distance_metric_names()</code> . The selected metric is resolved by <code>resolve_distance_metric()</code> into the <code>p</code> , <code>theta</code> , and <code>longlat</code> arguments used by <code>GWmodel</code> .
<code>kernel</code>	Character. Kernel function passed to <code>GWmodel::bw.gwr()</code> and <code>GWmodel::gwss()</code> . Must be one of "gaussian", "exponential", "bisquare", "boxcar", or "tricube". Default is "gaussian".
<code>target_crs</code>	Integer EPSG code used to project polygon geometries when the selected distance metric does not use longitude/latitude distances. Default is 5070, NAD83 / CONUS Albers.
<code>draw_rate</code>	Numeric value in $(0, 1]$. Fraction of observed polygons used for bandwidth cross-validation. The actual subsample size is bounded between 5 and $n_{\text{obs}} - 1$, where n_{obs} is the number of observed polygons. Default is 0.5.
<code>approach</code>	Character. Bandwidth selection criterion passed to <code>GWmodel::bw.gwr()</code> . Must be one of "CV", "AIC", or "AICc". Default is "CV".
<code>adaptive</code>	Logical. If TRUE, use an adaptive nearest-neighbor bandwidth. If FALSE, use a fixed-distance bandwidth. Default is TRUE.

Details

The function first prepares the input data by copying the polygon identifier specified by `fip_col` into a common internal column named `polygon_fips`. It then keeps one finite observation per polygon, joins those observations to the supplied `shape_file`, and uses the observed polygons

to fit GWSS. The estimated geographically weighted summaries are then evaluated at all polygon locations using points-on-surface.

The function is designed for polygon-level spatial smoothing. Observed values are taken from data, while the full set of possible evaluation locations comes from `shape_file`. This means the returned object can include polygons that were not present in data, with their local summaries estimated from nearby observed polygons.

Internally, the function:

1. validates the input data, variables, kernel, and bandwidth-selection approach;
2. resolves the selected distance metric using `resolve_distance_metric()`;
3. creates a generic polygon identifier, `polygon_fips`, from `fip_col`;
4. keeps one finite observation per polygon based on the first variable in `variable_list`;
5. transforms the polygon layer to EPSG:4326 when `longlat = TRUE`, or to `target_crs` otherwise;
6. joins the observed data to the polygon geometries while retaining all polygons in `shape_file`;
7. selects a bandwidth using `GWmodel::bw.gwr()` on a random subsample of observed polygons;
8. computes GWSS using observed polygons as the data locations and all polygons in `shape_file` as the summary locations.

Bandwidth selection uses only the first variable in `variable_list`, but the selected bandwidth is then used to compute GWSS for all variables in `variable_list`. Use `set.seed()` before calling this function if reproducible subsampling is needed.

The function returns `NULL` with a message when fewer than five polygons have finite observed values for the first variable in `variable_list`.

Value

A `data.table` containing geographically weighted summary statistics evaluated at all polygons in `shape_file`. The returned table includes the polygon identifier column and GWSS output columns following `GWmodel::gwss()` naming conventions. For a variable named `x`, returned columns may include local statistics such as `x_LM`, `x_LSD`, `x_LCV`, `x_LSKe`, and related GWSS summaries, depending on `GWmodel::gwss()` defaults.

The returned object also has the following attributes:

bandwidth The selected GW bandwidth.

distance_params A list containing `p`, `theta`, and `longlat`.

kernel The kernel used for bandwidth selection and GWSS.

approach The bandwidth selection approach.

adaptive Whether an adaptive bandwidth was used.

gw_distance_metric_names

List valid GW distance metric names

Description

List valid GW distance metric names

Usage

```
gw_distance_metric_names()
```

Value

Character vector of valid preset names.

gw_distance_metric_presets

GW distance metric presets for GWmodel

Description

Provides a curated set of distance metric presets (Minkowski family and great-circle) for **GWmodel**. Each preset specifies (p, theta, longlat) for `GWmodel::gw.dist()`.

Usage

```
gw_distance_metric_presets()
```

Value

A named list of presets, each entry a list(p, theta, longlat).

gw_optimal_class_by_point

Optimal class for point (lattice) units

Description

Collapses a stacked table of per-unit classifications (one row per unit per distance_metric x kernel setting, within a history window) to a single optimal class per unit: the mode across settings (modal_class) plus a first-order Queen contiguity vote for optional spatial de-speckling (queen_class), with ties resolved by widening the Queen order. Coordinates are read directly from the table, matching `estimate_gwss_by_point()`.

Usage

```
gw_optimal_class_by_point(
  class_dt,
  unit_col,
  class_col = "trend_class_05",
  coords = c("longitude", "latitude"),
  include_self = TRUE,
  max_order = 10L,
  class_levels = NULL,
  verbose = FALSE
)
```

Arguments

class_dt	A data.table/data frame stacked over settings, containing the unit id (unit_col), the categorical class (class_col), and the two coordinate columns named in coords.
unit_col	Name of the spatial-unit identifier column (e.g. "grid_id").
class_col	Name of the categorical class column. Default "trend_class_05".
coords	Length-2 character vector naming the longitude/latitude columns. Default c("longitude", "latitude").
include_self	Logical; count the unit itself in the Queen vote. Default TRUE.
max_order	Maximum Queen order to expand to when breaking ties. Default 10.
class_levels	Optional character vector of all class labels (fixes the count columns / vote ordering). Default: sorted unique observed classes.
verbose	Logical; print progress. Default FALSE.

Value

A data.table with one row per unit: the id column, longitude, latitude, n_settings, modal_class, modal_agreement, queen_class, queen_order (order at which the vote resolved), and queen_agreement.

See Also

Other Optimal class selection: [gw_optimal_class_by_polygon\(\)](#)

gw_optimal_class_by_polygon

Optimal class for polygon units

Description

As gw_optimal_class_by_point(), but the spatial units are polygons: the Queen neighbours are shared-boundary contiguities of a supplied geometry (matching estimate_gwss_by_polygon(), keyed by e.g. polygon_fips), and centroids for the output come from the same geometry. Accepts a terra SpatVector or an sf object.

Usage

```
gw_optimal_class_by_polygon(
  class_dt,
  unit_col,
  polygons,
  class_col = "trend_class_05",
  poly_id = unit_col,
  include_self = TRUE,
  max_order = 10L,
  class_levels = NULL,
  verbose = FALSE
)
```

Arguments

<code>class_dt</code>	A data.table/data frame stacked over settings, containing the unit id (<code>unit_col</code>) and the categorical class (<code>class_col</code>).
<code>unit_col</code>	Name of the spatial-unit identifier column (e.g. "polygon_fips").
<code>polygons</code>	A terra SpatVector or sf polygon layer whose id field (<code>poly_id</code>) matches <code>unit_col</code> .
<code>class_col</code>	Name of the categorical class column. Default "trend_class_05".
<code>poly_id</code>	Name of the id field in polygons. Default: value of <code>unit_col</code> .
<code>include_self</code> , <code>max_order</code> , <code>class_levels</code> , <code>verbose</code>	See <code>gw_optimal_class_by_point()</code> .

Value

A data.table with one row per unit (see `gw_optimal_class_by_point()`).

See Also

Other Optimal class selection: [gw_optimal_class_by_point\(\)](#)

 PACKAGE_GLOBALVARIABLES

global_names

Description

A combined dataset for `global_names`

Usage

```
PACKAGE_GLOBALVARIABLES
```

Format

A list of global names.

Source

Internal innovation

`resolve_distance_metric`*Resolve a GW distance metric preset*

Description

Resolve a GW distance metric preset

Usage

```
resolve_distance_metric(name, stop_on_error = TRUE)
```

Arguments

<code>name</code>	Character scalar. One of <code>gw_distance_metric_names()</code> .
<code>stop_on_error</code>	Logical. If TRUE, throw for unknown names; else NULL.

Value

`list(p, theta, longlat)` or NULL.

Index

- * **Geographically weighted regression**
 - estimate_gwr_by_point, [2](#)
 - estimate_gwr_by_polygon, [3](#)
- * **Optimal class selection**
 - gw_optimal_class_by_point, [11](#)
 - gw_optimal_class_by_polygon, [12](#)
- * **datasets**
 - PACKAGE_GLOBALVARIABLES, [13](#)

estimate_gwr_by_point, [2](#), [4](#)
estimate_gwr_by_polygon, [3](#), [3](#)
estimate_gwss_by_county, [4](#)
estimate_gwss_by_point, [6](#)
estimate_gwss_by_polygon, [8](#)

gw_distance_metric_names, [11](#)
gw_distance_metric_presets, [11](#)
gw_optimal_class_by_point, [11](#), [13](#)
gw_optimal_class_by_polygon, [12](#), [12](#)

PACKAGE_GLOBALVARIABLES, [13](#)

resolve_distance_metric, [14](#)