

Package ‘rfcipDemand’

September 12, 2025

Type Package

Title Estimate Federal Crop Insurance Program Demand Models

Version 0.0.0.9000

Author Francis Tsiboe [aut, cre] (<<https://orcid.org/0000-0001-5984-1072>>)

Maintainer Francis Tsiboe <ftsiboe@hotmail.com>

Contributor -

Reviewer -

Creator Francis Tsiboe

Description Tools to construct county–crop–practice–plan–unit panels from the USDA RMA Summary of Business (SOBTPU) and related sources, and to estimate FCIP demand systems with two-way cluster-robust covariance. The pipeline standardizes coverage measures, merges price and instrument variables, adds rental-rate and price-index controls, reconciles county acreage (FSA/NASS), and produces diagnostics including robust first-stage F-tests. Methods align with the empirical design in “The crop insurance demand response to premium subsidies Evidence from U.S. Agriculture” (Food Policy, 2023, 119(3)).

License GPL-3 + file LICENSE

URL <https://github.com/you/rfcipDemand>

BugReports <https://github.com/you/rfcipDemand/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

VignetteBuilder knitr

Depends R (>= 4.1.0)

Imports rfsa, data.table, systemfit, sandwich, doBy, car, plyr, usmap, stats, utils, tidyr, stringr

Remotes github::UrbanInstitute/urbnmapr, github::dylan-turner25/rfsa, github::JanMarvin/nlsur

Suggests knitr, rmarkdown, tibble, dplyr, lavaan, testthat (>= 3.0.0)

LazyData true

Cite-us If you find it useful, please consider starring the repository and citing the following studies

- Tsiboe, F. and Turner, D. (2025). “Incorporating buy-up price loss coverage into the United States farm safety net.” Applied Economic Perspectives and Policy.
- Tsiboe, F., et al. (2025). “Risk reduction impacts of crop insurance in the United States.”

Applied Economic Perspectives and Policy.
- Gaku, S. and Tsiboe, F. (2024). Evaluation of alternative farm safety net program combination strategies. Agricultural Finance Review.

Contents

calculate_mode	2
calibrate_fcip_demand_elasticities	3
estimate_fcip_instruments	4
fcip_contiguous_county	5
fcip_demand_data_dispatcher	5
fcip_demand_elasticities_lavaan	6
fcip_demand_sys_coeff_table	7
fcip_demand_sys_effect	7
fcip_demand_sys_estimate	8
fcip_demand_sys_fit	9
fcip_demand_sys_partial	10
fcip_demand_sys_prep	11
fcip_demand_sys_run	11
fcip_demand_sys_tests	12
fcip_demand_sys_vcov	12
fcip_recodes_commodity_groupings	13
fcip_recodes_insurance_plan	14
fcip_recodes_practice	14
fcip_recodes_type	15
fixed_effect_model_data_prep	15
format_fcip_demand_table	16
fsa_crop_linker	17
get_yu2018_instrument	17
nass_census_state_beginning_farmer_and_rancher_data	18
nass_index_for_price_recived	19
nass_marketing_year_avg_price	19
nass_state_rental_rates	20
nass_us_ag_price_index_monthly	20
Index	21

calculate_mode	<i>Calculate the Statistical Mode</i>
----------------	---------------------------------------

Description

Returns the element that occurs most frequently in a vector.

Usage

```
calculate_mode(x, na.rm = TRUE)
```

Arguments

<code>x</code>	A vector of any atomic type (numeric, character, factor,).
<code>na.rm</code>	Logical; should missing values be ignored? Defaults to TRUE. If FALSE and <code>x</code> contains any NAs, the function returns NA.

Details

Internally the function:

1. Optionally removes NAs (`na.rm = TRUE`).
2. Builds a lookup table of unique values via `unique(x)`.
3. Counts the frequency of each unique value with `tabulate(match(x, ux))`.
4. Returns the value with the maximum count.

Because it relies on base R functions, the implementation is vectorised and generally fast for typical data-frame column sizes.

Value

A single value giving the modal element of `x`. If two or more values are tied for the highest frequency, the first one encountered in `x` is returned.

calibrate_fcip_demand_elasticities
Calibrate FCIP demand elasticities

Description

Fits a 2-equation FCIP demand system over an estimation window ending in `calibration_year` and returns capped elasticities $(-2, 0)$ by disaggregation level using `rfcipDemand::fcip_demand_sys_estimate()`.

Usage

```
calibrate_fcip_demand_elasticities(
  calibration_year,
  estimation_window,
  data,
  drawn_pools = NULL,
  disaggregate = NULL
)
```

Arguments

<code>calibration_year</code>	Integer. Last year of the estimation window.
<code>estimation_window</code>	Integer (≥ 1). Number of years ending at <code>calibration_year</code> .
<code>data</code>	<code>data.table</code> . Input panel. Must include: <code>commodity_year</code> , <code>commodity_code</code> , <code>drawID</code> , <code>pool</code> , <code>insurance_plan_code</code> , <code>price</code> , <code>net_reporting_level_amount</code> , <code>coverage_level_percent_aggregate</code> , <code>rent</code> , <code>county_acreage</code> , <code>total_premium_amount</code> , <code>subsidy_amount</code> , <code>liability_amount</code> , <code>tau</code> , <code>subsidy_rate_65</code> , <code>subsidy_rate_75</code> .

`drawn_pools` Optional `data.table` used to filter data via an inner join on intersecting columns.

`disaggregate` Optional character vector of grouping variables passed to the estimator (e.g., `"commodity_code"` or `c("state", "commodity_code")`).

Details

Internally, the function (i) restricts data to the estimation years, (ii) collapses insurance plan codes and sets `price := 1` for non-RP crops, (iii) constructs log variables, trend and year dummies, and (iv) estimates the system with rate endogenous and τ_0 as the excluded instrument. Estimates are truncated to $(-2, 0)$ and returned in wide form.

Value

`data.table` with columns: `disag`, `level`, `gamma_elasticity`, `theta_elasticity`.

estimate_fcip_instruments

Estimate FCIP Instrumental Variables (Unloaded Rates)

Description

Uses historical FCIP rate data to build instrumented unloaded-rate variables following:

1. Tsiboe & Turner (2023), Econometric identification of crop insurance participation *Agricultural and Resource Economics Review*, 52(3):476-497. <https://doi.org/10.1017/age.2023.13>

Usage

```
estimate_fcip_instruments(year, statplan)
```

Arguments

`year` Integer. The target crop year for which to construct instruments.

`statplan` A `data.table` containing FCIP rate elements, including at least:

- `commodity_year`** Year of the rate observation.
- `state_code`, `county_code`** County identifiers.
- `commodity_code`** Crop identifier.
- `insured_area`, `lcr`, `contiguous_state_code`, `contiguous_county_code`** Fields required by `estimate_fcip_unloaded_rate()`.

Details

1. **Task list:** Identify all unique (state, county) pairs with data in the 2-21 years before year.
2. **Unloaded-rate calculation:** For each county in `task_list`, call `estimate_fcip_unloaded_rate()` on the same 2-21 year window to get τ . Errors return NULL so processing continues.
3. **Contiguous-county smoothing:**
 - Build a lookup table of contiguous counties (using `contiguous_county`).
 - For each contiguous group, compute the mean τ to get τ_{uc} .

4. **Merge & fill:** Left-join the raw adm and contiguous_adm; replace any zero/NA/Inf tau with the group mean tau_c into tau_sob.
5. **Cleanup:** Drop helper columns (tau, tau_c), remove invalid rows, add commodity_year, and return the result.

Value

A data.table with one row per county-crop for the specified year, containing:

state_code, county_code, commodity_code Keys.

tau_sob Smoothed unloaded rate (uses contiguous-county means to fill zeros/NAs).

commodity_year The input year, repeated.

See Also

Other FCIP instruments: [get_yu2018_instrument\(\)](#)

fcip_contiguous_county
fcip_contiguous_county

Description

A combined dataset for fcip_contiguous_county

Usage

```
data(fcip_contiguous_county)
```

Format

A data frame with 24307 rows and 12 columns covering Inf–Inf.

Source

USDA-RMA, Actuarial Data Master - A0123

```
fcip_demand_data_dispatcher
```

Build dataset to estimate Federal Crop Insurance Program (FCIP) demand (modular pipeline)

Description

End-to-end pipeline that: (1) prepares SOBTPU and coverage aggregates, (2) adds prices/instruments/rental rates/price index, (3) reconciles county acreage (FSA + NASS), and (4) finalizes bins/labels/pooling for demand estimation.

Usage

```
fcip_demand_data_dispatcher(
  study_years = 2001:(as.numeric(format(Sys.Date(), "%Y")) - 1),
  identifiers = c("commodity_year", FCIP_INSURANCE_POOL, "insurance_plan_code",
    "unit_structure_code")
)
```

Arguments

<code>study_years</code>	Integer vector of commodity years to include. Defaults to <code>2001:(as.numeric(format(Sys.Date(), "%Y")) - 1)</code> .
<code>identifiers</code>	Character vector of grouping keys that define the aggregation grain. Must be columns present in SOBTPU (e.g., "commodity_year", FCIP_INSURANCE_POOL, "insurance_plan_code", "unit_structure_code", and-if desired-additional keys like "commodity_code" or "practice_code"). Enrichment joins for re-codes are performed only when the required keys are included in identifiers

Details

Aligned with Asche, Bakkerman, & Li (2023), *Food Policy*, 119(3):102505 ([doi:10.1016/j.foodpol.2023.102505](https://doi.org/10.1016/j.foodpol.2023.102505)). Requires internet access to download release .rds assets and several in-memory lookup tables (see stage docs).

Value

A `data.table` ready for FCIP demand estimation.

```
fcip_demand_elasticities_lavaan
```

Calibrate FCIP demand elasticities via IV-SEM (lavaan)

Description

Fits a just-identified IV-style SEM where `instr_rate` instruments `tilda_rate`, and `tilda_rate` enters two outcome equations (`tilda_ghamma`, `tilda_theta`). Endogeneity is encoded via residual correlations between `tilda_rate` and each outcome. The instrument is excluded from the outcome disturbances.

Usage

```
fcip_demand_elasticities_lavaan(
  data,
  estimator = c("ML", "MLR"),
  missing = c("fiml", "listwise")
)
```

Arguments

data	data.frame with cols: instr_rate, tilda_rate, tilda_gamma, tilda_theta
estimator	"ML" or "MLR" (default "MLR" = robust SE/tests)
missing	"fiml" or "listwise" (default "fiml")

Details

Constraints imposed:

1. $b1 < 0$, 2) $b2 < 0$, 3) $b1 + b2 + b1*b2 < 0$

Value

A data.table of parameter estimates and logical convergence flag

fcip_demand_sys_coeff_table

Tidy coefficient table with cluster-robust SEs (from supplied VCOV)

Description

Builds a clean coefficient table for a systemfit model using a **user-supplied covariance matrix** (e.g., two-way clustered from fcip_demand_sys_vcov()). Estimates come from coef(fit), standard errors from diag(vcMat), then Z-scores and two-sided normal p-values are computed. The demand column is inferred from the equation prefix in the coefficient names:

- "gamma_*" to "gamma"
- "theta_*" to "theta" Otherwise the prefix itself is used.

Usage

```
fcip_demand_sys_coeff_table(fit, vcMat, p_digits = 5)
```

Arguments

fit	A fitted systemfit object.
vcMat	A covariance matrix conformable with coef(fit). Row/column names are used to align; if missing, positional alignment is assumed.
p_digits	Integer; number of digits to keep for p-values (default 5).

Value

A data.frame with columns: demand, coef, Estimate, StdError, Zvalue, Pvalue.

fcip_demand_sys_effect

Delta-method "total protection response"

Description

Combines equation-specific effects into a single "total" effect for each regressor in `c(fields$endogenous, fields$included)` using `car::deltaMethod` and a supplied covariance matrix.

Usage

```
fcip_demand_sys_effect(fit, vcMat, fields, data)
```

Arguments

<code>fit</code>	A fitted <code>systemfit</code> object (the structural system).
<code>vcMat</code>	Covariance matrix conformable with <code>coef(fit)</code> (e.g., from <code>fcip_demand_sys_vcov()</code>).
<code>fields</code>	Named list carrying model fields; must include <code>outcome</code> , <code>endogenous</code> , and <code>included</code> .
<code>data</code>	Estimation data used to check variable availability and build delta-method expressions.

Value

A `data.frame` with rows `demand="total"` and columns: `demand`, `coef`, `Estimate`, `StdError`, `Zvalue`, `Pvalue`.

fcip_demand_sys_estimate

System estimator (modular wrapper; preserves original outputs)

Description

Estimates a two-equation system with an endogenous regressor across disaggregation levels. The pipeline is: (1) per-level sample selection (min `n` per `commodity_year`), (2) partialling-out / tilda transforms, (3) system estimation (e.g., IV/3SLS via internal helpers), (4) clustered variance estimation, (5) delta-method totals, (6) optional constrained re-estimation of elasticities (`lavaan`), (7) diagnostics, and (8) row-binding results across levels.

Usage

```
fcip_demand_sys_estimate(model, data, constrained_elasticities = FALSE)
```


Arguments

model	<p>List specifying the system; required elements are:</p> <ul style="list-style-type: none"> • outcome (character(2)): names of the two outcomes in data. • endogenous (character(1)): endogenous regressor name. • included (character): included (exogenous) regressors. • disag (character(1) or NULL): disaggregation key column in data. • FE (logical): include fixed effects in the internal run (handled by helpers). <p>Optional elements:</p> <ul style="list-style-type: none"> • excluded (character or NULL): excluded instruments. • partial (character or NULL): variables to partial out (tilda). • restrict (logical): pass-through to internal restricted estimation. • name (character(1)): label carried to the output.
data	data.frame/data.table containing all referenced columns in model plus pool and commodity_year. Columns in model\$outcome, model\$endogenous, model\$included, and (if used) model\$excluded and model\$partial must exist in data.
constrained_elasticities	<p>Logical (default FALSE). If TRUE, re-estimate the elasticities via a constrained SEM (lavaan) and, where applicable, replace positive elasticity estimates with constrained ones. See Constrained elasticities (optional).</p>

Details

Inputs and preprocessing

- model\$outcome must be a character vector of length 2 giving the two outcome column names in data. Internally these are mapped to gamma and theta for estimation convenience.
- model\$disag is the name of the disaggregation key. If NULL, a dummy "full_sample" key is created.
- The disaggregation key is coerced to character.
- For each level of model\$disag, the function keeps only levels that have **at least 30 observations per** commodity_year (computed via doBy::summaryBy). Levels failing this threshold are dropped.

Per-level estimation For each retained level, the function calls internal helpers (fcip_demand_sys_run, etc.) to (i) partially out controls if requested, and (ii) estimate the system with clustered VCOV and delta-method totals. Errors at the level are caught and the level is skipped (no hard stop).

Constrained elasticities (optional) When constrained = TRUE, elasticities on the endogenous regressor are re-estimated per level via a lavaan SEM with sign restrictions (internal helper fcip_demand_elasticities_1 using estimator = "MLR", missing = "listwise"). The constrained estimates replace any positive system estimates for the elasticities; a logical flag constrained marks levels where a replacement occurred. The returned columns are reduced to disag, level, demand, constrained, and Estimate.

Returned shape

- If constrained_elasticities = FALSE (default), returns the full per-level system output from fcip_demand_sys_run with additional columns: disag, level, and rounded Zvalue, Pvalue.
- If constrained = TRUE, returns a compact table with disag, level, demand, constrained, Estimate after merging the constrained elasticities.

Value

A `data.table` aggregating results across all disaggregation levels. The column set depends on constrained (see **Returned shape**).

fcip_demand_sys_fit	<i>Build systemfit formulas and estimate the system</i>
---------------------	---

Description

Constructs the list of structural equations (g) and instrument sets (h), then runs `systemfit()` using OLS (when no excluded instruments) or 3SLS-GMM (when excluded instruments are present).

Usage

```
fcip_demand_sys_fit(
  data,
  fields,
  tilda_included,
  tilda_endogenous,
  tilda_excluded
)
```

Arguments

<code>data</code>	Estimation <code>data.frame</code> / <code>data.table</code> containing the <code>tilda_*</code> and <code>instr_*</code> variables referenced by the formulas.
<code>fields</code>	Named list with at least outcome, included, endogenous, and optionally excluded.
<code>tilda_included</code>	Character vector of residualized included regressor names (e.g., "tilda_x1").
<code>tilda_endogenous</code>	Character vector of residualized endogenous regressor names (e.g., "tilda_z1").
<code>tilda_excluded</code>	Character vector of instrument names (e.g., "instr_z1"), or NULL when no excluded instruments are used.

Value

A list with elements:

<code>fit</code>	Fitted <code>systemfit</code> object.
<code>g</code>	List of structural formulas.
<code>h</code>	List of instrument formulas.

fcip_demand_sys_partial

Residualize ("partial out") and build tilded / instrument variables

Description

If excluded instruments exist, runs first-stage OLS for each endogenous variable e : $e \sim 1 + \text{partial} + \text{included} + \text{excluded}$, storing the fitted values as `instr_e`. If `partial` is non-empty, it then regresses $\text{instr_e} \sim 1 + \text{partial}$ and replaces `instr_e <- instr_e - fitted(instr_e ~ partial)` (i.e., removes the partial component; conceptually $\widehat{\text{instr}_e}(\text{partial})$).

Outcomes, included, and endogenous variables are residualized on `partial` to create `tilda_<var>` (or copied if `partial` is empty).

Usage

```
fcip_demand_sys_partial(data, fields, partial_override = NULL)
```

Arguments

<code>data</code>	A <code>data.frame</code> / <code>data.table</code> with referenced variables.
<code>fields</code>	List with: <code>outcome</code> , <code>endogenous</code> , <code>included</code> , optional <code>excluded</code> , optional <code>partial</code> .
<code>partial_override</code>	Optional character vector to override <code>fields\$partial</code> .

Details

Uses defensive checks so absent columns are ignored (with a warning) rather than erroring. If `partial` is empty, residualization is a no-op and `tilda_*` simply copy the originals. Formulas are constructed via `stats::reformulate()` to avoid paste/quoting pitfalls.

Value

List with `data`, `tilda_included`, `tilda_endogenous`, `tilda_excluded`.

fcip_demand_sys_prep *Prepare data for analysis*

Description

Drops incomplete/invalid rows, removes constant partials, and optionally demeanes via a fixed-effects helper.

Usage

```
fcip_demand_sys_prep(data, fields)
```

Arguments

data	Estimation dataset that already contains all columns referenced by fields.
fields	Named list: outcome, endogenous, included, excluded (opt), partial (opt), FE (logical), disag (column name).

Value

A list: data (prepped), NFE (number of FE), partial (possibly reduced).

fcip_demand_sys_run	<i>Orchestrate analysis</i>
---------------------	-----------------------------

Description

Runs the full pipeline: prep -> partial/tilda creation -> systemfit -> two-way clustered VCOV -> delta-method totals -> optional restricted step -> diagnostics; then returns a tidy coefficient table with metadata.

Usage

```
fcip_demand_sys_run(data, fields)
```

Arguments

data	Estimation dataset
fields	Named list carrying model fields (see <code>fcip_demand_estimation()</code>), including disag, FE, outcome, endogenous, included, optional excluded, partial, restrict, and name.

Value

A data.frame with columns demand, coef, Estimate, StdError, Zvalue, Pvalue and meta-columns model, endogenous, FE, name, disag

fcip_demand_sys_tests	<i>System diagnostics: two-way robust first-stage F (+ optional approx. J)</i>
-----------------------	--

Description

Produces diagnostics **without** re-running GMM:

- **FTest**: joint relevance of excluded instruments in each first stage, using the same two-way (pool by crop year) cluster-robust covariance via `fcip_demand_sys_vcov()` with `kind = "lm"`. Reports the **minimum** F across endogenous regressors.
- **JTest** (optional): an *approximate* over-identification test computed as the sum of per-equation Sargan statistics $J_k \approx n_k R_k^2$ from regressions of equation residuals on that equation's instrument set. This is a quick check (not the system Hansen J).

Usage

```
fcip_demand_sys_tests(g, h, data, fit, NFE, approx_j = FALSE)
```

Arguments

<code>g</code>	List of system equations (the same formulas passed to <code>systemfit</code>).
<code>h</code>	List of instrument formulas (the same formulas passed to <code>systemfit</code>).
<code>data</code>	Estimation <code>data.frame</code> / <code>data.table</code> containing all variables in <code>g/h</code> plus clustering columns <code>pool</code> and <code>crop_yr</code> .
<code>fit</code>	A fitted <code>systemfit</code> object (used for <code>N</code> and <code>residCov_*</code> extraction).
<code>NFE</code>	Integer: number of absorbed fixed effects (for reporting only).
<code>approx_j</code>	Logical, compute the approximate (non-robust) Sargan J as described above. Default FALSE (returns NA for JTest).

Value

A `data.frame` with rows: `N`, `NFE`, `residCov_11`, `residCov_22`, `residCov_12`, `JTest`, `FTest`.

<code>fcip_demand_sys_vcov</code>	<i>Two-way cluster-robust covariance for FCIP demand models</i>
-----------------------------------	---

Description

Computes a Cameron-Gelbach-Miller two-way cluster-robust covariance matrix using inclusion-exclusion: $V = V_{pool} + V_{year} - V_{pool_year}$. Works for both `systemfit` (stacked system) and `lm` (first-stage).

Usage

```
fcip_demand_sys_vcov(
  object,
  data,
  kind = c("systemfit", "lm"),
  pool_col = "pool",
  year_col = "commodity_year",
  NFE = 0L,
  n_partial = 0L,
  n_eq = NULL
)
```

Arguments

<code>object</code>	Fitted model: either a <code>systemfit</code> or <code>lm</code> .
<code>data</code>	Estimation data containing <code>pool</code> and <code>year</code> identifiers.
<code>kind</code>	One of <code>c("systemfit", "lm")</code> . If omitted, auto-detected.
<code>pool_col</code>	Name of the pool/cluster id column in <code>data</code> (default <code>"pool"</code>).
<code>year_col</code>	Name of the year/time id column in <code>data</code> (default <code>"crop_yr"</code>).
<code>NFE</code>	Integer; number of absorbed fixed effects (for df rescaling).

n_partial	Integer; count of variables partialled out per equation.
n_eq	Integer; number of equations (length(object\$eq) for systemfit, 1 for lm). You can override if needed.

Details

Rescaling. Let n be the number of observations (stacked across equations for systemfit). With k_{old} the number of coefficients and $k_{new} = k_{old} + NFE + n_{partial} * n_{eq}$, the returned matrix is scaled by $(n - k_{old} - 1) / (n - k_{new} - 1)$.

Row alignment (lm). Rows used by lm are inferred from rownames(model.matrix(object)). If they cannot be mapped back to data, the first nobs(object) rows are used.

Value

Covariance matrix aligned with coef(object).

fcip_recodes_commodity_groupings
<i>fcip_recodes_commodity_groupings</i>

Description

A combined dataset for fcip_recodes_commodity_groupings

Usage

data(fcip_recodes_commodity_groupings)

Format

A data frame with 3572 rows and 10 columns covering 1997-2025.

Source

USDA-RMA, Actuarial Data Master - A00400 and A00420 supplemented data from legacy ADM files

fcip_recodes_insurance_plan
<i>fcip_recodes_insurance_plan</i>

Description

A combined dataset for fcip_recodes_insurance_plan

Usage

data(fcip_recodes_insurance_plan)

Format

A data frame with 773 rows and 10 columns covering 1989-2025.

Source

USDA-RMA, Actuarial Data Master - A00460 supplemented data from legacy ADM files

fcip_recodes_practice	<i>fcip_recodes_practice</i>
-----------------------	------------------------------

Description

A combined dataset for fcip_recodes_practice

Usage

```
data(fcip_recodes_practice)
```

Format

A data frame with 28639 rows and 8 columns covering 1997-2025.

Source

USDA-RMA, Actuarial Data Master - A00510 supplemented data from legacy ADM files

fcip_recodes_type	<i>fcip_recodes_type</i>
-------------------	--------------------------

Description

A combined dataset for fcip_recodes_type

Usage

```
data(fcip_recodes_type)
```

Format

A data frame with 232709 rows and 7 columns covering 1999-2025.

Source

Generated internally, using `harmonize_crop_type_codes()`

fixed_effect_model_data_prep

Prepare and demean data for fixed-effects models

Description

This function

1. Filters to complete cases on the specified panel, time, weight, variables, and output
2. If output is NULL, creates a dummy output column filled with 1s
3. Drops any panel with only one observation
4. Computes within-panel means for the output + each variable in varlist (`_mean_i`)
5. Computes overall sample means for the same set of variables (`_mean`)
6. Replaces each variable in varlist by $\text{value} - \text{within_panel_mean} + \text{overall_mean}$

Usage

```
fixed_effect_model_data_prep(
  data,
  varlist,
  panel,
  time,
  wvar = NULL,
  output = NULL
)
```

Arguments

<code>data</code>	A data.frame or data.table containing the data.
<code>varlist</code>	Character vector of variable names to be demeaned.
<code>panel</code>	Character vector of column name(s) defining the panel identifier.
<code>time</code>	Character scalar name of the time variable.
<code>wvar</code>	Character scalar name of a variable to keep but <i>not</i> demean (optional, default NULL).
<code>output</code>	Character scalar name of an output variable whose means are computed but not altered; if NULL, a dummy column named "output" is created (optional, default NULL).

Value

A list with components

- **data**: a data.table containing
 - the original panel, time, wvar, varlist, and output columns
 - two mean columns for each of `c(output, varlist)`: `<name>_mean_i` (within-panel) and `<name>_mean` (overall)
- **NFE**: the number of panels with more than one observation

format_fcip_demand_table

Table: Crop Insurance Demand System for US Federal Crop Insurance Pools (2001/22)

Description

Build a two-column, GitHub-safe panel table summarizing a crop insurance demand system. The table is organized into panels for coverage level (Theta), insured acres (Gamma), total protection response, a covariance matrix block, and additional statistics. Coefficients are formatted as estimate (std. error) with significance stars.

Usage

```
format_fcip_demand_table(df, var_labels)
```

Arguments

df	A data frame containing the results with columns: <ul style="list-style-type: none"> demand (chr): panel identifier; expected values include "Theta", "Gamma", and "Total". coef (chr): raw coefficient/row labels (e.g., "tilda_rate", "residCov_11", "N"). Estimate (dbl): point estimates. StdError (dbl): standard errors (may be NA for scalars). Pvalue (dbl): p-values used to add significance stars.
var_labels	A named character vector mapping raw names to display labels,

Details

Designed for README/output knitted as github_document; use with knitr::kable(..., format = "pipe") to avoid HTML-only features.

Value

A tibble with two columns, Variables and Estimates, where panel headers have empty Estimates to enable bolding (if rendered in HTML) and coefficients are formatted as "estimate*** (se)".

fsa_crop_linker

Simulator Helper Datasets

Description

A combined dataset for fsa_crop_linker

Usage

```
data(fsa_crop_linker)
```

Format

A data frame with 8594 rows and 8 columns covering Inf–Inf.

Source

Internal innovation

get_yu2018_instrument *Formulate & Merge National Subsidy Rate Instrument (Yu et al., 2018)*

Description

Downloads the historical Summary of Business RDS and computes national subsidy-rate instruments at specified coverage levels, following Yu et al. (2018).

Usage

```
get_yu2018_instrument(
  dt,
  delivery_systems = c("RBUP", "FBUP"),
  plan_codes = c(1:3, 90, 44, 25, 42),
  coverage_levels = c(65, 75)
)
```

Arguments

dt	sobcov
delivery_systems	Character vector. Delivery systems to include; default c("RBUP", "FBUP").
plan_codes	Integer vector. Insurance plan codes to include; default c(1:3, 90, 44, 25, 42).
coverage_levels	Numeric vector. Percent coverage levels to keep; default c(65, 75).

Value

A data.table with columns: commodity_year, subsidy_rate_65, subsidy_rate_75.

See Also

Other FCIP instruments: [estimate_fcip_instruments\(\)](#)

```
nass_census_state_beginning_farmer_and_rancher_data  
    nass_census_state_beginning_farmer_and_rancher_data
```

Description

A combined dataset for nass_census_state_beginning_farmer_and_rancher_data

Usage

```
data(nass_census_state_beginning_farmer_and_rancher_data)
```

Format

A data frame with 255 rows and 16 columns covering Inf–Inf.

Source

USDA NASS Quick Stats

```
nass_index_for_price_recived  
    nass_index_for_price_recived
```

Description

A combined dataset for nass_index_for_price_recived

Usage

```
data(nass_index_for_price_recived)
```

Format

A data frame with 35 rows and 3 columns covering 1990-2024.

Source

USDA NASS Quick Stats

nass_marketing_year_avg_price
nass_marketing_year_avg_price

Description

A combined dataset for nass_marketing_year_avg_price

Usage

data(nass_marketing_year_avg_price)

Format

A data frame with 31139 rows and 7 columns covering 1866-2024.

Source

USDA NASS Quick Stats

nass_state_rental_rates
nass_state_rental_rates

Description

A combined dataset for nass_state_rental_rates

Usage

data(nass_state_rental_rates)

Format

A data frame with 1792 rows and 5 columns covering 1994-2025.

Source

Output from get_state_rental_rates() function

`nass_us_ag_price_index_monthly`

nass_us_ag_price_index_monthly

Description

A combined dataset for `nass_us_ag_price_index_monthly`

Usage

```
data(nass_us_ag_price_index_monthly)
```

Format

A data frame with 2255 rows and 8 columns covering Inf–Inf.

Source

USDA NASS: https://www.nass.usda.gov/Charts_and_Maps/graphics/data

Index

- * **Estimation Data**
 - fcip_demand_data_dispatcher, [5](#)
 - * **Estimators panel models**
 - fixed_effect_model_data_prep, [15](#)
 - * **FCIP instruments**
 - estimate_fcip_instruments, [4](#)
 - get_yu2018_instrument, [17](#)
 - * **datasets**
 - fcip_contiguous_county, [5](#)
 - fcip_recodes_commodity_groupings, [13](#)
 - fcip_recodes_insurance_plan, [14](#)
 - fcip_recodes_practice, [14](#)
 - fcip_recodes_type, [15](#)
 - fsa_crop_linker, [17](#)
 - nass_census_state_beginning_farmer_and_rancher_data, [18](#)
 - nass_index_for_price_recived, [19](#)
 - nass_marketing_year_avg_price, [19](#)
 - nass_state_rental_rates, [20](#)
 - nass_us_ag_price_index_monthly, [20](#)
- calculate_mode, [2](#)
- calibrate_fcip_demand_elasticities, [3](#)
- estimate_fcip_instruments, [4](#), [18](#)
- fcip_contiguous_county, [5](#)
- fcip_demand_data_dispatcher, [5](#)
- fcip_demand_elasticities_lavaan, [6](#)
- fcip_demand_sys_coeff_table, [7](#)
- fcip_demand_sys_effect, [7](#)
- fcip_demand_sys_estimate, [8](#)
- fcip_demand_sys_fit, [9](#)
- fcip_demand_sys_partial, [10](#)
- fcip_demand_sys_prep, [11](#)
- fcip_demand_sys_run, [11](#)
- fcip_demand_sys_tests, [12](#)
- fcip_demand_sys_vcov, [12](#)
- fcip_demand_sys_vcov(), [12](#)
- fcip_recodes_commodity_groupings, [13](#)
- fcip_recodes_insurance_plan, [14](#)
- fcip_recodes_practice, [14](#)
- fcip_recodes_type, [15](#)
- fixed_effect_model_data_prep, [15](#)
- format_fcip_demand_table, [16](#)
- fsa_crop_linker, [17](#)
- get_yu2018_instrument, [5](#), [17](#)
- nass_census_state_beginning_farmer_and_rancher_data, [18](#)
- nass_index_for_price_recived, [19](#)
- nass_marketing_year_avg_price, [19](#)
- nass_state_rental_rates, [20](#)
- nass_us_ag_price_index_monthly, [20](#)