

Sparse recovery problem in a hierarchical Bayesian framework

Monica Pragliola, Daniela Calvetti, Erkki Somersalo, Alexander Strang

Abstract

A common task in inverse problems and imaging is finding a solution that is sparse, in the sense that most of its components vanish. In the framework of compressed sensing, general results guaranteeing exact recovery have been proven [5, 6]. In practice, sparse solutions are often computed combining ℓ_1 -penalized least squares optimization with an appropriate numerical scheme to accomplish the task. A computationally efficient alternative for finding sparse solutions to linear inverse problems is provided by Bayesian hierarchical models, in which the sparsity is encoded by defining a conditionally Gaussian prior model with the prior parameter obeying a generalized gamma distribution. An iterative alternating sequential (IAS) algorithm has been demonstrated to lead to a computationally efficient scheme, and combined with Krylov subspace iterations with an early termination condition, the approach is particularly well suited for large scale problems [1, 4, 3]. In this talk, we will discuss a hybrid version of the original IAS that first exploits the global convergence associated with gamma hyperpriors to arrive in a neighborhood of the unique minimizer, then adopts a generalized gamma hyperprior that promotes sparsity more strongly [2]. The hybrid IAS, that has been originally designed for linear inverse problems, is also extended to the case of non-linear forward model operators [8]. The algorithm will be tested on synthetic data for the linear image restoration inverse problem, and on real data for the non-linear electrical impedance tomography reconstruction [7].

References

- [1] D. Calvetti, A. Pascarella, F. Pitolli, E. Somersalo, B. Vantaggi (2019) Brain activity mapping from MEG data via a hierarchical Bayesian algorithm with automatic depth weighting. *Brain Topography*, 32.
- [2] D. Calvetti, M. Pragliola, E. Somersalo (2020) Sparsity promoting hybrid solvers for hierarchical Bayesian inverse problems. *SIAM Journal on Scientific Computing*, 42.
- [3] D. Calvetti, M. Pragliola, E. Somersalo, A. Strang (2020) Sparse reconstructions from few noisy data: analysis of hierarchical Bayesian models with generalized gamma hyperpriors. *Inverse Problems*, 36.
- [4] D. Calvetti, E. Somersalo, A. Strang (2019) Hierarchical Bayesian models and sparsity: ℓ_2 -magic. *Inverse Problems*, 35.
- [5] E.J. Candes, J.K. Romberg, T. Tao (2006) Stable signal recovery from incomplete and inaccurate measurements. *Communications on Pure and Applied Mathematics*, 59.
- [6] D. Donoho (2006) For most large underdetermined systems of linear equations the minimal ℓ_1 -norm solution is also the sparsest solution. *Communications on Pure and Applied Mathematics*, 59.
- [7] A. Hauptmann, A. Seppänen (2024) Preface. *Applied Mathematics for Modern Challenges*, 2.
- [8] M. Pragliola, D. Calvetti, E. Somersalo (2024) An efficient hierarchical Bayesian method for the Kuopio tomography challenge 2023. *Applied Mathematics for Modern Challenges*, 2.