



Text Classification and Naïve Bayes

The Task of Text Classification

Is this spam?

Subject: Important notice!

From: Stanford University <newsforum@stanford.edu>

Date: October 28, 2011 12:34:16 PM PDT

To: undisclosed-recipients;;

Greats News!

You can now access the latest news by using the link below to login to Stanford University News Forum.



<http://www.123contactform.com/contact-form-StanfordNew1-236335.html>

Click on the above link to login for more information about this new exciting forum. You can also copy the above link to your browser bar and login for more information about the new services.


© Stanford University. All Rights Reserved.

Who wrote which Federalist papers?

- 1787-8: anonymous essays try to convince New York to ratify U.S Constitution: Jay, Madison, Hamilton.
- Authorship of 12 of the letters in dispute
- 1963: solved by Mosteller and Wallace using Bayesian methods



James Madison



Alexander Hamilton

Male or female author?

1. By 1925 present-day Vietnam was divided into three parts under French colonial rule. The southern region embracing Saigon and the Mekong delta was the colony of Cochinchina; the central area with its imperial capital at Hue was the protectorate of Annam...
2. Clara never failed to be astonished by the extraordinary felicity of her own name. She found it hard to trust herself to the mercy of fate, which had managed over the years to convert her greatest shame into one of her greatest assets...

Positive or negative movie review?



- unbelievably disappointing



- Full of zany characters and richly applied satire, and some great plot twists




- this is the greatest screwball comedy ever filmed



- It was pathetic. The worst part about it was the boxing scenes.

What is the subject of this article?

MEDLINE Article



MeSH Subject Category Hierarchy

- Antagonists and Inhibitors
- Blood Supply
- Chemistry
- Drug Therapy
- Embryology
- Epidemiology
- ...

Text Classification

- Assigning subject categories, topics, or genres
- Spam detection
- Authorship identification
- Age/gender identification
- Language Identification
- Sentiment analysis
- ...

Text Classification: definition

- *Input:*

- a document d
- a fixed set of classes $C = \{c_1, c_2, \dots, c_J\}$

- *Output:* a predicted class $c \in C$

Classification Methods:

Hand-coded rules

- Rules based on combinations of words or other features
 - spam: black-list-address OR (“dollars” AND “have been selected”)
- Accuracy can be high
 - If rules carefully refined by expert
- But building and maintaining these rules is expensive

Classification Methods:

Supervised Machine Learning

- *Input:*

- a document d
- a fixed set of classes $C = \{c_1, c_2, \dots, c_J\}$
- A training set of m hand-labeled documents
 $(d_1, c_1), \dots, (d_m, c_m)$

- *Output:*

- a learned classifier $\gamma: d \rightarrow c$

Classification Methods:

Supervised Machine Learning

- Any kind of classifier
 - Naïve Bayes
 - Logistic regression
 - Support-vector machines
 - k-Nearest Neighbors
- ...

Text Classification and Naïve Bayes

Naïve Bayes (I)

Naïve Bayes Intuition

- Simple (“naïve”) classification method based on Bayes rule
- Relies on very simple representation of document
 - Bag of words

The bag of words representation

Y (

I love this movie! It's sweet, but with satirical humor. The dialogue is great and the adventure scenes are fun... It manages to be whimsical and romantic while laughing at the conventions of the fairy tale genre. I would recommend it to just about anyone. I've seen it several times, and I'm always happy to see it again whenever I have a friend who hasn't seen it yet.

) = C



The bag of words representation

Y (

I **love** this movie! It's **sweet**, but with **satirical** humor. The dialogue is **great** and the adventure scenes are **fun**... It manages to be **whimsical** and **romantic** while **laughing** at the conventions of the fairy tale genre. I would **recommend** it to just about anyone. I've seen it **several** times, and I'm always **happy** to see it **again** whenever I have a friend who hasn't seen it yet.

) = C



The bag of words representation:
using a subset of words

Y (

```
x love xxxxxxxxxxxxxxxxxxxx sweet
xxxxxxxx satirical xxxxxxxxxxx
xxxxxxxxxxxxxxxx great xxxxxxx
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx fun xxxx
xxxxxxxxxxxxxxxxxxxxxxxx whimsical xxxx
romantic xxxx laughing
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
xxxxxxxxxxxxxxxxxxxxxxxx recommend xxxxx
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
x several xxxxxxxxxxxxxxxxxxxxxxxxxxx
xxxxx happy xxxxxxxxxxxx again
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
```

) = C





The bag of words representation

$Y($

great	2
love	2
recommend	1
laugh	1
happy	1
...	...

$) = C$



Bag of words for document classification

?

Test
document

parser
language
label
translation
...

Machine
Learning

learning
training
algorithm
shrinkage
network...

NLP

parser
tag
training
translation
language...

Garbage
Collection

garbage
collection
memory
optimization
region...

Planning

planning
temporal
reasoning
plan
language...

GUI

...

Text Classification and Naïve Bayes

Formalizing the Naïve Bayes Classifier

Bayes' Rule Applied to Documents and Classes

- For a document *d* and a class *c*

$$P(c | d) = \frac{P(d | c)P(c)}{P(d)}$$

Naïve Bayes Classifier (I)

$$c_{MAP} = \operatorname{argmax}_{c \in C} P(c | d)$$

MAP is “maximum a posteriori” = most likely class

$$= \operatorname{argmax}_{c \in C} \frac{P(d | c)P(c)}{P(d)}$$

Bayes Rule

$$= \operatorname{argmax}_{c \in C} P(d | c)P(c)$$

Dropping the denominator

Naïve Bayes Classifier (II)

$$c_{MAP} = \operatorname{argmax}_{c \in C} P(d | c)P(c)$$

$$= \operatorname{argmax}_{c \in C} P(x_1, x_2, \dots, x_n | c)P(c)$$

Document d
represented as
features $x_1..x_n$

Naïve Bayes Classifier (IV)

$$c_{MAP} = \underset{c \in C}{\operatorname{argmax}} P(x_1, x_2, \dots, x_n | c) P(c)$$

$O(|X|^n \cdot |C|)$ parameters

Could only be estimated if a very, very large number of training examples was available.

How often does this class occur?

We can just count the relative frequencies in a corpus

Multinomial Naïve Bayes Independence Assumptions

$$P(x_1, x_2, \dots, x_n \mid c)$$

- **Bag of Words assumption:** Assume position doesn't matter
- **Conditional Independence:** Assume the feature probabilities $P(x_i \mid c_j)$ are independent given the class c .

$$P(x_1, \dots, x_n \mid c) = P(x_1 \mid c) \cdot P(x_2 \mid c) \cdot P(x_3 \mid c) \cdot \dots \cdot P(x_n \mid c)$$

Multinomial Naïve Bayes Classifier

$$c_{MAP} = \underset{c \in C}{\operatorname{argmax}} P(x_1, x_2, \dots, x_n | c) P(c)$$

$$c_{NB} = \underset{c \in C}{\operatorname{argmax}} P(c_j) \prod_{x \in X} P(x | c)$$

Applying Multinomial Naive Bayes Classifiers to Text Classification

positions \leftarrow all word positions in test document

$$c_{NB} = \underset{c_j \in C}{\operatorname{argmax}} P(c_j) \prod_{i \in \text{positions}} P(x_i | c_j)$$

Text Classification and Naïve Bayes

Naïve Bayes: Learning

Learning the Multinomial Naïve Bayes Model

- First attempt: maximum likelihood estimates
 - simply use the frequencies in the data

$$\hat{P}(c_j) = \frac{\text{doccount}(C = c_j)}{N_{doc}}$$

$$\hat{P}(w_i | c_j) = \frac{\text{count}(w_i, c_j)}{\sum_{w \in V} \text{count}(w, c_j)}$$

Parameter estimation

$$\hat{P}(w_i | c_j) = \frac{\text{count}(w_i, c_j)}{\sum_{w \in V} \text{count}(w, c_j)}$$

fraction of times word w_i appears
among all words in documents of topic c_j

- Create mega-document for topic j by concatenating all docs in this topic
 - Use frequency of w in mega-document

Problem with Maximum Likelihood

- What if we have seen no training documents with the word ***fantastic*** and classified in the topic **positive** (***thumbs-up***)?

$$\hat{P}(\text{"fantastic"} \mid \text{positive}) = \frac{\text{count}(\text{"fantastic"}, \text{positive})}{\sum_{w \in V} \text{count}(w, \text{positive})} = 0$$

- Zero probabilities cannot be conditioned away, no matter the other evidence!

$$c_{MAP} = \operatorname{argmax}_c \hat{P}(c) \prod_i \hat{P}(x_i \mid c)$$

Laplace (add-1) smoothing for Naïve Bayes

$$\hat{P}(w_i | c) = \frac{\text{count}(w_i, c) + 1}{\sum_{w \in V} (\text{count}(w, c) + 1)}$$

$$= \frac{\text{count}(w_i, c) + 1}{\sum_{w \in V} \text{count}(w, c) + |V|}$$

Multinomial Naïve Bayes: Learning

- From training corpus, extract *Vocabulary*

- Calculate $P(c_j)$ terms

- For each c_j in C do

$docs_j \leftarrow$ all docs with class = c_j

$$P(c_j) \propto \frac{|docs_j|}{|\text{total \# documents}|}$$

- Calculate $P(w_k | c_j)$ terms

- $Text_j \leftarrow$ single doc containing all $docs_j$

- For each word w_k in *Vocabulary*

$n_k \leftarrow$ # of occurrences of w_k in $Text_j$

$$P(w_k | c_j) \propto \frac{n_k + a}{n + a |Vocabulary|}$$

Laplace (add-1) smoothing: unknown words

Add one extra word to the vocabulary, the “unknown word” w_u

$$\begin{aligned}\hat{P}(w_u | c) &= \frac{\text{count}(w_u, c) + 1}{\sum_{w \in V \cup \{w_u\}} \text{count}(w, c) + |V + 1|} \\ &= \frac{1}{\sum_{w \in V} \text{count}(w, c) + |V + 1|}\end{aligned}$$

Text Classification and Naïve Bayes

Naïve Bayes: Relationship to
Language Modeling

Naïve Bayes and Language Modeling

- Naïve bayes classifiers can use any sort of feature
 - URL, email address, dictionaries, network features
- But if, as in the previous slides
 - We use **only** word features
 - we use **all** of the words in the text (not a subset)
- Then
 - Naïve bayes has an important similarity to language modeling.

Each class = a unigram language model

- Assigning each word: $P(\text{word} \mid c)$
- Assigning each sentence: $P(s \mid c) = \prod P(\text{word} \mid c)$

Class *pos*

0.1	I					
		<u>I</u>	<u>love</u>	<u>this</u>	<u>fun</u>	<u>film</u>
0.1	love					
		0.1	0.1	.05	0.01	0.1
0.01	this					
0.05	fun					
0.1	film					

$$P(s \mid \text{pos}) = 0.00000005$$

...

Naïve Bayes as a Language Model

- Which class assigns the higher probability to s?

Model pos		Model neg						
0.1	I	0.2	I	I	love	this	fun	film
0.1	love	0.001	love					
0.01	this	0.01	this					
0.05	fun	0.005	fun					
0.1	film	0.1	film					
				0.1	0.1	0.01	0.05	0.1
				0.2	0.001	0.01	0.005	0.1
				$P(s \text{pos}) > P(s \text{neg})$				

Text Classification and Naïve Bayes

Multinomial Naïve Bayes: A Worked Example

$$\hat{P}(c) = \frac{N_c}{N}$$

$$\hat{P}(w | c) = \frac{\text{count}(w, c) + 1}{\text{count}(c) + |V|}$$

	Doc	Words	Class
Training	1	Chinese Beijing Chinese	c
	2	Chinese Chinese Shanghai	c
	3	Chinese Macao	c
	4	Tokyo Japan Chinese	j
Test	5	Chinese Chinese Chinese Tokyo Japan	?

Priors:

$$P(c) = \frac{3}{4}$$

$$P(j) = \frac{1}{4}$$

Conditional Probabilities:

$$P(\text{Chinese} | c) = (5+1) / (8+6) = 6/14 = 3/7$$

$$P(\text{Tokyo} | c) = (0+1) / (8+6) = 1/14$$

$$P(\text{Japan} | c) = (0+1) / (8+6) = 1/14$$

$$P(\text{Chinese} | j) = (1+1) / (3+6) = 2/9$$

$$P(\text{Tokyo} | j) = (1+1) / (3+6) = 2/9$$

$$P(\text{Japan} | j) = (1+1) / (3+6) = 2/9$$

Choosing a class:

$$P(c | d5) \propto 3/4 * (3/7)^3 * 1/14 * 1/14 \\ \approx 0.0003$$

$$P(j | d5) \propto 1/4 * (2/9)^3 * 2/9 * 2/9 \\ \approx 0.0001$$

Naïve Bayes in Spam Filtering

- SpamAssassin Features:
 - Mentions Generic Viagra
 - Online Pharmacy
 - Mentions millions of (dollar) ((dollar) NN,NNN,NNN.NN)
 - Phrase: impress ... girl
 - From: starts with many numbers
 - Subject is all capitals
 - HTML has a low ratio of text to image area
 - One hundred percent guaranteed
 - Claims you can be removed from the list
 - 'Prestigious Non-Accredited Universities'
 - http://spamassassin.apache.org/old/tests_3_3_x.html

Summary: Naive Bayes is Not So Naive

- Very Fast, low storage requirements
- Robust to Irrelevant Features
 - Irrelevant Features cancel each other without affecting results
- Very good in domains with many equally important features
 - Decision Trees suffer from *fragmentation* in such cases – especially if little data
- Optimal if the independence assumptions hold: If assumed independence is correct, then it is the Bayes Optimal Classifier for problem
- A good dependable baseline for text classification
 - **But we will see other classifiers that give better accuracy**

Text Classification and Naïve Bayes

Precision, Recall, and the F measure

The 2-by-2 contingency table

	correct	not correct
selected	tp	fp
not selected	fn	tn

Precision and recall

- **Precision:** % of selected items that are correct
Recall: % of correct items that are selected

		<i>gold standard labels</i>		
		gold positive	gold negative	
<i>system output labels</i>	system positive	true positive	false positive	precision = $\frac{tp}{tp+fp}$
	system negative	false negative	true negative	
		recall = $\frac{tp}{tp+fn}$		accuracy = $\frac{tp+tn}{tp+fp+tn+fn}$

A combined measure: F

- A combined measure that assesses the P/R tradeoff is F measure (weighted harmonic mean):

$$F = \frac{1}{a \frac{1}{P} + (1 - a) \frac{1}{R}} = \frac{(b^2 + 1)PR}{b^2 P + R}$$

- The harmonic mean is a very conservative average
- People usually use balanced F1 measure
 - i.e., with $\beta = 1$ (that is, $\alpha = \frac{1}{2}$):

$$F = 2PR/(P+R)$$

Text Classification and Naïve Bayes

Text Classification: Evaluation

More Than Two Classes: Sets of binary classifiers

- Dealing with **any-of** or **multivalue** classification
 - A document can belong to 0, 1, or >1 classes.
- For each class $c \in C$
 - Build a classifier γ_c to distinguish c from all other classes $c' \in C$
- Given test doc d ,
 - Evaluate it for membership in each class using each γ_c
 - d belongs to **any** class for which γ_c returns true

More Than Two Classes: Sets of binary classifiers

- One-of or multinomial classification
 - Classes are mutually exclusive: each document in exactly one class
- For each class $c \in C$
 - Build a classifier γ_c to distinguish c from all other classes $c' \in C$
- Given test doc d ,
 - Evaluate it for membership in each class using each γ_c
 - d belongs to the one class with maximum score

More than two classes

		<i>gold labels</i>			
		urgent	normal	spam	
<i>system output</i>	urgent	8	10	1	precision_u = $\frac{8}{8+10+1}$
	normal	5	60	50	precision_n = $\frac{60}{5+60+50}$
	spam	3	30	200	precision_s = $\frac{200}{3+30+200}$
		recall_u = $\frac{8}{8+5+3}$	recall_n = $\frac{60}{10+60+30}$	recall_s = $\frac{200}{1+50+200}$	

Micro- vs. Macro-Averaging

- If we have more than one class, how do we combine multiple performance measures into one quantity?
- **Macroaveraging:** Compute performance for each class, then average.
- **Microaveraging:** Collect decisions for all classes, compute contingency table, evaluate.

Micro- vs. Macro-Averaging Example

Class 1: Urgent			Class 2: Normal			Class 3: Spam			Pooled		
	true urgent	true not		true normal	true not		true spam	true not		true yes	true no
system urgent	8	11	system normal	60	55	system spam	200	33	system yes	268	99
system not	8	340	system not	40	212	system not	51	83	system no	99	635
precision = $\frac{8}{8+11} = .42$			precision = $\frac{60}{60+55} = .52$			precision = $\frac{200}{200+33} = .86$			microaverage precision = $\frac{268}{268+99} = .73$		
			macroaverage precision = $\frac{.42+.52+.86}{3} = .60$								

Development Test Sets and Cross-validation


Metric: P/R/F1 or Accuracy

Unseen test set

- avoid overfitting ('tuning to the test set')
- more conservative estimate of performance

Cross-validation over multiple splits

- Handle sampling errors from different datasets
- Pool results over each split
- Compute pooled dev set performance



Credits

- This slide set has been adapted from:

<https://web.stanford.edu/~jurafsky/NLPCourseraSlides.html>