

# Lab 06-Textons and classifiers

Juan Carlos Leon Alcazar

March 30, 2016

## 1 Description of the database

The database[1] contains 1000 gray scale in JPG format, all of them have a standard 640x480 pixels resolution. Images are close ups of a given object surface, thus, containing textures found in different objects. There is a total of 17 classes <sup>1</sup>, each contains between 30 to 90 sample images in the train set and between 10 to 30 images in the test set. Finally, there is a plain text file which specifies the naming convention for the images.

## 2 Methodology

Overall the methodology used in this laboratory is presneten in figure ....

The original first step in the pipeline was the construction of a texton dictionary from the subset 'train'. However, due to hardware constraints, it was not possible to build this dictionary with the complete train set (750 images). Creating a texton dictionary with a set of 40 images already requires about 45 GB of RAM memory (At peak), and about 3 hours CPU time. For the experiments, a single 115GB RAM machine was available. As it was not possible to create a dictionary with the full training set, it was reduced to 85 images (5 images per class).

There is not a clear way to subsample the original training set while retaining the original data variability, in other words, it is expected that this sub sampling process should create some bias in the dictionary. However the nature of the dataset might help to mitigate this issue: textures are essentially local patterns repeated, with some variability, at the global level. Thus it can be assumed that each image contains several instances of these local patterns, that already contain some of the variability of the texture.

To further test this hypotesis...

---

<sup>1</sup>The object classes are: Bark Wood, Water, Granite, Marble, Floors, Pebbles, Wall Brick, Glass, Carpet, Upholstery, Wallpaper, Fur, Knit, Corduroy & Plaid

btreve ex-  
perimento  
con 4 his-  
togramas  
T1,5Imágenes  
T1n30I  
mages,  
T2n5Imágenes,T2n30Imágenes  
distancia  
chi-  
cuadrado




Figure 1: Elements of the proposed approach

## 2.1 Textons

After selecting the initial number of training images, there remains one final parameter for the construction of the texton dictionary, namely the  $K$  for the  $K$  means. For this matter we use a number of textons given by  $K = c32$  ( $c = 1, 2, 3$ ). The explanation behind this choice is that we expected the local patterns to closely match the shape of the filter bank; This is the case of  $c=1 \rightarrow K=32$ . However, not every local pattern will match perfectly one of the textons on the filterbank. This is the case of  $K = 2, 3$  where the resulting clusters might contain the response information of several filters. No further values for  $c$  are explored mostly, due to time constraints. The final setup for the texton dictionary construction is the following:

- Filter Bank: default filterbank provide in the implementations 16 orientations, 2 scales
- Number of training images: 85 (5 per each class)
- Number of clusters ( $N$ ): 32, 64, 96

## 2.2 Texton Calculation on Test Set

With the 3 Texton dictionaries built we then calculate response of every image in the test set filtered with the obtained textons. for each image we obtain 3 responses (3 dictionaries) which are then represented by means of an histogram where the number of bins depends on the value of  $K$  used for the construction of the dictionary.

## 2.3 Classification

There are two methods selected for the classification of the textures

**Nearest Neighbor** []

**Random Forest** []

The first method has a single parameter: the distance metric, as specified by the assignment, we use the Chi-square distance to choose the Nearest Neighbour.

For the second method there are more parameters, the MATLAB implementation allows to choose:

- Number of variables eligible for each decision split
- Cost of misclassifications
- Minimum number of observations per tree leaf

To allow for a maximum variability in the built trees we select the number of variables eligible for each decision split equals to the total amount of variables. Set the minimum number of observations to 1 and set no specific cost matrix for the experiments.

No adjustment is performed on the test data or the texture dictionary after being calculated.

Table

## References

- [1] S. Lazebnik, C. Schmid, and J. Ponce. A sparse texture representation using local affine regions. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 27(8):1265–1278, Aug 2005.