

# Decentralized non-convex optimization via bi-level SQP and ADMM

Alternating Direction Method of Multipliers Session, IEEE CDC 2022



Gösta Stomberg, Alexander Engelmann, Timm Faulwasser

Institute for Energy Systems, Energy Efficiency and Energy Economics

TU Dortmund University


goesta.stomberg@tu-dortmund.de

TuAT08.1



## Partially separable NLP

$$\begin{array}{ll}
 \min_{x_1, \dots, x_S} & \sum_{i \in \mathcal{S}} f_i(x_i) & f_i \in \mathcal{C}^2 : \mathbb{R}^{n_i} \rightarrow \mathbb{R} \\
 \text{s.t.} & \cancel{g_i(x_i) = 0} \quad | \quad \cancel{\nu_i} \quad \forall i \in \mathcal{S} & \cancel{g_i \in \mathcal{C}^2 : \mathbb{R}^{n_i} \rightarrow \mathbb{R}^{n_{gi}}} \quad g_i(x_i) \text{ in paper} \\
 & h_i(x_i) \leq 0 \quad | \quad \mu_i \quad \forall i \in \mathcal{S} & h_i \in \mathcal{C}^2 : \mathbb{R}^{n_i} \rightarrow \mathbb{R}^{n_{hi}} \\
 & \sum_{i \in \mathcal{S}} E_i x_i = c \quad | \quad \lambda & E_i \in \mathbb{R}^{n_c \times n_i}
 \end{array}$$



## Desirable algorithmic properties

- Communication only between neighbors (decentralized method)
- Convergence guarantees for non-convex problems
- Low-complexity computations per subsystem

How to design a suitable method?

# Sequential Quadratic Programming (SQP)

## Centralized NLP

$$\begin{aligned} \min_x \quad & f(x) \\ \text{s.t.} \quad & h(x) \leq 0 \mid \mu \\ & Ex = c \mid \lambda \end{aligned}$$

$$p^k = \begin{bmatrix} x^k \\ \mu^k \\ \lambda^k \end{bmatrix}$$

## QP approximation (convex)

$$\begin{aligned} \min_s \quad & \frac{1}{2} s^\top H^k s + \nabla f^k{}^\top s \\ \text{s.t.} \quad & h^k + \nabla h^k{}^\top s \leq 0 \mid \mu^{QP} \\ & E(x^k + s) = c \mid \lambda^{QP} \end{aligned}$$

$H^k \approx \nabla_{xx}^2 L(p^k)$

## SQP

→ Evaluate sensitivities  
Solve QP for  $d^k$   
→  $p^{k+1} = p^k + d^k$

$$d^k = \begin{bmatrix} s^k \\ \mu^{QP,k} - \mu^k \\ \lambda^{QP,k} - \lambda^k \end{bmatrix}$$

Local convergence via Newton's method

Boggs, P. and Tolle, J. "Sequential quadratic programming." *Acta numerica*, 1995

Nocedal, J. and Wright, S. "Numerical Optimization." *Springer Science & Business Media*, 2006

KKT conditions

$$\begin{aligned}\nabla_x L(p) &= 0 \\ h(x) &\leq 0, \mu \geq 0, \mu^\top h(x) = 0 \\ Ex - c &= 0\end{aligned}$$



$$F(p) \doteq \begin{bmatrix} \nabla_x L(p) \\ \min(-h(x), \mu) \\ Ex - c \end{bmatrix} = 0$$

Newton:  $p^{k+1} = p^k - \nabla(F^k)^{-1} F^k$

**Assumption 1** (KKT point)

The KKT point  $p^*$  satisfies


- i) Strict complementarity
- ii) SOSC
- iii) LICQ



Local convergence of SQP

If  $p^0 \in \mathcal{B}_{\varepsilon_1}(p^*)$ , then:

- i)  $\nabla F^{k-1}$  exists
- ii)  $p^{k+1} \in \mathcal{B}_{\varepsilon_1}(p^*)$
- iii) Active set  $\mathcal{A}^k$  stays constant
- iv)  $\{p^k\} \rightarrow p^*$  q-superlinearly



Apply SQP to partially separable NLP?

## Partially separable NLP

$$\begin{aligned} \min_{x_1, \dots, x_S} \quad & \sum_{i \in \mathcal{S}} f_i(x_i) \\ \text{s.t.} \quad & h_i(x_i) \leq 0 \mid \mu_i \\ & \sum_{i \in \mathcal{S}} E_i x_i = c \mid \lambda \end{aligned}$$

$$p^k = \begin{bmatrix} x^k \\ \mu^k \\ \lambda^k \end{bmatrix}$$

## QP approximation (convex)

$$\begin{aligned} \min_{s_1, \dots, s_S} \quad & \sum_{i \in \mathcal{S}} \frac{1}{2} s_i^\top H_i^k s_i + \nabla f_i^k{}^\top s_i \\ \text{s.t.} \quad & h_i^k + \nabla h_i^k{}^\top s_i \leq 0 \mid \mu_i^{QP} \\ & \sum_{i \in \mathcal{S}} E_i (x_i^k + s_i) = c \mid \lambda^{QP} \end{aligned}$$

$\nwarrow H_i^k \approx \nabla_{x_i x_i}^2 L(p^k)$

## Decentralized SQP (d-SQP)

Evaluate sensitivities per subsystem Solve in decentralized fashion?

Solve partially separable convex QP

$$x_i^{k+1} = x_i^k + s_i \quad \mu_i^{k+1} = \mu_i^{QP} \quad \lambda^{k+1} = \lambda^{QP}$$

Solve the QP with ADMM to obtain a decentralized SQP scheme

Inner QP

$$\begin{aligned} \min_{s_1, \dots, s_S} \quad & \sum_{i \in \mathcal{S}} \frac{1}{2} s_i^\top H_i^k s_i + \nabla f_i^{k\top} s_i \\ \text{s.t.} \quad & \left. \begin{aligned} h_i^k + \nabla h_i^{k\top} s_i &\leq 0 \\ \sum_{i \in \mathcal{S}} E_i(x_i^k + s_i) &= c \end{aligned} \right\} \mathbb{S}_i \end{aligned}$$

$$\bar{s}_i \in \mathbb{R}^{n_i}$$

$$\begin{aligned} \min_{s_i, \bar{s}_i, i \in \mathcal{S}} \quad & \sum_{i \in \mathcal{S}} \frac{1}{2} s_i^\top H_i^k s_i + \nabla f_i^{k\top} s_i \\ \text{s.t.} \quad & s_i \in \mathbb{S}_i \\ & s_i - \bar{s}_i = 0 \mid \gamma_i \\ & \sum_{i \in \mathcal{S}} E_i(x_i^k + \bar{s}_i) = c \end{aligned}$$

$$L_\rho(s, \bar{s}, \nu) = \sum_{i \in \mathcal{S}} L_{\rho,i}(s_i, \bar{s}_i, \nu_i) = \sum_{i \in \mathcal{S}} \frac{1}{2} s_i^\top H_i^k s_i + \nabla f_i^{k\top} s_i + \gamma_i^\top (s_i - \bar{s}_i) + \frac{\rho}{2} \|s_i - \bar{s}_i\|_2^2$$

ADMM

$$\begin{aligned} s_i^{l+1} &= \operatorname{argmin}_{s_i \in \mathbb{S}_i} L_{\rho,i}(s_i, \bar{s}_i^l, \gamma_i^l) \\ \bar{s}^{l+1} &= \operatorname{argmin}_{\bar{s} \in \mathbb{E}} \sum_{i \in \mathcal{S}} L_{\rho,i}(s_i^{l+1}, \bar{s}_i, \gamma_i^l) \\ \gamma_i^{l+1} &= \gamma_i^l + \rho(s_i^{l+1} - \bar{s}_i^{l+1}) \end{aligned}$$

Decentralized averaging

Convex inner QP  $\implies$  convergence

## Partially separable NLP

$$\begin{aligned} \min_{x_1, \dots, x_S} \quad & \sum_{i \in \mathcal{S}} f_i(x_i) \\ \text{s.t.} \quad & h_i(x_i) \leq 0 \mid \mu_i \\ & \sum_{i \in \mathcal{S}} E_i x_i = c \mid \lambda \end{aligned}$$


$$p^k = \begin{bmatrix} x^k \\ \mu^k \\ \lambda^k \end{bmatrix}$$

## QP approximation (convex)

$$\begin{aligned} \min_{s_1, \dots, s_S} \quad & \sum_{i \in \mathcal{S}} \frac{1}{2} s_i^\top H_i^k s_i + \nabla f_i^k{}^\top s_i \\ \text{s.t.} \quad & h_i^k + \nabla h_i^k{}^\top s_i \leq 0 \mid \mu_i^{QP} \\ & \sum_{i \in \mathcal{S}} E_i (x_i^k + s_i) = c \mid \lambda^{QP} \end{aligned}$$

$\nwarrow H_i^k \approx \nabla_{x_i x_i}^2 L(p^k)$

## Decentralized SQP (d-SQP)



Inexact decentralized SQP steps! Convergence?

KKT

$$F(p) = \begin{bmatrix} \nabla_x L(p) \\ \min(-h(x), \mu) \\ Ex - c \end{bmatrix}$$

Newton:


Inexact Newton:  $\|F^k + \nabla F^k d^k\| \leq \eta^k \|F^k\| \quad (\text{IN})$

$$F^k + \nabla F^k d^k = 0$$

**Lemma** (*Inexact SQP convergence*)

Let Assumption 1 hold and let  $d^k$  satisfy (IN).  
If  $p^0 \in \mathcal{B}_{\varepsilon_2}(p^*)$ , then:

- i)  $\{p^k\} \rightarrow p^*$  *q-linearly*, if  $\eta^k \leq \eta$
- ii)  $\{p^k\} \rightarrow p^*$  *q-superlinearly*, if  $\eta^k \rightarrow 0$




How to evaluate (IN) outside  $\mathcal{B}_{\varepsilon_1}$ ?



KKT

$$F(p) = \begin{bmatrix} \nabla_x L(p) \\ \min(-h(x), \mu) \\ Ex - c \end{bmatrix} \quad \begin{array}{l} \text{Newton:} \\ \text{Inexact Newton:} \end{array} \quad \begin{array}{l} F^k + \nabla F^k d^k = 0 \\ \|F^k + \nabla F^k d^k\| \leq \eta^k \|F^k\| \end{array} \quad (\text{IN})$$




Modified stopping criterion (decentralized)

$$\tilde{F}(p) \doteq \begin{bmatrix} \nabla_x L(p) \\ Ex - c \end{bmatrix} \quad \|\tilde{F}^k + \nabla \tilde{F}^k d^k\| \leq \eta^k \|\tilde{F}^k\| \quad (\text{SC})$$

If ADMM terminates at  $\mathcal{A}^*$ , then (SC)  $\implies$  (IN)

## Decentralized SQP (d-SQP)




### Theorem (*d-SQP convergence*)

Let Assumption 1 hold and initialize ADMM with  $s_i = 0$  and  $\gamma_i = E_i^\top \lambda^k$ . If  $p^0 \in \mathcal{B}_\varepsilon(p^*)$ , then:

- i)  $\{p^k\} \rightarrow p^*$   $q$ -linearly in the outer iterations, if  $\eta^k \leq \eta$
- ii)  $\{p^k\} \rightarrow p^*$   $q$ -superlinearly in the outer iterations, if  $\eta^k \rightarrow 0$

ADMM stays at  $\mathcal{A}^*$




d-SQP is guaranteed to converge locally for non-convex problems!

# Numerical Example: AC-OPF

## Partially separable NLP

$$\begin{aligned}
 \min_{x_1, \dots, x_S} \quad & \sum_{i \in \mathcal{S}} f_i(x_i) \quad x \in \mathbb{R}^{576} \\
 \text{s.t.} \quad & g_i(x_i) = 0 \quad g(x) \in \mathbb{R}^{470} \\
 & h_i(x_i) \leq 0 \quad h(x) \in \mathbb{R}^{792} \\
 & \sum_{i \in \mathcal{S}} E_i x_i = 0 \quad E \in \mathbb{R}^{52 \times 576}
 \end{aligned}$$



Method	Only neighbor-to-neighbor communication	Proven convergence
d-SQP	yes	yes
ADMM	yes	no
ALADIN/d-CG	no	yes
ALADIN/ADMM	yes	yes
d-IP	no	yes

Computation time until  $\|x - x^*\| < 10^{-6}$   
Matlab, one computer for all subsystems

d-SQP 30 s  
ADMM 67 s

d-SQP shows competitive performance while only solving QPs




Erseghe, T. "Distributed optimal power flow using ADMM." IEEE Trans. Power Syst., 2014

Frank, S and Rebennack, S. "An introduction to optimal power flow: theory, formulation, and examples." IIE transactions, 2016

Engelmann, A. et al. "Decomposition of nonconvex optimization via bi-level distributed ALADIN." IEEE Trans. Control Netw. Syst., 2020

# Application Example: Distributed MPC

## Mobile robots (4 subsystems)




Computation time to solve optimal control problem  
C++, one computer per robot

median 33.81 ms  
maximum 53.06 ms  $\leftarrow < \Delta t = 200 \text{ ms!}$

Promising results for distributed NMPC

Stomberg, G., Ebel, H., Faulwasser, T. and Eberhard, P. "Distributed Model Predictive Formation Control in Real-Time", arXiv, 2022

## Decentralized SQP (d-SQP)



## Key features and outlook

- Local convergence guarantees for non-convex NLPs
- Communication only between coupled subsystems (decentralized method)
- Solves convex QPs on a subsystem level
- Open problem: globalization

Thank you

Stomberg, G., Engelmann, A. and Faulwasser T. “Decentralized non-convex optimization via bi-level SQP and ADMM”, 61<sup>st</sup> CDC, 2022  
Stomberg, G., Ebel, H., Faulwasser, T. and Eberhard, P. “Distributed Model Predictive Formation Control in Real-Time”, arXiv, 2022

- Dembo, R. S., Eisenstat, S. C. and Steihaug, T. "Inexact newton methods" *SIAM J. Nume Anal.*, vol. 10, no. 2, pp. 400-408, 1982
- Boggs, P. and Tolle, J. "Sequential quadratic programming." *Acta numerica*, vol. 4, pp. 1-51, 1995
- Morini, B. "Convergence behavior of inexact newton methods." *Math. Comput.*, vol. 68, no. 228, pp. 1604-1613, 1999
- Nocedal, J. and Wright, S. "Numerical Optimization." *Springer Science & Business Media*, 2006
- Boyd, S., Parikh, N., Chu, E., Peleato, B. and Eckstein, J. "Distributed optimization and statistical learning via the alternating direction method of multipliers." *Found. Trends Mach. Learn.*, vol. 3, no. 1, pp. 1–122, 2011
- Erseghe, T. "Distributed optimal power flow using ADMM." *IEEE Trans. Power Syst.*, vol. 29, no. 5, pp. 2370-2380, 2014
- Frank, S and Rebennack, S. "An introduction to optimal power flow: Theory, formulation, and examples." *IEEE transactions* 48.12: 1172-1197, 2016
- Engelmann, A., Jiang, Y., Houska, B. and Faulwasser, T. "Decomposition of nonconvex optimization via bi-level distributed ALADIN." *IEEE Trans. Control Netw. Syst.*, vol. 7, no. 4, pp. 1848–1858, 2020
- Stomberg, G., Ebel, H., Faulwasser, T. and Eberhard, P. "Distributed Model Predictive Formation Control in Real-Time", arXiv, 2022