

# VIRTIO Introduction

--based on virtio-blk implementation

John.Gong


# Agenda

- ▶ What is VIRTIO?
- ▶ Hierarchy
- ▶ Vring
- ▶ Vring management
- ▶ Guest read process
- ▶ Q & A
- ▶ Reference



# What is VIRTIO

- ▶ VIRTIO is a virtual transport protocol, only exists in the para-virtualization environment. High performance due to:
  - ▶ share memory: no memory copy
  - ▶ lock-free queue: host and guest handle the queue concurrently


# Hierarchy



# vring - share between host and guest



# vring - vring\_desc && vring\_desc\_state



# Vring management - share with host and guest

```
struct vring_desc {
    __virtio64 addr; //GPA
    __virtio32 len;
    __virtio16 flags;
    __virtio16 next;
};

struct vring_avail {
    __virtio16 flags;
    __virtio16 idx;
    __virtio16 ring[];
};

struct vring_used {
    __virtio16 flags;
    __virtio16 idx;
    struct vring_used_elem ring[];
};
```

```
struct vring_used_elem {
    __virtio32 id;
    __virtio32 len; //in or out data lens in byte
};
```

# Vring management - guest private

```
struct vring_virtqueue {
    struct virtqueue vq;
    struct vring vring;
    unsigned int free_head; //index to desc
    unsigned int num_added;
    u16 last_used_idx; //ci of the used ring, equal to used_event_idx
    u16 avail_flags_shadow;
    u16 avail_idx_shadow;
    bool (*notify)(struct virtqueue *vq);
    size_t queue_size_in_bytes;
    dma_addr_t queue_dma_addr;
    /* Per-descriptor state. */
    struct vring_desc_state desc_state[];
};
```

```
struct virtqueue {
    void (*callback)(struct virtqueue *vq);
    unsigned int index;
    unsigned int num_free;
};
struct vring {
    unsigned int num;

    struct vring_desc *desc;

    struct vring_avail *avail;

    struct vring_used *used;
};
struct vring_desc_state {
    void *data;
    struct vring_desc *indir_desc;
};
```



# Vring management - host private

```
struct VirtQueue
```

```
{
```

```
    VRing vring;
```

```
    /* Next head to pop */
```

```
    uint16_t last_avail_idx;
```

```
    /* Last avail_idx read from VQ. */
```

```
    uint16_t shadow_avail_idx;
```

```
    uint16_t used_idx;
```

```
    uint16_t queue_index;
```


```
    unsigned int inuse;
```

```
    uint16_t vector;
```


```
    VirtIOHandleOutput handle_output;
```

```
};
```


# Guest read process (1) guest: virtblk\_request




# Guest read process (2)guest: virtqueue\_add\_sgs




# Guest read process (3)guest: save the virtblk\_req to vring\_desc\_state




# Guest read process (4)guest: virtqueue\_kick\_prepare && vp\_notify





# Guest read process (5)host: virtqueue\_pop



# Guest read process (6)host: virtqueue\_push




# Guest read process (7)host: virtio\_notify






# Guest read process (8)guest: vring\_interrupt -> virtblk\_done



# Guest read process (9)guest: vring\_interrupt -> virtblk\_done



4 last\_used\_idx++

# QA Discussion

- ▶ How to share the memory between the host(QEMU) and guest(VM) within the virtio implementation?

John.Gong

- ▶ No extra action is needed to implement it. Host(QEMU) and guest(VM) are within the same process user space. Host(QEMU) and Guest(VM) can access the same HPA with the same HVA.

# Reference

- ▶ Source code
  - ▶ linux kernel CN: 328b4ed93b69a6f2083d52f31a240a09e5de386a
  - ▶ qemu CN: eaefea537b476cb853e2edbd6c68e969ec777e4bb



Foxit Reader PDF  
Document



Foxit Reader PDF  
Document



Foxit Reader PDF  
Document



Foxit Reader PDF  
Document

John.Gong

The background features abstract, overlapping green geometric shapes, primarily triangles and polygons, in various shades of green, creating a modern and dynamic visual effect.

# Thank You !

John.Gong