Version : **1.1**
Date : **18 august 2026**

UNI GREASE

Characteristics

Uni Grease is a high quality multi-purpose lithium complex grease. The product contains in addition to corrosion-preventing and water-repellant components also microscopic solid lubricating particles. These particles are inert, have a very low friction-coefficient and withstand very high pressures, thus preventing metal to metal contacts when the lubrication is not longer sufficient. The solid lubricating particles can be considered as a mild and not toxic EP-additive.

Application

On all places where a long-lasting and high quality lubrication has to be guaranteed under all circumstances and in every environment, also at high speeds, in open and closed systems, like:
• bearings, slide bearings, sliding contacts, chains, cables

Properties

- Products withstands moisture
- Excellent corrosion prevention
- Repels water and preserves
- Reduces wear, pitting and stickslip
- Lubricates extra because of the solid lubricating particles
- Allows high rotating speeds
- Suitable for central lubricating systems

Volume	Art.no.
200 ml	72046200

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.