

Incorporating Model Complexity

- Rationale: Occam's Razor
 - Given two models of similar generalization errors, one should prefer the simpler model over the more complex model
 - A complex model has a greater chance of being fitted accidentally by errors in data
 - Therefore, one should include model complexity when evaluating a model

$$\text{Gen. Error}(\text{Model}) = \text{Train. Error}(\text{Model}, \text{Train. Data}) + \alpha \times \text{Complexity}(\text{Model})$$


Estimating the Complexity of Decision Trees

- **Pessimistic Error Estimate** of decision tree T with k leaf nodes:


$$err_{gen}(T) = err(T) + \Omega \times \frac{k}{N_{train}}$$

- $err(T)$: error rate on all training records
- Ω : trade-off hyper-parameter (similar to α)
 - ◆ Relative cost of adding a leaf node
- k : number of leaf nodes
- N_{train} : total number of training records

Estimating the Complexity of Decision Trees: Example



Decision Tree, T_L



Decision Tree, T_R

$$e(T_L) = 4/24$$

$$e(T_R) = 6/24$$

$$\Omega = 1$$


$$e_{\text{gen}}(T_L) = 4/24 + 1 \cdot 7/24 = 11/24 = 0.458$$

$$e_{\text{gen}}(T_R) = 6/24 + 1 \cdot 4/24 = 10/24 = 0.417$$


Estimating the Complexity of Decision Trees

□ Resubstitution Estimate:

- Using training error as an optimistic estimate of generalization error
- Referred to as optimistic error estimate



Decision Tree, T_L



Decision Tree, T_R

$$e(T_L) = 4/24$$

$$e(T_R) = 6/24$$