



# **FUJITSU Software SecDocs**

## **Fehlermeldungen**

Version SecDocs 4.1A00, Stand: 26.09.2024

# Inhaltsverzeichnis

Einleitung.....	1
Aufbau eines Eintrags.....	1
Liste der Fehlermeldungen.....	2
Accounting .....	2
Administration .....	2
Audit.....	16
SFTP Server.....	17
OverSign .....	19
Persistence .....	21
Archiving Request.....	22
Storage Adapter .....	32
Storage Connector.....	32
XAIP Archiving Request.....	41

---

## Einleitung

Je nach der verwendeten Schnittstelle werden Fehler bei der Verarbeitung von SecDocs auf verschiedene Weise mitgeteilt. Wird der Webservice ... verwendet (SDO-Schnittstelle) dann wird der wird HTTP-Error 500 zurückgegeben und eine Fault-Message gesendet.

Wird der Webservice ... verwendet (S4-Schnittstelle), dann wird auch im Fehlerfall der HTTP-Code 200 zurückgegeben. Detaillierte Informationen finden sich dann in der Antwortnachricht im Element Result/OptionalOutputs/faultDetails

Alle Fehlermeldung verfügen über eine Fehlernummer und einen Fehlertext. Der Fehlertext beginnt immer mit einem Fehlerschlüssel

Das folgende Dokument listet die möglichen Fehler in Tabellenform auf

## Aufbau eines Eintrags

Error-Code	Inhalt des Elements errorCode im Element faultDetails
Text	Template der Meldung im Element errorMessage
Kategorie	Bereich, in dem der Fehler auftrat (S=System,P=Produkt,U=User)
Beschreibung	Erläuterung des Fehlers und der möglichen Ursache
Maßnahme	Hinweise auf Maßnahmen bei Auftreten des Fehlers

---

# Liste der Fehlermeldungen

## Accounting

Schlüssel	Fehlercode	Text	Kategorie
ACC0000	900	Accounting exception	S,P
<b>Beschreibung:</b> AccountingException occurred.			
ACC0001	901	The tenant name "{0}" is unknown.	U
<b>Beschreibung:</b> The name of the wanted tenant is not known in SecDocs.			
ACC0002	902	The organisation name "{0}" is unknown.	U
<b>Beschreibung:</b> The name of the wanted organisation is not known in SecDocs.			
ACC0003	903	The TSP name "{0}" is unknown.	U
<b>Beschreibung:</b> The name of the wanted Time Stamp Provider (TSP) is not known in SecDocs.			
<b>Lösung:</b> Please use the operation getTSPs to obtain the list of known TSPs.			

## Administration

Schlüssel	Fehlercode	Text	Kategorie
ADM0001	101	Administration cannot be initialized: {0}	S,P
<b>Beschreibung:</b> The SecDocs application can't be used			
<b>Lösung:</b> Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files			
ADM0002	102	Internal error database: {0}	S,P
<b>Beschreibung:</b> An internal error in the database occurred			
<b>Lösung:</b> Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files			
ADM0003	103	Internal error: No database connection {0}	S,P
<b>Beschreibung:</b> The database cannot be reached			
<b>Lösung:</b> Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files			

---

---

ADM0004	104	Unknown Role {0}	U
---------	-----	------------------	---

**Beschreibung:**

The header element role contains an unknown value

**Lösung:**

Use the operation getRoles to obtain a list of valid roles, or contact the tenant administrator

ADM0005	105	Unknown Tenant {0}	U
---------	-----	--------------------	---

**Beschreibung:**

The header element mandant contains an unknown value

**Lösung:**

Use the operation getMandants to obtain a list of known tenants, or ask the archive administrator

ADM0006	106	Cannot access authentication files. SecDocs installation may be corrupt	S
---------	-----	---	---

**Beschreibung:**

Cannot find the authentication files SecDocs needs to identify itself to the certified DSEngine components

**Lösung:**

Please contact the SecDocs administrator to check if these files were installed correctly

ADM0007	107	Cannot start DSEngine components; either property cryptoAuditFiles was empty or none of the supplied audit files can be written	S
---------	-----	---	---

**Beschreibung:**

The logging files used by certified DSEngine components cannot be written

**Lösung:**

Check whether the files specified in the property cryptoAuditFiles can be created resp. written by user secdocs

ADM0008	108	Storage compromised: schema or filter of SDOType {0} of tenant {1} were changed	S
---------	-----	---	---

**Beschreibung:**

Filter or schema of the mentioned SDOType have been changed outside of SecDocs. This is a potential security breach on your system

ADM0009	109	Role {0} already exists in organisation {1}	U
---------	-----	---	---

**Beschreibung:**

There is already a role with the same name defined for this organisation

ADM0010	110	Element {0} contains illegal value {1}	U
---------	-----	--	---

**Beschreibung:**

The mentioned element contains an illegal value, for instance a role may contain functions, which are not supported

ADM0011	111	{0} cannot be used or changed. {0} is a reserved name in SecDocs	U
---------	-----	--	---

---

**Beschreibung:**

Names reserved in SecDocs cannot be used to define new objects or change objects of this name. Reserved names are all strings starting with SecDocs\_ as well as the names of the predefined roles Archivar, MandantAdmin and ArchiveAdmin

**ADM0012**      112      Cannot parse XML: {0}      U

**Beschreibung:**

The XML passed in the body of a request either to the ArchiveAdminService Web service or to the MandantAdminService Web service is not correct

**Lösung:**

Check the message and ensure that it contains well-formed XML only

**ADM0013**      113      Error in tag \"{0}\"      U

**Beschreibung:**

The tag has an invalid value

**Lösung:**

Check the value of the tag

**ADM0014**      114      Validation error in {1} : {0}      U

**Beschreibung:**

The body of a request either to the ArchiveAdminService Web service or to the MandantAdminService Web service does not comply with the SecDocs schema AdminData.xsd.

**Lösung:**

The error message contains the faulty element and the reason why the parser rejected it. Please check in the manual, which elements are allowed in the request, in which sequence they are expected and which values are allowed for an element.

**ADM0015**      115      Element {0} missing      U

**Beschreibung:**

The body of a request must contain at least one of the elements mentioned in the message

**Lösung:**

The error message contains the missing element. Please check in the manual, which elements are allowed in the request, in which sequence they are expected and which values are allowed for an element.

**ADM0016**      116      Unexpected/Invalid time interval, date or date format found \"{0}\"      U

**Beschreibung:**

Invalid date or date format used in the request: Possible values for dates are UNLIMITED or DEFERRED or in ISO 8601 format. Possibles values for Time intervals: UNLIMITED or P<year>Y<month>M<day>D. Valid date formats are: DD.MM.YYYY, MM.DD.YYYY, DD-MM-YYYY, MM-DD-YYYY,YYYY.DD.MM, YYYY.MM.DD,YYYY-DD-MM and YYYY-MM-DD.

**Lösung:**

Using the manual check which dates and date formats are allowed in a request and in keys in the filter

**ADM0017**      117      Unknown {0} : {1}      U

---

**Beschreibung:**

The current request referred to an unknown object (e.g. a Privilege)

**Lösung:**

Use the respective get-Operation (e.g. getPrivileges) to retrieve all valid objects.

**ADM0018**      118      {0} may not be used in current context "{1}"      U

**Beschreibung:**

Either the request message or the filter definition contained elements which may not be used in the current context

**Lösung:**

Check the manual for valid requests/filter-definitions

**ADM0019**      119      Web service {0} is temporarily not available: Reason {1}      S

**Beschreibung:**

At the moment all requests will be rejected for the tenant because a delete action is in progress (deleteTestMandant, deleteSDOType)

**Lösung:**

Wait for the delete action to finish

**ADM0020**      120      Global Role {0} cannot be used as long as roles are defined specifically for an organisation      U

**Beschreibung:**

Although the tenant created organisation-specific roles, a request was sent, that used the Default-Role "Archivar" without giving an organisation

**Lösung:**

Use the operation getRoles to get a list of all valid roles.

**ADM0021**      121      Operation {0} not supported      U

**Beschreibung:**

The element operation in the request's header contains a value not known in SecDocs

**Lösung:**

Use the manual to find out which operations are provided by the three Web services of SecDocs

**ADM0022**      122      {0} may not execute operation {1}      U

**Beschreibung:**

You do not have the permission to execute the current operation

**Lösung:**

Use the manual to find out which operations are allowed for the three Web services of SecDocs

**ADM0023**      123      Missing schema definition for import/include/redefined element ({0})      U

**Beschreibung:**

One of the schemas passed with createSDOType contains a import, include or redefine element for which the included schemas cannot be found in the request message

**Lösung:**

Check the values for namespace and schemaLocation you specified in createSDOType against the respective attributes in the import/include/redefine elements of the schemas used

---

---

ADM0024	124	Error in definition of dependent schema: Value of attribute namespace ({0}) differs from target namespace of including schema ({1})	U
---------	-----	---	---

**Beschreibung:**

The definition of a dependent schema is incorrect. For example: the value of the attribute namespace for a schema accessed by the element "include" has to be identical to the target namespace of the including schema

ADM0025	125	Operation {0} expects algorithm with type {1}	U
---------	-----	---	---

**Beschreibung:**

A hash algorithm was entered, where a signature algorithm was expected or vice versa

ADM0026	126	{3} not possible: {0} is not in state {1} but in state {2}	U
---------	-----	--	---

**Beschreibung:**

An operation is not possible because the tenant is not in the state required for the operation, e.g. the operation clearAOIDs can only be performed for a test tenant

**Lösung:**

Check the tenant for which the operation is to be performed

ADM0027	127	Operation {0} needs a tenant, please supply element <mandant>	U
---------	-----	---	---

**Beschreibung:**

Operation that needs a tenant name was called without a valid name

**Lösung:**

Supply the correct name in the header of the operation

ADM0028	128	Illegal Name :{0} [{1}]	U
---------	-----	-------------------------	---

**Beschreibung:**

A name has been specified (e.g. tenant, organisation, role, privilege), which starts with the reserved prefix SecDocs, or a user defined key doesn't conform to the names allowed in SPARQL

**Lösung:**

Please specify a correct name

ADM0029	129	Organisation {0} unknown	U
---------	-----	--------------------------	---

**Beschreibung:**

Unknown organisation supplied in the header field orgID or in the body

**Lösung:**

Use the operation getOrganisations to obtain a list of valid organisations and supply a correct organisation name

ADM0030	130	Internal error in Administration functions: {0}	S,P
---------	-----	---	-----

**Beschreibung:**

An unexpected internal error occurred

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files



---

<b>ADM0031</b>	131	Error in DSEngine function {1}: {0}	S,P,U
<b>Beschreibung:</b>			
One of the functions of the certified DSEngine components returned with error			
<b>Lösung:</b>			
Please contact the SecDocs administrator, who can look up the reason for the error in more detail in the file MSOS-ReturnCodesEN-<version>.pdf			
<b>ADM0032</b>	132	Storage recovery error: {0}	U
<b>Beschreibung:</b>			
Error during execution of storage recovery tool			
<b>Lösung:</b>			
In the manual you can find a description of the valid parameters and properties			
<b>ADM0033</b>	133	Tenant {0} already exists (state:{1})	U
<b>Beschreibung:</b>			
The tenant you tried to create already exists. Tenant names have to be unique in SecDocs			
<b>Lösung:</b>			
Use the operation getMandants to obtain a list of all tenants			
<b>ADM0034</b>	134	Element {0} in {1} cannot be changed	U
<b>Beschreibung:</b>			
When using one of the update functions you tried to change a property which may not be changed			
<b>Lösung:</b>			
Refer to the manual to find out which properties may be changed			
<b>ADM0035</b>	135	TSP {0} already exists	U
<b>Beschreibung:</b>			
The TSP you tried to create already exists. TSP names have to be unique in SecDocs			
<b>Lösung:</b>			
Use the operation getTSPs for a list of all currently defined TSPs			
<b>ADM0036</b>	136	No TSP provided	U
<b>Beschreibung:</b>			
A tenant needs at least one TSP, otherwise the documents cannot be sealed and thus evidence of their integrity and authenticity cannot be furnished			
<b>ADM0037</b>	137	Invalid Path {0}	U,S
Possible reasons:			
Path may not exist			
Path may not be writable			
Path may contain ..			
Path may be absolute			

---

---

**Beschreibung:**

The Path you specified for the tenant or the organisation cannot be used by SecDocs

**Lösung:**

Check first, if the path is syntactically correct (see manual), then ask the system administrator to check the file system

**ADM0038**      138      Unknown TSP {0}      U

**Beschreibung:**

The TSP you used is not known in SecDocs

**Lösung:**

Use the operation getTSPs to obtain the list of known TSPs

**ADM0039**      139      Unknown SDOType {0}      U

**Beschreibung:**

The SDOType you used is not known in SecDocs

**Lösung:**

Use the operation getSDOTypes to obtain the list of known SDOTypes

**ADM0040**      140      {0} already exists      U

**Beschreibung:**

The name is already in use

**Lösung:**

Use the appropriate get... operation to get a list of names already known in SecDocs

**ADM0041**      141      {1} Algorithm "{0}" does not exist      U

**Beschreibung:**

The algorithm you used is not known in SecDocs

**Lösung:**

Use the operation getHashAlgorithms, or getSignatureAlgorithms to obtain the list of algorithms supported by SecDocs

**ADM0042**      142      Error in {1}: {0}      U

**Beschreibung:**

Validation of the schema/filter failed. This can have various reasons: XML is not well formed, XML does not comply to the respective schema (Filtering.xsd; <http://www.w3.org/2001/XMLSchema>), the encoding may be wrong, ...

**Lösung:**

Validate the schema and filter before registering it in SecDocs using createSDOType

**ADM0043**      143      SDOType {0} already exists      U

**Beschreibung:**

The SDOType you tried to create already exists. SDOType names have to be unique within a tenant

**Lösung:**

Use the operation getSDOTypes to obtain the list of known SDOTypes

**ADM0044**      144      {1} Invalid xpath definition: {0}      U

---

**Beschreibung:**

xpath expression within a data node must be relativ, outside they must be absolute

**ADM0045**      145      Illegal value {0} for mapname in SDOType {1}.      U

**Beschreibung:**

The filter you tried to register contains a system key (\$...) not allowed in SecDocs

**Lösung:**

Refer to chapter "Using keys" in the manual for a complete list of allowed system keys

**ADM0046**      146      Filter must contain a valid definition for {0}      U

**Beschreibung:**

For each document archived in SecDocs the earliest time at which on this document may be deleted must be specified. Therefore the filter must contain at least one of the system keys \$RetentionPeriod or \$ExpirationDate

**Lösung:**

Refer to chapter "Using keys" in the manual for a detailed description of these keys

**ADM0047**      147      Organisation {0} already exists      U

**Beschreibung:**

The organisation you tried to create already exists. Organisation names must be unique within a tenant.

**Lösung:**

Use the operation getOrganisations to obtain a list of valid organisations and supply a correct organisation name

**ADM0048**      148      In the header either password or token can be used but not both      U

**Beschreibung:**

In the header of the operation you stated both password and token, only password is supported

**ADM0049**      149      principal or credentials not valid (role: {0} , mandant: {1} , orgID: {2})      U

**Beschreibung:**

Either a part of the principal is not valid or the credentials were rejected for this principal

**ADM0050**      150      operation not valid (role: {0} , mandant: {1} , organisation: {2} , operation: {3})      U

**Beschreibung:**

Either the operation passed in the header is not supported by the Web service addressed or the AOID does not belong to the tenant and organisation passed in the header

**Lösung:**

Refer to the manual for a complete list of supported operations.

**ADM0051**      151      Path for {0} already in use by {1}      U

---

**Beschreibung:**

Either the operation passed in the header is not supported by the Web service addressed or the AOID does not belong to the organisation passed in the header

**Lösung:**

Refer to the manual for a complete list of supported operations

<b>ADM0052</b>	152	\$ExpirationDate must have a xpath attribute and may not have a default attribute	U
----------------	-----	---	---

**Beschreibung:**

Since every document archived in SecDocs needs to calculate an individual expiration date, this date has to be part of the SDO and thus has to be addressed using xpath.

**Lösung:**

Supply a suitable xpath or if you wish SecDocs to compute the expiration date relatively to the date of submittal into the archive, use \$RetentionPeriod

<b>ADM0053</b>	153	Need security element password or token	U
----------------	-----	---	---

**Beschreibung:**

To execute an operation in SecDocs a password is needed

<b>ADM0054</b>	154	Need soap header security element role	U
----------------	-----	--	---

**Beschreibung:**

To execute an operation in SecDocs you have to pass a role in the header

**Lösung:**

Add a role element. If role is already in message: check the XML namespaces in use. Each Web Service version uses its own set of namespaces

<b>ADM0055</b>	155	Need soap header element operation	U
----------------	-----	------------------------------------	---

**Beschreibung:**

Please specify the operation you wish to execute in the operation element of the header

**Lösung:**

Add an operation element. If operation is already in message: check the XML namespaces in use. Each Web Service version uses its own namespaces

<b>ADM0056</b>	156	Operation {0} rejected: "{1}" is still running	U
----------------	-----	--	---

**Beschreibung:**

The operation cannot be started as long as another is running in the background

**Lösung:**

Wait till the operation in the background is finished and then try again

<b>ADM0059</b>	159	Different values provided in {2} ({0}) and {3} ({1})	U
----------------	-----	--	---

**Beschreibung:**

If you supply a tenant in the Credentials element it has to match the tenant given in the header of the operation

<b>ADM0060</b>	160	{0} cannot change credentials for role "{1}"	U
----------------	-----	--	---

---

**Beschreibung:**

To change a password you have to supply a valid role: MandantAdmin can change the passwords for MandantAdmin, SecDocs\_MandantAuditor and Archivar, ArchiveAdmin can change the passwords for ArchiveAdmin and MandantAdmin

**ADM0061**      161      Invalid body content {0} for operation {1}      U

**Beschreibung:**

The contents of the body does not comply with the body expected for the operation.

**Lösung:**

Refer to the manual for a detailed description of the message body for all operations supported by SecDocs

**ADM0062**      162      Need soap header security element mandant      U

**Beschreibung:**

Access to SecDocs with a role other then ArchiveAdmin requires the header element mandant

**ADM0063**      163      "{0}" cannot be used for timestamping: {1}      U

**Beschreibung:**

Once a TSP has been used to renew time stamps by renewHashAlgorithm or renewTSPSignature, this TSP can no longer be used to seal new AOIDs

**ADM0064**      164      Please supply different TSPs for operation \\ "{0} \\ "      U

**Beschreibung:**

To renew time stamps with either renewHashAlgorithm or renewTSPSignature you have to supply two different TSPs.

**ADM0065**      165      TSP {0} [{1}] does not work. Possible causes:      U,S,P  
URL {1} may not be reachable  
hash algorithm may not be supported by the time stamp  
provider  
One of the TSP properties is not supported by the time stamp  
provider  
Additional info: {2}

**Beschreibung:**

Failed to get a time stamp from the TSP. Maybe the URL is unreachable because of a typo in the URL, net work problems or problems with the server of the TSP. Alternatively you used parameter values not supported by the TSP (e.g. for KeyLength, HashAlgorithmName, ...)

**ADM0066**      166      Wrong number of credentials supplied for {0}: {1}      U

**Beschreibung:**

createMandant credentials for the role MandantAdmin and one for role Archivar if the tenant is NOT intended for XAIP

**ADM0067**      167      No AOIDs found in state {1} for {0}      U

---

**Beschreibung:**

renewHashAlgorithm or renewTSPSignature did not find any AOIDs which time stamps need to be renewed

**ADM0068**      168      Parameter {0} with value {1} not yet supported      U

**Beschreibung:**

The stated parameter or the value of the parameter is reserved for future use.

**Lösung:**

Omit the parameter or refer to the manual for a list of valid values

**ADM0070**      170      Cannot delete {0}: {1}      U

**Beschreibung:**

An object, e.g. a tenant, a role, a privilege or a SDOType, cannot be deleted due to the specified reason

**ADM0071**      171      Don't need soap header security element mandant for archive administration      U

**Beschreibung:**

Operations offered by ArchiveAdminService Web service apply to global data of the archive, therefore element mandant is not needed for access

**ADM0072**      172      Don't need soap header security element orgID for archive administration      U

**Beschreibung:**

Operations offered by ArchiveAdminService Web service apply to global data of the archive, therefore element orgID is not needed for access

**ADM0073**      173      Don't need soap header element {0} for archive administration      U

**Beschreibung:**

Operations offered by ArchiveAdminService Web service apply to global data of the archive, therefore given element is not needed for access

**ADM0074**      174      Invalid role for ArchiveAdminService Web service (role: {0})      U

**Beschreibung:**

ArchiveAdminService Web service can only be called by role ArchiveAdmin

**ADM0075**      175      Invalid role for MandantAdminService Web service (role: {0})      U

**Beschreibung:**

MandantAdminService Web service can only be called by roles MandantAdmin and SecDocs\_MandantAuditor

**ADM0076**      176      Invalid role for ArchivingService Web service (role: {0})      U

**Beschreibung:**

ArchivingService Web service can only be called by role Archivar

**ADM0077**      177      Unknown Web Service type (type: {0})      U

---

**Beschreibung:**

You tried to access a Web Service not supported by SecDocs. Supported Web services are: ArchivingService, ArchiveAdminService and MandantAdminService

**ADM0078**      178      Attribute/Element {0} is not yet supported for element {1}      U

**Beschreibung:**

The element or attribute (in the case of a filter definition) mentioned in the error message is reserved for future use

**ADM0079**      179      Wrong version for filter found      U

**Beschreibung:**

Only version=1.0 is allowed in filter definition

**ADM0080**      180      Role "{0}" cannot be used in context "{1}"      U

**Beschreibung:**

The role ArchiveAdmin must not be specified in the Credentials element for the operation createMandant

**Lösung:**

Please specify the role MandantAdmin resp. Archivar in the Credentials element for the operation createMandant

**ADM0081**      181      Invalid definition of node "\$DataNode":  
                                 {0}      U

**Beschreibung:**

Filter contains an incorrect datanode definition.

**Lösung:**

Refer to the manual chapter "\$DataNode" for a detailed description of the datanode

**ADM0082**      182      {0} uses undefined mapname "{1}"      U

**Beschreibung:**

The definitions of the element alias or the system keys \$Index, \$SDOPath and \$Subject may refer to keys defined in the filter. If one of the referenced keys is not defined the filter will be rejected.

**ADM0083**      183      Don't need soap header element {0} for archive administration U

**Beschreibung:**

Operations offered by ArchiveAdminService Web service apply to global data of the archive, therefore element SDOType is not needed for access

**ADM0084**      184      Don't need soap header element {0} for tenant administration U

**Beschreibung:**

Operations offered by MandantAdminService Web service apply to configuration data of one tenant, therefore elements orgID, aoid and SDOType are not needed for access

**ADM0085**      185      mapType=stream is not allowed for {0}, if xpath points to an  
                                 attribute      U

---

**Beschreibung:**

If the value of a xpath-attribute refers to an attribute in the XML document (@...) only the use of maptype="string" is allowed for such element definitions.

**ADM0086**      186      Corrupt Storage: {0}      U

**Beschreibung:**

The path to the tenant specific section of the archive is not valid, or tenants have been found on the storage system although there are no tenants in the SecDocs database

**Lösung:**

Please check the archiveRoot and the tenant specific path name, or use the recoverFromStorage script with operation "restore" to create the SecDocs database

**ADM0087**      187      mapType={0} is not allowed for {1}      U

**Beschreibung:**

In a filter maptype="stream" is only allowed for system keys \$Content and \$Signature provided the xpath expression does not point to an attribute (@...). All other element definitions must use maptype="string"

**ADM0088**      188      Object inconsistent: {0}      U

**Beschreibung:**

The information found on the storage differs from information in the internal data base

**Lösung:**

Call recoverFromStorage with option update to adjust the database

**ADM0089**      189      Property {0} in secdocs.properties may not be empty      U

**Beschreibung:**

The directory where the archive or the data transferred by sftp will be stored has to be specified in archiveRoot

**ADM0090**      190      Renew of {1} was already succesfully completed at {0} by {2}      U

**Beschreibung:**

A renewHashAlgorithm or renewTSPSignature operation has already resealed all AOIDs. They cannot be resealed again

**ADM0091**      191      Too many TSPs for one tenant, please select only those TSPs you will use for time stamping      U

**Beschreibung:**

The total length of all TSP-Names may not exceed 4000 characters.

**ADM0092**      192      Wrong default-value "{0}" for "{1}". {3} : {2}      U

**Beschreibung:**

In the filter definition an illegal default value for a system key was found

**Lösung:**

Some system keys in the filter definition may only have a fixed set of default values. Please refer to the manual for a detailed description of permitted values

**ADM0093**      193      Setting tenant specific properties failed: {0}      U



---

**Beschreibung:**

An error occurred when setting tenant specific properties

**Lösung:**

Only a subset of the properties may be set tenant specifically. Which properties can be set and which values are permitted can be found in the manual

**ADM0094**      194      Filter and Schema not matching: {0} is no root element      U

**Beschreibung:**

Within the filter definition the attribute "schema" of the element "filter" has to match to a root element in the XML schema

**ADM0095**      195      Element {0} must differ in {1} and {2}      U

**Beschreibung:**

When calling renewHashAlgorithm, to recompute the hash values of AOIDs and reseal them, you have to specify two TSPs whose HashAlgorithms elements differ

**ADM0096**      196      {1} is already in progress for {0}      U

**Beschreibung:**

Only one job of the type specified in the exception can run at any time for one tenant

**Lösung:**

Please wait for the previous job to finish before starting a new one

**ADM0097**      197      Element {0} has to be equal in {1} and {2}      U

**Beschreibung:**

The function renewTSPSignature requires two TSPs with the same hash algorithm

**ADM0098**      198      Hazelcast already initialized      S

**ADM0099**      199      Error in Hazelcast initialization: {0}      S

**ADM0100**      200      Invalid CryptoModule host name: {0}      U

**Beschreibung:**

host name must be set to 127.0.0.1 or localhost

**ADX0001**      10001      The certificate is already in use by {0}/{1}/{2}      U

**Beschreibung:**

The client certificate is already in use

**Lösung:**

Please use a unique certificate for each combination of Mandant/Organisation/Role

**ADX0002**      10002      The certificate is invalid: {0}      U

**Beschreibung:**

The client certificate is invalid

**Lösung:**

Please use a valid certificate for each combination of Mandant/Organisation/Role

**ADX0003**      10003      Unknown certificate ( subject:{0} serial number:{1} )      U

---

**Beschreibung:**

The client certificate which has been used in the operation is not known in SecDocs

**Lösung:**

Please use the operation setCredentials to add the certificate to SecDocs

<b>ADX0004</b>	10004	certificate missing	U
----------------	-------	---------------------	---

**Beschreibung:**

The operation setCredentials was used with Type Certificate, but no Certificate was given

**Lösung:**

Please supply certificate

<b>ADX0006</b>	10006	Type "Certificate" may not be used here	U
----------------	-------	---	---

**Beschreibung:**

Type "Certificate" may only be used for roles and tenants that use the XAIP Archiving Service

<b>ADX0007</b>	10007	Property {0} may only be set when tenant is created	U
----------------	-------	---	---

**Beschreibung:**

The property cannot be changed after a tenant has been created

<b>ADX0008</b>	10008	Schemas belonging to the XAIP specification may not be changed.	U
----------------	-------	---	---

**Beschreibung:**

Schemas belonging to the XAIP standard cannot be modified or deleted.

<b>ADX0009</b>	10009	Error in MSOS secure mode initialization	U
----------------	-------	--	---

**Beschreibung:**

Contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>ADX0010</b>	10010	Invalid Policy	U
----------------	-------	----------------	---

**Beschreibung:**

Please supply a valid policy

<b>ADX0011</b>	10011	Cannot secure Passwords: Possible Reasons: tenant has been deleted recently SecDocs was not properly migrated	U
----------------	-------	---	---

**Beschreibung:**

Use an existing Tenant or contact the SecDocs administrator

## Audit

Schlüssel	Fehlercode	Text	Kategorie
<b>AUD0000</b>	700	Data inconsistency in audit subsystem. Cannot log any audit records.	P

---

---

**Beschreibung:**

Cannot find any audit logger data structures. Internal data are inconsistent/corrupt.

**Lösung:**

Restart the SecDocs application. Contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>AUD0002</b>	702	The given audit log file name "{0}" is invalid. Cannot get any log file data.	U
----------------	-----	---	---

**Beschreibung:**

The given file name is not accepted by SecDocs as a valid audit log file name.

**Lösung:**

Specify a valid name for the requested audit log file.

<b>AUD0003</b>	703	The given audit log file name "{0}" is a directory. Cannot get any log file data.	U
----------------	-----	---	---

**Beschreibung:**

The given file name is not a file but a directory.

**Lösung:**

Specify a valid name for the requested audit log file.

<b>AUD0004</b>	704	The given audit log file "{0}" does not exist. Cannot get any log file data.	U
----------------	-----	--	---

**Beschreibung:**

The given file name does not exist.

**Lösung:**

Specify a valid name for the requested audit log file.

<b>AUD0005</b>	705	The audit log file name is missing.	U
----------------	-----	-------------------------------------	---

**Beschreibung:**

The specification of an audit log file name is mandatory.

**Lösung:**

Specify a valid name for the requested audit log file.

<b>AUD0006</b>	706	The audit log file "{0}" cannot be read. Cannot get any log file data.	U
----------------	-----	--	---

**Beschreibung:**

Cannot read the given audit log file.

**Lösung:**

Check the path and the permission of the given file.

## SFTP Server

Schlüssel	Fehlercode	Text	Kategorie
<b>FTP0002</b>	1102	The sftp command "{0}" is not supported.	U

---

---

**Beschreibung:**

The given sftp command is not supported.

**Lösung:**

User error

**FTP0003**      1103      Cannot create the transfer area directory "{0}".      S

**Beschreibung:**

The SFTP Server cannot create the AOID directory in the transfer area used to contain the external objects. Maybe another client application has also issued the sftp command "put" for this external reference ID.

**Lösung:**

Make sure that the sftp command "put" for a certain external reference ID is not issued by more than one client application at the same time.

Possibly a system administrator has to check the file permissions of the tenant/organisation in the transfer area.

**FTP0004**      1104      Cannot remove Reference ID "{0}".      U

**Beschreibung:**

The SFTP Server cannot remove the given Reference ID in the transfer area.

**Lösung:**

A system administrator has to check the file permissions of the tenant/organisation in the transfer area.

**FTP0006**      1106      no such path "{0}"      S

**Beschreibung:**

The SFTP-Server cannot access the given path.

**Lösung:**

S

**FTP0007**      1107      no such directory "{0}"      U

**Beschreibung:**

The given directory does not exist.

**Lösung:**

User error

**FTP0010**      1110      The access to "{0}" is denied.      U

**Beschreibung:**

The access to the given resource is denied due to missing permissions.

**Lösung:**

User error

**FTP0011**      1111      "{0}" IO operation "{1}" failed      S

**Beschreibung:**

An IO operation failed.

**Lösung:**

Report the problem to SecDocs support.

**FTP0012**      1112      The SecDocs user "{0}" is not authorized to access SFTP server. U

---

**Beschreibung:**

The usage of SFTP is not permitted to the given user.

**Lösung:**

Only Archivars are enabled to use SFTP.

<b>FTP0015</b>	1115	Illegal use of Reference ID "{0}": Either it was not obtained with getAOIDWithRef/registerRefs4LXAIP or SDO/LXAIP using it is already submitted	U
----------------	------	---	---

**Beschreibung:**

Either the reference ID was not retrieved by getAOIDWithRef/registerRefs4LXAIP or the SDO/LXAIP using this Reference ID was already submitted.

**Lösung:**

Obtain a valid refID with getAOIDWithRef/registerRefs4LXAIP or check whether the SDO/LXAIP was already submitted

<b>FTP0022</b>	1122	File "{0}" cannot be empty.	U
----------------	------	-----------------------------	---

**Beschreibung:**

The file being transferred to the SFTP server is empty.

**Lösung:**

Check the input file.

## OverSign

Schlüssel	Fehlercode	Text	Kategorie
<b>OVS0000</b>	800	Oversign Error {0}	P
<b>Beschreibung:</b> unexpected error situation			
<b>Lösung:</b> report problem to SecDocs support			
<b>OVS0001</b>	801	Invalid Timer Value {0} {1}	P
<b>Beschreibung:</b> unexpected timer value read from configuration			
<b>Lösung:</b> report problem to SecDocs support			
<b>OVS0002</b>	802	Oversign unrecoverable Error	S,P,U
<b>Beschreibung:</b> Error in communication with the crypto module			
<b>Lösung:</b> evaluate embedded message/exception for root cause analysis			
<b>OVS0003</b>	803	HDO stream for AOID {0} has invalid length 0	P

---

**Beschreibung:**

no SDO content on storage

**Lösung:**

report to SecDocs support

<b>OVS0004</b>	804	Application stopped	U
----------------	-----	---------------------	---

**Beschreibung:**

exception due to forced shutdown

<b>OVS0005</b>	805	Evidence record read error for AOID {0}	P,S
----------------	-----	---	-----

**Beschreibung:**

cannot read evidence record from storage

**Lösung:**

report to SecDocs support

<b>OVS0006</b>	806	Renew Job rejected - Timestamping already running {0}	U
----------------	-----	---	---

**Beschreibung:**

multiple start of renew job

<b>OVS0007</b>	807	Unexpected AOID State for Renew Job {0} {1}	P
----------------	-----	---	---

**Lösung:**

report to SecDocs support

<b>OVS0008</b>	808	Exception during Oversign Handling {0}	S,P,U
----------------	-----	--	-------

**Lösung:**

evaluate exception for root cause analysis

<b>OVS0009</b>	809	No AOID(s)	U
----------------	-----	------------	---

**Beschreibung:**

no AOIDs for renewal available

<b>OVS0010</b>	810	ER verification failure for TSP {0} / {1}	S,P
----------------	-----	---	-----

**Beschreibung:**

TSP\_SIG\_INVALID\_WARNING : the TimeStamp is positively verified but a final statement cannot be met e.g. if despite of using valid or current CRL data the signature were issued before collecting the revocation information and the OCSP check was not automatically performed to that time.

TSP\_SIG\_ERROR : the TimeStamp could not be completely positive verified.

**Lösung:**

check TSP configuration

<b>OVS0011</b>	811	Error while extracting \$content/\$signature for hash value computation	P
----------------	-----	---	---

---

**Beschreibung:**

An error occurred when sdo was read and analyzed, so that all contents and signatures can be hashed individually

**Lösung:**

evaluate exception for root cause analysis

## Persistence

Schlüssel	Fehlercode	Text	Kategorie
PER0000	300	Database error: {0}	P

**Beschreibung:**

An internal error occurred when trying to access the SecDocs database

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

PER0001	301	No such table: {0}	P
---------	-----	--------------------	---

**Beschreibung:**

An internal error occurred when trying to access the SecDocs database

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

PER0002	302	Missing Data source	P
---------	-----	---------------------	---

**Beschreibung:**

An internal error occurred when trying to access the SecDocs database

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

PER0003	303	Table {0} already exists	P
---------	-----	--------------------------	---

**Beschreibung:**

An internal error occurred when trying to access the SecDocs database

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

PER0004	304	Error when accessing the data base	P
---------	-----	------------------------------------	---

**Beschreibung:**

An internal error occurred when trying to access the SecDocs database

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

PER0005	305	Cannot create AOID: AOID already exists	P
---------	-----	---	---

**Beschreibung:**

An internal error occurred when trying to access the SecDocs database

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

---

<b>PER0006</b>	306	Access denied to database table {0}: {1}	P
----------------	-----	--	---

**Beschreibung:**

An internal error occurred when trying to access the SecDocs database

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>PER0007</b>	307	Timeout during wait for a commit of a COID {0}	P
----------------	-----	--	---

**Beschreibung:**

This error occurs whenever two processes try to archive a SDO for a COID at the same time and one of these processes is aborted unexpectedly.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

## Archiving Request

Schlüssel	Fehlercode	Text	Kategorie
<b>REQ0000</b>	400	Unknown AOID: {0}	U

**Beschreibung:**

the given AOID is unknown or invalid

**Lösung:**

use a valid AOID

<b>REQ0001</b>	401	Data not yet available for AOID	U
----------------	-----	---------------------------------	---

**Beschreibung:**

no SDO data are yet available for this AOID (AOID status = Reserved)

**Lösung:**

operation getAOID was called but operation submitSDO wasn't yet called

<b>REQ0002</b>	402	AOID not in a retrievable state ({0})	U
----------------	-----	---------------------------------------	---

**Beschreibung:**

The state of the specified AOID is not allowed for the current operation

**Lösung:**

Please specify an AOID which is in a state permitted for the current operation

<b>REQ0003</b>	403	AOID not in an updateable state ({0})	U
----------------	-----	---------------------------------------	---

**Beschreibung:**

The state of the specified AOID is not allowed for the current operation

**Lösung:**

Please specify an AOID which is in a state permitted for the current operation

<b>REQ0004</b>	404	AOID already deleted	U
----------------	-----	----------------------	---



---

**Beschreibung:**

It has been tried to change the expiration time or to delete an AOID which was already deleted

**Lösung:**

Please specify an AOID which is not yet deleted

**REQ0005**      405      AOID not in a deletable state ({0})      U

**Beschreibung:**

The state of the specified AOID is not allowed for the current operation

**Lösung:**

Please specify an AOID which is in a state permitted for the current operation

**REQ0006**      406      AOID not in a submittable state ({0})      U

**Beschreibung:**

It has been tried to submit an AOID which was already deleted or which is in an inconsistent state

**Lösung:**

Please specify an AOID which is not yet deleted resp. contact the SecDocs administrator for looking up the reason in the SecDocs logging files

**REQ0007**      407      AOID/COID was reserved by a different user or organisation      U

**Beschreibung:**

The AOID specified in a submitSDO request has been reserved for another user and/or organisation than that contained in the request header of the submitSDO request

**Lösung:**

The operation submitSDO can only be executed using the same user and orgID used to request the AOID

**REQ0008**      408      invalid AOID: {0}      U

**Beschreibung:**

the given string doesn't represent a valid AOID

**Lösung:**

use a valid AOID

**REQ0009**      409      SDO not yet expired      U

**Beschreibung:**

the desired SDO isn't yet expired

**Lösung:**

either wait until the SDO is expired, or use the operation forceDeleteSDO

**REQ0010**      410      soap request size > maxSoapRequestSize ({0})      U

**Beschreibung:**

the SOAP request exceeds the max. SOAP request size

**Lösung:**

either use smaller SDOs or adapt the property maxSoapRequestSize in the file secdocs.properties

**REQ0011**      411      The byte array cannot be created      P

---

**Beschreibung:**

An internal error occurred during the processing of the SOAP request

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**REQ0012**      412      invalid XML data in request: {0}      P,U

**Beschreibung:**

Either the XML syntax of the SOAP request of the user is not correct, or an internal error occurred during the processing of a SPARQL request

**Lösung:**

Please correct the XML syntax in the SOAP request. In case of an error when processing a SPARQL request, contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**REQ0013**      413      error in parsing XML data request      P

**Beschreibung:**

An internal error occurred during parsing the XML syntax of the SOAP request

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**REQ0014**      414      exception in mandant data validator creation: {0}      P

**Beschreibung:**

An internal error occurred during the creation of a tenant specific data validator

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**REQ0015**      415      encoding exception for encoding: {0}      P,U

**Beschreibung:**

Either the SOAP request of the user contains passages which are not conform to UTF-8, or an internal error occurred during the processing of a SPARQL request

**Lösung:**

Please correct the encoding in the SOAP request. In case of an error when processing a SPARQL request, contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**REQ0016**      416      XML parser configuration exception: {0}      P

**Beschreibung:**

An internal error occurred during parsing the XML syntax of the SOAP request (XML parser could not be created)

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**REQ0017**      417      XML data i/o exception: {0}      P

**Beschreibung:**

An internal error occurred during parsing the XML syntax of the SOAP request

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**REQ0018**      418      no XML data root element found      U

the request data (content of SOAP body) for the operation forceDeleteSDO are invalid

REQ0019	419	XML element {0} not found	U
---------	-----	---------------------------	---

**Beschreibung:**

the request data (content of SOAP body) for the operation forceDeleteSDO are invalid

<b>REQ0020</b>	420	element SDOType missing in SOAP header	U
----------------	-----	--	---

**Beschreibung:**

The element `SDOType` is missing in the SOAP request header

**Lösung:**

Add the element `SDOTType` to your SOAP request header

<b>REQ0021</b>	421	operation: {0}: expected root element for request message: {1} U
----------------	-----	--

**Beschreibung:**

The element operation in the SOAP request header does not match the request message sent

**Lösung:**

Either the element operation is set wrong or the sent message does not fit the desired operation

REQ0022	422	data reading i/o exception: {0}	S,P
---------	-----	---------------------------------	-----

**Beschreibung:**

i/o error in data reading

**Lösung:**

Please contact SecDocs administration

REQ0023	423	empty COID	U
---------	-----	------------	---

**Beschreibung:**

the given string doesn't represent a valid COID

**Lösung:**

use a valid COID

<b>REQ0024</b>	424	exception in XML data processing: {0}	S,P
----------------	-----	---------------------------------------	-----

**Beschreibung:**

internal error in XML processing

**Lösung:**

Please contact SecDocs administration

<b>REQ0025</b>	425	Error in DSEngine function {1}: {0} (ECODE: {2}) {3}	S,U
----------------	-----	---	-----

**Beschreibung:**

{1}: called DSEngine function, {0}: DSEngine error message, {2}: DSEngine ECODE (see MSOS return codes), {3}: detailed error information for each signature in SDO

<b>REQ0026</b>	426	SOAP body data stream is null	P
----------------	-----	-------------------------------	---

---

**Beschreibung:**

An internal error occurred during the processing of the SOAP request

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**REQ0027**      427      XML subelement path of navigate request: path is null      U

**Beschreibung:**

user must give a path in operation navigate

**Lösung:**

add a path string to element path

**REQ0028**      428      XML subelement path of navigate request: text must start with U  
/

**Beschreibung:**

In operation navigate the path specified in element "path" is syntactically incorrect

**Lösung:**

Please correct the path string in the element path

**REQ0029**      429      XML subelement maxResults is not a number      U

**Beschreibung:**

user must give a number for element maxResults in operation navigate

**Lösung:**

Please specify a positive number for maxResults

**REQ0030**      430      XML subelement maxResults is a negative number      U

**Beschreibung:**

user can't use a negative number in element maxResults in operation navigate

**Lösung:**

Please specify a positive number for maxResults

**REQ0031**      431      XML subelement path contains not a valid name: {0}      U

**Beschreibung:**

user has not used a valid path name: path name doesn't point to an existing path

**Lösung:**

add a valid path string to element path

**REQ0032**      432      Archiving web services are temporarily not available for this  
tenant      U

**Beschreibung:**

The tenant is a test tenant and data for this tenant are in deletion

**Lösung:**

Please wait until the deletion has been finished

**REQ0033**      433      External reference error: {0}      U,S

---

**Beschreibung:**

Erroneous external reference file

**Lösung:**

Upload a corrected version of the indicated external reference.

**REQ0035**      435      COID {0} is unknown      U

**Beschreibung:**

the coid passed in the header is unknown in SecDocs

**Lösung:**

check coid

**REQ0036**      436      COID is not unique: {0} is already known for {1} and {2}      U

**Beschreibung:**

The COID used in a submitSDO request has already been used with a different organisation or sdoType

**Lösung:**

check coid

**REQ0037**      437      Wrong AOID for COID {0}      U

**Beschreibung:**

COID and AOID were provided, but the AOID does not belong to the COID

**Lösung:**

use statusSDO with either the COID or the AOID to retrieve the matching AOID/COID

**REQ0038**      438      Header Element {0} not allowed in Operation {1}      U

**Beschreibung:**

Illegal use of a headerfield. For example coid is not allowed in header of getAOID

**Lösung:**

check manual which header fields are supported for the operation

**REQ0039**      439      Illegal COID {0}      U

**Beschreibung:**

The provided COID was syntactically incorrect. For example COIDs may not be longer than 256 characters

**REQ0040**      440      SDO cannot be replaced while being in state {0}      U

**Beschreibung:**

The AOID or COID was either not yet used by submitSDO or the AOID was already deleted

**REQ0041**      441      Operation {0} needs header element coid      U

**Beschreibung:**

The operation called does not work without a valid coid

**Lösung:**

Supply coid

**REQ0042**      442      Internal error: {0}      P

---

**Beschreibung:**

An internal error occurred during the processing of the SOAP request

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**REQ0043**      443      SDOs of SDO type {0} cannot be replaced      U

**Beschreibung:**

The SDO to be replaced has a SDO type which cannot be replaced

**Lösung:**

Please contact the tenant administrator to create a SDO type that can be replaced.

**REQ0044**      444      Unknown operation: {0}      U

**Beschreibung:**

The called operation of the Web service ArchivingService is not known in this version

**Lösung:**

Typically newer versions have operations that are unknown in older versions. Try an endpoint URL of a newer version.

**REQ0045**      445      Element hashAlgorithmName is missing in the SOAP body      U

**Beschreibung:**

If the element "hashValue" has been specified in the SOAP body of the getAOIDWithRef request, the element "hashAlgorithmName" must be specified too.

**Lösung:**

Add the element "hashAlgorithmName" to the SOAP body of the request.

**REQ0046**      446      Neither the element descriptionText nor the elements  
hashValue and hashAlgorithmName have been specified in the  
SOAP body      U

**Beschreibung:**

To request an external reference ID the element "descriptionText" or both elements "hashValue" and "hashAlgorithmName" must be specified in the SOAP body of the getAOIDWithRef request.

**Lösung:**

Add the element "descriptionText" or both elements "hashValue" and "hashAlgorithmName" to the SOAP body of the request. You may also specify all these elements.

**REQ0047**      447      Operation replaceSDO not allowed for AOID with external  
reference IDs      U

**Beschreibung:**

AOIDs having been requested with the operation getAOIDWithRef cannot be replaced with replaceSDO.

**Lösung:**

To replace an AOID containing external reference IDs by a recent version, you must archive the recent version with submitSDO under a new AOID and delete the AOID of the old version with deleteSDO. Refer to the manual for a detailed description of the actions necessary for this purpose.

**REQ0048**      448      For one AOID more external reference IDs have been  
requested than allowed. Maximum allowed number: {0}      U

---

**Beschreibung:**

Only a limited number of external reference IDs is allowed per SDO/LXAIP.

**Lösung:**

Reduce the number of requests for external reference IDS in the SOAP body of the request.

**REQ0049**      449      Hash algorithm "{0}" not known in SecDocs      U

**Beschreibung:**

The specified hash algorithm is not known in SecDocs.

**Lösung:**

Please contact the SecDocs administrator to obtain the list of algorithms supported by SecDocs.

**REQ0050**      450      Operation getAOIDWithRef/registerRefs4LXAIP is not allowed if the SecDocs SFTP server has not been started      U

**Beschreibung:**

The SecDocs SFTP server must have been started before you can request an external reference ID with the operation getAOIDWithRef/registerRefs4LXAIP.

**Lösung:**

Set the configuration parameter createSftpServer to "true" in the file secdocs.properties and perform a restart of SecDocs.

**REQ0051**      451      Operation getAOIDWithRef/registerRefs4LXAIP is not allowed if the configuration parameter archiveRootExternalFiles is not provided      U

**Beschreibung:**

The configuration parameter archiveRootExternalFiles must have been provided before you can request an external reference ID with the operations getAOIDWithRef or registerRefs4LXAIP.

**Lösung:**

Set the configuration parameter archiveRootExternalFiles to a valid value in the file secdocs.properties and perform a restart of SecDocs.

**REQ0052**      452      Operation {0} cannot be called from a remote host      U

**Beschreibung:**

The operation can only be called from a client on the machine SecDocs is running on.

**Lösung:**

Call the operation from a client that is located on the machine SecDocs is running on.

**REQ0053**      453      COID {0} already exists for tenant {1} and organisation {2}      U

**Beschreibung:**

The specification of an already existing COID is equivalent to the request of an AOID for a new version of a document. However, the archiving of document versions is not possible for SDOs with external reference IDs.

**Lösung:**

Remove the COID from the SOAP header or specify a COID which does not yet exist.

**REQ0054**      454      COID {0} was reserved by a different organisation of the tenant      U

---

**Beschreibung:**

The COID specified in the SOAP header of the request has been reserved for another organisation of the tenant than that contained in the SOAP header of the request.

**Lösung:**

Remove the COID from the SOAP header or specify a COID which does not yet exist.

<b>REQ0055</b>	455	Operation moveSDO not allowed for AOID with external reference IDs	U
----------------	-----	--	---

**Beschreibung:**

AOIDs having been requested with the operation getAOIDWithRef cannot be moved with moveSDO.

**Lösung:**

To move an AOID containing external reference IDS by a recent version, you must archive the recent version with submitSDO under a new AOID and delete the AOID of the old version with deleteSDO. Refer to the manual for a detailed description of the actions necessary for this purpose.

<b>REQ0056</b>	456	Element hashValue is missing in the SOAP body	U
----------------	-----	---	---

**Beschreibung:**

If the element "hashAlgorithmName" has been specified in the SOAP body of the getAOIDWithRef request, the element "hashValue" must be specified too.

**Lösung:**

Add the element "hashValue" to the SOAP body of the request, or remove the element "hashAlgorithmName" if you don't want to specify a hash value.

<b>REQ0057</b>	457	Value of element descriptionText "{0}...." is too long	U
----------------	-----	--	---

**Beschreibung:**

The value of the element "descriptionText" in the SOAP body of the getAOIDWithRef request must not exceed 1000 characters.

**Lösung:**

Reduce the value of the concerned element to a maximum of 1000 characters.

<b>REQ0058</b>	458	Value of element path is too long	U
----------------	-----	-----------------------------------	---

**Beschreibung:**

The value of the element "path" in the SOAP body of the navigate request must not exceed 512 characters if "useDatabase=true" is set.

**Lösung:**

Set useDatabase=false.

<b>REQ0059</b>	459	EvidenceRecord creation in progress	U
----------------	-----	-------------------------------------	---

**Beschreibung:**

EvidenceRecord creation is in progress for current AOID.

**Lösung:**

Try again after a short wait time.

<b>REQ0060</b>	460	SecDocs SOAP header element token not supported	U
----------------	-----	---	---



---

**Beschreibung:**

SecDocs SOAP header element token not supported

**Lösung:**

Use element password instead.

**REQ0061**      461      This web service operation is not allowed in TR-ESOR mode      U

**Beschreibung:**

this web service operation can't be used in the TR-ESOR certified mode.

**Lösung:**

Either don't use this operation or run SecDocs not in the TR\_ESOR certified mode.

**REQ0062**      462      Operation registerRefs4LXAIP is not allowed if the configuration parameter archiveRootExternalFiles is not provided      U

**Beschreibung:**

The configuration parameter archiveRootExternalFiles must have been provided before you can request an external reference ID with the operation registerRefs4LXAIP.

**Lösung:**

Set the configuration parameter archiveRootExternalFiles to a valid value in the file secdocs.properties and perform a restart of SecDocs.

**REQ0063**      463      Attribute {0} too long      U

**Beschreibung:**

The attributes can have at most 1000 characters.

**Lösung:**

Shorten your attribute in use.

**REQ0064**      464      unexpected attribute version in SecDocs SOAP header element      U

**Beschreibung:**

the attribute version is only supported for SecDocs 4.0 and above.

**Lösung:**

remove attribute version from the SecDocs SOAP header element.

**REQ0065**      465      value of attribute version is not a number      U

**Beschreibung:**

the value of the attribute version must be a positive integer.

**Lösung:**

use a proper value for the attribute version.

**REQ0066**      466      value of attribute version is not supported      U

**Beschreibung:**

the value of the attribute version is not supported.

**Lösung:**

use a proper value for the attribute version.

**REQ0067**      467      This web service operation is not supported      U

---

**Beschreibung:**

this web service operation is not supported by SecDocs.

**Lösung:**

Do not use this operation as it is not supported by SecDocs.

## Storage Adapter

Schlüssel	Fehlercode	Text	Kategorie
STA0000	600	StorageAdaptor exception	S,P
<b>Beschreibung:</b> StorageAdaptorException occurred.			
STA0001	601	SecDocsException	S,P
<b>Beschreibung:</b> SecDocsException occurred.			
STA0002	602	Illegal parameter: {0}	S,P
<b>Beschreibung:</b> Illegal parameter {0} received.			
STA0003	603	Illegal object type: {0}	S,P
<b>Beschreibung:</b> Illegal object type {0} received.			
STA0004	604	Illegal content type: {0}	S,P
<b>Beschreibung:</b> Illegal content type {0} received.			

## Storage Connector

Schlüssel	Fehlercode	Text	Kategorie
STC0000	500	StorageConnector exception	S,P
<b>Beschreibung:</b> StorageConnectorException occurred.			
STC0001	501	I/O exception: {0}	S,P
<b>Beschreibung:</b> IOException occurred.			
<b>Lösung:</b> Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.			
STC0002	502	Illegal object type: {0}	S,P

---

---

**Beschreibung:**

Illegal object type {0} received.

<b>STC0003</b>	503	Illegal parameter: {0}	S,P
----------------	-----	------------------------	-----

**Beschreibung:**

Illegal parameter {0} received.

<b>STC0004</b>	504	Could not create: {0}	S,P
----------------	-----	-----------------------	-----

**Beschreibung:**

Object {0} couldn't be created.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0005</b>	505	Value already set: {0}	S,P
----------------	-----	------------------------	-----

**Beschreibung:**

Value {0} has already been set.

<b>STC0006</b>	506	ADO path {0} invalid for AOID {1}	S,P
----------------	-----	-----------------------------------	-----

**Beschreibung:**

ADO path {0} is invalid for AOID {1}.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0007</b>	507	Object not available: {0}	S,P
----------------	-----	---------------------------	-----

**Beschreibung:**

Object {0} isn't available.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0008</b>	508	FileNotFoundException	S,P
----------------	-----	-----------------------	-----

**Beschreibung:**

FileNotFoundException occurred.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0009</b>	509	AOIDTable exception	S,P
----------------	-----	---------------------	-----

**Beschreibung:**

AOIDTableException occurred.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0010</b>	510	InvalidDate exception: {0}	U
----------------	-----	----------------------------	---

**Beschreibung:**

InvalidDateException occurred.

**Lösung:**

Use a date with a valid format.

---

<b>STC0011</b>	511	InvalidExpirationDate exception	S,P
<b>Beschreibung:</b>			
InvalidExpirationDateException occurred.			
<b>Lösung:</b>			
Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.			
<b>STC0012</b>	512	{0} could not be deleted	S,P
<b>Beschreibung:</b>			
{0} could not be deleted.			
<b>Lösung:</b>			
Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.			
<b>STC0013</b>	513	Illegal AOID status: {0}	S,P
<b>Beschreibung:</b>			
AOID status {0} not allowed.			
<b>Lösung:</b>			
Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.			
<b>STC0014</b>	514	Illegal path component: {0}	U
<b>Beschreibung:</b>			
Path must not contain string {0}.			
<b>Lösung:</b>			
use another character. Description of allowed characters in SecDocs manual chap. "\$SDOPath".			
<b>STC0015</b>	515	UnsupportedEncodingException	S,P
<b>Beschreibung:</b>			
UnsupportedEncodingException occurred.			
<b>Lösung:</b>			
Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.			
<b>STC0016</b>	516	path {0} must not contain {1}	U
<b>Beschreibung:</b>			
Path {0} must not contain string {1}.			
<b>Lösung:</b>			
use another character. Description of allowed characters in SecDocs manual chap. "\$SDOPath".			
<b>STC0017</b>	517	path {0} must not start with {1}	U
<b>Beschreibung:</b>			
Path {0} must not start with string {1}.			
<b>Lösung:</b>			
use another character. Description of allowed characters in SecDocs manual chap. "\$SDOPath".			
<b>STC0018</b>	518	\$SoftWorm requested but no ExpirationDate available for {0}	U

---

---

**Beschreibung:**

ExpirationDate is not available but \$SoftWorm is requested for file {0}.

**Lösung:**

set a valid ExpirationDate.

**STC0019**      519      \$SoftWorm requested but ExpirationDate/RetentionPeriod U  
is set to UNLIMITED for {0}

**Beschreibung:**

ExpirationDate/RetentionPeriod UNLIMITED is not possible if \$SoftWorm is requested for file {0}.

**Lösung:**

set a valid ExpirationDate/RetentionPeriod.

**STC0020**      520      \$SoftWorm requested but invalid ExpirationDate specified for U  
{0}

**Beschreibung:**

Specified ExpirationDate is not possible if \$SoftWorm is requested for {0}.

**Lösung:**

set a valid ExpirationDate.

**STC0021**      521      Could not set ReadOnly mode for {0}      S,P

**Beschreibung:**

ReadOnly mode could not be set for {0}.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0022**      522      "{0}" could not be renamed to "{1}"      S,P

**Beschreibung:**

"{0}" could not be renamed to "{1}".

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0023**      523      XMLStreamException      S,P

**Beschreibung:**

XMLStreamException occurred.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0024**      524      ParserConfigurationException "{0}"      S,P

**Beschreibung:**

ParserConfigurationException "{0}" occurred.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0025**      525      SAXException - could not parse file {0}      S,P

---

**Beschreibung:**

SAXException for file {0} occurred.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0026**      526      InvalidArgumentException "{0}" during calculation of "{1}"      S,P

**Beschreibung:**

During calculation of {1} InvalidArgumentException {0} occurred.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0027**      527      Error in DSEngine function {1}: {0} (ECODE: {2})      S,P

**Beschreibung:**

Error {0} occurred during execution of DSEngine function {1}. ECODE {2}.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0028**      528      FilterException "{0}" during calculation of "{1}"      U

**Beschreibung:**

During calculation of {1} FilterException {0} occurred.

**Lösung:**

Current SDO doesn't match with the specified filter. Check your SDO.

**STC0029**      529      NoSuchAlgorithmException "{0}" for algorithm "{1}"      S,P

**Beschreibung:**

NoSuchAlgorithmException {0} for algorithm {1} occurred.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0030**      530      Corrupted document - invalid hash value for AOID {0}: now: {1}, in archive: {2}      S

**Beschreibung:**

document with AOID {0} has been modified unauthorized on the file system after input verification and archiving. Current hash value {1}, original hash value: {2}.

**Lösung:**

check whether the original document can be restored from backup.

**STC0031**      531      {0} already deleted      S,P

**Beschreibung:**

{0} has been deleted before.

**Lösung:**

An error has occurred during a previous request for this AOID. Please contact the SecDocs administrator for looking up the erroneous request in the SecDocs logging files.

**STC0032**      532      could not read {0}      S

---

**Beschreibung:**

Could not read {0}.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0033</b>	533	SDOPath inconsistency for {0}	S
----------------	-----	-------------------------------	---

**Beschreibung:**

SDOPath inconsistency for {0}

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0034</b>	534	Error during compression of SignatureVerificationInfo for AOID: {0}	S
----------------	-----	---	---

**Beschreibung:**

Error during compression of SignatureVerificationInfo for AOID: {0}

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0035</b>	535	ExpirationDate=today+RetentionPeriod requested, but invalid value "{0}" for RetentionPeriod is supplied	U
----------------	-----	---	---

**Beschreibung:**

ExpirationDate=today+RetentionPeriod is requested, but invalid value {0} for RetentionPeriod is supplied.

**Lösung:**

Supply a valid value for RetentionPeriod.

<b>STC0036</b>	536	Invalid hash data object size "{0}" exceeds maxHashDataObjectSize "{1}"	U
----------------	-----	---	---

**Beschreibung:**

Invalid hash data object size {0} exceeds maxHashDataObjectSize {1}

**Lösung:**

Reduce length of hash data object.

<b>STC0037</b>	537	No subpaths/aoids existing for path "{0}"	U
----------------	-----	---	---

**Beschreibung:**

No subpaths/aoids existing for path {0}. If a valid path has been specified: normal situation - no SDOs have been submitted until now.

**Lösung:**

Check if a valid path has been specified.

<b>STC0038</b>	538	moveSDO not allowed for AOID with \$SoftWorm=YES	U
----------------	-----	--	---

**Beschreibung:**

moveSDO not allowed for AOID with \$SoftWorm=YES.

**Lösung:**

Don't use SoftWorm for AOID which has to be moved.

<b>STC0039</b>	539	New (preliminary) ExpirationDate "{0}" smaller/equal ExpirationDate set in archive "{1}"	U
----------------	-----	--	---

---

**Beschreibung:**

New (preliminary) ExpirationDate "{0}" smaller/equal ExpirationDate set in archive "{1}"

**Lösung:**

Choose bigger ExpirationDate or RetentionPeriod.

<b>STC0040</b>	540	\$Index data of AOID "{0}" could not be inserted into TripleStore	S
----------------	-----	---	---

**Beschreibung:**

\$Index data of AOID "{0}" could not be inserted into TripleStore

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0041</b>	541	no XML root element found in file {0}	S,P
----------------	-----	---------------------------------------	-----

**Beschreibung:**

No XML root element found in file {0}.

<b>STC0042</b>	542	File "{0}" not found	S,P
----------------	-----	----------------------	-----

**Beschreibung:**

File "{0}" could not be found.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files. In certain cases the archive entry needs to be repaired by the StorageRecovery tool.

<b>STC0043</b>	543	Try later - AOID "{0}" is currently in use of another WebService operation.	S,P
----------------	-----	---	-----

**Beschreibung:**

Try later - AOID "{0}" is currently in use of another WebService operation.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0044</b>	544	Double release: FileLock for AOID "{0}" already released.	S,P
----------------	-----	---	-----

**Beschreibung:**

Double release: FileLock for AOID "{0}" already released.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0045</b>	545	No input data available for {0}.	S,P
----------------	-----	----------------------------------	-----

**Beschreibung:**

No input data available for {0}.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>STC0046</b>	546	File "{0}" is empty.	S,P
----------------	-----	----------------------	-----



---

**Beschreibung:**

File "{0}" is empty.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0047**      547      Could not get FileLock for path "{0}" after "{1}" attempts.      S,P

**Beschreibung:**

Could not get FileLock for path "{0}" after "{1}" attempts

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0048**      548      File/path already exists: {0}      S,P

**Beschreibung:**

File/path {0} is already existing.

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

**STC0049**      549      replaceSDO not allowed for AOID with \$SoftWorm=YES      U

**Beschreibung:**

replaceSDO not allowed for AOID with \$SoftWorm=YES.

**Lösung:**

Don't use SoftWorm for AOID which has to be replaced.

**STC0050**      550      Number of references in getAOIDWithRef/registerRefs4LXAIP {0} not equal number of external references in submitSDO/ArchiveSubmission {1}.      U

**Beschreibung:**

Number of references in getAOIDWithRef/registerRefs4LXAIP {0} not equal number of external references in submitSDO/ArchiveSubmission {1}.

**Lösung:**

All references which have been registered by getAOIDWithRef have to be used as external references in submitSDO.

**STC0051**      551      SDO/LXAIP contains external references although used AOID has been requested without references.      U

**Beschreibung:**

SDO/LXAIP contains external references although used AOID has been requested without references.

**Lösung:**

Use an AOID with external references (requested by getAoidWithRef or registerRefs4LXAIP).

**STC0052**      552      External reference {0} already used.      U

**Beschreibung:**

External reference {0} already used.

**Lösung:**

An external reference must be set once in a SDO/LXAIP.

---

<b>STC0053</b>	553	External reference {0} not registered by getAOIDWithRef/registerRefs4LXAIP.	U
<b>Beschreibung:</b> External reference {0} not registered by getAOIDWithRef/registerRefs4LXAIP			
<b>Lösung:</b> An external reference has to be registered by getAOIDWithRef/registerRefs4LXAIP			
<b>STC0054</b>	554	Current value of \$Index keyword {0} is too long.	U
<b>Beschreibung:</b> Current value of \$Index keyword {0} is too long			
<b>Lösung:</b> Set a smaller value for keyword {0} (< 1.000 char)			
<b>STC0055</b>	555	I/O-Exception: {0} for {1}	S,P
<b>Beschreibung:</b> IOException {0} occurred for object {1}.			
<b>Lösung:</b> Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.			
<b>STC0056</b>	556	XAIPContainerException: "{0}", AOID: {1}	S,P
<b>Beschreibung:</b> XAIPContainerException {0} occurred for object {1}.			
<b>Lösung:</b> Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.			
<b>STC0057</b>	557	no evidence record(s) available (aoid:{0})	P
<b>Beschreibung:</b> internal error: no evidence record(s) available (aoid:{0})			
<b>Lösung:</b> Report problem to SecDocs support.			
<b>STC0058</b>	558	no suitable evidence record found (aoid:{0}, tsp:{1})	P
<b>Beschreibung:</b> no suitable evidence record found (aoid:{0}, tsp:{1})			
<b>Lösung:</b> Report problem to SecDocs support.			
<b>STC0059</b>	559	Path "{0}" does not represent a directory.	S,P
<b>Beschreibung:</b> Path "{0}" does not represent a directory.			
<b>Lösung:</b> Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.			

---

---

## XAIP Archiving Request

Schlüssel	Fehlercode	Text	Kategorie
XRQ0000	1200	Internal error: {0}	S,P

**Beschreibung:**

An internal error occurred during the processing of the SOAP request

**Lösung:**

Please contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

XRQ0001	1201	AOID/COID was reserved by a different user or organisation	P,U
---------	------	--	-----

**Beschreibung:**

The AOID specified in a ArchiveSubmission request has been reserved for another user and/or organisation than that contained in the request header of the ArchiveSubmission request

**Lösung:**

The operation ArchiveSubmission can only be executed using the same user and orgID used to request the AOID

XRQ0002	1202	AOID not in a submitable state ({0})	P,U
---------	------	--------------------------------------	-----

**Beschreibung:**

It has been tried to submit an AOID which was already deleted or which is in an inconsistent state.

**Lösung:**

Please specify an AOID which is not yet deleted resp. contact the SecDocs administrator for looking up the reason in the SecDocs logging files

XRQ0003	1203	External references are not supported for XAIP documents	P,U
---------	------	--	-----

**Beschreibung:**

External references are not supported for XAIP documents.

**Lösung:**

Check the AOID you have specified.

XRQ0004	1204	Error in DSEngine function {1}: {0} (ECODE: {2}) {3}	S,P,U
---------	------	---	-------

**Beschreibung:**

{1}: called DSEngine function, {0}: DSEngine error message, {2}: DSEngine ECODE (see MSOS return codes), {3}: detailed error information for each signature in XAIP object

XRQ0005	1205	Unknown AOID: {0}	U
---------	------	-------------------	---

**Beschreibung:**

The specified AOID is unknown or invalid

**Lösung:**

Specify a valid AOID

XRQ0006	1206	AOID not in a retrievable state ({0})	U
---------	------	---------------------------------------	---

---

**Beschreibung:**

The state of the specified AOID is not allowed for the current operation

**Lösung:**

Specify an AOID which is in a state permitted for the current operation

<b>XRQ0007</b>	1207	Unexpected operation {0} in SecDocs request context	S,P
----------------	------	---	-----

**Beschreibung:**

The operation in the request context has an unexpected value.

**Lösung:**

Contact the SecDocs administrator for looking up the reason in the SecDocs logging files.

<b>XRQ0008</b>	1208	SOAP request of operation {0}: no XML data root element found	U
----------------	------	---	---

**Beschreibung:**

The request data (content of SOAP body) for one of the operations ArchiveRetrieval, ArchiveEvidence or ArchiveDeletion are invalid.

**Lösung:**

Correct the XML syntax in the SOAP request.

<b>XRQ0009</b>	1209	SOAP request of operation {0}: specification of {1} is missing	U
----------------	------	--	---

**Beschreibung:**

The request data (content of SOAP body) for one of the operations ArchiveRetrieval, ArchiveEvidence or ArchiveDeletion are incomplete.

**Lösung:**

Add the missing data to the SOAP request.

<b>XRQ0010</b>	1210	Data not yet available for AOID {0}	U
----------------	------	-------------------------------------	---

**Beschreibung:**

It has been tried to delete an AOID the archiving of which with the ArchiveSubmission operation has not yet been completed.

**Lösung:**

Wait until the ArchiveSubmission operation has been completed and then repeat the ArchiveDeletion operation.

<b>XRQ0011</b>	1211	AOID {0} already deleted	U
----------------	------	--------------------------	---

**Beschreibung:**

It has been tried to delete an AOID which was already deleted.

**Lösung:**

Specify an AOID which is not yet deleted.

<b>XRQ0012</b>	1212	SOAP request of operation {0}: request is invalid {1}	U
----------------	------	---	---

**Beschreibung:**

The request data (content of SOAP body) is invalid.

**Lösung:**

Add the missing data to the SOAP request and/or fix invalid values.

<b>XRQ0013</b>	1213	EvidenceRecord creation in progress for AOID {0}	U
----------------	------	--	---

---

---

**Beschreibung:**

EvidenceRecord creation is in progress for current AOID.

**Lösung:**

Try again after a short wait time.

XRQ0014	1214	XAIP document not yet expired	U
---------	------	-------------------------------	---

**Beschreibung:**

the desired XAIP document isn't yet expired

**Lösung:**

either wait until the XAIP document is expired, or use a deletion reason

XRQ0015	1215	XAIP Meta Data Store: XAIP document can't yet be deleted	U
---------	------	--	---

**Beschreibung:**

the desired XAIP document can't yet be deleted

**Lösung:**

either wait until the XAIP document can be deleted, or use a deletion reason

XRQ0016	1216	Retention period for AOID {0} can only be changed for data objects that are already sealed (current state: {1})	U
---------	------	---	---

**Beschreibung:**

Retention Period can only be changed for data objects that are already sealed

**Lösung:**

Please enter an AOID in the correct state-

XRQ0017	1217	ArchiveUpdate can only be used to change the retention period, all other changes are not supported {0}	U
---------	------	--	---

**Beschreibung:**

Update Request can only be used to change the retention period. New meta data, data objects or credentials are not supported

**Lösung:**

Remove all such elements

XRQ0018	1218	The VersionID "{0}" is already in use: {1}	U
---------	------	--	---

**Beschreibung:**

The versionID used in the ArchiveUpdate-request is already in use

**Lösung:**

Please use a unique versionID. TR-ESOR: The versionID-attribute should be built like "v1", "v2", "v3" etc.

XRQ0019	1219	Only the current version can be updated: The value given in prevVersion "{0}" and the versionID "{1}" of the current version do not match	U
---------	------	---	---

**Beschreibung:**

Wrong previous version given

**Lösung:**

Only the current version can be updated

---

<b>XRQ0020</b>	1220	ArchiveUpdate-Requests must contain precisely one versionManifest element.	U
<b>Beschreibung:</b> ArchiveUpdate-Requests must contain precisely one versionManifest element			
<b>Lösung:</b> Please send a correct request			
<b>XRQ0021</b>	1221	In ArchiveUpdate-Requests all metadata, data objects and credentials must be provided as protected/unprotectedObjectPointer elements: Found in {2} "{0}"; expected "{1}"	U
<b>Beschreibung:</b> In ArchiveUpdate-Requests all metadata, data objects and credentials must be provided as protected/unprotectedObjectPointer elements			
<b>Lösung:</b> Add a protectedObjectPointer element for each object, which will be sealed, or an unprotectedObjectPointer element otherwise.			
<b>XRQ0022</b>	1222	Invalid Request: {0}	U
<b>Beschreibung:</b> An invalid request was sent			
<b>Lösung:</b> Please provide a requests which conforms to the "Technische Richtlinie 03125 (TR_ESOR)"			
<b>XRQ0023</b>	1223	Invalid Location Type: {0} The following location types are permitted: <a href="http://www.w3.org/TR/2007/REC-xpath20-20070123/">http://www.w3.org/TR/2007/REC-xpath20-20070123/</a> for XPATH <a href="http://www.w3.org/TR/2007/REC-xquery-20070123/">http://www.w3.org/TR/2007/REC-xquery-20070123/</a> for XQuery <a href="http://www.w3.org/TR/2003/REC-xptr-framework-20030325">http://www.w3.org/TR/2003/REC-xptr-framework-20030325</a> for XPointer	U
<b>Beschreibung:</b> An invalid location type was sent			
<b>Lösung:</b> Please provide a requests which conforms to the "Technische Richtlinie 03125 (TR_ESOR)"			
<b>XRQ0024</b>	1224	The following functionality is not yet supported in prototype of ArchiveData: {0}	U
<b>Beschreibung:</b> Functionality not supported in prototype of ArchiveData			
<b>XRQ0025</b>	1225	The Location of the requested data must be given in a text element that is an immediate child of the element DataLocation	U

---

---

**Beschreibung:**

The Location of the requested data must be given in a text element that is an immediate child of the element DataLocation, complex data types are not supported

<b>XRQ0026</b>	1226	Invalid XPath {0}	U
----------------	------	-------------------	---

<b>XRQ0027</b>	1227	None of the locations yielded a result	U
----------------	------	--	---

**Beschreibung:**

None of the locations yielded a result

<b>XRQ0028</b>	1228	hash of external reference {0} and LXAIP DigestValue (dataObjectID:{1}) do not match	U
----------------	------	--	---

**Beschreibung:**

external reference hash and LXAIP DigestValue don't match

**Lösung:**

Check the hash values.

<b>XRQ0029</b>	1229	hash algorithm of external reference {0} and LXAIP DigestMethod (dataObjectID:{1}) do not match	U
----------------	------	---	---

**Beschreibung:**

external reference hash algorithm and LXAIP DigestMethod don't match

**Lösung:**

Check the DigestMethod in your XAIP document.

Diese Dokumentation ist geistiges Eigentum der Fujitsu.

Sie darf ohne vorherige schriftliche Einwilligung der Fujitsu nicht (auch nicht in Auszügen) vervielfältigt oder veröffentlicht werden, unabhängig von der Art und Weise oder mit welchen Mitteln, elektronisch oder mechanisch, dieses geschieht. Die in dieser Dokumentation verwendeten Soft- und Hardwarebezeichnungen sind genau wie Firmen- oder Markennamen in den meisten Fällen eingetragene Warenzeichen oder Marken und Eigentum der jeweiligen Hersteller. Sie werden ohne Gewährleistung der freien Verwendbarkeit benutzt. Wir richten uns im Wesentlichen nach den Schreibweisen der Hersteller. Die Wiedergabe von Waren- und Handelsnamen etc. in dieser Dokumentation - auch ohne besondere Kennzeichnung - berechtigt nicht zu der Annahme, dass solche Namen im Sinne der Warenzeichen- und Markenschutz-Gesetzgebung als frei zu betrachten sind. In Einzelfällen kann es zu Abweichungen zwischen den beschriebenen Abläufen der Dokumentation und der tatsächlichen Anwendung kommen. Die Fujitsu übernimmt keine Haftung für etwaige Abweichungen und deren Folgen.

Hinweise und Kommentare richten Sie bitte an <[secdocs@fujitsu.com](mailto:secdocs@fujitsu.com)>

© 2024 Fujitsu