

Technical drawing of a bridge structure, likely a culvert or small bridge, showing various components and dimensions. The drawing includes a north arrow pointing upwards.

Key components and dimensions shown:

- CVV (2[□] × 8[□]) P28 8.0**: A component on the left side.
- CVV (2[□] × 8[□]) P28 9.**: A component on the right side.
- CVV-SS (2[□] × 4[□]) 1**: A component at the bottom right.
- Φ 250 L=1.0 鉄製**: A vertical pipe or column.
- Φ 250 L=1.5 鉄製**: Another vertical pipe or column.
- 押入タン箱**: A box or container, labeled multiple times.
- 20P→20T**: A label near a red circle.
- 果實 (1) 4**: A label on the right side.
- 川**: River, labeled in two locations.
- 至 沼田**: Directional label on the left side.
- 至 己斐橋**: Directional label on the right side.

	5.7m 歩灯4 	至 己斐橋 至 沼田 	流動図
---	---	--	------------

[illegible]

パ タ ン 切 替		(1) 平日			(2) 土曜			(3) 日曜			(4)特殊日1			(5)特殊日2			(6)特殊日3			(7)特殊日4		
	切替 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号
	1	7	00	3	7	00	3	7	00	3												
	2	9	00	1	9	00	1	9	00	1												
	3	17	00	2	17	00	2	17	00	2												
	4	19	00	1	19	00	1	19	00	1												
	5																					
	6																					
	7																					
	8																					
9																						
A																						
動 作 切 替	系統	00:00～00:00			00:00～00:00			00:00～00:00														
	リコール	09:00～07:00			09:00～07:00			09:00～07:00														
系 統 動 作 定 数	同期点				1ステップ 始め																	
	追従幅				-5%/+20%																	
	追従階梯秒数配分				スプリット比配分																	
	主現示追従階梯				1																	
	従現示追従階梯				6																	
	時刻修正				●																	
連 動 子 機 能 定 数	DC方式								分 周 期 連 動 機 能 定 数	実行しきい値												
	AC方式									連動パターン												
	同期階梯1(B/Y1)																					
	同期階梯2(A/Y2)																					
	周期監視時間																					
	共通オフセット1																					
	共通オフセット2																					
連動親機																						
交通弱者感応定数																						
感応階梯										ステップ												
補正階梯										ステップ												
倍率指定 (10～19)										×0.1倍												
弱者用保証青時間 (0～99)										秒												
ギ ャ ッ プ 感 応 定 数	単位1								単位2													
	短縮		延長		単位青		単位青		短縮		延長		単位青		単位青							
	Ts		Te		上り0.1秒 下り0.1秒				Ts		Te		上り0.1秒 下り0.1秒									
	P1								P1													
	P2								P2													
	P3								P3													
	P4								P4													
	P5								P5													
	P6								P6													
	P7								P7													
	P8								P8													
	P9								P9													
	PA								PA													
	感応階梯								感応階梯													
補正階梯								補正階梯														
感知器指定								感知器指定														
リ コ ー ル 定 数	感応階梯		1		ステップ																	
	補正階梯				ステップ																	
	感知器指定		押ボタン		PB1		車両															
	押ボタン受付禁止階梯								開始		5		終了		5							
	車両リコール受付禁止階梯								開始				終了									
曜日固定祝祭日テーブル																						
月		週		曜日																		
1		1		2		1																
2		10		2		1																
3		7		3		1																
4		9		3		1																
特殊日指定																						
月		日		日種		設定種別																
1																						
2																						
設定変更履歴																						
年月日				変更内容																		
2012年2月17日				設定変更 バタン秒数及びオフセット変更																		
2012年3月15日				設定変更 オフセット変更																		
2014年11月25日				制御機更新																		
2015年1月14日				連動子機廃止、系統制御に変更																		

備 考
地点感応制御機の場合左記の
ギャップ感応定数表の内容は
下記の通りです。

短縮 Ts → ありません。
延長 Te → 限度青です。
単位青 上り → 単位青です。
単位青 下り → ありません。
単位青秒数は 0.5秒単位です。

名称はこうに変更してください。