

		(1) 平日			(2) 土曜			(3) 日曜			(4) 特殊日1			(4) 特殊日2			(4) 特殊日3			(4) 特殊日4				
パターン切替	番号	時	分	パターン番号	時	分	パターン番号	時	分	パターン番号	時	分	パターン番号	時	分	パターン番号	時	分	パターン番号	時	分	パターン番号		
	1	6	00	1	6	00	1	6	00	1														
	2																							
	3																							
	4																							
	5																							
	6																							
	7																							
	8																							
	9																							
A																								
動作切替	閃光	00:00～06:00			00:00～06:00			00:00～06:00																
	連動子機	00:00～00:00			00:00～00:00			00:00～00:00																
系統動作定数	同期点																							
	追従幅																							
	追従階梯秒数配分																							
	主現示追従階梯																							
	従現示追従階梯																							
	時刻修正																							
連動子機能定数	DC方式				●				分周期連動機能定数	実行しきい値		0												
	AC方式									運動パターン		1/1												
	同期階梯1(B/Y2)				1																			
	同期階梯2(A/Y3)																							
	周期監視時間				255																			
	共通オフセット1				個別オフセット																			
	共通オフセット2																							
	連動親機				01-0039 牛田大橋北詰																			
交通弱者感応定数																								
感応階梯					ステップ																			
補正階梯					ステップ																			
倍率指定 (10～19)					×0.1倍																			
弱者用保証青時間(0～99)					秒																			
ギャップ感応定数	単位1					単位2																		
		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青														
		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒														
	P1					P1																		
	P2					P2																		
	P3					P3																		
	P4					P4																		
	P5					P5																		
	P6					P6																		
	P7					P7																		
	P8					P8																		
	P9					P9																		
	PA					PA																		
	感応階梯					感応階梯																		
	補正階梯					補正階梯																		
感知器指定					感知器指定																			
リコール定数	感応階梯		ステップ																					
	補正階梯		ステップ																					
	感知器指定		押ボタン			車両																		
	押ボタン受付禁止階梯					開始				終了														
	車両リコール受付禁止階梯					開始</																		