

Technical drawing of a road intersection. The drawing shows a central intersection with four main approaches. Lane markings include solid and dashed lines, and arrows indicating traffic flow. Dimensions are provided for various segments: 29.1m and 13.9m for the central approaches, and 20m, 12m, and 24.0m for the side approaches. Traffic signs are indicated by circles with numbers (e.g., 20, 12) and rectangular signs with text like "速度表示無し" (No speed limit). A compass rose is located in the top right corner. Text labels include "中環状 出入線分岐" (Inner Ring Road Branching Point), "運動場 : 江波本町北交差点" (Sports Ground: Hama Honcho North Intersection), and "国道165号" (National Route 165).

流動図	4. 6m 歩灯なし 至 (←.....→) 至 江波沖町 4. 4m 歩灯なし	23. 0m 歩灯2	
------------	--	-------------------	--

[illegible]

パ タ ン 切 替		(1) 平日		(2) 土曜		(3) 日曜		(4)特殊日1		(5)特殊日2		(6)特殊日3		(7)特殊日4			
	切替 番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	
	1	6	00	1	6	00	1	6	00	1							
	2																
	3																
	4																
	5																
	6																
	7																
	8																
9																	
A																	
動 作 切 替	連動子機	00:00～00:00		00:00～00:00		00:00～00:00											
系 統 動 作 定 数	同期点																
	追従幅																
	追従階梯秒数配分																
	主現示追従階梯																
	従現示追従階梯																
	時刻修正				●												
	連動子機				DC方式												
	AC方式				●												
	同期階梯1(B/Y1)				1												
	同期階梯2(A/Y2)																
機 能 定 数	周期監視時間				255												
	共通オフセット1				1秒												
	共通オフセット2																
	連動親機				01-0772 江波本町北												
交通弱者感応定数																	
感応階梯								ステップ									
補正階梯								ステップ									
倍率指定 (10～19)								×0.1倍									
弱者用保証青時間 (0～99)								秒									
ギ ャ ッ プ 感 応 定 数	単位1								単位2								
	短縮		延長		単位青		単位青		短縮		延長		単位青		単位青		
	Ts		Te		上り0.1秒		下り0.1秒		Ts		Te		上り0.1秒		下り0.1秒		
	P1								P1								
	P2								P2								
	P3								P3								
	P4								P4								
	P5								P5								
	P6								P6								
	P7								P7								
	P8								P8								
	P9								P9								
	PA								PA								
	感応階梯								感応階梯								
補正階梯								補正階梯									
感知器指定								感知器指定									
リ コ ー ル 定 数	感応階梯				ステップ												
	補正階梯				ステップ												
	感知器指定				押ボタン				車両								
	押ボタン受付禁止階梯								開始				終了				
	車両リコール受付禁止階梯								開始				終了				
曜日固定祝祭日テーブル																	
月		週		曜日													
1		1		2		1											
2		7		3		1											
3		9		3		1											
4		10		2		1											
設定変更履歴																	
年月日				変更内容													
2011年8月3日				制御機更新													

備 考
地点感応制御機の場合左記の
ギャップ感応定数表の内容は
下記の通りです。

短縮 Ts → ありません。
延長 Te → 限度青です。
単位青 上り → 単位青です。
単位青 下り → ありません。
単位青秒数は 0.5秒単位です。

名称はこうに変更してください。