

[illegible]

パ タ ン 切 替		(1) 平日				(2) 土曜				(3) 日曜				(4) 特殊日1				(5) 特殊日2				(6) 特殊日3				(7) 特殊日4			
	切替 番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号				
	1	6	00	1	6	00	1	6	00	1																			
	2	7	00	5	7	00	5	7	00	2																			
	3	9	00	4	9	00	4	9	00	3																			
	4	10	00	3	10	00	3	10	00	4																			
	5	17	00	5	17	00	5	17	00	5																			
	6	19	00	3	19	00	3	19	00	3																			
	7	20	00	2	20	00	2	20	00	2																			
	8	22	00	1	22	00	1	22	00	1																			
9																													
A																													
動 作 切 替	系統	00:00～00:00				00:00～00:00				00:00～00:00																			
系 統 動 作 定 数	同期点						1ステップ始まり																						
	追従幅						+15%・-5%																						
	追従階梯秒数配分						均等																						
	主現示追従階梯						1ステップ																						
	従現示追従階梯						6ステップ																						
	時刻修正						○(GPS)																						
連 動 子 機 機 能 定 数	DC方式												実行しきい値																
	AC方式												連動パターン																
	同期階梯1(B/Y1)																												
	同期階梯2(A/Y2)																												
	周期監視時間																												
	共通オフセット1																												
	共通オフセット2																												
	連動親機																												
交通弱者感応定数																													
感応階梯												ステップ																	
補正階梯												ステップ																	
倍率指定 (10～19)												×0.1倍																	
弱者用保証青時間(0～99)												秒																	
ギ ャ ッ プ 感 応 定 数	単位1								単位2																				
	短縮		延長		単位青		単位青		短縮		延長		単位青		単位青														
	Ts		Te		上り0.1秒		下り0.1秒		Ts		Te		上り0.1秒		下り0.1秒														
	P1								P1																				
	P2								P2																				
	P3								P3																				
	P4								P4																				
	P5								P5																				
	P6								P6																				
	P7								P7																				
	P8								P8																				
P9								P9																					
PA								PA																					
感応階梯												感応階梯																	
リ コ ー ル 定 数	感応階梯								ステップ																				
	補正階梯								ステップ																				
	感知器指定				押ボタン								車両																
	押ボタン受付禁止階梯												開始								終了								