

パ タ ン 切 替		(1) 平日			(2) 土曜			(3) 日曜			(4) 特殊日1			(5) 特殊日2			(6) 特殊日3			(7) 特殊日4						
		時	分	ハタ 番号	時	分	ハタ 番号	時	分	ハタ 番号	時	分	ハタ 番号	時	分	ハタ 番号	時	分	ハタ 番号	時	分	ハタ 番号				
	1	6	00	1	6	00	1	6	00	1																
	2	7	00	3	7	00	3	8	00	2																
	3	9	00	2	9	00	2	20	00	1																
	4	17	00	3	17	00	3																			
	5	19	00	2	19	00	2																			
	6	21	00	1	21	00	1																			
	7																									
	8																									
9																										
A																										
動 作 切 替	系統	00:00～00:00			00:00～00:00			00:00～00:00																		
	閃光	22:00～06:00			22:00～06:00			22:00～06:00																		
系 統 動 作 定 数	同期点			1ステップ始め																						
	追従幅			-5/+15																						
	追従階梯秒数配分			等分																						
	主現示追従階梯			1																						
	従現示追従階梯			6																						
	時刻修正			●(GPS)																						
連 動 子 機 能 数	DC方式																									
	AC方式																									
	同期階梯1(B/Y1)																									
	同期階梯2(A/Y2)																									
	周期監視時間																									
	共通オフセット1																									
	共通オフセット2																									
連動親機																										
交通弱者感応定数																										
感応階梯						ステップ																				
補正階梯						ステップ																				
倍率指定 (10～19)						×0.1倍																				
弱者用保証青時間 (0～99)						秒																				
ギ ャ ッ プ 感 応 定 数	単位1						単位2																			
	短縮		延長		単位青		単位青		短縮		延長		単位青		単位青											
	Ts		Te		上り0.1秒		下り0.1秒		Ts		Te		上り0.1秒		下り0.1秒											
	P1								P1																	
	P2								P2																	
	P3								P3																	
	P4								P4																	
	P5								P5																	
	P6								P6																	
	P7								P7																	
	P8								P8																	
	P9								P9																	
	PA								PA																	
	感応階梯		補正階梯		感知器指定				感応階梯		補正階梯		感知器指定													
リ コ ー ル 定 数	感応階梯				ステップ																					
	補正階梯				ステップ																					
	感知器指定		押ボタン				車両																			